Dspic30f family reference manual ds70046 pdf

Continue

/~’”\|:,.? 7. Push Select or Enter Character to let the oscilloscope know that you have picked the proper character to use. You can use the lower-bezel buttons to edit the name, as needed. Enter Character Back Space Delete Clear 8. Continue scrolling and pushing Select until you have entered all the desired characters. 194 DPO4000 Series User Manual Save and Recall Information 9. Push the down arrow key to move the character cursor down a row to the Server Name field. 10. Turn multipurpose knob a and push Select or Enter Character as often as needed to enter the name. 11. If desired, push the down arrow key to move the character cursor down a row to the Server IP Address: field. 12. Turn multipurpose knob a and push Select or Enter Character as often as needed to enter the name. Add Printer 13. When done, push OK Accept. OK Accept DPO4000 Series User Manual 195 Save and Recall Information NOTE. If you have multiple printers connected to the oscilloscope at the same time, the oscilloscope will print to the printer listed in the Utility > System > Print Setup > Select Printer menu item. Print to a Printer Once you have connected a printer to your oscilloscope and set up print parameters, you can print current screen images with a single push of a button: 1. Push the printer icon button in the lower left corner of the front panel. Erasing DPO4000 Memory You can erase all setup and waveform information saved in the nonvolatile memory with the TekSecure function. If you have acquired confidential data on your oscilloscope, you may want to execute the TekSecure function before you return the oscilloscope to general use. The TekSecure function: Replaces all waveforms in all reference memories with null values 196 DPO4000 Series User Manual Save and Recall Information Replaces the current front-panel setup and all stored setups with the default setup Displays a confirmation or warning message, depending on whether the verification is successful or unsuccessful To use TekSecure: 1. Push Utility. 2. Push System repeatedly until you select Config. Config 3. Push TekSecure. System Config Language English Set Date & Time TekSecure Erase Memory Version v1.00 DPO4000 Series User Manual 197 Save and Recall Information 4. Push OK Erase Setup and Ref Memory from the side-bezel menu. OK Erase Setup and Ref Memory To abort the procedure, push Menu Off. 198 DPO4000 Series User Manual Save and Recall Information 5. Power off the oscilloscope, and then power it back on to complete the process. DPO4000 Series User Manual 199 Use Application Modules Use Application Modules Optional application module packages extend the capability of your oscilloscope. Install up to four application modules at one time. Application modules go into the two slots with windows in the upper right corner of the front panel. Two additional slots are directly behind the two that you can see. Refer to the DPO4000 Series Application Module Installation Instructions that came with your application module for instructions on installing and testing an application module. Some modules are described below. Additional packages may be available. Contact your Tektronix representative or visit our Web site at www.tektronix.com for more information. Also, refer to Contacting Tektronix at the beginning of the manual. The DPO4EMBD Serial Triggering and Analysis Module adds triggering on packet level information in serial buses used in embedded designs (I2C and SPI), as well as analytical tools to help you efficiently analyze your serial bus. These include digital views of the signal, bus views, packet decoding, search tools, and event tables with timestamp information. The DPO4AUTO Serial Triggering and Analysis Module adds triggering on packet level information in serial buses used in automotive designs (CAN), as well as analytical tools to help you efficiently analyze your serial bus. These include digital views of the signal, bus views, packet decoding, search tools, and event tables with timestamp information. 200 DPO4000 Series User Manual Application Examples Application Examples This section contains ways to use your instrument in both common and advanced troubleshooting tasks. Taking Simple Measurements If you need to see a signal in a circuit, but you do not know the signal amplitude or frequency, connect the probe from channel 1 of the oscilloscope to the signal. Then display the signal and measure its frequency and peak-to-peak amplitude. DPO4000 Series User Manual 201 Application Examples Using Autoset To quickly display a signal: 1. Push Autoset. 202 DPO4000 Series User Manual Application Examples The oscilloscope sets vertical, horizontal, and trigger controls automatically. You can manually adjust any of these controls if you need to optimize the display of the waveform. When you are using more than one channel, the autoset function sets the vertical controls for each channel and uses the lowest-numbered active channel to set the horizontal and trigger controls. Selecting Automatic Measurements The oscilloscope can take automatic measurements of most displayed signals. To measure signal frequency and peak-to-peak amplitude: 1. Push Measure. 2. Push Select Measurement. Select Measurement a 1 Remove Measurement Gating Off Statistics Off Reference Levels Indicators Configure Cursors DPO4000 Series User Manual 203 Application Examples 3. Turn multipurpose knob a to select the channel from which you want to measure. For example, select channel 1. This step is only needed if you are acquiring data on more than one channel. 4. Select the Frequency measurement from the side-bezel menu. Frequency 5. Push -more- until you can select the Pk-Pk measurement. -more- 6. Push Menu Off. 204 DPO4000 Series User Manual Application Examples 7. Observe that the measurements appear on the screen and update as the signal changes. DPO4000 Series User Manual 205 Application Examples Measuring Two Signals In this example, you are testing a piece of equipment and need to measure the gain of its audio amplifier. You have an audio generator that can inject a test signal at the amplifier input. Connect two oscilloscope channels to the amplifier input and output as shown. Measure both signal levels and use these measurements to calculate the gain. 206 DPO4000 Series User Manual Application Examples To display the signals connected to channels 1 and 2: 1. Push channel 1 and channel 2 to activate both channels. 2. Push Autoset. To select measurements for the two channels: 1. Push Measure to see the measurement menu. DPO4000 Series User Manual 207 Application Examples 2. Push Select Measurement. Select Measurement a 1 Remove Measurement Gating Off Statistics Off Reference Levels Indicators Configure Cursors 3. Turn multipurpose knob a to select channel 1. 4. Page through the measurement menus until you find Amplitude. Select Amplitude. Amplitude 208 DPO4000 Series User Manual Application Examples 5. Turn multipurpose knob a to select channel 2. 6. Select Amplitude. Amplitude 7. Calculate the amplifier gain using the following equations: Gain = (output amplitude ÷ input amplitude) = (3.155 V ÷ 130.0 mV) = 24.27 Gain (dB) = 20 x log(24.27) = 27.7 dB DPO4000 Series User Manual 209 Application Examples Customizing Your Measurements In this example, you want to verify that the incoming signal to digital equipment meets its specifications. Specifically, the transition time from a low logic level (0.8 V) to a high logic level (2.0 V) must be 10 ns or less. To select the rise time measurement. 1. Push Measure. 210 DPO4000 Series User Manual Application Examples 2. Push Select Measurement. Select Measurement a 1 Remove Measurement Gating Off Statistics Off Reference Levels Indicators Configure Cursors 3. Turn multipurpose knob a to select channel 1. This step is only needed if you are acquiring data on more channels than just channel 1. 4. Select the Rise Time measurement from the side-bezel menu. Rise Time DPO4000 Series User Manual 211 Application Examples 5. Press Reference Levels. Reference Levels 6. Push Set Levels in to select units. Set Levels in % units 7. Push High Ref and turn multipurpose knob a to enter 2.00 V. If needed, push Fine to change the sensitivity of the multipurpose knob. High Ref a 2.00 V Mid Ref 8. Push Low Ref and turn multipurpose knob a to enter 800 mV. If needed, push Fine to change the sensitivity of the multipurpose knob. Low Ref a 800 mV 212 DPO4000 Series User Manual Application Examples Rise time is typically measured between the 10% and 90% amplitude levels of a signal. These are the default reference levels that the oscilloscope uses for rise time measurements, However, in this example, you need to measure the time that the signal takes to pass between the 0.8 V and 2.0 V levels. You can customize the rise time measurement to measure the signal transition time between any two reference levels. You can set each of these reference levels to a specific percent of the signal amplitude or to a specific level in vertical units (such as volts or amperes). Measuring Specific Events. Next you want to see the pulses in the incoming digital signal, but the pulse widths vary so it is hard to establish a stable trigger. To look at a snapshot of the digital signal, do this step: 1. Push Single to capture a single acquisition. Now you want to measure the width of each displayed pulse. You can use measurement gating to select a specific pulse to measure. To measure the second pulse: 1. Push Measure. DPO4000 Series User Manual 213 Application Examples 2. Push Select Measurement. Select measurement a 1 Remove Measurement Gating Statistics Reference Levels Indicators Configure Cursors 3. Turn multipurpose knob a to select channel 1. 4. Select Positive Pulse Width measurement. Positive Pulse Width 214 DPO4000 Series User Manual Application Examples 5. Push Gating. Select Measurement Remove Measurement Gating Off Statistics Off Reference Levels Indicators Configure Cursors 6. Select Between Cursors from the side-bezel menu to choose measurement gating using cursors. Between Cursors 7. Place one cursor to the left and one cursor to the right of the second pulse. DPO4000 Series User Manual 215 Application Examples 8. View the resulting width measurement (160 ms) for the second pulse. 216 DPO4000 Series User Manual Application Examples Analyzing Signal Detail In this example, you have a noisy signal displayed on the oscilloscope, and you need to know more about it. You suspect that the signal contains much more detail than you can currently see in the display. DPO4000 Series User Manual 217 Application Examples Looking at a Noisy Signal The signal appears noisy. You suspect that noise is causing problems in your circuit. To better analyze the noise: 1. Push Acquire. 2. Push Mode on the lower-bezel menu. Mode Record Length 10k Reset Horizontal Position Waveform Display 218 DPO4000 Series User Manual Application Examples 3. Push Peak Detect on the side-bezel menu. Sample Peak Detect Hi Res Envelope Average 4. Push Intensity and turn multipurpose knob a to see the noise more easily. DPO4000 Series User Manual 219 Application Examples 5. View the results on the display. Peak detect emphasizes noise spikes and glitches in your signal as narrow as 1 ns, even when the time base is set to a slow setting. 220 DPO4000 Series User Manual Application Examples Peak-detect and the other acquisition modes are explained earlier in this manual. (See page 75, Acquisition Concepts.) Separating the Signal from Noise Now you want to analyze the signal shape and ignore the noise. To reduce random noise in the oscilloscope display: 1. Push Acquire. 2. Push Mode. Mode Record Length Reset Horizontal Position Waveform Display 3. Push Average on the side-bezel menu. Average DPO4000 Series User Manual 221 Application Examples Averaging reduces random noise and makes it easier to see detail in a signal. In the example to the right, a ring shows on the rising and falling edges of the signal when the noise is removed. 222 DPO4000 Series User Manual Application Examples Taking Cursor Measurements You can use the cursors to take quick measurements on a waveform. To measure the ring frequency at the rising edge of the signal: 1. Push channel 1 to select the channel 1 signal. 2. Push Measure. 3. Push Configure Cursors. Select Measurement Remove Measurement Gating Statistics Reference Levels Indicators Configure Cursors DPO4000 Series User Manual 223 Application Examples 4. Push Vertical Bar Units repeatedly to select Hz (1/s). Vertical Bar Units Hz (1/s) 5. Push Cursors repeatedly until the two vertical bar cursors appear on the selected waveform. 6. Place one cursor on the first peak of the ring using multipurpose knob a. 7. If the cursor readout says that the cursors are linked, push Select to unlink them. 224 DPO4000 Series User Manual Application Examples 8. Place the other cursor on the next peak of the ring using multipurpose knob b. 9. The cursor Δ readout shows the measured ring frequency is 227 kHz. DPO4000 Series User Manual 225 Application Examples Triggering on a Video Signal The DPO4000 Series of oscilloscopes supports triggering on NTSC, SECAM, and PAL signals. In this example, you are testing the video circuit in a piece of medical equipment and need to display the video output signal. The video output is an NTSC standard signal. Use the video signal to obtain a stable display. To trigger on the video fields: 1. Push Trigger Menu. 226 DPO4000 Series User Manual Application Examples 2. Push Type repeatedly to select Video. Video 3. Push Standard repeatedly to select 525/NTSC. Type Video Standard 525/NTSC Source 1 Trigger on All Lines Mode Auto & Holdoff 4. Push Trigger On. 5. Select Odd Fields. Odd Fields If the signal had been noninterlaced, you could choose to trigger on All Fields. 6. Turn the Horizontal Scale knob to see a complete field across the screen. DPO4000 Series User Manual 227 Application Examples 7. View results. Triggering on Lines Triggering on Lines. To look at the video lines in the field: 1. Push Trigger Menu. 228 DPO4000 Series User Manual Application Examples 2. Push Type repeatedly to select Video. Video Type Video Standard 525/NTSC Source 1 Trigger On All Lines Mode Auto & Holdoff 3. Push Trigger On. 4. Select All Lines. All Lines 5. Adjust Horizontal Scale to see a complete video line across the screen. DPO4000 Series User Manual 229 Application Examples 6. Observe the results. Capturing a Single-Shot Signal In this example, the reliability of a reed relay in a piece of equipment has been poor, and you need to investigate the problem. You suspect that the relay contacts arc when the relay opens. The fastest you can open and close the relay is about once per minute, so you need to capture the voltage across the relay as a single-shot acquisition. To set up for a single-shot acquisition: 1. Adjust the Vertical Scale and Horizontal Scale to appropriate ranges for the signal you expect to see. 230 DPO4000 Series User Manual Application Examples 2. Push Acquire. 3. Push Mode. 4. Select Sample. 5. Push Trigger Menu. 6. Push Slope and . 7. Turn the Trigger Level knob to adjust the trigger level to a voltage midway between the open and closed voltages of the replay. DPO4000 Series User Manual 231 Application Examples 8. Push Single (single sequence). When the relay opens, the oscilloscope triggers and captures the event. The Single sequence button disables auto triggering so that only a valid triggered signal is acquired. 232 DPO4000 Series User Manual Application Examples Optimizing the Acquisition The initial acquisition shows the relay contact beginning to open at the trigger point. This is followed by large spikes that indicate contact bounce and inductance in the circuit. The inductance can cause contact arcing and premature relay failure. Before you take the next acquisition, you can adjust the vertical and horizontal controls to give you a preview of how the next acquisition might appear. As you adjust these controls, the current acquisition is repositioned, expanded, or compressed. This preview is useful to optimize the settings before the next single-shot event is captured. When the next acquisition is captured with the new vertical and horizontal settings, you can see more detail about the relay contact opening. You can now see that the contact bounces several times as it opens. DPO4000 Series User Manual 233 Application Examples Using the Horizontal Zoom Function To take a close look at a particular point on the acquired waveform, use the horizontal zoom function. To look closely at the point where the relay contact first begins to open: 1. Turn the Zoom knob. 2. Turn the Pan knob to place the center of the zoom box close to where the relay contact begins to open. 3. Turn the Zoom knob to magnify the waveform in the zoom window. 234 DPO4000 Series User Manual Application Examples The ragged waveform and the inductive load in the circuit suggest that the relay contact may be arcing as it opens. The zoom function works equally well when the acquisition is running or is stopped. Horizontal position and scale changes affect only the display, not the next acquisition. Correlating Data With a TLA5000 Logic Analyzer To troubleshoot designs with fast clock edges and data rates, it helps to view analog characteristics of digital signals in relation to complex digital events in the circuit. You can do that with iView, which lets you transfer analog waveforms from the oscilloscope to the logic analyzer display. You can then view time-correlated analog and digital signals side-by-side and use this to pinpoint sources of glitches and other problems. DPO4000 Series User Manual 235 Application Examples The iView External Oscilloscope Cable allows you to connect your logic analyzer to a Tektronix oscilloscope. This enables communication between the two instruments. The Add External Oscilloscope wizard, which is available from the TLA application System menu, guides you through the process of connecting the iView cable between your logic analyzer and oscilloscope. The TLA also provides a setup window to assist you in verifying, changing, and testing the oscilloscope settings. Before acquiring and displaying a waveform you must establish a connection between your Tektronix logic analyzer and oscilloscope using the Add External Oscilloscope wizard. To do this: 1. Select Add iView External Oscilloscope ... from the logic analyzer System menu. 236 DPO4000 Series User Manual Application Examples 2. Select your model of oscilloscope. 3. Follow the on-screen instructions, and then click Next. 4. See your Tektronix Logic Analyzer documentation for more information on correlating data between a DPO4000 Series Oscilloscope and a Tektronix Logic Analyzer. DPO4000 Series User Manual 237 Application Examples Tracking Down Bus Anomalies In this example, you are testing your new I2C circuit. Something is not working. You tell the master IC to send a message to the slave IC. Then you expect to receive data back and an LED to light. The light never goes on. Where in the ten or so commands that were sent out did the problem occur? Once you locate the problem location, how do you determine what went wrong? You can use your DPO4000 Series oscilloscope, with its serial triggering and long-record length management features, to track down the problem in both the physical layer and in the protocol layer of the bus. Basic strategy First, you will display and acquire the bus signal by setting up the bus parameters and trigger. Then, you will search through each packet with the search/mark functions. NOTE. Triggering on bus signals requires use of the DPO4EMBD or the DPO4AUTO Serial Triggering and Analysis Module. 238 DPO4000 Series User Manual Application Examples 1. Connect the channel 1 probe to the clock line. 2. Connect the channel 2 probe to the data line. 3. Push Autoset. DPO4000 Series User Manual 239 Application Examples 4. Push the B1 button and enter the parameters of your I2C bus in the resulting screen menus. 5. Push Trigger Menu. 6. Push Type to select Bus. Enter trigger parameters in the resulting screen menus. Type Bus Source Bus B1 (I2C) Trigger On Address Address 07F Direction Read Mode Auto & Holdoff 240 DPO4000 Series User Manual Application Examples 7. Analyze the physical layer. For example, you can use the cursors for manual measurements. (See page 144, Taking Manual Measurements with Cursors.) You can also use the automated measurements. (See page 129, Taking Automatic Measurements.) 8. Push Search. Set Search Marks to On. Enter a search type, source, and other parameters as relevant on the lower-bezel menu and associated side-bezel menus. (See page 163, Managing Long Record Length Waveforms.) 9. Jump ahead to the next search point by pushing the right arrow key. Push it again and again until you see all the events. Jump back with the left arrow key. Do you have all the packets that you expected to have? If not, at least you have narrowed your search down to the last packet sent. DPO4000 Series User Manual 241 Application Examples 10. Analyze the decoded packets in the protocol layer. Did you send the data bytes in the correct order? Did you use the correct address? 242 DPO4000 Series User Manual Index Index Symbols and Numbers 50 Ω protection, 128 A Accessories, 1 Acquire button, 49, 80, 112, 218, 221 Acquisition input channels and digitizers, 75 modes defined, 78 readout, 60 sampling, 75 Adapter TEK-USB-488, 4 TPA-BNC, 4, 10 Adding waveform, 112 Advanced math, 157 Altitude DPO4000, 7 P6139A, 8 Analysis and Connectivity, xii Application module DPO4AUTO, 84 DPO4EMBD, 84 Application Module, xiii, 19 Applications modules, 200 Attenuation, 127 Auto trigger mode, 92 Autoset, 74, 202 Autoset button, 17, 49, 56, 71, 74, 202, 207 Autoset undo, 74 Auxiliary readout, 64 Average acquisition mode, 79 BB Trigger, 109 B1 / B2 button, 51, 84, 85, 102 Backlight intensity, 119 Bandwidth, x Before Installation, 1 Blackman-Harris FFT window, 157 BNC interface, 10 Bus button, 84, 85, 102 menu, 51, 85 Bus trigger, defined, 102 Buses, 84, 102 Button Acquire, 49, 80, 112, 218, 221 Autoset, 17, 49, 56, 71, 74, 202, 207 B1 / B2, 51, 84, 85, 102 bus, 84, 85, 102 Channel, 50 Cursors, 52, 144, 224 Default Setup, 50, 58, 73 Fine, 48, 52, 53, 54, 55, 57 Force Trig, 56, 93 hard copy, 57, 196 Intensity, 115 M, 51, 150, 153 Math, 51, 150, 153 Measure, 49, 129, 139, 140, 203, 207, 210, 213 Menu Off, 58, 204 Next, 55 play-pause, 167 Play-pause, 54 Previous, 54 printer icon, 57, 196 Ref, 51, 160, 182 DPO4000 Series User Manual 243 Index Run/Stop, 56, 83, 111 Save / Recall, 50, 58, 174 Search, 49, 170 Select, 53, 224 Set / Clear Mark, 55, 169 Set to 50%, 56, 97 Single, 56, 111, 213, 232 Test, 49 Trigger, 49 Trigger level, 56 Trigger menu, 226 Trigger Menu, 98 Utility, 20, 23, 26, 50, 117, 118, 189 Vertical, 50 Zoom, 54 C Calibration, 25, 27 Calibration certificate, 2 CAN, 51, 84, 102 Channel button, 50 Channel readout, 64 Clearance, DPO4000, 6 Communications, 35, 40 CompactFlash, x, 2, 5, 50, 58, 174 Compensate probe, 17 Compensate signal path, 25 Confidential data, 196 Connectivity, 2, 35, 40 Connector, side-panel, 67 Connectors front-panel, 66 rear-panel, 68 Controls, 45 Coupling, trigger, 94 Cover, front, 2 Cross Hair graticule style, 118 Cursor readout, 62, 149 Cursor, measurements, 144 Cursors, 144 button, 52, 144, 224 linking, 145 Cursors menu, 144 D Date and time, changing, 23 Default setup, 187 Default Setup, 73 button, 50, 58, 73 menu, 50 Undo, 73 Delayed trigger, 107 Depth, DPO4000, 6 Deskew, 127 Display persistence, 112 style, 112 Displaying, reference waveforms, 182 Documentation, xii DPO4AUTO, 84 DPO4EMBD, 84 Drivers, 35, 39 Dual waveform math, 150 Ee *Scope, 40 Edge trigger, defined, 99 Envelope acquisition mode, 79 Erase setup and ref memory, 196 Ethernet, x, 37, 40, 41 port, 68 printing, 192 Event Table, 88, 89 Excel, 34 Expansion point icon, 61 244 DPO4000 Series User Manual Index FF actory calibration, 27 FFT Blackman-Harris, 157 controls, 153 Hamming, 156 Hanning, 157 Rectangular, 156 File format, 175 Internal File Format (ISF), 182 Spreadsheet file format (.CSV), 182 File system, 174, 177, 180 Fine, 53 Fine button, 48, 52, 54, 55, 57 Firmware upgrade, 28 Force Trig button, 56, 93 Frame graticule style, 118 Frequency, Input power DPO4000, 6 Front cover, 2 Front panel, 45 Front-panel connectors, 66 Front-panel overlay, 22 Full graticule style, 118 Functional check, 15 G Gating, 137 GPIB, 36, 38, 68 GPIB address, 38 Graticule Cross Hair, 118 Frame, 118 Full, 118 Grid, 118 intensity, 115 styles, 117 Grid graticule style, 118 Ground, 11 Ground lead, 19 Ground strap, 67 H Hamming FFT window, 156 Hanning FFT window, 157 Hard copy, 57, 189 Height, DPO4000, 6 Hi Res acquisition mode, 79 Holdoff, trigger, 93 Horizontal delay, 94 Horizontal position, 55, 94, 95, 120, 156, 234, 235 and math waveforms, 152 defined, 72 Horizontal position/scale readout, 64 Horizontal scale, 55, 120, 156, 227, 229, 230, 234 and math waveforms, 152 defined, 72 How to erase memory, 196 print a hard copy, 189 recall setups, 184 recall waveforms, 174 save screen images, 174 save setups, 184 save waveforms, 174 Humidity DPO4000, 7 P6139A, 9 I I2C, 51, 84, 102 DPO4000 Series User Manual 245 Index Icon Expansion point, 61 Trigger level, 63 Trigger position, 61 Image orientation, 175, 191 Impedance, 123 Indicator, waveform baseline, 65 Infinite persistence, 115 Ink Saver, 175, 191 Inner knob, 54, 152 Installing, application modules, xiii Intensity button, 115 Internal File Format, 182 K Knob inner, 54, 152 Multipurpose, 24, 48, 53, 54, 80, 86, 177, 224, 225 outer, 54 pan, 54, 166, 169 Trigger level, 97 Vertical position, 57, 72 Vertical scale, 57, 72 zoom, 54, 152, 164 LL abView, 34 Landscape, 175, 191 Language change, 20 overlay, 22 Level, trigger, 96 Logic trigger, defined, 100 Long record length, 238 Long record length management, 163 MM button, 51, 150, 153 Main trigger, 107 Mark, 169 Math Advanced, 157 button, 51, 150, 153 Dual waveform, 150 FFT, 153 menu, 51 waveforms, 150 Measure button, 49, 129, 139, 140, 203, 207, 210, 213 Measurement menu, 49 Measurements automatic, 129 cursor, 144 defined, 131 reference levels, 142 snapshot, 140 statistics, 139 Memory, erasure of, 196 Menu Bus, 51, 85 Cursors, 144 Default Setup, 50 Math, 51 Measurement, 49 Reference, 51, 160, 161 Save / Recall, 50, 58, 174 Trigger, 49, 98, 108, 226 Utility, 20, 23, 50, 57, 117, 189 Vertical, 50, 122 Menu buttons, 49 Menu Off button, 58, 204 Menus, 45 Mode, roll, 83 Multipurpose knob, 48, 53, 54, 80, 86, 177, 224, 225 246 DPO4000 Series User Manual Index N Network printing, 192 Next button, 55 Normal trigger mode, 92 O Offset and position, 128 OpenChoice, 2, 35 Operating specifications, 6 Orientation of the image, 175, 191 Outer knob, 54 Overlay, 22 P Pan, 164, 166 knob, 54, 166, 169 Pause, 166 Peak detect acquisition mode, 79 Performance verification, xii Persistence display, 112 infinite, 115 variable, 115 Play, 166 Play-pause button, 54, 167 Play-pause mode, 167 Pollution Degree DPO4000, 7 P6139A, 9 Portrait, 175, 191 Position Horizontal, 94, 95, 120, 156, 234, 235 Vertical, 121 Position and offset, 128 Posttrigger, 91, 96 Power cord, 3 input, 69 off, 14 removing, 14 supply, 11 switch, 57 Power consumption, DPO4000, 6 Predefined math expressions, 150 Pretrigger, 91, 96 Previous button, 54 Print, 57, 189 Printing a hard copy, 189 Printing, Ethernet, 192 Probe Comp, 16 Probe compensation, 17 Probes BNC, 10 connecting, 10 ground lead, 19 TEK-USB-488 Adapter, 4 TekVPI, 10 TPA-BNC Adapter, 4, 10 Programmer Commands, xii Pulse/Width trigger, defined, 100 R Rackmount, 4 Readout Acquisition, 60 Auxiliary, 64 Channel, 64 Cursor, 62, 149 Horizontal position/scale, 64 Record length/sampling rate, 63 Trigger, 63, 107 Trigger status, 62 Rear-panel connectors, 68 Recalling setups, 184 waveforms, 174 Record length, x DPO4000 Series User Manual 247 Index Record length/sampling rate readout, 63 Rectangular FFT window, 156 Ref button, 51, 160 Ref R, 182 Reference button, 182 Reference levels, 142 Reference menu, 51, 160, 161 Reference waveforms, 160 displaying, 182 removing, 161, 183 saving, 182 saving 10M waveforms, 162 Related documents, xii Removing reference waveforms, 183 Removing reference waveforms, 161 Removing waveform, 112 Rise/Fall trigger, defined, 101 Roll mode, 83 Run/Stop button, 56, 83, 111 Runt trigger, defined, 100 SS afety Summary, v Sample acquisition mode, 78 Sample rates, x Sampling process, defined, 75 Sampling, real-time, 76 Save / Recall menu, 50, 58, 174 Save / Recall Menu button, 50 Save / Recall Save button, 58, 174 Saving reference waveforms, 182 screen images, 174 waveforms, 174 Saving and recalling Information, 174 Saving setups, 184 Scale Horizontal, 55, 120, 156, 227, 229, 230, 234 Vertical, 121, 230 Search, 169 Search / Mark, 238 Search button, 49, 170 Securing DPO4000 memory, 196 Select button, 53, 224 Sequential triggering, 107 Serial, 84, 102, 238 Service information, xiii Set / Clear Mark button, 55, 169 Set to 50% button, 56, 97 Setup default, 58, 187 Default, 73 Setup and Hold trigger, defined, 101 Side panel connector, 67 Signal path compensation, 25 Single button, 56, 111, 213, 232 Single sequence, 83, 111 Slope, trigger, 96 Snapshot, 140 Software drivers, 35, 39 Software, optional, 200 SPC, 25 Specifications, xii operating, 6 power supply, 11 SPI, 51, 84, 102 Spreadsheet file format (.CSV), 182 Start an acquisition, 111 Statistics, 139 Stop an acquisition, 111 Switch, power, 57 T Table, Event, 88, 89 TDSPCS1, 35 248 DPO4000 Series User Manual Index TEK-USB-488 Adapter, 36, 38, 68 TEK-USB–488 Adapter, 4 TekSecure, 196 TekVPI, 10 Temperature DPO4000, 6 P6139A, 8 Termination, 123 Test button, 49 TPA-BNC Adapter, 4, 10 Transit case, 4 Transition trigger, defined, 101 Trigger concepts, 91 coupling, 94 delayed, 107 event, defined, 91 forcing, 92 holdoff, 93 level, 96 modes, 92, 98 posttrigger, 91, 96 pretrigger, 91, 96 readout, 107 sequential, 107 Serial, 84, 102, 238 slope, 96 Trigger level button, 56 Icon, 63 knob, 97 Trigger menu, 49, 98, 108, 226 Trigger menu button, 226 Trigger Menu button, 98 Trigger modes Auto, 92 Normal, 92 Trigger position icon, 61 Trigger readout, 63 Trigger status readout, 62 Trigger types, defined, 99 U Undo Autoset, 74 Default Setup, 73 Upgrading firmware, 28 USB, x, 5, 36, 39, 50, 58, 69, 174, 189 port, 68 USBTMC, 68 User marks, 169 Utility button, 20, 23, 26, 50, 117, 118, 189 Utility menu, 20, 23, 50, 57, 117 V Variable persistence, 115 Versatile Probe Interface, 10 Vertical button, 50 menu, 50, 122 Position, 121 position and autoset, 75 position and offset, 128 Position knob, 57, 72 Scale, 121, 230 Scale knob, 57, 72 Vibration, DPO4000, 7 Video lines, 228 port, 68 Video trigger, defined, 101 View waveform record, 61 Voltage, Input DPO4000, 6 P6139A, 8 DPO4000 Series User Manual 249 Index Voltage, Output, P6139A, 8 W Waveform adding, 112 display style, 112 intensity, 115 pan, 164, 166 pause, 166 play, 166 play-pause, 167 record defined, 77 removing, 112 search and mark, 169 user marks, 169 zoom, 164 Waveform baseline indicator, 65 Waveform record, 77 Waveform record view, 61 Weight DPO4000, 6 Width DPO4000, 6 ZZ oom, 164 button, 54 graticule size, 166 Horizontal, 234 knob, 54, 164 PBSS9110Z 100 V, 1 A PNP low VCEsat (BISS) transistor Rev. 03 — 11 December 2009 Product data sheet Table 1. Quick reference data Symbol Parameter Conditions Min Typ Max Unit VCEO collector-emitter voltage open base - - −100 V IC collector current - - −1 A ICM peak collector current single pulse; tp ≤ 1 ms - - −3 A RCEsat collector-emitter saturation resistance IC = −1 A; IB = −100 mA [1] - 170 320 mΩ PBSS9110Z_3 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 03 — 11 December 2009 2 of 14 NXP Semiconductors PBSS9110Z 100 V, 1 A PNP low VCEsat (BISS) transistor 2. Pinning information 3. Ordering information 4. Marking 5. Limiting values Table 2. Pinning Pin Description Simplified outline Symbol 1 base 2 collector 3 emitter 4 collector 1 2 3 4 sym028 2, 4 3 1 Table 3. Ordering information Type number Package Name Description Version PBSS9110Z SC-73 plastic surface-mounted package with increased heat sink; 4 leads SOT223 Table 4. Marking codes Type number Marking code PBSS9110Z PB9110 Table 5. Limiting values In accordance with the Absolute Maximum Rating System (IEC 60134). Symbol Parameter Conditions Min Max Unit VCBO collector-base voltage open emitter - −120 V VCEO collector-emitter voltage open base - −100 V VEBO emitter-base voltage open collector - −5 V IC collector current - −1 A ICM peak collector current single pulse; tp ≤ 1 ms - −3 A IB base current - −0.3 A Ptot total power dissipation Tamb ≤ 25 °C [1] - 0.65 W [2] - 1 W [3] - 1.4 W PBSS9110Z_3 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 03 — 11 December 2009 3 of 14 NXP Semiconductors PBSS9110Z 100 V, 1 A PNP low VCEsat (BISS) transistor [1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint. [2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1cm2. [3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6cm2. 6. Thermal characteristics [1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint. [2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1cm2. [3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6cm2. Tj junction temperature - 150 °C Tamb ambient temperature −65 +150 °C Tstg storage temperature −65 +150 °C (1) FR4 PCB, mounting pad for collector 6cm2 (2) FR4 PCB, mounting pad for collector 1cm2 (3) FR4 PCB, standard footprint Fig 1. Power derating curves Table 5. Limiting values ...continued In accordance with the Absolute Maximum Rating System (IEC 60134). Symbol Parameter Conditions Min Max Unit Tamb (°C) 0 40 80 120 160 001aaa508 0.8 0.4 1.2 1.6 Ptot (W) 0 (1) (2) (3) Table 6. Thermal characteristics Symbol Parameter Conditions Min Typ Max Unit Rth(j-a) thermal resistance from junction to ambient in free air [1]- - 192 K/W [2]- - 125 K/W [3]- - 89 K/W Rth(j-sp) thermal resistance from junction to solder point - - 17 K/W PBSS9110Z_3 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 03 — 11 December 2009 4 of 14 NXP Semiconductors PBSS9110Z 100 V, 1 A PNP low VCEsat (BISS) transistor FR4 PCB, standard footprint Fig 2. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values FR4 PCB, mounting pad for collector 1cm2 Fig 3. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values 006aaa819 10 1 102 103 Zth(j-a) (K/W) 10−1 10−5 10−4 10−2 10−1 10 102 tp (s) 10−3 1 103 duty cycle = 1 0.75 0.5 0.33 0.2 0.1 0.05 0.02 0.01 0 006aaa820 10 1 102 103 Zth(j-a) (K/W) 10−1 10−5 10−4 10−2 10−1 10 102 tp (s) 10−3 1 103 duty cycle = 0.75 0.5 0.33 0.2 0.1 0.05 0.02 0.01 0 1 PBSS9110Z_3 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 03 — 11 December 2009 5 of 14 NXP Semiconductors PBSS9110Z 100 V, 1 A PNP low VCEsat (BISS) transistor FR4 PCB, mounting pad for collector 6cm2 Fig 4. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values 006aaa821 10 1 102 103 Zth(j-a) (K/W) 10−1 10−5 10−4 10−2 10−1 10 102 tp (s) 10−3 1 103 duty cycle = 1 0.75 0.5 0.33 0.2 0.1 0.05 0.02 0.01 0 PBSS9110Z_3 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 03 — 11 December 2009 6 of 14 NXP Semiconductors PBSS9110Z 100 V, 1 A PNP low VCEsat (BISS) transistor 7. Characteristics [1] Pulse test: tp ≤ 300 μs; δ ≤ 0.02. Table 7. Characteristics Tamb = 25°C unless otherwise specified. Symbol Parameter Conditions Min Typ Max Unit ICBO collector-base cut-off current VCB = −80 V; IE = 0 A - - −100 nA VCB = −80 V; IE = 0 A; Tj = 150 °C - - −50 μA ICES collector-emitter cut-off current VCE = −80 V; VBE = 0 V - - −100 nA IEBO emitter-base cut-off current VEB = −4 V; IC = 0 A - - −100 nA hFE DC current gain VCE = −5 V; IC = −1 mA 150 - - VCE = −5 V; IC = −250 mA 150 - - VCE = −5 V; IC = −0.5 A [1] 150 - 450 VCE = −5 V; IC = −1 A [1] 125 - - VCEsat collector-emitter saturation voltage IC = −250 mA; IB = −25 mA - - −120 mV IC = −500 mA; IB = −50 mA [1]- - −180 mV IC = −1 A; IB = −100 mA [1]- - −320 mV RCEsat collector-emitter saturation resistance IC = −1 A; IB = −100 mA [1] - 170 320 mΩ VBEsat base-emitter saturation voltage IC = −1 A; IB = −100 mA [1]- - −1.1 V VBEon base-emitter turn-on voltage VCE = −5 V; IC = −1 A [1]- - −1.0 V td delay time VCC = −10 V; IC = −0.5 A; IBon = −0.025 A; IBoff = 0.025 A - 20 - ns tr rise time - 60 - ns ton turn-on time - 80 - ns ts storage time - 290 - ns tf fall time - 120 - ns toff turn-off time - 410 - ns fT transition frequency VCE = −10 V; IC = −50 mA; f = 100 MHz 100 - - MHz Cc collector capacitance VCB = −10 V; IE = ie = 0 A; f = 1 MHz - - 17 pF PBSS9110Z_3 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 03 — 11 December 2009 7 of 14 NXP Semiconductors PBSS9110Z 100 V, 1 A PNP low VCEsat (BISS) transistor VCE = −10 V (1) Tamb = 100 °C (2) Tamb = 25 °C (3) Tamb = −55 °C Tamb = 25 °C Fig 5. DC current gain as a function of collector current; typical values Fig 6. Collector current as a function of collector-emitter voltage; typical values VCE = −10 V (1) Tamb = −55 °C (2) Tamb = 25 °C (3) Tamb = 100 °C IC/IB = 10 (1) Tamb = −55 °C (2) Tamb = 25 °C (3) Tamb = 100 °C Fig 7. Base-emitter voltage as a function of collector current; typical values F

where explicitly agreed otherwise, the sale of products referred to in this publication is subject to the general terms and conditions of sale of Huntsman Advanced Materials LLC or of its affiliated companies including without limitation, Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., and Huntsman Advanced Materials (Hong Kong) Ltd. Huntsman Advanced Materials is an international business unit of Huntsman Corporation. Huntsman Advanced Materials trades through Huntsman affiliated companies in different countries including but not limited to Huntsman Advanced Materials LLC in the USA and Huntsman Advanced Materials (Europe) BVBA in Europe. [Araldite® 2014-1] is a registered trademark of Huntsman Corporation or an affiliate thereof. Copyright © 2007 Huntsman Corporation or an affiliate thereof. All rights reserved. Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France : 1.1 Identifiant du produit 1.3 Renseignements concernant le fournisseur de la fiche de données de sécurité Adresse email de la personne responsable pour cette FDS : Global_Product_EHS_AdMat@huntsman.com Description du produit : Non disponible. 1.2 Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées SECTION 1: Identification de la substance/du mélange et de la société/l'entreprise Code du produit : 00057058 1.4 Numéro d'appel d'urgence Organisme de conseil/centre antipoison national Fournisseur Numéro de téléphone : EUROPE: +32 35 75 1234 France ORFILA: +33(0)145425959 ASIA: +65 6336-6011 China: +86 20 39377888 Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1/800/424.9300 Système Utilisation du produit : adhésif bi-composants Fournisseur : Huntsman Advanced Materials (Europe)BVBA Everslaan 45 3078 Everberg / Belgium Tel.: +41 61 299 20 41 Fax: +41 61 299 20 40 France : ORFILA 01.45.42.59.59 - Hors de France : +33.(0)1.45.42.59.59 Classification Xi; R41, R38 R43 N; R51/53 : Dangers pour la santé : humaine Risque de lésions oculaires graves. Irritant pour la peau. Peut entraîner une sensibilisation par contact avec la peau. Dangers pour : l'environnement Toxique pour les organismes aquatiques, peut entraîner des effets néfastes à long terme pour l'environnement aquatique. Pour plus de détails sur les conséquences en termes de santé et les symptômes, reportez-vous à la section 11. SECTION 2: Identification des dangers 2.1 Classification de la substance ou du mélange Définition du produit : Working pack (preparation) Voir section 16 pour le texte intégral des phrases R et mentions H déclarées ci-dessus. Classification selon la directive 1999/45/CE [DPD] Le produit est classé dangereux selon la directive 1999/45/CE et ses amendements. 2.2 Éléments d'étiquetage Date d'édition / Date de révision : 3 Août 2011 1/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 2/19 SECTION 2: Identification des dangers Autres dangers qui ne : donnent pas lieu à une classification Non disponible. Récipients devant être pourvus d'une fermeture de sécurité pour les enfants Non applicable. Avertissement tactile de danger Non applicable. : : Exigences d'emballages spéciaux Symbole(s) de danger Conseils de prudence S26- En cas de contact avec les yeux, laver immédiatement et abondamment avec de l'eau et consulter un spécialiste. S39- Porter un appareil de protection des yeux/du visage. S61- Éviter le rejet dans l'environnement. Consulter les instructions spéciales/la fiche de données de sécurité. R41- Risque de lésions oculaires graves. R38- Irritant pour la peau. R43- Peut entraîner une sensibilisation par contact avec la peau. R51/53- Toxique pour les organismes aquatiques, peut entraîner des effets néfastes à long terme pour l'environnement aquatique. Phrases de risque Ingrédients dangereux : : : : Irritant, Dangereux pour l'environnement produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) résine époxidique à base de bisphénol F éther diglycidique du 1,4-butanediol N(3-diméthylaminopropyl)-1,3-propylènediamine Indication de danger : 2.3 Autres dangers Éléments d'étiquetage supplémentaires : Contient des composés époxydiques. Voir les informations transmises par le fabricant. Substance/préparation : Working pack (preparation) Nom du Identifiants 67/548/CEE produit/composant SECTION 3: Composition/informations sur les composants % Règlement (CE) Type n° 1272/2008 [CLP] Classification produit de réaction: bisphénol-Aépichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) REACH #: 01- 2119456619-26 CAS: 25068-38-6 13 - 30 Xi; R36/38 R43 N; R51/53 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 [1] résine époxidique à base de bisphénol F REACH #: 01- 2119454392-40 CAS: 9003-36-5 3 - 7 Xi; R36/38 R43 N; R51/53 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 [1] éther diglycidique du 1,4-butanediol REACH #: 01- 2119494060-45 CAS: 2425-79-8 1 - 3 Xn; R20/21 Xi; R36/38 Acute Tox. 4, H312 Acute Tox. 4, H332 [1] Date d'édition / Date de révision : 3 Août 2011 2/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 3/19 SECTION 3: Composition/informations sur les composants Les limites d'exposition professionnelle, quand elles sont disponibles, sont énumérées à la section 8. Dans l'état actuel des connaissances du fournisseur et dans les concentrations d'application, aucun autre ingrédient présent n'est classé comme dangereux pour la santé ou l'environnement, et donc nécessiterait de figurer dans cette section. Voir section 16 pour le texte intégral des phrases R mentionnées cidessus Voir section 16 pour le texte intégral des mentions H déclarées ci-dessus. R43 R52/53 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 N(3- diméthylaminopropyl)- 1,3-propylènediamine CAS: 10563-29-8 1 - 3 Xn; R21/22 C; R34 R43 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 [1] diglycidylester de l'acide téréphthalique CAS: 7195-44-0 0.1 - 1 Xi; R36/38 R43 N; R51/53 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 [1] triglycidylester de l'acide trimellitique CAS: 7237-83-4 0.1 - 1 Xi; R36/38 R43 N; R51/53 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 [1] [1] Substance classée avec un danger pour la santé ou l'environnement [2] Substance avec une limite d'exposition au poste de travail [3] La substance remplit les critères des PTB selon le Règlement (CE) n° 1907/2006, Annexe XIII [4] La substance remplit les critères des tPtB selon le Règlement (CE) n° 1907/2006, Annexe XIII Type Contact avec la peau Consulter un médecin immédiatement. Rincer immédiatement les yeux à grande eau, en soulevant de temps en temps les paupières supérieures et inférieures. Vérifier si la victime porte des verres de contact et dans ce cas, les lui enlever. Continuez de rincer pendant 10 minutes au moins. Les brûlures chimiques doivent être traitées sans tarder par un médecin. Rincer la peau contaminée à grande eau. Retirer les vêtements et les chaussures contaminés. Laver abondamment à l'eau les vêtements contaminés avant de les retirer, ou porter des gants. Continuez de rincer pendant 10 minutes au moins. Consulter un médecin. En cas d'affections ou de symptômes, évitez d'exposer plus longuement. Laver les vêtements avant de les réutiliser. Laver les chaussures à fond avant de les remettre. 4.1 Description des premiers secours Transporter la victime à l'extérieur et la maintenir au repos dans une position où elle peut confortablement respirer. S'il ne respire pas, en cas de respiration irrégulière ou d'arrêt respiratoire, que le personnel qualifié pratique la respiration artificielle ou administre de l'oxygène. Il peut être dangereux pour la personne assistant une victime de pratiquer le bouche à bouche. Appelez un médecin en cas de persistance ou d'aggravation des effets néfastes sur la santé. En cas d'évanouissement, placez la personne en position latérale de sécurité et appelez un médecin immédiatement. Assurez-vous d'une bonne circulation d'air. Détacher tout ce qui pourrait être serré, comme un col, une cravate, une ceinture ou un ceinturon. En cas d'inhalation de produits de décomposition lors d'un incendie, les symptômes peuvent être différés. La personne exposée peut avoir besoin de rester sous surveillance médicale pendant 48 heures. Inhalation Contact avec les yeux : : : SECTION 4: Premiers secours Date d'édition / Date de révision : 3 Août 2011 3/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 4/19 SECTION 4: Premiers secours Rincez la bouche avec de l'eau. Enlever les prothèses dentaires s'il y a lieu. Transporter la victime à l'extérieur et la maintenir au repos dans une position où elle peut confortablement respirer. Si une personne a avalé de ce produit et est consciente, lui faire boire de petites quantités d'eau. Si la personne est indisposée, cesser de la faire boire car des vomissements pourraient entraîner un risque supplémentaire. Ne pas faire vomir sauf indication contraire émanant du personnel médical. En cas de vomissement, maintenez la tête vers le bas pour empêcher le passage des vomissures dans les poumons. Appelez un médecin en cas de persistance ou d'aggravation des effets néfastes sur la santé. Ne rien faire ingérer à une personne inconsciente. En cas d'évanouissement, placez la personne en position latérale de sécurité et appelez un médecin immédiatement. Assurez-vous d'une bonne circulation d'air. Détacher tout ce qui pourrait être serré, comme un col, une cravate, une ceinture ou un ceinturon. Note au médecin traitant En cas d'inhalation de produits de décomposition lors d'un incendie, les symptômes peuvent être différés. La personne exposée peut avoir besoin de rester sous surveillance médicale pendant 48 heures. Ingestion : : : Traitements spécifiques Protection des sauveteurs : Aucune initiative ne doit être prise qui implique un risque individuel ou en l'absence de formation appropriée. Il peut être dangereux pour la personne assistant une victime de pratiquer le bouche à bouche. Laver abondamment à l'eau les vêtements contaminés avant de les retirer, ou porter des gants. 4.2 Effets et symptômes les plus importants, aigus ou différés Effets aigus potentiels sur la santé Inhalation : L'exposition aux produits de décomposition peut présenter des risques pour la santé. Les effets graves d'une exposition peuvent être différés. Irritant pour la bouche, Ingestion : la gorge et l'estomac. Contact avec la peau : Irritant pour la peau. Peut entraîner une sensibilisation par contact avec la peau. Contact avec les yeux : Gravement irritant pour les yeux. Risque de lésions oculaires graves. Signes/symptômes de surexposition Contact avec la peau Ingestion Inhalation Aucune donnée spécifique. Aucune donnée spécifique. Les symptômes néfastes peuvent éventuellement comprendre ce qui suit: irritation rougeur : : : Contact avec les yeux : Les symptômes néfastes peuvent éventuellement comprendre ce qui suit: douleur ou irritation larmoiement rougeur 4.3 Indication quant à la nécessité d'une prise en charge médicale immédiate ou d'un traitement spécial : Traitement symptomatique et thérapie de soutien comme indiqué. Après une exposition sévère le patient doit être gardé sous contrôle médical pendant au moins 48 heures. Utiliser un agent extincteur approprié pour étouffer l'incendie avoisinant. 5.1 Moyens d'extinction Aucun connu. Moyens d'extinction appropriés : Moyens d'extinction inappropriés : SECTION 5: Mesures de lutte contre l'incendie 5.2 Dangers particuliers résultant de la substance ou du mélange Date d'édition / Date de révision : 3 Août 2011 4/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 5/19 SECTION 5: Mesures de lutte contre l'incendie En présence d'incendie, circonscrire rapidement le site en évacuant toute personne se trouvant près des lieux de l'accident. Aucune initiative ne doit être prise qui implique un risque individuel ou en l'absence de formation appropriée. Ce produit est toxique pour les organismes aquatiques. L'eau du réseau d'extinction d'incendie qui a été contaminée par ce produit doit être conservée en milieu fermé et ne doit être déversée ni dans le milieu aquatique, ni aucun égout ou conduit d'évacuation. Risque lié aux produits de décomposition thermique Dangers dus à la substance ou au mélange Les produits de décomposition peuvent éventuellement comprendre les substances suivantes: dioxyde de carbone monoxyde de carbone oxydes d'azote oxydes de soufre oxyde/oxydes de métal L'augmentation de pression résultant d'un incendie ou d'une exposition à des températures élevées peut provoquer l'explosion du conteneur. Les pompiers devront porter un équipement de protection approprié ainsi qu'un appareil de protection respiratoire autonome avec masque intégral fonctionnant en mode pression positive. Les vêtements pour sapeurs-pompiers (y compris casques, bottes de protection et gants) conformes à la Norme européenne EN 469 procurent un niveau de protection de base contre les accidents chimiques. Équipement de protection spécial pour le personnel préposé à la lutte contre l'incendie : : : 5.3 Conseils aux pompiers Précautions spéciales pour les pompiers : 6.2 Précautions pour la protection de l'environnement Arrêter la fuite si cela ne présente aucun risque. Écarter les conteneurs de la zone de déversement accidentel. S'approcher des émanations dans la même direction que le vent. Bloquer toute pénétration possible dans les égouts, les cours d'eau, les caves ou les zones confinées. Laver le produit répandu dans une installation de traitement des effluents ou procéder comme suit. Contenir les fuites et les ramasser à l'aide de matières absorbantes non combustibles telles que le sable, la terre, la vermiculite, la terre à diatomées. Les placer ensuite dans un récipient pour élimination conformément à la réglementation locale. Élimination par une entreprise Évitez la dispersion des matériaux déversés, ainsi que leur écoulement et tout contact avec le sol, les cours d'eau, les égouts et conduits d'évacuation. Informez les autorités compétentes en cas de pollution de l'environnement (égouts, voies d'eau, sol et air) par le produit. Matière propre à polluer l'eau. Peut-être nocif pour l'environnement en cas de déversement de grandes quantités. Grand déversement accidentel : Arrêter la fuite si cela ne présente aucun risque. Écarter les conteneurs de la zone de déversement accidentel. Diluer avec de l'eau et éponger si la matière est soluble dans l'eau. Sinon, ou si la matière est insoluble dans l'eau, absorber avec un matériau sec inerte et placer dans un conteneur à déchets approprié. Élimination par une entreprise autorisée de collecte des déchets. Petit déversement accidentel : 6.3 Méthodes et matériel de confinement et de nettoyage SECTION 6: Mesures à prendre en cas de dispersion accidentelle 6.1 Précautions individuelles, équipement de protection et procédures d'urgence Pour le personnel autre que le personnel d'intervention : Pour les agents d'intervention : Aucune initiative ne doit être prise qui implique un risque individuel ou en l'absence de formation appropriée. Évacuer les environs. Empêcher l'accès aux personnes non requises et ne portant pas de vêtements de protection. NE PAS TOUCHER ni marcher dans le produit répandu. Éviter de respirer les vapeurs ou le brouillard. Assurer une ventilation adéquate. Porter un appareil de protection respiratoire approprié lorsque le système de ventilation est inadéquat. Porter un équipement de protection individuelle adapté. Si des vêtements spécifiques sont nécessaires pour traiter le déversement, consulter la section 8 pour les matériaux appropriés et inappropriés. Voir également la section 8 pour plus d'informations sur les mesures d'hygiène. : Date d'édition / Date de révision : 3 Août 2011 5/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 6/19 SECTION 6: Mesures à prendre en cas de dispersion accidentelle autorisée de collecte des déchets. Les matériaux absorbants contaminés peuvent présenter les mêmes risques que le produit répandu. 6.4 Référence à d'autres sections Voir section 1 pour les coordonnées d'urgence. Voir la section 8 pour toute information sur les équipements de protection individuelle adaptés. Voir la section 13 pour toute information supplémentaire sur le traitement des déchets. : Stocker entre les températures suivantes: 2 à 40°C (35.6 à 104°F). Stocker conformément à la réglementation locale. Stocker dans le récipient d'origine à l'abri de la lumière directe du soleil dans un endroit sec, frais et bien ventilé à l'écart des matériaux incompatibles (cf. la section 10). Garder le récipient hermétiquement fermé lorsque le produit n'est pas utilisé. Les récipients ayant été ouverts doivent être refermés avec soin et maintenus en position verticale afin d'éviter les fuites. Ne pas stocker dans des conteneurs non étiquetés. Utiliser un récipient approprié pour éviter toute contamination du milieu ambiant. SECTION 7: Manipulation et stockage Les informations de cette section contiennent des directives et des conseils généraux. Consulter la liste des Utilisations Identifiées de la section 1 pour toute information spécifique aux usages disponible dans le(s) scénario(s) d'exposition. 7.1 Précautions à prendre pour une manipulation sans danger Mesures de protection : Conseils sur l'hygiène professionnelle en général : 7.2 Conditions d'un stockage sûr, y compris d'éventuelles incompatibilités 7.3 Utilisations finales spécifiques Recommandations : Solutions spécifiques au : secteur industriel Non disponible. Non disponible. Revêtir un équipement de protection individuelle approprié (voir Section 8). Les personnes ayant des antécédents de sensibilisation cutanée ne doivent pas intervenir dans les processus utilisant ce produit. Ne pas mettre en contact avec les yeux, la peau ou les vêtements. Ne pas ingérer. Éviter de respirer les vapeurs ou le brouillard. Éviter le rejet dans l'environnement. Consulter les instructions spéciales/la fiche de données de sécurité. Garder dans le conteneur d'origine ou dans un autre conteneur de substitution homologué fabriqué à partir d'un matériau compatible et tenu hermétiquement clos lorsqu'il n'est pas utilisé. Les conteneurs vides retiennent des résidus de produit et peuvent présenter un danger. Ne pas réutiliser ce conteneur. Il est interdit de manger, boire ou fumer dans les endroits où ce produit est manipulé, entreposé ou mis en oeuvre. Il est recommandé au personnel de se laver les mains et la figure avant de manger, boire ou fumer. Retirer les vêtements contaminés et les équipements de protection avant d'entrer dans un lieu de restauration. Voir également la section 8 pour plus d'informations sur les mesures d'hygiène. : Classe de danger de stockage Huntsman Advanced Materials : Classe de stockage 10, Liquide nocif pour l'ambience Date d'édition / Date de révision : 3 Août 2011 6/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 7/19 Procédures de surveillance recommandées Limites d'exposition professionnelle Si ce produit contient des ingrédients présentant des limites d'exposition, il peut s'avérer nécessaire d'effectuer un examen suivi des personnes, de l'atmosphère sur le lieu de travail ou des organismes vivants pour déterminer l'efficacité de la ventilation ou d'autres mesures de contrôle ou évaluer le besoin d'utiliser du matériel de protection des voies respiratoires. Il importe de vous reporter à la norme européenne EN 689 concernant les méthodes pour évaluer l'exposition par inhalation aux agents chimiques et aux documents de politique générale nationaux relatifs aux méthodes pour déterminer les substances dangereuses. Protection des mains Le port de gants imperméables et résistants aux produits chimiques conformes à une norme approuvée, est obligatoire en tout temps lors de la manutention de produits chimiques si une évaluation des risques le préconise. Utiliser une protection oculaire conforme à une norme approuvée dès lors qu'une évaluation du risque indique qu'il est nécessaire d'éviter l'exposition aux projections de liquides, aux fines particules pulvérisées ou aux poussières. Protection oculaire/faciale Aucune valeur de limite d'exposition connue. : : : Protection de la peau Contrôles d'ingénierie appropriés : Aucune ventilation particulière requise. Une bonne ventilation générale devrait être suffisante pour contrôler l'exposition du technicien aux contaminants en suspension dans l'air. Si ce produit contient des composants pour lesquels des contraintes liées à l'exposition existent, utiliser des enceintes de protection, une ventilation locale par aspiration, ou d'autres moyens de contrôle automatiques intégrés afin de maintenir le seuil d'exposition du technicien inférieur aux limites recommandées ou légales. Se laver abondamment les mains, les avant-bras et le visage après avoir manipulé des produits chimiques, avant de manger, de fumer et d'aller aux toilettes ainsi qu'à la fin de la journée de travail. Il est recommandé d'utiliser les techniques appropriées pour retirer les vêtements potentiellement contaminés. Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail. Laver les vêtements contaminés avant de les réutiliser. S'assurer que les dispositifs rince-oeil automatiques et les douches de sécurité se trouvent à proximité de l'emplacement des postes de travail. 8.2 Contrôles de l'exposition Mesures d'hygiène : Aucune DEL disponible. Concentrations prédites avec effet Aucune PEC disponible. SECTION 8: Contrôles de l'exposition/protection individuelle Les informations de cette section contiennent des directives et des conseils généraux. Consulter la liste des Utilisations Identifiées de la section 1 pour toute information spécifique aux usages disponible dans le(s) scénario(s) d'exposition. 8.1 Paramètres de contrôle Doses dérivées avec effet Mesures de protection individuelles Les limites d'exposition sur la place de travail doivent être dans les normes (poussière totale, poussière de quartz potentiellement inhalable). Si les limites sont dépassées, portez un masque à poussière approprié. A T T E N T I O N ! Ce produit contient du quartz, classé par l'IARC parmi les substances carcinogènes pour l'homme (Groupe 1), pouvant causer une silicose ou un cancer des poumons par inhalation des poussières. Il est donc important d'éviter de s'exposer à toute inhalation lors des opérations mécaniques effectuées avec le produit fini (mouture, décapage, coupe...). QUARTZ (CAS RN 14808-60-7): France: TWA: 0.1 mg/m³ 8 hour(s). Form: respirable aerosol Suisse: TWA: 0.15 mg/m³ 8 hour(s). Form: respirable dust Belgique: TWA: 0.1 mg/m³ 8 hour(s). Form: respirable dust Date d'édition / Date de révision : 3 Août 2011 7/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 8/19 SECTION 8: Contrôles de l'exposition/protection individuelle Lorsque la ventilation du local est insuffisante, porter un équipement de protection respiratoire. Le choix de l'appareil de protection respiratoire doit être fondé sur les niveaux d'expositions prévus ou connus, les dangers du produit et les limites d'utilisation sans danger de l'appareil de protection respiratoire retenu. Protection respiratoire : L'équipement de protection personnel pour le corps devra être choisi en fonction de la tâche à réaliser ainsi que des risques encourus, et il est recommandé de le faire valider par un spécialiste avant de procéder à la manipulation du produit. : Contrôle de l'exposition de l'environnement : Il importe de tester les émissions provenant des systèmes de ventilation ou du matériel de fabrication pour vous assurer qu'elles sont conformes aux exigences de la législation sur la protection de l'environnement. Dans certains cas, il sera nécessaire d'équiper le matériel de fabrication d'un épurateur de gaz ou d'un filtre ou de le modifier techniquement afin de réduire les émissions à des niveaux acceptables. Protection corporelle : Autre protection cutanée Des chaussures adéquates et toutes mesures de protection corporelle devraient être déterminées en fonction de l'opération effectuée et des risques impliqués, et devraient être approuvées par un spécialiste avant toute manipulation de ce produit. Alcool éthylvinylique laminé (EVAL), caoutchouc butyle néoprène, Matériaux pour gants caoutchouc nitrile pour utilisation à court terme/projection (10 min480 min): Non disponible. État physique Point de fusion/point de congélation Point d'ébullition initial et intervalle d'ébullition Liquide. [Pâte.] Non disponible. Odeur Non disponible. pH Couleur Non disponible. Vitesse d'évaporation Non disponible. Point d'éclair Vase clos: >100°C [DIN 51758 EN 22719 (Pensky-Martens Closed Cup)] Non disponible. Non disponible. Seuil d'odeur Non disponible. Limites supérieures/inférieures d'inflammabilité ou d'explosion : : : : : : : : : : 9.1 Informations sur les propriétés physiques et chimiques essentielles Aspect Durée de combustion Non applicable. Vitesse de combustion Non applicable. : : SECTION 9: Propriétés physiques et chimiques Inflammabilité (solide, gaz) : Non disponible. Date d'édition / Date de révision : 3 Août 2011 8/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 9/19 SECTION 9: Propriétés physiques et chimiques Pression de vapeur Densité relative Densité de vapeur Solubilité(s) Non disponible. Non disponible. Non disponible. Température d'autoinflammation Non disponible. Non disponible. Non disponible. Viscosité Non disponible. Coefficient de partage noctanol/ eau Propriétés d'explosivité : : : : : : : Propriétés comburantes : Non disponible. 9.2 Autres informations Température de décomposition : Non disponible. Masse volumique : 1.4 g/cm3 [20°C (68°F)] Solubilité dans l'eau : 10.6 Produits de décomposition dangereux 10.4 Conditions à éviter Aucune donnée spécifique. Dans des conditions normales de stockage et d'utilisation, aucun produit de décomposition dangereux ne devrait apparaître. 10.2 Stabilité chimique Le produit est stable. Aucune donnée spécifique. : : : 10.5 Matières incompatibles : 10.3 Possibilité de réactions dangereuses : Dans des conditions normales de stockage et d'utilisation, aucune réaction dangereuse ne se produit. SECTION 10: Stabilité et réactivité 10.1 Réactivité : Aucune donnée d'essai spécifique relative à la réactivité n'est disponible pour ce produit ou ses composants. Toxicité aiguë produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) CL0 Inhalation Vapeurs Rat - Mâle 0.00001 ppm 5 heures DL50 Cutané Rat - Mâle, Femelle >2000 mg/kg - DL50 Orale Rat - Femelle >2000 mg/kg - résine époxidique à base de bisphénol F DL50 Cutané Rat - Mâle, Femelle >2000 mg/kg - DL50 Orale Rat - Mâle, >5000 mg/kg - Nom du produit/composant Endpoint Espèces Résultat Exposition SECTION 11: Informations toxicologiques 11.1 Informations sur les effets toxicologiques Date d'édition / Date de révision : 3 Août 2011 9/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 10/19 SECTION 11: Informations toxicologiques Femelle éther diglycidique du 1,4- butanediol DL50 Cutané Rat - Mâle, Femelle >2150 mg/kg - DL50 Orale Rat - Mâle, Femelle 1163 mg/kg - N(3-diméthylaminopropyl)- 1,3-propylènediamine DL50 Cutané Lapin 1310 mg/kg - DL50 Orale Rat 1670 mg/kg - Mutagénicité Irritation/Corrosion produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) OECD 404 Effet irritant/corrosif aigu sur la peau Lapin Faiblement irritant OECD 405 Effet irritant/corrosif aigu sur les yeux Lapin Faiblement irritant résine époxidique à base de bisphénol F OECD 405 Effet irritant/corrosif aigu sur les yeux Lapin Non irritant. OECD 404 Effet irritant/corrosif aigu sur la peau Lapin Faiblement irritant éther diglycidique du 1,4- butanediol OECD 404 Effet irritant/corrosif aigu sur la peau Lapin Non irritant. OECD 405 Effet irritant/corrosif aigu sur les yeux Lapin Irritant puissant Nom du produit/composant Test Résultat Conclusion/Résumé : Peau : produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700): Légèrement irritant pour la peau. résine époxidique à base de bisphénol F: Légèrement irritant pour la peau. éther diglycidique du 1,4-butanediol: Non irritant pour la peau. Yeux : produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700): Légèrement irritant pour les yeux. résine époxidique à base de bisphénol F: Non irritant pour les yeux. éther diglycidique du 1,4-butanediol: Gravement irritant pour les yeux. Non disponible. Sensibilisant produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) OECD 429 Sensibilisation cutanée : essai des ganglions lymphatiques locaux peau Souris Sensibilisant résine époxidique à base de bisphénol F OECD 429 Sensibilisation cutanée : essai des ganglions lymphatiques locaux peau Souris Sensibilisant éther diglycidique du 1,4- butanediol OECD 406 Sensibilisation de la peau peau cobaye Sensibilisant Nom du produit/composant Test Voie d'exposition Résultat Conclusion/Résumé : Non disponible. Espèces Espèces Date d'édition / Date de révision : 3 Août 2011 10/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 11/19 SECTION 11: Informations toxicologiques Cancérogénicité produit de réaction: bisphénol-Aépichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) OECD 453 Etudes combinées de toxicité chronique et de cancérogénèse Rat 2 années; 7 jours par semaine Négatif Orale - OECD 453 Etudes combinées de toxicité chronique et de cancérogénèse Rat 2 années; 5 jours par semaine Négatif Cutané - OECD 453 Etudes combinées de toxicité chronique et de cancérogénèse Souris 2 années; 3 jours par semaine Négatif Cutané - Nom du produit/composant Test Espèces Exposition Résultat produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) OECD 471 Essai de mutation réverse sur des bactéries Positif OECD 476 Essai in vitro de mutation génique sur des cellules de mammifères Positif OECD 478 Toxicologie génétique : Essai de mutation létale dominante chez le rongeur Négatif EPA OPPTS Négatif résine époxidique à base de bisphénol F OECD 471 Essai de mutation réverse sur des bactéries Positif OECD 476 Essai in vitro de mutation génique sur des cellules de mammifères Positif OECD 473 Essai d'aberration chromosomique in vitro chez les mammifères Positif OECD 474 Le test de micronoyaux sur les érythrocytes de mammifère Négatif OECD 486 Essai de synthèse non programmée de l'ADN (UDS) sur des hépatocytes de mammifères in vivo Négatif éther diglycidique du 1,4- butanediol OECD 471 Essai de mutation réverse sur des bactéries Positif OECD 473 Essai d'aberration chromosomique in vitro chez les mammifères Positif OECD 474 Le test de micronoyaux sur les érythrocytes de mammifère Négatif Nom du produit/composant Test Résultat Conclusion/Résumé : Non disponible. Toxicité pour la reproduction Nom du produit/composant Test Espèces Résultat/Type de résultat Organes cibles Voie d'exposition Organes cibles Date d'édition / Date de révision : 3 Août 2011 11/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 12/19 SECTION 11: Informations toxicologiques Effets chroniques potentiels pour la santé Effets aigus potentiels sur la santé Inhalation : L'exposition aux produits de décomposition peut présenter des risques pour la santé. Les effets graves d'une exposition peuvent être différés. Irritant pour la bouche, Ingestion : la gorge et l'estomac. Contact avec la peau : Irritant pour la peau. Peut entraîner une sensibilisation par contact avec la peau. Contact avec les yeux : Gravement irritant pour les yeux. Risque de lésions oculaires graves. Nom du produit/composant Test Type de résultat Résultat Organes cibles Tératogénicité produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) OECD 414 Etude de la toxicité pour le développement prénatal Rat - Femelle >540 mg/kg Pas d'effets observés à : EPA CFR Lapin - Femelle >300 mg/kg Pas d'effets observés à : OECD 414 Etude de la toxicité pour le développement prénatal Lapin - Femelle 180 mg/kg NOAEL résine époxidique à base de bisphénol F EPA CFR Lapin - Femelle >300 mg/kg Pas d'effets observés à : Nom du produit/composant Test Espèces Résultat/Type de résultat produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) OECD 416 Étude de toxicité pour la reproduction sur deux générations Rat Orale: 540 mg/kg Pas d'effets observés à : - résine époxidique à base de bisphénol F OECD 416 Étude de toxicité pour la reproduction sur deux générations Rat Orale: 540 mg/kg Pas d'effets observés à : - Symptômes correspondant aux caractéristiques physiques, chimiques et toxicologiques Contact avec la peau Ingestion Inhalation Aucune donnée spécifique. Aucune donnée spécifique. Les symptômes néfastes peuvent éventuellement comprendre ce qui suit: irritation rougeur : : : Contact avec les yeux : Les symptômes néfastes peuvent éventuellement comprendre ce qui suit: douleur ou irritation larmoiement rougeur Informations sur les voies Non disponible. d'exposition probables : Effets retardés, effets immédiats et effets chroniques d'une exposition à court ou long terme Exposition de courte durée Exposition prolongée Effets potentiels immédiats Effets potentiels différés : : Effets potentiels immédiats Effets potentiels différés : : Non disponible. Non disponible. Non disponible. Non disponible. Date d'édition / Date de révision : 3 Août 2011 12/19 ARALDITE 2014-1 Conforme au règlement (CE) n° 1907/2006 (REACH), Annexe II - France Date d'impression : Date d'édition : 3 Août 2011 3 Août 2011 N° de FDS. Version : : 00057058 1 13/19 SECTION 11: Informations toxicologiques Une fois sensibilisé, une vive réaction allergique peut éventuellement se déclencher lors d'une exposition ultérieure à de très faibles niveaux. Généralités : Aucun effet important ou Cancérogénicité : danger critique connu. Mutagénicité : Aucun effet important ou danger critique connu. Tératogénicité : Aucun effet important ou danger critique connu. produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) OECD 408 Toxicité orale à doses répétées –rongeurs : 90 jours NOAEL Subchronique NOAEL Oral 50 mg/kg - OECD 411 Toxicité cutanée subchronique : 90 jours Pas d'effets observés à : Subchronique Pas d'effets observés à : Dermal 10 mg/kg - OECD 411 Toxicité cutanée subchronique : 90 jours NOAEL Subchronique NOAEL Dermal 100 mg/kg - résine époxidique à base de bisphénol F OECD 408 Toxicité orale à doses répétées –rongeurs : 90 jours NOAEL Subchronique NOAEL Oral 250 mg/kg - éther diglycidique du 1,4- butanediol OECD 407 Toxicité orale à dose répétée - pendant 28 jours sur les rongeurs NOAEL Subchronique NOAEL Oral 200 mg/kg - Conclusion/Résumé : Non disponible. Effets sur le développement : Aucun effet important ou danger critique connu. Effets sur la fertilité : Aucun effet important ou danger critique connu. Autres informations : Non disponible. 12.1 Toxicité produit de réaction: bisphénol-A-épichlorhydrine; résines époxydiques (poids moléculaire moyen < 700) - Aiguë CE50 72 heures Static Algues 9.4 mg/L OECD 202 Daphnia sp. Essai d'immobilisation immédiate Aiguë CE50 48 heures Static Daphnie 1.7 mg/L - Aiguë CI50 3 heures Static Bactéries >100 mg/L OECD 203 Poisson, essai de toxicité aiguë Aiguë CL50 96 heures Static Poisson 1.5 mg/L OECD 211 Daphnia magna, essai de reproduction Chronique NOEC 21 jours Semistatic Daphnie 0.3 mg/L résine époxidique à base de bisphénol F OECD 201 Algues, essai d'inhibition de la croissance Aiguë CE50 72 heures Static Algues 1.8 mg/L OECD OECD 202: Part I (Daphnia sp., Acute Immobilisation test) Aiguë CE50 48 heures Static Daphnie 1.

automotive applications beyond NXP Semiconductors’ standard warranty and NXP Semiconductors’ product specifications. 9.4 Trademarks Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners. Adelante, Bitport, Bitsound, CoolFlux, CoReUse, DESFire, EZ-HV, FabKey, GreenChip, HiPerSmart, HITAG, I²C-bus logo, ICODE, I-CODE, ITEC, Labelution, MIFARE, MIFARE Plus, MIFARE Ultralight, MoReUse, QLPAK, Silicon Tuner, SiliconMAX, SmartXA, STARplug, TOPFET, TrenchMOS, TriMedia and UCODE — are trademarks of NXP B.V. HD Radio and HD Radio logo — are trademarks of iBiquity Digital Corporation. 10. Contact information For more information, please visit: For sales office addresses, please send an email to: salesaddresses@nxp.comNXP Semiconductors PSMN1R7-30YL N-channel 30 V 1.7 mΩ logic level MOSFET in LFPAK © NXP B.V. 2011. All rights reserved. For more information, please visit: For sales office addresses, please send an email to: salesaddresses@nxp.com Date of release: 30 May 2011 Document identifier: PSMN1R7-30YL Please be aware that important notices concerning this document and the product(s) described herein, have been included in section ‘Legal information’. 11. Contents 1 Product profile . . . . . 1 1.1 General description . . . . . 1 1.2 Features and benefits. . . . . 1 1.3 Applications . . . . . 1 1.4 Quick reference data . . . . . 1 2 Pinning information. . . . . 2 3 Ordering information. . . . . 2 4 Limiting values. . . . . 3 5 Thermal characteristics . . . . . 5 6 Characteristics. . . . . 6 7 Package outline . . . . . 11 8 Revision history. . . . . 12 9 Legal information. . . . . 13 9.1 Data sheet status . . . . . 13 9.2 Definitions. . . . . 13 9.3 Disclaimers . . . . . 13 9.4 Trademarks. . . . . 14 10 Contact information. . . . . 14 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state Rev. 01 — 13 August 2009 Product data sheet Rev. 01 — 13 August 2009 2 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 3. Ordering information 4. Functional diagram Table 1. Ordering information Type number Package Temperature range Name Description Version 74VHC126D -40 °C to +125 °C SO14 plastic small outline package; 14 leads; body width 3.9 mm SOT108-1 74VHCT126D 74VHC126PW -40 °C to +125 °C TSSOP14 plastic thin shrink small outline package; 14 leads; body width 4.4 mm SOT402-1 74VHCT126PW 74VHC126BQ -40 °C to +125 °C DHVQFN14 plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 14 terminals; body 2.5 ´ 3 ´ 0.85 mm SOT762-1 74VHCT126BQ Fig 1. Functional diagram mna235 2 1A 1Y 1 3 1OE 5 2A 2Y 4 6 2OE 9 3A 3Y 10 8 3OE 12 4A 4Y 13 11 4OE Fig 2. Logic symbol Fig 3. IEC logic symbol mna234 nOE nA nY mna236 1 EN1 1 3 2 4 6 5 10 8 9 13 11 12 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 3 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 5. Pinning information 5.1 Pinning 5.2 Pin description (1) The die substrate is attached to this pad using conductive die attach material. It can not be used as a supply pin or input. Fig 4. Pin configuration SO14 and TSSOP14 Fig 5. Pin configuration DHVQFN14 74VHC126 74VHCT126 1OE VCC 1A 4OE 1Y 4A 2OE 4Y 2A 3OE 2Y 3A GND 3Y 001aak056 1 2 3 4 5 6 7 8 10 9 12 11 14 13 001aak076 74VHC126 74VHCT126 Transparent top view 2Y 3A 2A 3OE 2OE 4Y 1Y 4A 1A 4OE GND 3Y 1OE VCC 6 9 5 10 4 11 3 12 2 13 7 8 1 14 terminal 1 index area GND(1) Table 2. Pin description Symbol Pin Description 1OE 1 output enable input 1 (active HIGH) 1A 2 data input 1 1Y 3 data output 1 2OE 4 output enable input 2 (active HIGH) 2A 5 data input 2 2Y 6 data output 2 GND 7 ground (0 V) 3Y 8 data output 3 3A 9 data input 3 3OE 10 output enable input 3 (active HIGH) 4Y 11 data output 4 4A 12 data input 4 4OE 13 output enable input 4 (active HIGH) VCC 14 supply voltage 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 4 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 6. Functional description [1] H = HIGH voltage state; L = LOW voltage state; X = don’t care; Z = high-impedance OFF-state. 7. Limiting values [1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed. [2] For SO14 packages: above 70 °C the value of Ptot derates linearly at 8 mW/K. For TSSOP14 packages: above 60 °C the value of Ptot derates linearly at 5.5 mW/K. For DHVQFN14 packages: above 60 °C the value of Ptot derates linearly at 4.5 mW/K. Table 3. Function table[1] Control Input Output nOE nA nY H L L H H H L X Z Table 4. Limiting values In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V). Symbol Parameter Conditions Min Max Unit VCC supply voltage -0.5 +7.0 V VI input voltage -0.5 +7.0 V IIK input clamping current VI < -0.5 V [1] -20 - mA IOK output clamping current VO < -0.5 V or VO > VCC + 0.5 V [1] -20 +20 mA IO output current VO = -0.5 V to (VCC + 0.5 V) -25 +25 mA ICC supply current - +75 mA IGND ground current -75 - mA Tstg storage temperature -65 +150 °C Ptot total power dissipation Tamb = -40 °C to +125 °C [2] - 500 mW 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 5 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 8. Recommended operating conditions 9. Static characteristics Table 5. Operating conditions Symbol Parameter Conditions Min Typ Max Unit 74VHC126 VCC supply voltage 2.0 5.0 5.5 V VI input voltage 0 - 5.5 V VO output voltage 0 - VCC V Tamb ambient temperature -40 +25 +125 °C Dt/DV input transition rise and fall rate VCC = 3.0 V to 3.6 V - - 100 ns/V VCC = 4.5 V to 5.5 V - - 20 ns/V 74VHCT126 VCC supply voltage 4.5 5.0 5.5 V VI input voltage 0 - 5.5 V VO output voltage 0 - VCC V Tamb ambient temperature -40 +25 +125 °C Dt/DV input transition rise and fall rate VCC = 4.5 V to 5.5 V - - 20 ns/V Table 6. Static characteristics At recommended operating conditions; voltages are referenced to GND (ground = 0 V). Symbol Parameter Conditions 25 °C -40 °C to +85 °C -40 °C to +125 °C Unit Min Typ Max Min Max Min Max 74VHC126 VIH HIGH-level input voltage VCC = 2.0 V 1.5 - - 1.5 - 1.5 - V VCC = 3.0 V 2.1 - - 2.1 - 2.1 - V VCC = 5.5 V 3.85 - - 3.85 - 3.85 - V VIL LOW-level input voltage VCC = 2.0 V - - 0.5 - 0.5 - 0.5 V VCC = 3.0 V - - 0.9 - 0.9 - 0.9 V VCC = 5.5 V - - 1.65 - 1.65 - 1.65 V VOH HIGH-level output voltage VI = VIH or VIL IO = -50 mA; VCC = 2.0 V 1.9 2.0 - 1.9 - 1.9 - V IO = -50 mA; VCC = 3.0 V 2.9 3.0 - 2.9 - 2.9 - V IO = -50 mA; VCC = 4.5 V 4.4 4.5 - 4.4 - 4.4 - V IO = -4.0 mA; VCC = 3.0 V 2.58 - - 2.48 - 2.40 - V IO = -8.0 mA; VCC = 4.5 V 3.94 - - 3.80 - 3.70 - V VOL LOW-level output voltage VI = VIH or VIL IO = 50 mA; VCC = 2.0 V - 0 0.1 - 0.1 - 0.1 V IO = 50 mA; VCC = 3.0 V - 0 0.1 - 0.1 - 0.1 V IO = 50 mA; VCC = 4.5 V - 0 0.1 - 0.1 - 0.1 V IO = 4.0 mA; VCC = 3.0 V - - 0.36 - 0.44 - 0.55 V IO = 8.0 mA; VCC = 4.5 V - - 0.36 - 0.44 - 0.55 V 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 6 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state II input leakage current VI = 5.5 V or GND; VCC = 0 V to 5.5 V - - 0.1 - 1.0 - 2.0 mA IOZ OFF-state output current VI = VIH or VIL; VO = VCC or GND; VCC = 5.5 V - - ±0.25 - ±2.5 - ±10.0 mA ICC supply current VI = VCC or GND; IO = 0 A; VCC = 5.5 V - - 2.0 - 20 - 40 mA CI input capacitance VI = VCC or GND - 3 10 - 10 - 10 pF CO output capacitance - 4 - - - - - pF 74VHCT126 VIH HIGH-level input voltage VCC = 4.5 V to 5.5 V 2.0 - - 2.0 - 2.0 - V VIL LOW-level input voltage VCC = 4.5 V to 5.5 V - - 0.8 - 0.8 - 0.8 V VOH HIGH-level output voltage VI = VIH or VIL; VCC = 4.5 V IO = -50 mA 4.4 4.5 - 4.4 - 4.4 - V IO = -8.0 mA 3.94 - - 3.80 - 3.70 - V VOL LOW-level output voltage VI = VIH or VIL; VCC = 4.5 V IO = 50 mA - 0 0.1 - 0.1 - 0.1 V IO = 8.0 mA - - 0.36 - 0.44 - 0.55 V II input leakage current VI = 5.5 V or GND; VCC = 0 V to 5.5 V - - 0.1 - 1.0 - 2.0 mA IOZ OFF-state output current VI = VIH or VIL; VO = VCC or GND per input pin; other inputs at VCC or GND; IO = 0 A; VCC = 5.5 V - - ±0.25 - ±2.5 - ±10.0 mA ICC supply current VI = VCC or GND; IO = 0 A; VCC = 5.5 V - - 2.0 - 20 - 40 mA DICC additional supply current per input pin; VI = VCC - 2.1 V; other pins at VCC or GND; IO = 0 A; VCC = 4.5 V to 5.5 V - - 1.35 - 1.5 - 1.5 mA CI input capacitance VI = VCC or GND - 3 10 - 10 - 10 pF CO output capacitance - 4 - - - - - pF Table 6. Static characteristics ...continued At recommended operating conditions; voltages are referenced to GND (ground = 0 V). Symbol Parameter Conditions 25 °C -40 °C to +85 °C -40 °C to +125 °C Unit Min Typ Max Min Max Min Max 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 7 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 10. Dynamic characteristics Table 7. Dynamic characteristics Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 8. Symbol Parameter Conditions 25 °C -40 °C to +85 °C -40 °C to +125 °C Unit Min Typ[1] Max Min Max Min Max 74VHC126 tpd propagation delay nA to nY; see Figure 6 [2] VCC = 3.0 V to 3.6 V CL = 15 pF - 4.7 8.0 1.0 9.5 1.0 10.0 ns CL = 50 pF - 6.7 11.5 1.0 13.0 1.0 14.5 ns VCC = 4.5 V to 5.5 V CL = 15 pF - 3.3 5.5 1.0 6.5 1.0 7.0 ns CL = 50 pF - 4.7 7.5 1.0 8.5 1.0 9.5 ns ten enable time nOE to nY; see Figure 7 [3] VCC = 3.0 V to 3.6 V CL = 15 pF - 5.3 8.0 1.0 9.5 1.0 10.0 ns CL = 50 pF - 7.6 11.5 1.0 13.0 1.0 14.5 ns VCC = 4.5 V to 5.5 V CL = 15 pF - 3.6 5.3 1.0 6.1 1.0 7.0 ns CL = 50 pF - 5.1 7.6 1.0 8.7 1.0 9.5 ns tdis disable time nOE to nY; see Figure 7 [4] VCC = 3.0 V to 3.6 V CL = 15 pF - 6.6 9.7 1.0 11.5 1.0 12.5 ns CL = 50 pF - 9.4 13.2 1.0 15.0 1.0 16.5 ns VCC = 4.5 V to 5.5 V CL = 15 pF - 4.7 6.8 1.0 8.0 1.0 8.5 ns CL = 50 pF - 6.7 8.8 1.0 10.0 1.0 11.0 ns CPD power dissipation capacitance fi = 1 MHz; VI = GND to VCC [5] - 10 - - - - - pF 74VHCT126; VCC = 4.5 V to 5.5 V tpd propagation delay nA to nY; see Figure 6 [2] CL = 15 pF - 3.0 5.5 1.0 6.5 1.0 7.0 ns CL = 50 pF - 4.3 7.5 1.0 8.5 1.0 9.5 ns ten enable time nOE to nY; see Figure 7 [3] CL = 15 pF - 3.3 5.1 1.0 6.0 1.0 6.5 ns CL = 50 pF - 4.7 7.1 1.0 8.0 1.0 9.0 ns tdis disable time nOE to nY; see Figure 7 [4] CL = 15 pF - 4.8 6.8 1.0 8.0 1.0 8.5 ns CL = 50 pF - 6.9 8.9 1.0 10.0 1.0 11.5 ns CPD power dissipation capacitance fi = 1 MHz; VI = GND to VCC [5] - 12 - - - - - pF 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 8 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state [1] Typical values are measured at nominal supply voltage (VCC = 3.3 V and VCC = 5.0 V). [2] tpd is the same as tPLH and tPHL. [3] ten is the same as tPZL and tPZH. [4] tdis is the same as tPLZ and tPHZ. [5] CPD is used to determine the dynamic power dissipation (PD in mW). PD = CPD ´ VCC 2 ´ fi ´ N + S(CL ´ VCC 2 ´ fo) where: fi = input frequency in MHz; fo = output frequency in MHz; CL = output load capacitance in pF; VCC = supply voltage in V; N = number of inputs switching; S(CL ´ VCC 2 ´ fo) = sum of the outputs. 11. Waveforms Measurement points are given in Table 8. VOL and VOH are typical voltage output levels that occur with the output load. Fig 6. Input to output propagation delays mna237 tPHL tPLH VM nA input VM nY output GND VI VOH VOL Measurement points are given in Table 8. VOL and VOH are typical voltage output levels that occur with the output load. Fig 7. Enable and disable times mna949 tPLZ tPHZ outputs disabled outputs enabled VY VX outputs enabled output LOW-to-OFF OFF-to-LOW output HIGH-to-OFF OFF-to-HIGH nOE input VOL VOH VCC VI VM GND GND tPZL tPZH VM VM 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 9 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state Table 8. Measurement points Type Input Output VM VM VX VY 74VHC126 0.5VCC 0.5VCC VOL + 0.3 V VOH - 0.3 V 74VHCT126 1.5 V 0.5VCC VOL + 0.3 V VOH - 0.3 V Test data is given in Table 9. Definitions test circuit: RT = termination resistance should be equal to output impedance Zo of the pulse generator. CL = load capacitance including jig and probe capacitance. RL = load resistance. S1 = test selection switch. Fig 8. Test circuitry for measuring switching times VM VM tW tW 10 % 90 % 0 V VI VI negative pulse positive pulse 0 V VM VM 90 % 10 % tf tr tr tf 001aad983 DUT VCC VCC VI VO RT RL S1 CL G open Table 9. Test data Type Input Load S1 position VI tr, tf CL RL tPHL, tPLH tPZH, tPHZ tPZL, tPLZ 74VHC126 VCC £ 3.0 ns 15 pF, 50 pF 1 kW open GND VCC 74VHCT126 3.0 V £ 3.0 ns 15 pF, 50 pF 1 kW open GND VCC 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 10 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 12. Package outline Fig 9. Package outline SOT108-1 (SO14) UNIT A max. A1 A2 A3 bp c D(1) E(1) e HE L Lp Q v w y Z (1) q OUTLINE REFERENCES VERSION EUROPEAN PROJECTION ISSUE DATE IEC JEDEC JEITA mm inches 1.75 0.25 0.10 1.45 1.25 0.25 0.49 0.36 0.25 0.19 8.75 8.55 4.0 3.8 1.27 6.2 5.8 0.7 0.6 0.7 0.3 8 0 o o 0.25 0.1 DIMENSIONS (inch dimensions are derived from the original mm dimensions) Note 1. Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included. 1.0 0.4 SOT108-1 X w M q A A 1 A2 bp D HE Lp Q detail X E Z e c L v M A (A 3) A 7 8 1 14 y 076E06 MS-012 pin 1 index 0.069 0.010 0.004 0.057 0.049 0.01 0.019 0.014 0.0100 0.0075 0.35 0.34 0.16 0.15 0.05 1.05 0.041 0.244 0.228 0.028 0.024 0.028 0.012 0.01 0.25 0.01 0.004 0.039 0.016 99-12-27 03-02-19 0 2.5 5 mm scale SO14: plastic small outline package; 14 leads; body width 3.9 mm SOT108-1 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 11 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state Fig 10. Package outline SOT402-1 (TSSOP14) UNIT A1 A2 A3 bp c D(1) E (2) e HE L Lp Q v w y Z (1) q OUTLINE REFERENCES VERSION EUROPEAN PROJECTION ISSUE DATE IEC JEDEC JEITA mm 0.15 0.05 0.95 0.80 0.30 0.19 0.2 0.1 5.1 4.9 4.5 4.3 0.65 6.6 6.2 0.4 0.3 0.72 0.38 8 0 o 1 0.2 0.13 0.1 o DIMENSIONS (mm are the original dimensions) Notes 1. Plastic or metal protrusions of 0.15 mm maximum per side are not included. 2. Plastic interlead protrusions of 0.25 mm maximum per side are not included. 0.75 0.50 SOT402-1 MO-153 99-12-27 03-02-18 w M bp D Z e 0.25 1 7 14 8 q A A1 A2 Lp Q detail X L (A 3) HE E c v M A X A y 0 2.5 5 mm scale TSSOP14: plastic thin shrink small outline package; 14 leads; body width 4.4 mm SOT402-1 A max. 1.1 pin 1 index 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 12 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state Fig 11. Package outline SOT762-1 (DHVQFN14) terminal 1 index area 1 0.5 UNIT A1 b Eh e y 0.2 c OUTLINE REFERENCES VERSION EUROPEAN PROJECTION ISSUE DATE IEC JEDEC JEITA mm 3.1 2.9 Dh 1.65 1.35 y1 2.6 2.4 1.15 0.85 e1 2 0.30 0.18 0.05 0.00 0.05 0.1 DIMENSIONS (mm are the original dimensions) SOT762-1 - - - MO-241 - - - 0.5 0.3 L 0.1 v 0.05 w 0 2.5 5 mm scale SOT762-1 DHVQFN14: plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 14 terminals; body 2.5 x 3 x 0.85 mm A(1) max. A A1 c detail X e y1 C y L Eh Dh e e1 b 2 6 13 9 8 1 7 14 X D E C B A 02-10-17 03-01-27 terminal 1 index area C A C v M B w M E(1) Note 1. Plastic or metal protrusions of 0.075 mm maximum per side are not included. D(1) 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 13 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 13. Abbreviations 14. Revision history Table 10. Abbreviations Acronym Description CDM Charged Device Model CMOS Complementary Metal-Oxide Semiconductor DUT Device Under Test ESD ElectroStatic Discharge HBM Human Body Model LSTTL Low-power Schottky Transistor-Transistor Logic MM Machine Model Table 11. Revision history Document ID Release date Data sheet status Change notice Supersedes 74VHC_VHCT126_1 20090813 Product data sheet - - 74VHC_VHCT126_1 © NXP B.V. 2009. All rights reserved. Product data sheet Rev. 01 — 13 August 2009 14 of 15 NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state 15. Legal information 15.1 Data sheet status [1] Please consult the most recently issued document before initiating or completing a design. [2] The term ‘short data sheet’ is explained in section “Definitions”. [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL . 15.2 Definitions Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information. Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail. 15.3 Disclaimers General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof. Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer’s own risk. Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability. Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail. No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights. Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities. 15.4 Trademarks Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners. 16. Contact information For more information, please visit: For sales office addresses, please send an email to: salesaddresses@nxp.com Document status[1][2] Product status[3] Definition Objective [short] data sheet Development This document contains data from the objective specification for product development. Preliminary [short] data sheet Qualification This document contains data from the preliminary specification. Product [short] data sheet Production This document contains the product specification. NXP Semiconductors 74VHC126; 74VHCT126 Quad buffer/line driver; 3-state © NXP B.V. 2009. All rights reserved. For more information, please visit: For sales office addresses, please send an email to: salesaddresses@nxp.com Date of release: 13 August 2009 Document identifier: 74VHC_VHCT126_1 Please be aware that important notices concerning this document and the product(s) described herein, have been included in section ‘Legal information’. Product specification July 1998 DISCRETE SEMICONDUCTORS BYV79E series Rectifier diodes ultrafast, rugged Semiconductors Product specification Rectifier diodes BYV79E series ultrafast, rugged FEATURES SYMBOL QUICK REFERENCE DATA • Low forward volt drop VR = 150 V/ 200 V • Fast switching • Soft recovery characteristic VF ≤ 0.9 V • Reverse surge capability • High thermal cycling performance IF(AV) = 14 A • Low thermal resistance IRRM ≤ 0.2 A trr ≤ 30 ns GENERAL DESCRIPTION PINNING SOD59 (TO220AC) Ultra-fast, epitaxial rectifier diodes PIN DESCRIPTION intended for use as output rectifiers in high frequency switched mode 1 cathode power supplies. 2 anode The BYV79E series is supplied in the conventional leaded SOD59 tab cathode (TO220AC) package. LIMITING VALUES Limiting values in accordance with the Absolute Maximum System (IEC 134). SYMBOL PARAMETER CONDITIONS MIN. MAX. UNIT BYV79E -150 -200 VRRM Peak repetitive reverse voltage - 150 200 V VRWM Crest working reverse voltage - 150 200 V VR Continuous reverse voltage Tmb ≤ 145˚C - 150 200 V IF(AV) Average forward current1 square wave - 14 A δ = 0.5; Tmb ≤ 120 ˚C IFRM Repetitive peak forward current t = 25 µs; δ = 0.5; - 28 A Tmb ≤ 120 ˚C IFSM Non-repetitive peak forward t = 10 ms - 150 A current t = 8.3 ms - 160 A sinusoidal; with reapplied VRWM(max) IRRM Repetitive peak reverse current tp = 2 µs; δ = 0.001 - 0.2 A IRSM Non-repetitive peak reverse tp = 100 µs - 0.2 A current Tstg Storage temperature -40 150 ˚C Tj Operating junction temperature - 150 ˚C 1. Neglecting switching and reverse current losses. ESD LIMITING VALUE SYMBOL PARAMETER CONDITIONS MIN. MAX. UNIT VC Electrostatic discharge Human body model; - 8 kV capacitor voltage C = 250 pF; R = 1.5 kΩ k a 1 2 1 tab 2 July 1998 1 Rev 1.200 Semiconductors Product specification Rectifier diodes BYV79E series ultrafast, rugged THERMAL RESISTANCES SYMBOL PARAMETER CONDITIONS MIN. TYP. MAX. UNIT Rth j-mb Thermal resistance junction to - - 2 K/W mounting base Rth j-a Thermal resistance junction to in free air - 60 - K/W ambient STATIC CHARACTERISTICS Tj = 25 ˚C unless otherwise stated SYMBOL PARAMETER CONDITIONS MIN. TYP. MAX. UNIT VF Forward voltage IF = 14 A; Tj = 150˚C - 0.83 0.90 V IF = 14 A - 0.95 1.05 V IF = 50 A - 1.2 1.4 V IR Reverse current VR = VRWM; Tj = 100 ˚C - 0.5 1.3 mA VR = VRWM - 5 50 µA Qs Reverse recovery charge IF = 2 A; VR ≥ 30 V; -dIF/dt = 20 A/µs - 6 15 nC trr1 Reverse recovery time IF = 1 A; VR ≥ 30 V; - 20 30 ns -dIF/dt = 100 A/µs trr2 Reverse recovery time IF = 0.5 A to IR = 1 A; Irec = 0.25 A - 13 22 ns Vfr Forward recovery voltage IF = 1 A; dIF/dt = 10 A/µs - 1 - V July 1998 2 Rev 1.200 Semiconductors Product specification Rectifier diodes BYV79E series ultrafast, rugged Fig.1. Definition of trr1, Qs and Irrm Fig.2. Definition of Vfr Fig.3. Circuit schematic for trr2 Fig.4. Definition of trr2 Fig.5. Maximum forward dissipation PF = f(IF(AV)); square current waveform where IF(AV) =IF(RMS) x √D. Fig.6. Maximum forward dissipation PF = f(IF(AV)); sinusoidal current waveform where a = form factor = IF(RMS) / IF(AV). Q s 10% 100% time dI dt F I R I F I rrm t rr I = 1A R I rec = 0.25A 0A trr2 0.5A IF IR time time V F V fr V F I F 0 5 10 15 20 25 0 5 10 15 20 0.5 0.2 0.1 BYV79 IF(AV) / A PF / W D = 1.0 Tmb(max) / C 150 140 130 120 110 Vo = 0.744 V Rs = 0.0112 Ohms tp D = tp T T t I shunt Current to ‘scope D.U.T. Voltage Pulse Source R 0 5 10 15 0 5 10 15 1.9 2.2 2.8 4 BYV79 IF(AV) / A PF / W Tmb(max) / C 150 140 130 a = 1.57 120 Vo = 0.744 V Rs = 0.0112 Ohms July 1998 3 Rev 1.200 Semiconductors Product specification Rectifier diodes BYV79E series ultrafast, rugged Fig.7. Maximum trr at Tj = 25 ˚C. Fig.8. Maximum Irrm at Tj = 25 ˚C. Fig.9. Typical and maximum forward characteristic IF = f(VF); parameter Tj Fig.10. Maximum Qs at Tj = 25 ˚C. Fig.11. Transient thermal impedance; Zth j-mb = f(tp). 1 10 trr / ns 1 10 100 1000 dIF/dt (A/us) IF=1A IF=10A 100 1.0 10 100 Qs / nC 1.0 10 100 -dIF/dt (A/us) 1000 IF=10A 5A 2A 10 1 0.1 0.01 Irrm / A 1 10 100 -dIF/dt (A/us) IF=10A IF=2A 1us 10us 100us 1ms 10ms 100ms 1s 10s 0.001 0.01 0.1 1 10 pulse width, tp (s) BYV79E Transient thermal impedance, Zth j-mb (K/W) tp D = tp T T P t D 0 2 60 50 40 30 20 10 0 max typ Tj = 150 C Tj = 25 C 0.5 1.0 IF / A VF / V 1.5 July 1998 4 Rev 1.200 Semiconductors Product specification Rectifier diodes BYV79E series ultrafast, rugged MECHANICAL DATA Dimensions in mm Net Mass: 2 g Fig.12. SOD59 (TO220AC). pin 1 connected to mounting base. Notes 1. Refer to mounting instructions for TO220 envelopes. 2. Epoxy meets UL94 V0 at 1/8". 10,3 max 3,7 2,8 3,0 3,0 max not tinned 1,3 max (2x) 2,4 0,6 4,5 max 5,9 min 15,8 max 1,3 0,9 max (2x) 13,5 min 5,08 1 2 July 1998 5 Rev 1.200 NXP Semiconductors Legal information DATA SHEET STATUS Notes 1. Please consult the most recently issued document before initiating or completing a design. 2. The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL . DOCUMENT STATUS(1) PRODUCT STATUS(2) DEFINITION Objective data sheet Development This document contains data from the objective specification for product development. Preliminary data sheet Qualification This document contains data from the preliminary specification. Product data sheet Production This document contains the product specification. DEFINITIONS Product specification The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet. DISCLAIMERS Limited warranty and liability Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory. Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors’ aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors. Right to make changes NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof. Suitability for use NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer’s own risk. Applications Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer’s sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer’s applications and products planned, as well as for the planned application and use of customer’s third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products. NXP Semiconductors Legal information NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer’s applications or products, or the application or use by customer’s third party customer(s). Customer is responsible for doing all necessary testing for the customer’s applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer’s third party customer(s). NXP does not accept any liability in this respect. Limiting values Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device. Terms and conditions of commercial sale NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer’s general terms and conditions with regard to the purchase of NXP Semiconductors products by customer. No offer to sell or license Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights. Export control This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities. Quick reference data The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding. Non-automotive qualified products Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications. In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors’ warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors’ specifications such use shall be solely at customer’s own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors’ standard warranty and NXP Semiconductors’ product specifications. Contact information For additional information please visit: For sales offices addresses send e-mail to: salesaddresses@nxp.com Customer notification This data sheet was changed to reflect the new company name NXP Semiconductors, including new legal definitions and disclaimers. No changes were made to the content, except for the legal definitions and disclaimers. © NXP B.V. 2011 All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof

MICRO 32 BITS ARM CORTEX M3 208LQFP MICRO 32 BITS ARM CORTEX M3 180TFBGA MICRO 32 BITS ARM CORTEX M3 208LQFP MICRO 32 BITS ARM CORTEX M3 208LQFP MICRO 32 BITS ARM CORTEX M3 208LQFP MICRO 32 BITS ARM CORTEX M3 144LQFP MICRO 32 BITS ARM CORTEX M3 100TFBGA MICRO 32 BITS ARM CORTEX M3 144LQFP MICRO 32 BITS ARM CORTEX M3 100TFBGA MICRO 32 BITS ARM CORTEX M3 144LQFP MICRO 32 BITS ARM CORTEX M3 100TFBGA MICRO 32 BITS ARM CORTEX M3 256LBGA MICRO 32 BITS ARM CORTEX M4 100TFBGA MICRO 32 BITS ARM CORTEX M3 144LQFP MICRO 32 BITS ARM CORTEX M3 100TFBGA MICRO 32 BITS ARM CORTEX M3 144LQFP MICRO 32 BITS ARM CORTEX M3 100TFBGA MICRO 32 BITS ARM CORTEX M3 256LBGA MICRO 32 BITS ARM CORTEX M3 144LQFP LED,ORANGE,1.2MM X 0.55MM,100MCD,605NM LED,YELLOW,1.2MM X 0.55MM,63MCD,590NM LED,YELLOW GREEN,1.2MM X 0.55MM,25MCD,572NM LED,SMD,WHITE,170MCD LED,RED,1.6MM X 2.3MM,63MCD,630NM LED,RED,1.6MM X 2.3MM,100MCD,620NM LED,ORANGE,1.6MM X 2.3MM,160MCD,605NM LED,GREEN,1.6MM X 2.3MM,18MCD,560NM LED,GREEN,1.6MM X 2.3MM,140MCD,525NM LED,YELLOW,1.6MM X 2.3MM,160MCD,590NM LED,YELLOW GREEN,1.6MM X 2.3MM,25MCD,572NM LED,BLUE,1.6MM X 2.3MM,100MCD,470NM LED,WHITE,84MW,900MCD SWITCH,SAFETY INTERLOCK,DPST,750MA,240V SWITCH,SAFETY INTERLOCK,DPST-NC,750MA,240V SWITCH,SAFETY INTERLOCK,DPST-NC,750MA,240V SWITCH,SAFETY INTERLOCK,DPST-NC,750MA,240V SWITCH,SAFETY INTERLOCK,DPST-NC,750MA,240V SWITCH,SAFETY INTERLOCK,3PST,750MA,240V SWITCH,SAFETY INTERLOCK,3PST,750MA,240V SWITCH,SAFETY INTERLOCK,3PST,750MA,240V SWITCH,SAFETY INTERLOCK,3PST,750MA,240V SWITCH,SAFETY INTERLOCK,3PST,750MA,240V SWITCH,SAFETY INTERLOCK,3PST-NC,750MA,240V AD9608,ADC,SPI,EVALUATION BOARD AD9628,ADC,SPI,EVALUATION BOARD RECEIVER IC LED,XLAMP XP-E,AMBER,62LM,SMD LED,BLUE,780MCD,470NM LED,BLUE,1.1CD,470NM LED,BLUE,1.5CD,470NM LED,WARM WHITE,2.5CD,6LM LED,COOL WHITE,2.8CD LED,COOL WHITE,2.8CD,7LM LED,COOL WHITE,3.8CD,9.5LM LED,BLUE,450MCD,470NM LED,BLUE,450MCD,470NM LED,GREEN,1.3CD,527NM LED,AMBER,5CD,591NM LED,AMBER,1.5CD,591NM LED,BLUE,550MCD,470NM WRENCH,DISCONNECT,& ASSEMBLY TOOL TWEEZER,CROSS ACTION,160MM TWEEZER,CERAMIC,140MM TWEEZER,RADIO,155MM SOLDERING IRON 25W,UK PLUG SOLDERING IRON 40W,UK PLUG TIP,25W TIP,40W SCREWDRIVER SET,WATCHMAKER,SET 4 SCREWDRIVER,ROBERTSON,SIZE 1 SCREWDRIVER,ROBERTSON,SIZE 2 SCREWDRIVER,ROBERTSON,SIZE 3 POWDER,CHALK,RED,100G SQUARE,JOINERS,225MM PLIERS,CIRCLIP,INSIDE,170MM PLIERS,CIRCLIP,INSIDE,180MM PLIERS,CIRCLIP,OUTSIDE,180MM PLIERS,CIRCLIP,OUTSIDE,BENT,180MM HAMMER,ENGINEERS,1LB GUN,GLUE,80W,UK PLUG STICK,GLUE 100 X 11MM,PK OF 25 KNIFE,CABLE,NO.28HX STRIPPER,AUTOMATIC,NO.6-16 PLIERS,CRIMPING,0.25-2.5MM,140MM PLIERS,CRIMPING,0.25-16MM,180MM KIT,CRIMPING PLIERS / TERMINALS PLIERS,LONG NOSE,HEAVY DUTY,W CUTTER CUTTER,MULTIFUNCTION,DIAGONAL,HD SET,PLIERS,WATERPUMP,3PCS SSR,PANEL MOUNT,200VDC,32VDC,10A TIP CARTRIDGE,SOLDER,30Â° CHISEL 0.06IN OSCILLOSCOPE,2 CH,50 MHZ,1GSPS OSCILLOSCOPE,70 MHZ,2 CHANNEL OSCILLOSCOPE,100 MHZ,2 CHANNEL OSCILLOSCOPE,150 MHZ,2 CHANNEL VENTILATEUR. 119MM 12V C.C VENTILATEUR 119MM 12 VCC VENTILATEUR 60MM 12 VCC VENTILATEUR. 80MM 12V C.C WIRE-BOARD CONN,RECEPTACLE,12POS,2MM THERMAL IMAGER,22.5H X 31V,1.2M THERMAL IMAGER,9HZ THERMAL IMAGER,9HZ VISOR TRIPOD MOUNTING BATTERY,LITHIUM-ION,RECHARGEABLE RJ12,JACK,6POS,6CONTACT,1PORT TERMINAL BLOCK,HEADER,3.5MM,5POS TERMINAL BLOCK,HEADER,3.5MM,5POS TERMINAL BLOCK,HEADER,3.81MM,2POS TERMINAL BLOCK,HEADER,3.81MM,3POS TERMINAL BLOCK,HEADER,3.81MM,4POS TERMINAL BLOCK,HEADER,3.81MM,5POS RJ11 MODULAR JACK,6POS,1 PORT TERMINAL BLOCK,HEADER,3.81MM,2POS TERMINAL BLOCK,HEADER,3.81MM,3POS TERMINAL BLOCK,HEADER,3.81MM,4POS TERMINAL BLOCK,HEADER,3.5MM,2POS TERMINAL BLOCK,HEADER,3.5MM,3POS TERMINAL BLOCK,HEADER,3.81MM,2POS TERMINAL BLOCK,HEADER,3.81MM,3POS TERMINAL BLOCK,HEADER,3.5MM,2POS TERMINAL BLOCK,HEADER,3.5MM,3POS TERMINAL BLOCK,HEADER,3.81MM,2POS TERMINAL BLOCK,HEADER,3.81MM,3POS CAT3 RJ50 MODULAR JACK,10POS,1 PORT CAT3 RJ45 MODULAR JACK,8POS,1 PORT CAT5 RJ45 MODULAR JACK,8POS,1 PORT CAT5 RJ45 MODULAR JACK,8POS,1 PORT CRIMP TOOL,SAI M23,0.14 - 4.0MM2 CRIMP TOOL,SAI M23,0.14 - 2.5MM2 No description available - 2095421 RELAY,HIGH FREQ,DPDT,12VDC,SMD RELAY,HIGH FREQ,DPDT,24VDC,SMD RELAY,HIGH FREQ,DPDT,3VDC,SMD RELAY,HIGH FREQ,DPDT,4.5VDC,SMD RELAY,HIGH FREQ,DPDT,5VDC,SMD CAPACITOR CERAMIC,1UF,4V,X5R,20%,0201 CAPACITOR CERAMIC,4.7UF,25V,X5R,10%,1206 CAPACITOR CERAMIC,4.7UF,50V,X7R,10%,1206 DETECTION SENSOR,Â±1.2g,1.333V/g,12VDC DETECTION SENSOR,Â±1.2g,1.333V/g,24VDC DETECTION SENSOR,Â±0.5g,3V/g,5VDC DETECTION SENSOR,Â±0.5g,3V/g,12VDC DETECTION SENSOR,Â±0.5g,3V/g,24VDC POWER CORD,IEC 320 C14 TO IEC 320 C136FT,10A DC-DC CONV,ISO POL,1 O/P,204W,17A,12V DC-DC CONV,ISO POL,1 O/P,204W,17A,12V DC-DC CONV,ISO POL,1 O/P,204W,17A,12V DC-DC CONV,ISO POL,1 O/P,204W,17A,12V VREG 1% 2.495V 36V 3SOT23 VREG 1% 2.495V 36V 3SOT23 VREG 1% 2.495V 36V 3SOT23 VREG 0.5% 2.495V 36V 3SOT23 VREG 0.5% 2.495V 36V 3SOT23 VREG 0.5% 2.495V 36V 3SOT23 VREG 2% 2.495V 36V 3SOT23 VREG 2% 2.495V 36V 3SOT23 VREG 2% 2.495V 36V 3SOT23 VREG 2% 2.495V 36V 3SOT23 VREG 2% 2.495V 36V 3SOT23 VREG 2% 2.495V 36V 3SOT23 LDO 1.2V 200MA 6SOT886 LDO 1.8V 200MA 6SOT886 LDO 2.5V 200MA 6SOT886 LDO 2.8V 200MA 6SOT886 LDO 2.9V 200MA 6SOT886 LDO 3.0V 200MA 6SOT886 LDO 3.3V 200MA 6SOT886 LDO 1.5V 200MA 5SOT753 LDO 2.5V 200MA 5SOT753 LDO 2.9V 200MA 5SOT753 LDO 3.0V 200MA 5SOT753 LDO 3.3V 200MA 5SOT753 LDO 1.2V 200MA 5SOT753 LDO 1.5V 200MA 5SOT753 LDO 1.8V 200MA 5SOT753 LDO 2.5V 200MA 5SOT753 LDO 2.8V 200MA 5SOT753 LDO 2.9V 200MA 5SOT753 LDO 3.0V 200MA 5SOT753 LDO 1.2V 150MA 4HUSON LDO 1.5V 150MA 4HUSON LDO 1.8V 150MA 4HUSON LDO 2.5V 150MA 4HUSON LDO 2.8V 150MA 4HUSON LDO 2.9V 150MA 4HUSON LDO 3.0V 150MA 4HUSON LDO 3.1V 150MA 4HUSON LDO 3.3V 150MA 4HUSON LDO 1.2V 150MA 4HUSON LDO 1.5V 150MA 4HUSON LDO 1.8V 150MA 4HUSON LDO 2.5V 150MA 4HUSON LDO 2.8V 150MA 4HUSON LDO 2.9V 150MA 4HUSON LDO 3.0V 150MA 4HUSON LDO 3.1V 150MA 4HUSON LDO 3.3V 150MA 4HUSON CAPACITOR ALUM ELEC 1UF ELECTROMECHANICAL TOTALIZING COUNTER CONTACT,FEMALE,24-22AWG,CRIMP IC PWM MOTOR DRVR,1A,MSOP10 CARTE DÂ´EVAL 5V MICROCO 8 BITS & CAPTEUR MCU CARTE PXN COMMS PROTOCOL KIT DÂ´EVAL PXN COMMS PROTOCOL KIT DÂ´EVAL PXS20 MCU KIT DÂ´EVAL PXS30 MCU KIT DÂ´EVAL TOUCH SENSING W/H CAPTEURS DSC 32 BITS MC56F84 100MHZ 100LQFP DSC 32 BITS MC56F84 100MHZ 80LQFP DSC 32 BITS MC56F84 100MHZ 64LQFP DSC 32 BITS MC56F84 100MHZ 48LQFP DSC 32 BITS MC56F84 100MHZ 100LQFP DSC 32 BITS MC56F84 100MHZ 80LQFP DSC 32 BITS MC56F84 100MHZ 64LQFP DSC 32 BITS MC56F84 100MHZ 48LQFP RELAY CARTE PROTOTYPE DPCO 9VDC RELAY CARTE PROTOTYPE DPCO 12VDC RELAY CARTE PROTOTYPE DPCO 12VDC RELAY CARTE PROTOTYPE DPCO 4.5VDC RELAY CARTE PROTOTYPE DPCO 5VDC RELAY CARTE PROTOTYPE DPCO 12VDC RELAY CARTE PROTOTYPE DPCO 4.5VDC RELAY CARTE PROTOTYPE SPNO 12VDC RELAY CARTE PROTOTYPE SPNO 3VDC RELAY CARTE PROTOTYPE DPNO 12VDC RELAY CARTE PROTOTYPE DPNO 5VDC RELAY CARTE PROTOTYPE DPNO 4.5VDC RELAY CARTE PROTOTYPE DPCO 8A 24VDC RELAY CARTE PROTOTYPE DPCO 8A 12VDC RELAY CARTE PROTOTYPE DPCO 8A 12VDC RELAY CARTE PROTOTYPE DPCO 8A 24VDC RELAY CARTE PROTOTYPE SPNO 10A 12VDC RELAY CARTE PROTOTYPE SPNO 10A 5VDC RELAY CARTE PROTOTYPE DPNO 8A 24VDC RELAY CARTE PROTOTYPE SPNO 8A 5VDC RELAY CARTE PROTOTYPE SPNO 8A 6VDC RELAY CARTE PROTOTYPE DPNO 8A 12VDC RELAY CARTE PROTOTYPE DPNO 8A 48VDC RELAY CARTE PROTOTYPE DPNO 8A 3VDC RELAY CARTE PROTOTYPE SPNO 5A 18VDC RELAY CARTE PROTOTYPE SPNO 20A 12VDC RELAY CARTE PROTOTYPE SPCO 16A 12VDC RELAY CARTE PROTOTYPE SPNO 16A 12VDC RELAY CARTE PROTOTYPE SPNO 16A 24VDC RELAY CARTE PROTOTYPE SPNO 16A 12VDC RELAY CARTE PROTOTYPE SPNO 16A 24VDC RELAY CARTE PROTOTYPE SPNO 5A 12VDC RELAY CARTE PROTOTYPE SPNO 5A 5VDC RELAY CARTE PROTOTYPE SPNO 10A 24VDC RELAY CARTE PROTOTYPE SPNO 10A 12VDC RELAY CARTE PROTOTYPE SPCO 5A 24VDC RELAY CARTE PROTOTYPE SPCO 10A 12VDC RELAY CARTE PROTOTYPE SPCO 10A 24VDC RELAY CARTE PROTOTYPE SPCO 10A 48VDC RELAY CARTE PROTOTYPE SPCO 10A 5VDC RELAY CARTE PROTOTYPE SPNO 10A 12VDC RELAY CARTE PROTOTYPE SPNO 10A 24VDC RELAY CARTE PROTOTYPE SPCO 10A 24VDC RELAY CARTE PROTOTYPE SPCO 10A 48VDC RELAY CARTE PROTOTYPE SPNO 16A 24VDC RELAY CARTE PROTOTYPE SPNO 16A 5VDC RELAY CARTE PROTOTYPE SPNO 16A 12VDC RELAY CARTE PROTOTYPE SPNO 16A 24VDC RELAY CARTE PROTOTYPE DPCO 16A 48VDC RELAY CARTE PROTOTYPE DPCO 16A 6VDC RELAY CARTE PROTOTYPE SPNO 10A 24VDC RELAY CARTE PROTOTYPE SPNO 5A 5VDC MICROCOMMUTATEUR HINGE LEVER MICROCOMMUTATEUR PLONGEUR MICROCOMMUTATEUR PLONGEUR MICROCOMMUTATEUR HINGE LEVER MICROCOMMUTATEUR PLONGEUR MICROCOMMUTATEUR SIM ROLLER LEVER MICROCOMMUTATEUR SIM ROLLER LEVER DRIVER MOSFET 8.2V RELAY PHOTOMOS 100V 0.32A RELAY PHOTOMOS 60V 0.5A RELAY PHOTOMOS 350V 0.12A CAPTEUR MOUVEMENT 5M BLANC CAPTEUR MOUVEMENT 5M BLANC CAPTEUR MOUVEMENT 5M NOIR CAPTEUR MOUVEMENT 5M PEARL BLANC CAPTEUR MOUVEMENT 5M BLANC CAPTEUR MOUVEMENT 5M NOIR CAPTEUR MOUVEMENT 5M PEARL BLANC CAPTEUR MOUVEMENT 5M BLANC CAPTEUR MOUVEMENT 5M NOIR CAPTEUR MOUVEMENT 5M PEARL BLANC CAPTEUR MOUVEMENT 12M BLANC CAPTEUR MOUVEMENT 12M NOIR CAPTEUR MOUVEMENT 12M PEARL BLANC CAPTEUR MOUVEMENT 12M BLANC CAPTEUR MOUVEMENT 12M NOIR CAPTEUR MOUVEMENT 12M PEARL BLANC CAPTEUR MOUVEMENT 12M PEARL BLANC STRIPPERS,SHEATHING,AM16 TOOL,CABLE GLAND,FOR M12 CON TOOL,CABLE GLAND,FOR M8 CON TOOL,CRIMP,HDC CON,4-10MM TOOL,CRIMP,FOR PV CONNECT IC,PSE CONTROLLER,3.3V,QFN-52 IC,PSE CONTROLLER,3.3V,QFN-52 IC,PSE CONTROLLER,3.3V,QFN-52 IC,PSE CONTROLLER,3.3V,QFN-24 IC,SYNC BUCK DC-DC CONV,4 MHz,MSOP-12 IC,SURGE STOPPER,500 V,DFN-8 IC,SURGE STOPPER,500 V,DFN-8 IC,SURGE STOPPER,500 V,8-SOT-23 IC,SURGE STOPPER,500 V,8-SOT-23 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,LED BXRA-C0400,CL-L330,CXA20 LED REFLECTOR,LED BXRA-C0400,CL-L330,CXA20 LED LENS,RECT,CREE MX-3,ASYMMETRIC SAW FILTER,GPS,1.5754GHZ ENABLLING PUSHBUTTON SWITCH,DPST-NO/DPST-NO ENABLLING PUSHBUTTON SWITCH,DPST-NO/SPST-NC ENABLLING PUSHBUTTON SWITCH LED LENS,RECT,CREE XP-E,ASYMMETRIC LED REFLECTOR,CREE LED CXA20 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,CREE LED CXA20 LED REFLECTOR,LED BXRA-C0800/1200/2000 LED REFLECTOR,Cree LED MT-G LED REFLECTOR,Cree LED MT-G LED LENS,RECT,CREE XP-E,ASYMMETRIC LED REFLECTOR,Cree LED MT-G LED REFLECTOR,Cree LED MT-G LED LENS,ROUND,CREE XP-E,WIDE SHEILD ARDUINO MODULE GPS AMPLI CLASSE D 3W 5V 4OHM 9WCSP BUCK 0.5A 4MHZ 2.5V MICROSIP BUCK 0.6A 5.5MHZ 1.5V MICROSIP BUCK 0.6A 5.5MHZ 1.8V MICROSIP BUCK 3.5V TO 42VIN 2.5A 2.5MHZ 10SON CONTROLEUR VOLTAGE MODE 0.2A 8SO LDO 2V A 5.5VIN 0.3A 2.8V 6SON LDO 2V A 5.5VIN 0.3A 3.6V 6SON LDO 2V A 5.5VIN 2.5V 0.5% 4DSBGA LDO 2V A 5.5VIN 3V 0.5% 4DSBGA LDO 3V A 24VIN 3V 0.05A 6SON LDO DOUBLE 2.85V / 1.8V 2% 6WSON LDO DOUBLE 3.3V / 3V 2% 6WSON LDO DOUBLE 3V / 3V 2% 6WSON AMPLI OP QUADRUPLE RRO 1MHZ 14TSSOP PMU I2C 3 BUCK 11 LDO 120BGA SEQUENCER ALIMENTATION 12 RAIL 64VQFN FREQ SYNTHETAILLER 480/80MHZ 44QFN FREQ SYNTHETAILLER 125MHZ 24QFN FREQ SYNTHETAILLER 125MHZ 44QFN FREQ SYNTHETAILLER 156.25MHZ 24QFN FREQ SYNTH 125MHZ DOUBLE 24QFN FREQ SYNTH 156.25/312.5MHZ 44QFN LIMITING AMP 1.25GBPS 16QFN KIT DÂ´EVAL 18DB WIFI EX ANT GS10111 KIT DÂ´EVAL 18DB WIFI CARTE ANT GS10111 ROM SMARTWATCH 64K/256K 28-SOCKET TCXO,19.2MHZ,SMD TCXO,16.3676MHZ,SMD TCXO,19.2MHZ,SMD CRYSTAL,48MHZ,18PF,DIP KIT SYNTHETAILLER / MIXER RFFC5071 KIT SYNTHETAILLER / MIXER RFFC5072 DIODE,TVS,SOD-323 OSCILLATOR,33MHZ,3.3V,SMD CRYSTAL,25MHZ,18pF,HC-49S CRYSTAL,25MHZ,16pF,HC-49S CRYSTAL,48MHZ,10pF,HC-49S OSCILLATOR,LVPECL,100MHZ,SMD OSCILLATOR,LVPECL,106.25MHZ,SMD OSCILLATOR,LVPECL,125MHZ,SMD OSCILLATOR,LVPECL,150MHZ,SMD OSCILLATOR,LVPECL,155.52MHZ,SMD OSCILLATOR,LVPECL,156.25MHZ,SMD OSCILLATOR,LVPECL,166MHZ,SMD OSCILLATOR,LVPECL,50MHZ,SMD OSCILLATOR,LVPECL,75MHZ,SMD OSCILLATOR,LVDS,100MHZ,SMD OSCILLATOR,LVDS,125MHZ,SMD OSCILLATOR,LVDS,156.25MHZ,SMD OSCILLATOR,LVDS,62.5MHZ,SMD OSCILLATOR,VCO,155.52MHZ,SMD OSCILLATOR,VCO,156.25MHZ,SMD OSCILLATOR,VCO,122.88MHZ,SMD OSCILLATOR,VCO,61.44MHZ,SMD OSCILLATOR,VCO,77.76MHZ,SMD OSCILLATOR,LVPECL,106.25MHZ,SMD OSCILLATOR,LVPECL,125MHZ,SMD OSCILLATOR,LVPECL,150MHZ,SMD OSCILLATOR,LVPECL,156.25MHZ,SMD OSCILLATOR,LVPECL,212.5MHZ,SMD OSCILLATOR,LVPECL,250MHZ,SMD OSCILLATOR,LVPECL,312.5MHZ,SMD OSCILLATOR,LVDS,150MHZ,SMD OSCILLATOR,LVDS,156.25MHZ,SMD OSCILLATOR,LVDS,212.5MHZ,SMD OSCILLATOR,LVDS,250MHZ,SMD OSCILLATOR,LVDS,312.5MHZ,SMD OSCILLATOR,LVPECL,106.25MHZ,SMD OSCILLATOR,LVPECL,156.25MHZ,SMD OSCILLATOR,LVPECL,212.5MHZ,SMD OSCILLATOR,LVPECL,312.5MHZ,SMD OSCILLATOR,LVDS,156.25MHZ,SMD OSCILLATOR,LVDS,212.5MHZ,SMD OSCILLATOR,LVDS,312.5MHZ,SMD OSCILLATOR,VCO,27MHZ,SMD OSCILLATOR,VCO,38.88MHZ,SMD OSCILLATOR,TCXO,16.368MHZ,SMD OSCILLATOR,TCXO,16.368MHZ,SMD OSCILLATOR,TCXO,16.369MHZ,SMD OSCILLATOR,TCXO,16.369MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,38.4MHZ,SMD OSCILLATOR,TCXO,38.4MHZ,SMD OSCILLATOR,TCXO,40MHZ,SMD OSCILLATOR,TCXO,40MHZ,SMD OSCILLATOR,TCXO,40MHZ,SMD OSCILLATOR,TCXO,40MHZ,SMD OSCILLATOR,TCXO,16.3676MHZ,SMD OSCILLATOR,TCXO,16.3676MHZ,SMD OSCILLATOR,TCXO,16.367667MHZ,SMD OSCILLATOR,TCXO,16.367667MHZ,SMD OSCILLATOR,TCXO,16.367667MHZ,SMD OSCILLATOR,TCXO,16.367667MHZ,SMD OSCILLATOR,TCXO,16.368MHZ,SMD OSCILLATOR,TCXO,16.368MHZ,SMD OSCILLATOR,TCXO,16.368MHZ,SMD OSCILLATOR,TCXO,16.368MHZ,SMD OSCILLATOR,TCXO,16.369MHZ,SMD OSCILLATOR,TCXO,16.369MHZ,SMD OSCILLATOR,TCXO,16.369MHZ,SMD OSCILLATOR,TCXO,16.369MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,19.2MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,40MHZ,SMD OSCILLATOR,TCXO,40MHZ,SMD OSCILLATOR,TCXO,26MHZ,3.3V,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD OSCILLATOR,TCXO,26MHZ,SMD MODULE ANTENNE RADIO 433MHZ 40DB BUCK 2.9-5.5VIN 2A AJUSTABLE 4MHZ 12MLF RESET DOUBLE ACTIVE-LOW 6WLCSP RESET DOUBLE ALIMENTATION MONITOR 8MLF RESET DOUBLE ALIMENTATION MONITOR 8MLF DOUBLE INTG PULL UP RESISTANCE 8MLF RESET DOUBLE 1.6V TO 5.5V 8MLF BUCK 4.5V TO 75VIN 4A AJUSTABLE 28MLF LDO 2.375V TO 5.5VIN 1A 1.8V 8SOIC LDO 2.375V TO 5.5VIN 1A 1.8V 6MLF LDO 2.375V TO 5.5VIN 1A 1.8V 3SOT223 LDO 2.375V TO 5.5VIN 1A AJUSTABLE 8SOIC LDO 2.375V TO 5.5VIN 1A AJUSTABLE 6MLF LDO 2.375V TO 5.5VIN 1A 1.8V 6MLF LDO 2.375V TO 5.5VIN 1A AJUSTABLE 8SOIC LDO 2.375V TO 5.5VIN 1A AJUSTABLE 6MLF LDO 2.3V A 30VIN 0.15A AJUSTABLE 8SOIC LOAD COMMUTATEUR 1.8V TO 3.6VIN 4WLCSP REG RIPPLE 1.8V-3.6VIN 1.2V 4MLF REG RIPPLE 1.8V-3.6VIN 1.5V 4MLF REG RIPPLE 1.8V-3.6VIN 1.8V 4MLF REG RIPPLE 1.8V-3.6VIN 3.3V 4MLF PINCE MULTI-USAGES 160MM JEU DE 4 PINCES ISOLEES VDE PINCE MULTI-USAGES 160MM JEU DE 4 PINCES ISOLEES VDE PINCE COUPANTE DE COTE 180MM PINCE COUPANTE/DENUDANT D.COTE CUTTER,CABLE,ONE-HAND COUPE-CABLES BATTERIE LITHIUM 3.6V 2.4AH AA BATTERIE LITHIUM 3.6V 8.5AH C BATTERIE LITHIUM 3.6V 19AH D JUMPER,FFC,0.5MM,50MM,30WAY JUMPER,FFC,1MM,152MM,8WAY JUMPER,FFC,1MM,50MM,16WAY JUMPER,FFC,1MM,152MM,16WAY JUMPER,FFC,0.3MM,104MM,25WAY JUMPER,FFC,0.3MM,104MM,27WAY JUMPER,FFC,0.3MM,104MM,33WAY CARTE DÂ´EVAL LOGARITH DECTECTOR AD8304 CARTE DÂ´EVAL CAN 16 BITS 200MSPS AD9467 CARTE DÂ´EVAL CAN 16 BITS 250MSPS AD9467 CARTE DÂ´EVAL CAN 14 BITS 80MSPS AD9644 CARTE DÂ´EVAL CAN 14 BITS 155MSPS AD9644 CARTE DÂ´EVAL DIFFERENCE AMP 18V ADA4830 CARTE DÂ´EVAL DAC 16 BITS SPI AD5541A CARTE DÂ´EVAL DAC QUAD 16 BIT SPI AD5755S CARTE DÂ´EVAL CAN 24BIT 4.8KSPS AD7195 CARTE DÂ´EVAL CAN 16BITS 500KSPS AD7988-5 CARTE DÂ´EVAL DAC 16 BITS DOUBLE AD9122 CARTE DÂ´EVAL DAC 16 BITS DOUBLE AD9122 MODULE RF 868MHZ 10DBM MODULE RF 900MHZ 10DBM MODULE RF 2400MH 10DBM MODULE RF 900MHZ 10DBM MODULE RF 2400MH 10DBM MODULE DÂ´EVAL RF 433MHZ MODULE DÂ´EVAL RF 686MHZ MODULE DÂ´EVAL RF 900MHZ MODULE DÂ´EVAL RF 2400MHZ MODULE DÂ´EVAL RF 868MHZ MODULE DÂ´EVAL RF 900MHZ MODULE DÂ´EVAL RF 2400MHZ MODULE DÂ´EVAL RF 2.4GHZ CARTE DÂ´EVAL RF A/P 433MHZ CARTE DÂ´EVAL RF E/P 433MHZ CARTE DÂ´EVAL RF A/P 868MHZ CARTE DÂ´EVAL RF E/P 868MHZ CARTE DÂ´EVAL RF A/P 900MHZ CARTE DÂ´EVAL RF E/P 900MHZ CARTE DÂ´EVAL RF A/P 2400MHZ CARTE DÂ´EVAL RF E/P 2400MHZ CARTE DÂ´EVAL RF A/P 868MHZ CARTE DÂ´EVAL RF E/P 868MHZ CARTE DÂ´EVAL RF A/P 900MHZ CARTE DÂ´EVAL RF E/P 900MHZ CARTE DÂ´EVAL RF A/P 2400MHZ CARTE DÂ´EVAL RF E/P 2400MHZ MODULE RF RADIO 900MHZ. SPI MODULE RF RADIO 2.4GHZ 16DBM MODULE ANTENNE 04C 433MHZ U.FL MODULE ANTENNE 09C 900MHZ U.FL MODULE ANTENNE 24C 2400MHZ U.FL Tools,Tips Soldering Leaded Process Com Tools,Tips Soldering Leaded Process Com KEY OPERATED SWITCH DRIVER CAN AMPLI DIFF 16 BIT 8MSOP DAC 14BIT +/-4LSB 5.5VIN 6LFCSP DAC 8BIT +/-6LSB 5.5VIN 6LFCSP DAC 8BIT +/-4LSB 5.5VIN 6LFCSP DAC 8BIT +/-0.5LSB 5.5VIN 6SC70 DAC 8BIT +/-0.5LSB 5.5VIN 6LFCSP CAN DIFF ENTREE 16 BIT 250KSPS 8MSOP CAN DIFF ENTREE 14BIT 80MSPS 32LFCSP CAN 16 BITS 250MSPS +/-3.5LSB 72LFCSP CAN 14 BITS 80MSPS +/-0.5LSB 48LFCSP CAN 14 BITS 155MSPS +/-0.55LSB 48LFCSP CAN 14 BITS 80MSPS +/-0.5LSB 48LFCSP CAN 260MHZ 16 BITS 3-7VIN 8SOIC DRIVER LED 1MHZ 36V 14LFCSP AMPLI CLASSE G STEREO 0.1W 16WLCSP DAC 16 BITS +/-2LSB 0.05PPMC 10LFCSP DAC 16 BITS +/-1LSB 0.05PPMC 8LFCSP DAC 16 BITS +/-1LSB 0.05PPMC 10LFCSP DAC QUAD 16 BITS -26.4/33VIN 64LFCSP CAN 4.8KHZ 24BIT 3FIL/SPI 32LFCSP CAN 500KSPS 16 BITS SPI 10LFCSP DAC DOUBLE 16 BITS 1230MSPS 72LFCSP IC SOCKET,DIP,2.54MM,24POS No description available - 2096203 IC SOCKET,SIP,1ROW,2.54MM,64POS IC SOCKET,22POS,THRU HOLE,2.54MM,10.16MM ROW DIP SOCKET,32POS,THROUGH HOLE No description available - 2096208 No description available - 2096209 No description available - 2096210 IC SOCKET,SIP,1ROW,1.27MM,100POS TRANSISTOR SOCKET,4POS ANTENNE YAGI 7 ELEMENT 434MHZ ANTENNE YAGI 9 ELEMENT 869-915MHZ ANTENNE YAGI 16 ELEMENT 2.4GHZ ANTENNE STUB STRAIGHT 868-915MHZ ANTENNE STUB ANGLE DROIT 868-915MHZ ANTENNE STUB STRAIGHT 434MHZ ANTENNE STUB 2.4GHZ MODULE AUDIO/VIDEO TRANSMITER RECEPTEUR 2 CH WITH 2 ALIEN FOB TELECOMMANDE FOB KEELOQ RECEPTEUR 4 CH WITH 2 LIDER FOB LIDER-4 FOB KEY FOB DUET 2 BOUTON MODULE DUET RECEPTEUR PROGRAMMATEUR REMOTE CONTROL EMETTEUR AVEC CANAL AU CHOIX RECEIVER,WITH SELECTABLE CH MODULE ERA TCVR 420-470MHZ MODULE ERA TX 420-470MHZ MODULE ERA TCVR 802-940MHZ MODULE ERA TX 802-940MHZ ICM F-CONN DB STARTER KIT WITH COMPRESSION TOOL/STRIPPER/FIT TOOL AND CONNECTORS 50T8943 N CHANNEL MOSFET,30V,9.5A,SOIC CARTE DÂ´EVALUATION CORTEX M0 STM32F0 TERMINAL BLOCK,PLUG,12POS,30-14AWG TERMINAL BLOCK,PLUG,12POS,30-14AWG TERMINAL BLOCK,PLUG,12POS,30-14AWG TERMINAL BLOCK,PLUG,12POS,30-14AWG TERMINAL BLOCK,PLUG,2POS,30-14AWG TERMINAL BLOCK,PLUG,3POS,30-14AWG TERMINAL BLOCK,PLUG,4POS,30-14AWG TERMINAL BLOCK,PLUG,6POS,30-14AWG TERMINAL BLOCK,PLUG,8

REDRESSEMENT 1KV 1A SMA DIODE DE REDRESSEMENT 1.3KV 3A DO-201AD PONT REDRESSEUR 200V 1A DFS KIT,TEST PROBE,FUSED KIT,TEST PROBE,FUSED,TEST LEADS ALLIGATOR CLIPS LEADS,TEST WRAPS,TEST LEAD PROBES,TEST,VOLTAGE/CURRENT,2MM SCREWDRIVER SET,ELECTRONIC,5 PIECES SCREWDRIVER,PHILLIPS,76MM SCREWDRIVER,SLOT,51MM SCREWDRIVER,SLOT,76MM SCREWDRIVER,SLOT,102MM SCREWDRIVER,SLOT,152MM WALL PLATE,1 GANG,SST POTENTIOMETRE 470R SUBMERSIBLE 20% POTENTIOMETRE 1K SUBMERSIBLE 20% POTENTIOMETRE 4K7 SUBMERSIBLE 20% POTENTIOMETRE 47K SUBMERSIBLE 20% POTENTIOMETRE 470R SUBMERSIBLE 20% POTENTIOMETRE 1K SUBMERSIBLE 20% POTENTIOMETRE 4K7 SUBMERSIBLE 20% POTENTIOMETRE 10K SUBMERSIBLE 20% POTENTIOMETRE 47K SUBMERSIBLE 20% POTENTIOMETRE 470R SUBMERSIBLE 20% POTENTIOMETRE 1K SUBMERSIBLE 20% POTENTIOMETRE 4K7 SUBMERSIBLE 20% POTENTIOMETRE 10K SUBMERSIBLE 20% POTENTIOMETRE 47K SUBMERSIBLE 20% RESISTANCE 1U 5% THICK FILM PUISSANCE RESISTANCE 4U7 5% THICK FILM PUISSANCE RESISTANCE 47U 5% THICK FILM PUISSANCE RESISTANCE 100U 5% THICK FILM PUISSANCE RESISTANCE 470U 5% THICK FILM PUISSANCE RFI Line Filter Current Rating:15A MOSFET CANAL N 525V 10A D2PAK MOSFET CANAL N 40V 80A D2PAK MOSFET CANAL N 600V 11A D2PAK MOSFET CANAL N 500V 12A D2PAK MOSFET CANAL N 30V 80A D2PAK MOSFET CANAL N 600V 14A D2PAK MOSFET CANAL N 55V 120A D2PAK MOSFET CANAL N 550V 13A D2PAK MOSFET CANAL N 600V 13A D2PAK MOSFET CANAL N 800V 17A D2PAK MOSFET CANAL N 650V 17A D2PAK MOSFET CANAL N 600V 17A D2PAK MOSFET CANAL N 600V 21A D2PAK MOSFET CANAL N 600V 20A D2PAK MOSFET CANAL N 650V 24A D2PAK MOSFET CANAL N 600V 29A D2PAK MOSFET CANAL N 600V 29A D2PAK MOSFET CANAL N 650V 27A D2PAK MOSFET CANAL N 620V 2.7A D2PAK MOSFET CANAL N 100V 40A D2PAK MOSFET CANAL N 500V 4.4A D2PAK MOSFET CANAL N 625V 5.5A D2PAK MOSFET CANAL N 650V 7A D2PAK MOSFET CANAL N 30V 80A D2PAK MOSFET CANAL N 500V 7.2A D2PAK MOSFET CANAL N 700V 7.5A I2PAK MOSFET CANAL N 500V 7A DPAK MOSFET CANAL N 600V 8A DPAK MOSFET CANAL N 600V 8A DPAK MOSFET CANAL N 650V 9A DPAK MOSFET CANAL N 500V 9A DPAK MOSFET CANAL N 650V 8.5A DPAK MOSFET CANAL N 60V 12A DPAK MOSFET CANAL N 500V 12A DPAK MOSFET CANAL N 30V 80A DPAK MOSFET CANAL N 30V 80A D2PAK MOSFET CANAL N 650V 12A DPAK MOSFET CANAL N 620V 2.2A DPAK MOSFET CANAL N 1000V 1.85A DPAK MOSFET CANAL N 620V 2.5A DPAK MOSFET CANAL N 600V 2.4A DPAK MOSFET CANAL N 620V 3.8A DPAK MOSFET CANAL N 525V 4.4A DPAK MOSFET CANAL N 620V 4.2A DPAK MOSFET CANAL N 950V 4A DPAK MOSFET CANAL N 600V 5A IPAK MOSFET CANAL N 620V 5.5A DPAK MOSFET CANAL N 525V 6A DPAK MOSFET CANAL N 525V 6.2A DPAK MOSFET CANAL N 800V 6.5A IPAK MOSFET CANAL N 200V 7A DPAK MOSFET CANAL N 650V 7A DPAK MOSFET CANAL N 500V 5A DPAK MOSFET CANAL N 600V 6.5A DPAK MOSFET CANAL N 620V 8.4A TO 220FP MOSFET CANAL N 500V 7.0A TO220FP MOSFET CANAL N 525V 10A TO 220FP MOSFET CANAL N 500V 9A TO 220FP MOSFET CANAL N 650V 8.5A TO 220FP MOSFET CANAL N 500V 12A TO 220FP MOSFET CANAL N 600V 14A TO 220FP MOSFET CANAL N 550V 13A TO 220FP MOSFET CANAL N 500V 14A TO 220FP MOSFET CANAL N 650V 15A TO 220FP MOSFET CANAL N 650V 17A TO 220FP MOSFET CANAL N 600V 17A TO 220FP MOSFET CANAL N 600V 16A TO 220FP MOSFET CANAL N 550V 17A TO 220FP MOSFET CANAL N 600V 19.5A TO 220FP MOSFET CANAL N 650V 17A TO 220FP MOSFET CANAL N 600V 21A TO 220FP MOSFET CANAL N 500V 21A TO 220FP MOSFET CANAL N 620V 2.2A TO 220FP MOSFET CANAL N 600V 29.0A TO 220FP MOSFET CANAL N 600V 29A TO 220FP MOSFET CANAL N 620V 2.5A TO 220FP MOSFET CANAL N 620V 2.7A TO 220FP MOSFET CANAL N 1000V 2.5A TO 220FP MOSFET CANAL N 650V 33A TO 220FP MOSFET CANAL N 525V 2.5A TO 220FP MOSFET CANAL N 620V 3.8A TO 220FP MOSFET CANAL N 525V 4.4A TO 220FP MOSFET CANAL N 620V 4.2A TO220FP MOSFET CANAL N 950V 4A TO220FP MOSFET CANAL N 620V 5.5A TO 220FP MOSFET CANAL N 525V 6A TO 220FP MOSFET CANAL N 525V 6.2A TO 220FP MOSFET CANAL N 650V 7A TO220FP MOSFET CANAL N 600V 6.5A TO220FP MOSFET CANAL N 1500V 4A TO3PF MOSFET CANAL N 650V 46A TO 3PF MOSFET CANAL N 100V 120A H2PAK MOSFET CANAL N 100V 180A H2PAK MOSFET CANAL N 75V 180A H2PAK MOSFET CANAL N 75V 180A H2PAK MOSFET CANAL N 40V 180A H2PAK MOSFET CANAL N 600V 8.4A I2PAK MOSFET CANAL N 650V 8.5A I2PAK MOSFET CANAL N 600V 11A I2PAK MOSFET CANAL N 650V 12A I2PAK MOSFET CANAL N 650V 17A I2PAK MOSFET CANAL N 30V 16A I2PAK MOSFET CANAL N 30V 17A I2PAK MOSFET CANAL N 650V 22A I2PAK MOSFET CANAL N 650V 27A I2PAK MOSFET CANAL N 650V 33A I2PAK MOSFET CANAL N 620V 3.8A I2PAK MOSFET CANAL N 620V 5.5A I2PAK MOSFET CANAL N 650V 7A I2PAK MOSFET CANAL N 12V 100A POWERFLAT MOSFET CANAL N 20V 28A POWERFLAT MOSFET CANAL N 600V 10A POWERFLAT MOSFET CANAL N 40V 15A POWERFLAT MOSFET CANAL N 30V 160A POWERFLAT MOSFET CANAL N 650V HV POWERFLAT MOSFET CANAL N 30V 17A POWERFLAT MOSFET CANAL N 600V 6A POWERFLAT MOSFET CANAL N 600V 19.5A POWERFLAT MOSFET CANAL N 600V 16A POWERFLAT MOSFET CANAL N 600V 19A POWERFLAT MOSFET CANAL N 400V 1.8A SOT223 MOSFET CANAL N 620V 8.4A TO220 MOSFET CANAL N 600V 8A TO220 MOSFET CANAL N 600V 8A TO 220 MOSFET CANAL N 525V 10A TO 220 MOSFET CANAL N 500V 9A TO 220 MOSFET CANAL N 950V 10A TO 220 MOSFET CANAL N 600V 14A TO 220 MOSFET CANAL N 710V 12A TO 220 MOSFET CANAL N 650V 12A TO 220 MOSFET CANAL N 600V 13A TO 220 MOSFET CANAL N 800V 17A TO 220 MOSFET CANAL N 500V 14A TO 220 MOSFET CANAL N 550V 20A TO 220FP MOSFET CANAL N 75V 120A TO 220AB MOSFET CANAL N 650V 17A TO 220 MOSFET CANAL N 600V 17A TO 220 MOSFET CANAL N 600V 16A TO 220 MOSFET CANAL N 500V 17A TO 220 MOSFET CANAL N 600V 19.5A TO 220 MOSFET CANAL N 600V 17A TO 220 MOSFET CANAL N 600V 21A TO 220 MOSFET CANAL N 60V 120A TO 220 MOSFET CANAL N 500V 21A TO 220 MOSFET CANAL N 620V 2.2A TO 220 MOSFET CANAL N 1000V 1.85A TO 220 MOSFET CANAL N 650V 24A TO 220 MOSFET CANAL N 600V 29A TO 220 MOSFET CANAL N 600V 29A TO 220AB MOSFET CANAL N 650V 27A TO 220 MOSFET CANAL N 620V 2.5A TO 220 MOSFET CANAL N 620V 2.7A TO 220 MOSFET CANAL N 650V 33A TO 220 MOSFET CANAL N 525V 2.5A TO 220 MOSFET CANAL N 620V 3.8A TO 220 MOSFET CANAL N 525V 4.4A TO 220 MOSFET CANAL N 620V 4.2A TO 220AB MOSFET CANAL N 950V 4A TO 220AB MOSFET CANAL N 600V 5A TO 220FP MOSFET CANAL N 525V 5A TO 220 MOSFET CANAL N 620V 5.5A TO 220 MOSFET CANAL N 500V 5.6A TO 220 MOSFET CANAL N 525V 6A TO 220 MOSFET CANAL N 525V 6.2A TO 220 MOSFET CANAL N 950V 7.2A TO 220 MOSFET CANAL N 600V 5A TO 220AB MOSFET CANAL N 30V 80A TO 220 MOSFET CANAL N 40V 80A TO 220 MOSFET CANAL N 600V 6.5A TO 220 MOSFET CANAL N 450V 0.5A 8SOIC MOSFET CANAL N 600V 8A IPAK MOSFET CANAL N 650V 8.5A IPAK MOSFET CANAL N 30V 80A IPAK MOSFET CANAL N 650V 12A IPAK MOSFET CANAL N 620V 2.2A IPAK MOSFET CANAL N 1000V 1.85A IPAK MOSFET CANAL N 620V 2.5A IPAK MOSFET CANAL N 450V 1.8A IPAK MOSFET CANAL N 620V 2.7A IPAK MOSFET CANAL N 525V 2.5A TO 220 MOSFET CANAL N 620V 3.8A IPAK MOSFET CANAL N 525V 4.4A IPAK MOSFET CANAL N 620V 4.2A IPAK MOSFET CANAL N 950V 4A IPAK MOSFET CANAL N 620V 5.5A IPAK MOSFET CANAL N 650V 7A IPAK MOSFET CANAL N 500V 5A IPAK MOSFET CANAL N 75V 240A POWERSO MOSFET CANAL N 24V 280A POWERSO MOSFET CANAL N 600V 14A TO 247 MOSFET CANAL N 500V 14A TO 247 MOSFET CANAL N 650V 17A TO 247 MOSFET CANAL N 600V 17A TO 247 MOSFET CANAL N 600V 16A TO 247 MOSFET CANAL N 500V 17A TO 247 MOSFET CANAL N 600V 19.5A TO 247 MOSFET CANAL N 650V 17A TO 247 MOSFET CANAL N 950V 22A TO 247 MOSFET CANAL N 500V 21A TO 247 MOSFET CANAL N 600V 29A TO 247 MOSFET CANAL N 600V 29A TO 247 MOSFET CANAL N 600V 35A TO 247 MOSFET CANAL N 600V 39A TO 247 MOSFET CANAL N 600V 51A TO 247 MOSFET CANAL N 650V 46A TO 247 MOSFET CANAL N 650V 69A TO 247 MOSFET CANAL N 950V 7.2A TO 247 MOSFET CANAL N 650V 93A MAX247 MOSFET CANAL NN 30V 40A POWERFLAT MOSFET CANAL PP 30V 4A 8SOIC WALL PLATE,1 GANG,IVORY WALL PLATE,1 GANG,RED WALL PLATE,2 GANG,GREY WALL PLATE,2 GANG,IVORY WALL PLATE,2 GANG,RED WALL PLATE,2 GANG,WHITE WALL PLATE,1 GANG,1 DUPLEX,GREY WALL PLATE,1 GANG,1 DUPLEX,IVORY WALL PLATE,1 GANG,1 DUPLEX,RED WALL PLATE,2 GANG,2 DUPLEX,GREY WALL PLATE,2 GANG,2 DUPLEX,IVORY WALL PLATE,2 GANG,2 DUPLEX,RED WALL PLATE,2 GANG,2 DUPLEX,WHITE WALL PLATE,2 GANG,1 DUPLEX,GREY WALL PLATE,2 GANG,1 DUPLEX,IVORY WALL PLATE,2 GANG,1 DUPLEX,WHITE WIRE-BOARD CONNECTOR HEADER 2POS,3.96MM TEST LEAD,4MM,1M,BROWN,MICRO KLEPS TEST PROBE,4MM,BLACK,MLS TEST PROBE,4MM,RED,MLS KIT,TEST SERVICE EQUIPMENT,MLS KIT,TEST EQUIPMENT,MLS KIT,TEST EQUIPMENT,MLS PLUG,4MM,BLACK,MVL S PLUG,4MM,RED,MZS PLUG,4MM,BLACK,MZS PLUG,4MM,RED,MZS PROGRAMMATEUR FLASHER ST7 PROGRAMMATEUR FLASHER 5 PROGRAMMATEUR FLASHER PPC PROGRAMMATEUR FLASHER RX ADAPTATEUR J-LINK 19 BROCHES CORTEX-M ADAPTATEUR J-LINK 9 BROCHES CORTEX-M ADAPTATEUR J-LINK ADAPTATEUR J-LINK ARM-14 ISOLATEUR JTAG EMULATEUR JTAG J-LINK USB POWERED EMULATEUR J-LINK/PRO BUNDLE EMULATEUR J-LINK EDU EMULATEUR J-TRACE ARM EMULATEUR J-LINK PRO EMULATEUR J-TRACE POUR CORTEX-M EMULATEUR J-LINK ULTRA EMULATEUR J-LINK ULT/ARM RDI BUNDLE EMULATEUR J-LINK ULTRA/PRO BUNDLE EMULATEUR J-LINK ULTRA/FLASH BUNDLE EMULATEUR J-LINK ULTRA/J-FLASH BUNDLE EMULATEUR J-LINK/J-FLASH BUNDLE WALL PLATE,1 GANG,RED LED MOD BLANC FROID 1W 3DEG LED MOD BLANC NEUTRE 1W 3DEG LED MOD BLANC CHAUD 1W 3DEG LED MOD BLANC FROID 1W 3/60DEG LED MOD BLANC CHAUD 1W 3/60DEG LED MOD BLANC NEUTRE 1W 3/60DEG LED MOD BLANC FROID 1W 10DEG LED MOD BLANC CHAUD 1W 10DEG LED MOD BLANC CHAUD 1W 15DEG LED MOD BLANC FROID 1W 30DEG LED MOD BLANC CHAUD 1W 30DEG LED MOD BLANC FROID 1W 45DEG LED MOD BLANC CHAUD 1W 45DEG LED MOD BLANC FROID 1W 60DEG LED MOD BLANC CHAUD 1W 60DEG LED MOD BLANC FROID 1W 110DEG LED MOD BLANC CHAUD 1W 110DEG LED MOD BLANC CHAUD 3W 10DEG LED MOD BLANC FROID 3W 15DEG LED MOD BLANC CHAUD 3W 15DEG LED MOD BLANC FROID 3W 30DEG LED MOD BLANC CHAUD 3W 30DEG LED MOD BLANC FROID 3W 45DEG LED MOD BLANC CHAUD 3W 45DEG LED MOD BLANC FROID 3W 60DEG LED MOD BLANC CHAUD 3W 60DEG LED MOD RGB 3W 140DEG CC CAPACITOR POLY FILM 0.1UF 100V 5%,RADIAL CAPACITOR POLY FILM 0.22UF 63V 5%,RADIAL Z+ BLANKING PANEL FOR 19Â´Â´ RACK,ZNL100 BENCH POWER SUPPLY,60V ADJUSTABLE HFE2500 Rack Power Cord (C19) RACK,1U FOR HFE2500,SINGLE OUTPUT,IEC INPUT RACK,1U FOR HFE2500,SINGLE OUT,TERM BLOCK INPUT OLED VERBATIM VELVE KIT DÂ´EVALUATION OLED VERBATIM VELVE PANEL MODULE CONNECTOR ASSEMBLIES,HOOKS TEST CABLE,RJ45,MAGELIS DISPLAY UNIT ACCELEROMETRE 2 AXES +/-50G 16QFN CAPTEUR GESTURE PROG 4.5KB 16LGA KIT DÂ´EVAL ACCEL 3 AXES MMA955XL KIT DÂ´EVAL ACCEL 3 AXES MMA955XL TOUCHSCREEN,GRAPHICAL,10.4 TIMER 50B8199 BOARD-BOARD CONNECTOR RECEPTACLE,15WAY,1ROW TVS-DIODE,12V,BIDIRECTIONAL,SOD-323 TVS-DIODE,24V,BIDIRECTIONAL,SOD-323 CABLE,MINIDIN-RJ45,MAGELIS DISPLAY UNIT CONNECTOR ASSEMBLIES,LEAD SET TEST CONNECTOR ASSEMBLIES,LEAD SET TEST TEST PROBE,OSCILLOSCOPE DMM TEST LEAD ACCESSORY KIT DMM TEST LEAD ACCESSORY KIT TEST PROBE,OSCILLOSCOPE TEST PROBE,OSCILLOSCOPE TEST PROBE,OSCILLOSCOPE TOUCHSCREEN,GRAPHICAL,5.7 CABLE,RJ45,MODBUS SERIAL LINK IC,BUCK DC-DC CONTROLLER,5.5MHz,uSIP-8 DIODE,ULTRA FAST,1A,150V,DO-214AC MICROSCOPE,USB,1280 X 1024,30FPS MICROSCOPE,USB,VGA,640 X 480,30FPS MICROSCOPE,USB,640 X 480,60FPS MICROSCOPE,USB,640 X 480,TV OUTPUT MICROSCOPE,USB,1280 X 1024,30FPS MICROSCOPE,USB,VGA,800 X 600,60FPS MICROSCOPE,USB,5MP,30FPS,200X MICROSCOPE,USB,5MP,30FPS,400X EYEPIECE,DINO-EYE,USB,1.3M PIXEL EYEPIECE,DINO-EYE,USB,5M PIXEL RTC I2C 64BYTES SRAM 8MSOP RTC I2C 64BYTES SRAM 8SOIC RTC I2C 64BYTES SRAM 8TSSOP RTC I2C 64BYTES SRAM 8TDFN RTC I2C 64BYTES SRAM 8PDIP CHIP MODULE ANTENNE XBEE 1MW CHIP ANTENNE MOD XBEEPRO 100MILW MOD XBEE PRO ZB 10MW W/CHIP ANT POWER RELAY,DPDT,24VDC,25A,FLANGE POWER RELAY,SPDT,24VDC,10A,PC BOARD FUSED TERMINAL BLOCK,6.3x32MM,SCREW,30-10AWG Desktop Ethernet Switch POTENTIOMETER,ROTARY,200 OHM,2W SWITCH,TOGGLE,SPST,15A,250V SWITCH,REED,SPDT,250mA,125VAC PROGRAMMABLE CABLE ZIPSCOPE USB DIGITAL MICROSCOPE,2M RF BJT,NPN,25V,6A,27MHZ,TO-220AB IC,OVERVOLTAGE CROWBAR,DIP-8 THERMOCOUPLE CONNECTOR,K TYPE SELECTOR HANDLE,RED N CH POWER MOSFET,HEXFET,100V,85A,D2PAK N CHANNEL MOSFET,100V,42A,TO-252AA MOSFET,N CH,80V,39A,DPAK CAP MOUNTING BRACKET,2.69Â´Â´ BASE CAT5E SNGLS PATCH CABLE RJ45M/RJ45M WHT,10FT SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 TIP-UP FOOT,19Â´Â´,DESK-TOP CASES FRONT PANEL HANDLE,8HP,GREY TRAPEZIFORM HANDLE,8HP,BLACK EXTRACTOR HANDLE,BLACK TRAPEZIFORM HANDLE,4HP,BLACK IEL HNDL BOT BLK/GRY (10 PCS) PLUG-IN UNIT,19 CHEESEHEAD SCREW,HORIZONTAL RAILS,M2.5 COUNTERSUNK SCREW,PLUG-IN UNITS,M2.5 SLEEVE,PLASTIC,GREY,100PCS MOUNTING HARDWARE HANDLE (2) 64T7220 COLLAR SCREW,PLUG-IN UNITS,M2.5 PANHEAD SCREW,GUIDE RAILS,M2.5,100 PCS SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 EARTHING KIT,DESK-TOP CASES HORIZ RAIL REAR 84HP 64T8754 HORIZONTAL RAIL,HL HANDLE,ALUMINIUM EMC COVER,PMC MEZZANINE FRONT PANEL GUIDE RAIL,GREY,70MM,1 PCS GUIDE RAIL,RED,220MM,1 PCS GUIDE RAIL,GREY,220MM,1 PCS DOUBLE TEST SOCKET,MOUNTING PLANE MOSFET,-150V,-150A,D2-PAK STANDARD DIODE,3A,1.3KV,DO-201AD ROCKER SWITCH LOAD CENTER MECHANICAL INTERLOCK FERRULES,WIRE END,4MM2,CRIMP,UNINSUL FASTENER,FOR SUBRACK GASKET,FOR PANEL GASKET,FOR PANEL SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 SUBRACK,19 MOSFET,N CH,HEXFET,30V,8.2A,TSOP-6 CARTE DÂ´EVALUATION PIC16LF1947 F1 XLP DEV BDC MOTEUR ADD-ON F1 LV PLATFORM DEV BIPOLAIRE MOTEUR ADD-ON F1 LV PLAT DEV UNIPOLAR MOTEUR ADD-ON F1 LV PLAT FUSE,4A,FAST,5X20MM,250V,AXIAL FUSE,8A,FAST,5X20MM,250V,AXIAL FUSE,1.6A,FAST,5X20MM,250V,AXIAL FUSE,2.5A,FAST,5X20MM,250V,AXIAL FUSE,6.3A,FAST,5X20MM,250V,AXIAL FUSE,0.8A,TE7,TIME LAG,300V,RADIAL FUSE,1A,TE7,TIME LAG,300V,RADIAL FUSE,1.25A,TE7,TIME LAG,300V,RADIAL FUSE,1.6A,TE7,TIME LAG,300V,RADIAL FUSE,2A,TE7,TIME LAG,300V,RADIAL FUSE,2.5A,TE7,TIME LAG,300V,RADIAL FUSE,3.15A,TE7,TIME LAG,300V,RADIAL FUSE,4A,TE7,TIME LAG,300V,RADIAL FUSE,5A,TE7,TIME LAG,300V,RADIAL FUSE,6.3A,TE7,TIME LAG,300V,RADIAL CONTACTOR,16 KVAR,220V AC CONTACTOR,30 KVAR,24V AC CONTACTOR,30 KVAR,48V AC CONTACTOR,30 KVAR,110V AC CONTACTOR,30 KVAR,120V AC CONTACTOR,30 KVAR,220V AC CONTACTOR,30 KVAR,230V AC CONTACTOR,30 KVAR,240V AC CONTACTOR,30 KVAR,380V AC CONTACTOR,30 KVAR,400V AC CONTACTOR,30 KVAR,415V AC CONTACTOR,30 KVAR,440V AC CONTACTOR,40 KVAR,24V AC CONTACTOR,40 KVAR,48V AC CONTACTOR,40 KVAR,110V AC CONTACTOR,40 KVAR,120V AC CONTACTOR,40 KVAR,220V AC CONTACTOR,40 KVAR,230V AC CONTACTOR,40 KVAR,240V AC CONTACTOR,40 KVAR,380V AC CONTACTOR,40 KVAR,400V AC CONTACTOR,40 KVAR,415V AC CONTACTOR,40 KVAR,440V AC N CHANNEL MOSFET,100V,9.3A,PQFN WALL PLATE,1 GANG PANELMAX DIN RAIL WIRING DUCT,PVC,2.15IN H PLUG & SOCKET CONN,PLUG,4POS,6.35MM TERMINAL,RING TONGUE,#10,CRIMP SUPER GRIP TIE MOUNTS,NYLON 6.6,1X1 IN SUPER GRIP TIE MOUNTS,NYLON 6.6,2X2 IN BRIDGE RECTIFIER,1PHASE,35A,600V,isoCink+ PB BRIDGE RECTIFIER,1PHASE,40A,600V,isoCink+ PB BRIDGE RECTIFIER,1PHASE,45A,600V,isoCink+ PB SWITCH,TOGGLE,SPST,15A,277V CABINET RACK,19IN,23IN,20U BARRE LUMINEUSE VERT 7.5MM X 14MM BARRE LUMINEUSE ROUGE 7.5MM X 14MM BARRE LUMINEUSE JAUNE 7.5MM X 14MM BARRE LUMINEUSE VERT 15MM X 15MM Tapped Rail BARRE LUMINEUSE ROUGE 15MM X 15MM Tapped Rail BARRE LUMINEUSE JAUNE 15MM X 15MM TAPPED RAIL Tapped Rail BARRE LUMINEUSE VERT 8MM X 5MM Tapped Rail TAPPED RAIL,HAMMOND C2,C3 or REFK SERIES RACKS,STEEL BARRE LUMINEUSE ROUGE 8MM X 5MM Tapped Rail BARRE LUMINEUSE JAUNE 8MM X 5MM BARRE LUMINEUSE VERT 16MM X 5MM BARRE LUMINEUSE ROUGE 16MM X 5MM BARRE LUMINEUSE JAUNE 16MM X 5MM LED ROUGE SOT-23 CMS LED JAUNE SOT-23 CMS LED HYPER ROUGE SOT-23 CMS LED VERT 0603 CMS LED ROUGE 0603 CMS LED VERT 0603 CMS LED VERT 0603 CMS LED ROUGE 0603 LENTILLE A DOME CMS LED JAUNE 0603 LENTILLE A DOME CMS LED ORANGE 0805 CMS LED VERT 0805 CMS LED JAUNE 0805 CMS LED JAUNE 0805 CMS LED ROUGE 1206 CMS LED JAUNE 1206 CMS LED VERT 1206 CMS LED JAUNE 1206 CMS LED JAUNE 1206 CMS AFFICHEUR CMS 0.2 ANODE COM ROUGE AFFICHEUR CMS 0.2 ANODE COM JAUNE AFFICHEUR CMS 0.2 CATHODE COM ROUGE AFFICHEUR CMS 0.2 CATHODE COM VERT AFFICHEUR CMS 0.2 CATHODE COM JAUNE AFFICHEUR CMS 0.2 ANODE COM ROUGE AFFICHEUR CMS 0.2 ANODE COM VERT AFFICHEUR CMS 0.2 ANODE COM JAUNE AFFICHEUR CMS 0.2 CATHODE COM ROUGE AFFICHEUR CMS 0.2 CATHODE COM VERT AFFICHEUR CMS 0.2 CATHODE COM JAUNE AFFICHEUR CMS 0.3 ANODE COM VERT AFFICHEUR CMS 0.3 ANODE COM JAUNE AFFICHEUR CMS 0.3 CATHODE COM ROUGE AFFICHEUR CMS 0.3 CATHODE COM JAUNE AFFICHEUR CMS 0.3 ANODE COM VERT AFFICHEUR CMS 0.3 ANODE COM JAUNE AFFICHEUR CMS 0.3 CATHODE COM ROUGE AFFICHEUR CMS 0.3 CATHODE COM VERT AFFICHEUR CMS 0.3 CATHODE COM JAUNE AFFICHEUR CMS 0.4 ANODE COM ROUGE AFFICHEUR CMS 0.4 ANODE COM VERT AFFICHEUR CMS 0.4 ANODE COM JAUNE AFFICHEUR CMS 0.4 CATHODE COM ROUGE AFFICHEUR CMS 0.4 CATHODE COM VERT AFFICHEUR CMS 0.4 CATHODE COM JAUNE AFFICHEUR CMS 0.4 ANODE COM ROUGE AFFICHEUR CMS 0.4 ANODE COM VERT AFFICHEUR CMS 0.4 ANODE COM JAUNE AFFICHEUR CMS 0.4 CATHODE COM ROUGE AFFICHEUR CMS 0.4 CATHODE COM VERT AFFICHEUR CMS 0.4 CATHODE COM JAUNE AFFICHEUR CMS 0.56 ANODE COM ROUGE AFFICHEUR CMS 0.56 ANODE COM VERT AFFICHEUR CMS 0.56 ANODE COM JAUNE AFFICHEUR CMS 0.56 CATHODE COM ROUGE AFFICHEUR CMS 0.56 CATHODE COM VERT AFFICHEUR CMS 0.56 CATHODE COM YELL AFFICHEUR CMS 0.56 ANODE COM ROUGE AFFICHEUR CMS 0.56 ANODE COM VERT AFFICHEUR CMS 0.56 ANODE COM JAUNE AFFICHEUR CMS 0.56 CATHODE COM ROUGE AFFICHEUR CMS 0.56 CATHODE COM VERT AFFICHEUR CMS 0.56 CATHODE COM YELL AFFICHEUR CMS 0.56 ANODE COM VERT AFFICHEUR CMS 0.56 ANODE COM JAUNE AFFICHEUR CMS 0.56 CATHODE COM ROUGE AFFICHEUR CMS 0.56 CATHODE COM VERT AFFICHEUR CMS 0.56 CATHODE COM YELL FAN TOP,AC,1 FAN,35W,550CFM N CH POWER MOSFET,HEXFET,150V,33A,DPAK N CH POWER MOSFET,HEXFET,60V,120A,D2PAK N CH MOSFET,HEXFET,60V,79A,D2PAK N CH POWER MOSFET,HEXFET,60V,270A,D2PAK DRAWER,STORAGE,19IN,STEEL,BLACK LOUVERED DOOR CABINET RACK 34.75IN STEEL DB25 EXT CABLE 6 FT MF TERMINAL,RING TONGUE,#10,CRIMP YELLOW CABINET RACK,19IN,21.34IN,20U NULL MODEM CABLE ASSEMBLY,25 FT,7.6 M,GREY BRIDGE RECTIFIER,1PH,15A,600V,GSIB-5S BRIDGE RECTIFIER,1PH,25A,600V,GSIB-5S SEAL PLUG,SHS HARNESS CONNECTOR RECTANGULAR CONN,SOCKET,18WAY,CRIMP VOLTAGE TESTER CAPACITOR PP FILM 2UF,2KV,10%,CASE IC,32BIT MCU,PIC32,40MHz,VFTLA-44 CAPACITOR PP FILM 0.5UF,1KV,10%,CASE CAPACITOR PP FILM 1UF,1KV,10%,CASE BRIDGE RECTIFIER,1PHASE,30A,800V,isoCink+ PB BRIDGE RECTIFIER,1PHASE,35A,800V,isoCink+ PB CIRCULAR CONNECTOR,PLUG,3POS,CABLE INTERFACE CONVERTER CABINET RACK,19IN,23IN,36U CABINET RACK,19IN,23IN,40U DRAWER,STORAGE,19IN,STEEL,BLACK RESISTOR,METAL FILM,250 OHM,1W,1% TERMINAL,RING TONGUE,#4,CRIMP,BLUE ADJUSTABLE SHELF,5.22IN,STEEL S-VIDEO CABLE,6FT,BLACK S-VIDEO CABLE,25FT,BLACK IC,PWM CONT,FLYBACK,15V,SOIC-16 DIODE,STANDARD,4A,200V,TO-277A DIODE,STANDARD,4A,400V,TO-277A DIODE,STANDARD,4A,600V,TO-277A DIODE,STANDARD,4A,800V,TO-277A DIODE,FAST RECOVERY,2A,800V,TO-277A DIODE,FAST RECOVERY,3A,800V,TO-277A TERMINAL,RING TONGUE,1/4IN,CRIMP RACK CABINET,TABLE TOP,17.5IN,STL BLK TERMINAL,RING TONGUE,1/2IN,CRIMP TERMINAL,SPADE/FORK,#10,CRIMP,BLUE FOLDING HANDLE,CHROME-PLATED STEEL HEX NUT PROGRAMMABLE VOICE SYNTHESIZER CONTACT,SOCKET,20-18AWG,CRIMP ALIMENTATION MEDICAL 250W SIMPLE SORTIE ALIMENTATION MEDICAL 250W SIMPLE SORTIE ALIMENTATION MEDICAL 250W SIMPLE SORTIE ALIMENTATION MEDICAL 250W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE ALIMENTATION MEDICAL 350W SIMPLE SORTIE CAPOT VENTIL EMH250/EMH350 CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 10W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 5W SINGE SORTIE ALIMENTATION 75W DOUBLE SORTIE ALIMENTATION 75W DOUBLE SORTIE ALIMENTATION 100W DOUBLE SORTIE ALIMENTATION 100W DOUBLE SORTIE ALIMENTATION MEDICAL 1.5KW SIMPLE SORTIE ALIMENTATION MEDICAL 1.5KW SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 60W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W SIMPLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE CONVERTISSEUR DC/DC 15W DOUBLE SORTIE ALIMENTATION 5W SIMPLE SORTIE ALIMENTATION 15W SIMPLE SORTIE ALIMENTATION 24W SIMPLE SORTIE ALIMENTATION 150W SIMPLE SORTIE ALIMENTATION 60W SIMPLE SORTIE ALIMENTATION 65W SIMPLE SORTIE ALIMENTATION 100W SIMPLE SORTIE ALIMENTATION 40W DOUBLE SORTIE AL

PUISSANCEPAK MOSFET CANAL N 60V 55A TO-220 MOSFET CANAL P 60V 18.3A TO-252 MOSFET CANAL P 20V 0.58A TO-236 TRANSISTOR NPN 800MHZ 30V TO39 TRANSISTOR NPN 1.2GHZ 20V TO39 MODULE IGBT 600V 16A IMS-2 MODULE IGBT 600V 24A IMS-2 MOSFET CANAL NN 20V MICROFET 2X2 MOSFET CANAL NN 80V 8SOIC MOSFET NCANAL P 30V/20V 8SOIC MOSFET NCANAL P 60V SC-89 MOSFET NCANAL P 20V SC-70 MOSFET CANAL NN 30V 8SOIC MOSFET NCANAL P 20V 1206 MOSFET CANAL PP 60V 8SOIC MOSFET CANAL PP 20V 8SOIC, PATCH ANTENNE 1575MHZ 50 OHM VSWR RF/ IF EMETTEUR AND RECEPTEUR ADAPTATEUR BANDSTRAP 38999 TAILLE 9 ADAPTATEUR BANDSTRAP 38999 TAILLE 13 ADAPTATEUR BANDSTRAP 38999 TAILLE 15 ADAPTATEUR BANDSTRAP 38999 TAILLE 17 ADAPTATEUR BANDSTRAP 38999 TAILLE 19 ADAPTATEUR BANDSTRAP 38999 TAILLE 21 ADAPTATEUR BANDSTRAP 38999 TAILLE 23 ADAPTATEUR BANDSTRAP 38999 TAILLE 25 ADAPTATEUR BANDSTRAP 38999 TAILLE 9 ADAPTATEUR BANDSTRAP 38999 TAILLE 11 ADAPTATEUR BANDSTRAP 38999 TAILLE 17 ADAPTATEUR BANDSTRAP 38999 TAILLE 19 ADAPTATEUR BANDSTRAP 38999 TAILLE 21 ADAPTATEUR BANDSTRAP 38999 TAILLE 23 ADAPTATEUR BANDSTRAP 38999 TAILLE 25 CORPS CONNECT ANGLE VARIABLE38999 9 CORPS CONNECT ANGLE VARIABLE38999 11 CORPS CONNECT ANGLE VARIABLE38999 13 CORPS CONNECT ANGLE VARIABLE38999 15 CORPS CONNECT ANGLE VARIABLE38999 17 CORPS CONNECT ANGLE VARIABLE38999 9 CORPS CONNECT ANGLE VARIABLE38999 11 CORPS CONNECT ANGLE VARIABLE38999 13 CORPS CONNECT ANGLE VARIABLE38999 15 CORPS CONNECT ANGLE VARIABLE38999 17 TINEL-LOCK ADAPTATEUR 38999 TAILLE 9 TINEL-LOCK ADAPTATEUR 38999 TAILLE 11 TINEL-LOCK ADAPTATEUR 38999 TAILLE 13 TINEL-LOCK ADAPTATEUR 38999 TAILLE 15 TINEL-LOCK ADAPTATEUR 38999 TAILLE 17 TINEL-LOCK ADAPTATEUR 38999 TAILLE 9 TINEL-LOCK ADAPTATEUR 38999 TAILLE 11 TINEL-LOCK ADAPTATEUR 38999 TAILLE 13 TINEL-LOCK ADAPTATEUR 38999 TAILLE 15 TINEL-LOCK ADAPTATEUR 38999 TAILLE 17 MICRO 32 BITS V850ES JC3-H 48LFQFP MICRO 32 BITS V850ES JC3-L 48LFQFP MICRO 32 BITS V850ES JE3-E 64LFQFP MICRO 32 BITS V850ES JE3-H 64LFQFP MICRO 32 BITS V850ES JE3-L 64LFQFP MICRO 32 BITS V850ES JF3-L 80LFQFP MICRO 32 BITS V850ES JF3-L 80LFQFP MICRO 32 BITS V850ES 100LFQFP MICRO 32 BITS V850ES L 100LFQFP MICRO 32 BITS V850ES L 100LFQFP MICRO 32 BITS V850ES L 100LFQFP MICRO 32 BITS V850ES JX 100LFQFP MICRO 32 BITS V850ES JX 100LFQFP MICRO 32 BITS V850ES JX3-L 100LFQFP MICRO 32 BITS V850ES JJ3 144LFQFP MICRO 32 BITS V850ES JJ3 144LFQFP MICRO 32 BITS V850ES JJ3 144LFQFP POTENTIOMETER,LINEAR,250KOHM,250mW,2 POTENTIOMETER,LINEAR,500KOHM,250mW,2 TESTER,CABLE CONTINUITY,SINGLE ENDED,9V RECEPTACLE HOUSING METAL RECEPTACLE HOUSING PLASTIC SIGNAL HOUSING 5 VOIES CONTACT RECEPTACLE MCON 2.5-4MM2 CONTACT RECEPT MCON 0.25-0.4MM2 CONTACT RECEPT MCON 0.5-0.75MM2 INSERT EMBASE 4 VOIES TAB CONNECTEUR KIT HOOD CAPOT SCREEN METAL LATERAL CLIP METAL KIT HOOD CAPOT SCREEN PLASTIC LATERAL CLIP PLASTIC PROTECTION CAPOT PROTECTION CAPOT SEALING VARISTANCE 275V 10% VARISTANCE 275V 10% VARISTANCE 14V 10% VARISTANCE 20V 10% VARISTANCE 25V 10% VARISTANCE 30V 10% VARISTANCE 30V 10% VARISTANCE 30V 10% VARISTANCE 35V 10% VARISTANCE 35V 10% VARISTANCE 40V 10% VARISTANCE 14V 10% VARISTANCE 14V +23% TO 0% VARISTANCE 14V +23% TO 0% ECLATEUR A GAZ 2 ELECTRODES 200V 30% ECLATEUR A GAZ 2 ELECTRODES 90V 20% ECLATEUR A GAZ 2 ELECTRODES 200V 20% ECLATEUR A GAZ 2 ELECTRODES 400V 20% THERMISTANCE DISC CTN 16 OHM 20% THERMISTANCE DISC CTN 4 OHM 20% THERMISTANCE DISC CTN 50 OHM 20% TRANSDUCER AUDIO SMT POTENTIOMETRE LINEAIR 5K 500MW 20% POTENTIOMETRE LINEAIR 10K 500MW 20% POTENTIOMETRE LINEAIR 5K 500MW 20% POTENTIOMETRE LINEAIR 10K 500MW 20% POTENTIOMETRE LINEAIR 10K 500MW 20% RESISTANCE PUISSANCE 10K 0.05 35W RESISTANCE PUISSANCE 100R 0.05 35W RESISTANCE PUISSANCE 15R 0.05 35W RESISTANCE PUISSANCE 1R 0.05 35W RESISTANCE PUISSANCE 20R 0.01 35W RESISTANCE PUISSANCE 470R 0.05 35W CONNECTEUR HOUSING RECEPTACLE 2 VOIES CONNECTEUR HOUSING RECEPTACLE 4 VOIES CONNECTEUR HOUSING RECEPTACLE 7 VOIES CONNECTEUR EMBASE THT 6 VOIES CONNECTEUR EMBASE THT 7 VOIES CONNECTEUR EMBASE R/A 2 VOIES CONNECTEUR EMBASE R/A 3 VOIES CONNECTEUR EMBASE R/A 6 VOIES CONNECTEUR EMBASE R/A 7 VOIES CONNECTEUR EMBASE R/A 2 VOIES CONNECTEUR EMBASE R/A 3 VOIES CONNECTEUR EMBASE R/A 4 VOIES CONNECTEUR EMBASE R/A 6 VOIES CONNECTEUR EMBASE R/A 7 VOIES KIT DEV ARRIA II GX 6G KIT DEV CYCLONE IV GX BIT SET 50MM IMPAKTOR 6PC BIT SET 25MM IMPAKTOR 10PC BIT SET 25MM IMPAKTOR 30PC LED EMBASE SOLDERLESS NO LATCH LS LED EMBASE SOLDERLESS LATCH LS TRANSISTOR NPNNPN 45V SOT-363 TRANS NPN 10K 50V 0.1A SC-75 TRANSISTOR NPN 45V 0.1A TO92 TRANSISTOR NPN 300V 0.5A TO92 TRANSISTOR PNP 300V 0.5A TO92 TRANSISTOR NPN 160V 0.6A TO92 TRANSISTOR NPN 45V 0.8A TO-92 TRANSISTOR NPN 300V 0.1A SOT-223 TRANSISTOR NPN 45V 0.1A SOT-23 TRANSISTOR NPN 45V 0.1A TO-92 TRANSISTOR NPN 30V 0.1A TO-92 TRANSISTOR NPN 45V 0.1A TO-92 TRANSISTOR PNP 60V 4A TO-225 TRANSISTOR NPN 80V 0.5A SOT-23 MOSFET NCANAL P 20V SOT-563 MOSFET CANAL N 30V 0.56A SOT-23 DIODE DE REDRESSEMENT 200V 1A DO-41 DIODE ZENER 5.6V 5W DO-41 DIODE ZENER 15V 0.5W SOD-123 DIODE ZENER 16V 0.5W SOD-123 DIODE ZENER 36V 0.225W SOT-23 DIODE ZENER 4.3V 3W SMB DIODE TVS 5V SOD-923 DIODE TVS 0.15W 7.8V SOD-923 RESEAU DE DIODE 30V 0.2A SOT323 RESEAU DE DIODE 40V 5A SMC INVERSEUR DOUBLE SCH TRIG 6SOT-363 BUFFER NON INV SCH TRIG 5SOT-353 BUFFER DOUBLE OPEN DRAIN 6SOT-363 INVERSEUR HEX SCHMITT TRIG 14TSSOP NPORTE ET SIMPLE 5SOT-23 BUFFER NON INVERTING SGL 5SOT-353 BUFFER CLOCK FANOUT 8SOIC PLL CLOCK MULTIPLIER 8SOIC BUFFER NON INVERTING SGL 5SOT-353 INVERSEUR SIMPLE 5SOT-23 EEPROM 256KBIT SPI 8DIP FICHE SEAL FIL CONTACT A SERTIR EMBASE 12-10AWG CONNECTEUR RECEPTACLE 23 37 EMBASE CONNECTEUR FICHE 23-37 VOIES HOUSING BULKHEAD METAL HOUSING FLANGE METAL TERMINAL BLOCK FUSED 22-12AWG 5X20MM, TERMINAL BLOCK FICHE 5POS 28-20AWG TERMINAL RING TONGUE 8MM CONTACT TERMINAL SLEEVE 2.65MM BLEU TERMINAL SLEEVE 1.47MM RED TERMINAL CONTACT FLAG 0.11IN TERMINAL CONTACT PIGGYBACK 6.35MM RED TERMINAL CONTACT CABLE SPLICE RED TERMINAL CONTACT FEMALE 0.25IN TERMINAL CONTACT 2.7MM CLAIR TERMINAL SPADE/FORK 4 CONTACT RED TERMINAL CONTACT RING 8MM JAUNE TERMINAL CONTACT FEMALE 9.53MM LOCKING LEVER HAN 10/16/24B RUBANR CODING BROCHE HAN CONNECTEUR HANDLE WITH HARDWARE SB50 SERIES CONN, HOUSING RECEPTACLE FASTON TERMINAL INSULATOR NYLON SERIES 250 LOCKING TABS,ACCESSORY TYPE:LOCKING TAB HOOD LATERAL ENTRY TAILLE 3A METAL RECEPTACLE PROTECTIVE CAP ALUMINUM ALLOY PROTECTIVE CAP ALUMINUM,SERIES:D3 PROTECTIVE CAP RECEPTACLE ALUMINUM TERMINAL BLOCK JUMPER 2 VOIES 5.1MM TERMINAL BLOCK MARKER EXTERNE PUISSANCE CONNECTEUR DC PUISSANCE 5A SERRE CABLE TAILLE 23 THERMOPLASTIQUE CONNECT CIRCUL TAILLE 11 ALUMINUM CONNECT CIRCUL TAILLE 13 ALUMINUM CONNECT CIRCUL TAILLE 17 ALUMINUM CONNECT CIRCUL TAILLE 11 ALUMINUM CONNECT CIRCUL TAILLE 15 ALUMINUM CONNECT CIRCUL TAILLE 23 ALUMINUM CONTACT A SERTIR EMBASE 16-14AWG CONTACT A SERTIR EMBASE 16AWG MI CONTACT A SERTIR EMBASE 30-26AWG CONTACT A SERTIR EMBASE 24-20AWG. CONTACT,CONNECTEUR TYPE:CONTACT CONTACT A SERTIR EMBASE 20-18AWG CONTACT A SERTIR BROCHE 22-18AWG CONTACT A SERTIR EMBASE 20-14AWG CONTACT A SERTIR EMBASE 26-22AWG FICHE CONNECTEUR HOUSING NOIR FICHE CONNECTEUR HOUSING AMP FICHE CONNECTEUR HOUSING MOLEX FICHE CONNECTEUR HOUSING NYLON FICHE CONNECTEUR HOUSING TE FICHE CONNECTEUR HOUSING NYLON FICHE CONNECTEUR HOUSING SERIE FICHE CONNECTEUR HOUSING SERIE FICHE CONNECTEUR HOUSING SERIE FICHE CONNECTEUR HOUSING NYLON CONNECTEUR FICHE & EMBASE HOUSING RECEPTACLE NYLON FICHE & EMBASE HOUSING FICHE NYLON,SERI FICHE & EMBASE HOUSING RCPT POLYESTER, FICHE & EMBASE CONNECTEUR FICHE 23POS, FICHE & EMBASE CONN EMBASE 2POS 4.2MM, FICHE & EMBASE CONNECT FICHE 1POS,SER FICHE & EMBASE CONNECT FICHE 1POS,SER FICHE & EMBASE CONN EMBASE 3POS 6.71MM FICHE & EMBASE CONNECT FICHE 1POS,SER FICHE & EMBASE CONNECT FICHE 2POS,SER FICHE & EMBASE CONNECT FICHE 2POS,SER FICHE & EMBASE CONNECT EMBASE 3POS 3MM FICHE & EMBASE CONNECT FICHE 2POS,SER FICHE & EMBASE CONNECT FICHE 1POS,SER FICHE & EMBASE CONNECT FICHE 1POS,SER FICHE & EMBASE CONNECT FICHE 1POS,SER FICHE & EMBASE CONNECT FICHE 1POS,SER DIODE,FAST,1.5A,200V,SMA CONTACT TOOL 20-32 AWG CONTACT TOOL 12-26 AWG LOCATOR POUR AFM8 CONTACT TOOL LOCATOR POUR AF8 CONTACT TOOL TWEEZERS BAMBOO 150MM TWEEZER SET ANTISTATIC INTERCHANG. SET FOUNT PUNCH ALESOIR AJUSTABLE 6.50 - 7.00MM ALESOIR AJUSTABLE 7.00 - 7.75MM ALESOIR AJUSTABLE 7.75 -8.50MM ALESOIR AJUSTABLE 8.50 - 9.25MM ALESOIR AJUSTABLE 9.25 - 10.00MM ALESOIR AJUSTABLE 10.00 - 10.75MM ALESOIR AJUSTABLE 10.75 - 11.75MM ALESOIR AJUSTABLE 11.75 - 12.75MM ALESOIR AJUSTABLE 12.75 - 13.75MM ALESOIR AJUSTABLE 13.75 - 15.25MM ALESOIR AJUSTABLE 15.25 - 17.00MM ALESOIR AJUSTABLE 17.00 - 19.00MM ALESOIR AJUSTABLE 19.00 - 21.00MM ALESOIR AJUSTABLE 21.00 - 23.00MM PICK-UP TOOL WITH INSPECTION MIRROR MICROSCOPE DE POCHE X75 MAG KIT MAG BASE CALIPER INDICATOR SET MICROMETER MECH 0-150MM SET MICROMETER MECH 0-6 MICROMETRE ANVIL 0-150MM / 6 HEAD MICROMETER 0.01MM/0-6.5MM HEAD MICROMETER 0.01MM/0-13MM HEAD MICROMETER 0.01MM/0-25MM INDICATOR LEVER DIAL TEST DUA-DIAL RULE CARREE END MAGNETIQUE 150MM RULE CARREE END MAGNETIQUE 300MM RULE CARREE END MAGNETIQUE 450MM RULE CARREE END MAGNETIQUE 600MM RULE CARREE END MAGNETIQUE 1000MM RULE MAGNETIQUE 150MM/6 RULE MAGNETIQUE 300MM/12 RULE MAGNETIQUE 600MM/24 LED ORANGE 5MM STANDARD LED ORANGE 3MM STANDARD KIT FEELER GAUGE BRASS SOLDER FIL CORDON FREE 0.38MM 250G MULTIMETER ANALOG 6 FUNCTIONS KIT CORDON DE TESTS HEAVY DUTY CORDON DE TEST 4MM 1M RED CONTACT RECEPTACLE TEST PCB SONDE DE TEST PCB BRAID DESOLDERING 2.5MM 0.25M CONVERTISSEUR DC/DC 30W AJUSTABLE SORTIE CONVERTISSEUR DC/DC 4.95W SIMPLE SORTIE CONVERTISSEUR DC/DC 7.5W SIMPLE SORTIE CONVERTISSEUR DC/DC 30W AJUSTABLE SORTIE CABLE 4 CORE CHROME 18AWG 30.5M CABLE 4 CORE NOIR 152.4M CABLE 2 CORE BLANC 26AWG 30.5M CABLE 2 PAIRES CHROME 24AWG 30.5M OSCILLOSCOPE 60MHZ 2 VOIES OSCILLOSCOPE 100MHZ 2 VOIES OSCILLOSCOPE 70MHZ 2 VOIES OSCILLOSCOPE 70MHZ 4 VOIES OSCILLOSCOPE 100MHZ 2 VOIES OSCILLOSCOPE 100MHZ 4 VOIES OSCILLOSCOPE 200MHZ 2 VOIES OSCILLOSCOPE 200MHZ 4 VOIES OSCILLOSCOPE 300MHZ 2 VOIES OSCILLOSCOPE 300MHZ 4 VOIES COFFRET120X103X53 VOIES MOUNT COFFRET120X103X53 VOIES MOUNT COFFRET160X103X53 VOIES MOUNT COFFRET220X103X53 VOIES MOUNT COFFRET220X103X53 VOIES MOUNT BOLTS POUR 1455NC SERIES NUTS POUR 1455NC SERIES NUTS & SPRINGS POUR 1455NC SERIES COFFRET119X94X30 JAUNE COFFRET145X121X35 PURPLE COFFRET145X121X35 JAUNE COFFRETOCTAGON PURPLE COFFRETOCTAGON JAUNE COFFRETNARRANGEE TRAPEZOID JAUNE COFFRETWIDE TRAPEZOID PURPLE COFFRETWIDE TRAPEZOID JAUNE ALIMENTATION AC/DC 24V 14.7A 350W ALIMENTATION AC/DC 48V 7.5A 350W ALIMENTATION AC/DC 24V 25A 750W ALIMENTATION AC/DC 48V 12.5A 750W KIT TESTER FIBER ONESHOT PRO TESTER FIBER ONESHOT PRO TESTEUR FIBER QUICKMAP KIT TESTER FIBER QUICKMAP KIT TESTER FIBER QUICKMAP CAPTEUR ROTATIF HALL 60DEG 5V CAPTEUR ROTATIF HALL 60DEG 10-30V CAPTEUR ROTATIF HALL 90DEG 5V CAPTEUR ROTATIF HALL 90DEG 10-30V CAPTEUR ROTATIF HALL 120DEG 10-30V CAPTEUR ROTATIF HALL 180DEG 5V CAPTEUR ROTATIF HALL 180DEG 10-30V CAPTEUR ROTATIF HALL 360DEG 5V CAPTEUR ROTATIF HALL 360DEG 10-30V MODULAR COUPLAR IN-LINE CAT5E RELAIS 3 PHASE 2C/O 160-300VAC RELAIS 3 PHASE 2C/O 300-500VAC RELAIS 3 PHASE 2C/O 380VSC RELAIS 3 PHASE 2C/O 400VSC RELAIS 3 PHASE 2C/O 160-300VAC RELAIS 3 PHASE 2C/O 300-500VAC RELAIS 3 PHASE 2C/O 160-300VAC RELAIS 3 PHASE 2C/O 300-500VAC RELAIS 3 PHASE 2C/O 90-170VSC RELAIS 3 PHASE 2C/O 180-280VAC RELAIS 3 PHASE 2C/O 180-280VAC RELAIS 3 PHASE 2C/O 350-580VAC RELAIS 3 PHASE 2C/O 450-720VAC RELAIS 3 PHASE 2C/O 530-820VAC RELAIS 3 PHASE 2C/O 200-500VAC RELAIS 1 PHASE 1C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 1C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 1C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 1C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 2C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 2C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 2C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 2C/O OVER/UNDER VOLTAGE RELAIS 1 PHASE 1C/O OVER/UNDER COURANT RELAIS 1 PHASE 1C/O OVER/UNDER COURANT RELAIS 1 PHASE 1C/O OVER/UNDER COURANT RELAIS 1 PHASE 1C/O OVER/UNDER COURANT RELAIS 1 PHASE 1C/O OVER/UNDER COURANT RELAIS 1 PHASE 1C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT RELAIS 1 PHASE 2C/O OVER/UNDER COURANT TIME COMMUTATEUR NUMERIQUE ONE VOIES TIME COMMUTATEUR NUMERIQUE TWO VOIES FICHE UTL 4 VOIES BROCHE FICHE UTL 4 VOIES SKT RECEPTACLE PANEL UTL 4 VOIES BROCHE RECEPTACLE PANEL UTL 4 VOIES SKT RECEPTACLE JAM NUT UTL 4 VOIES BROCHE RECEPTACLE JAM NUT UTL 4 VOIES SKT RECEPTACLE INLINE UTL 4 VOIES BROCHE RECEPTACLE INLINE UTL 4 VOIES SKT CAPOT ANTI POUSS UTL RECEPTACLE INSTR-AMPLIFIER,15MHZ,90DB,SOIC-8 OP-AMP,16.3MHZ,25V/ us,LFCSP-8 MONITOR,VOLTAGE,6.5UA,5.5V,TSOT-6 LED DRIVER,PWM,1MHZ,LFCSP-14 DC-DC REGULATOR,BUCK,5A,LFCSP-32 DAC,16BIT,LFCSP-10 DAC,16BIT,LFCSP-10 DAC,16BIT,LFCSP-8 DAC,10BIT,LFCSP-6 DAC,10BIT,LFCSP-6 DAC,10BIT,SC70-6 IC,DAC,12BIT,1.7MSPS,LFCSP-6 DAC,14BIT,LFCSP-6 DAC,14BIT,SC70-6 DAC,QUAD,16BIT,LFCSP-64 AMPLIFIER,CLASS G,50mW,WLCSP-16 PCB CONTACT,PIN,SOLDER PCB CONTACT,PIN,SOLDER PCB CONTACT,PIN,SOLDER PCB CONTACT,PIN,SOLDER PCB CONTACT,PIN,SOLDER PCB CONTACT,PIN,SOLDER PCB CONTACT,PIN,SOLDER PCB CONTACT,PIN,SOLDER CONDENSATEUR 120UF 250V 20% 18X20MM CONDENSATEUR 200UF 200V 20% 35X40MM CONDENSATEUR 800UF 250V 20% 35X50MM CONDENSATEUR 68UF 100V 20% 8X20MM CONDENSATEUR 680UF 100V 20% 18X35.5MM CONDENSATEUR 390UF 25V 20% 10X12.5MM CONDENSATEUR 0.1F 3.5V CONDENSATEUR 0.1F 3.5V CMS CONDENSATEUR 50000UF 3.5V CONDENSATEUR 50000UF 3.5V CMS CONDENSATEUR 0.24F 4.2V CONDENSATEUR 0.24F 4.2V CMS CONNECTOR,AC OUTLET,DUPLEX,RCPT,15A,120V OPTOC. 6MM 24/5-24V 100MA 2L. 10KH Â´REF DE TENS SERIES 5V 0.005V 8SOIC CONVERTISSUER N-A 10BIT 50MHZ 48LQFP CAPTEUR TEMP 10BIT +/-2DEG 8MSOP AMP TRANSIMPEDANCE 240MHZ 8SOIC AMPLI OP 125MHZ 62V/US 8SOT23 AMPLI OP 10MHZ 4V/US 8MSOP CAN 14 BITS 8CH MUX 250KSPS 20LFCSP ISOLATEUR QUADRUPLE 100NS 16WSOIC CAN 16 BITS 6CH MUX 200KSPS 64QFP V REG 37VIN 0.5A AJUSTABLE 3DPAK REGULATEUR LDO 37VIN 0.1A 5V 3DPAK AMPLI OP 44VIN 4.5MHZ 13V/US 8SOIC REGUL LDO 20VIN 0.8A AJUSTABLE 8SOIC AMPLI OP 32VIN 1MHZ 0.6V/US 8SOIC AMPLI OP 32VIN 1MHZ 0.6V/US 8SOIC BUCK 37VIN 1A 5V 5TO220 CTRL MOTEUR 3PHASE 30V 20WSOIC REGULATEUR LDO 9VIN 3A AJUSTABLE 5DPAK V REG 37VIN 0.5A AJUSTABLE 3DPAK REGULATEUR LDO 0.1A 5V 0.5% 3DPAK REGULATEUR LDO 35VIN 1A 12V 3D2PAK REGULATEUR LDO 35VIN 1A 12V 3D2PAK AMPLI OP DOUBLE 10MHZ 9V/US 16SOIC CONTROLEUR PWM MODE COURANT 500KHZ 8SOIC REGULATEUR LDO -35VIN 1A -15V 3TO220 REGULATEUR LDO 35VIN 1A 5V 3D2PAK REGULATEUR LDO 35VIN 1A 9V 3D2PAK CAPTEUR DE PRESSION 20 TO 304KPA SSOP8 MOTEUR DRIVER HALF BRIDGE 5A QFN32 REG LINEAIR 1.2V TO 37V AJUSTABLE 3TO92 BUCK DOUBLE 0.6A 1.5MHZ 10MSOP BUCK 4.5A 500KHZ 7DPAK AMPLI OP 90MHZ 22V/US 8SOIC REGULATEUR LDO 0.5A 1.5V 8SOIC REGULATEUR LDO 0.9-10VIN 0.5A 1.2V 16DFN DAC 16 BITS 5.5VIN 50MHZ 10MSOP BUCK 0.3A 1.8V 1.5MHZ 6TSOT23 BUCK 36VIN 0.6A 500KHZ 6SOT23 COMPARATEUR 5V 10NS 8SOIC LDO VREF 2.5V 0.15% 8SOIC CHARGEUR BATTERIE LI-ION 1.5A 8SOIC HOT SWAP BUS BUFFER 400KHZ 8MSOP REGULATEUR LDO 1.8V 0.3A 8MSOP BUCK DOUBLE 36VIN 1.4A 16TSSOP LIMITEUR DE PUISSE -60V TO 100V 16SOIC BUCK 45VIN 0.05A 3.3V 8MSOP BUCK DOUBLE 36VIN 0.7A 14DFN BUCK DOUBLE 36VIN 0.7A 16MSOP AMPLI OP E/S RAIL 5.25V 180MHZ 6TSOT23 AMPLI OP E/S RAIL 5.25V 180MHZ 6TSOT23 BOOST DOUBLE 38VIN AJUSTABLE 32QFN REGUL LDO 0.6V TO 44.5V AJUSTABLE 12MSOP BUCK 40V 200KHZ-2.2MHZ 0.35A 10DFN CAPTEUR TEMP -40 TO 100 DEG 8SOIC BUCK 42VIN 550KHZ 0.6A 6TSOT CNTRL HOT SWAP 17VIN PROG 10MSOP AMPLI OP 35VIN 2A 8V/US 5TO263 IC,LINEAR VOLT REGULATOR 3.3V SOT-223-4 CONDENSATEUR ALUMINIUM ELECTROLYTIQUE CONDENSATEUR ALUMINIUM ELECTROLYTIQUE CONDENSATEUR ALUMINIUM ELECTROLYTIQUE

TAILLE 18 11 V SKT (L/C) CONNECT CIRCUL TAILLE 18 11 V SKT (L/C) CONNECT CIRCUL TAILLE 18 11 V SKT (L/C) CONNECT CIRCUL TAILLE 18 11 V SKT (L/C) CONNECT CIRCUL TAILLE 18 11 V SKT (L/C) CONNECT CIRCUL TAILLE 18 11 V SKT (L/C) CONNECT CIRCUL TAILLE 18 14 V (L/C) CONNECT CIRCUL TAILLE 18 14 V (L/C) CONNECT CIRCUL TAILLE 18 14 VOIES BROCHE CONNECT CIRCUL TAILLE 18 14 VOIES BROCHE

VOIES SKT CONNECT CIRCUL TAILLE14 4 VOIES SKT CONNECT CIRCUL TAILLE14 7 VOIES (L/C) CONNECT CIRCUL TAILLE14 7 VOIES (L/C) CONNECT CIRCUL TAILLE14 7 VOIES BROCHE CONNECT CIRCUL TAILLE14 7 VOIES BROCHE

CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE CONNECT CIRCUL TAILLE 14 7 VOIES (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE SWITCH,INDUSTRIAL PUSHBUTTON,40MM CONNECT CIRCUL TAILLE 14 7 VOIES (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE CONNECT CIRCUL TAILLE 14 7 VOIES (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE CONNECT CIRCUL TAILLE 14 7 VOIES BROCHE CONNECT CIRCUL TAILLE 14 7 VOIES SKT (L/C) CONNECT CIRCUL TAILLE 14 7 V SKT (L/C) CONNECT CIRCUL TAILLE 14 7 V SKT (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES SKT CONNECT CIRCUL TAILLE 14 7 VOIES SKT CONNECT CIRCUL TAILLE 14 7 V SKT (L/C) CONNECT CIRCUL TAILLE 14 7 V SKT (L/C) CONNECT CIRCUL TAILLE 14 7 V SKT (L/C) CONNECT CIRCUL TAILLE 14 7 V SKT (L/C) CONNECT CIRCUL TAILLE 14 7 VOIES SKT CONNECT CIRCUL TAILLE 14 7 VOIES SKT

SKT CONNECT CIRCUL TAILLE 22 55 V SKT (L/C) CONNECT CIRCUL TAILLE 22 55 VOIES SKT CONNECT CIRCUL TAILLE 22 55 V SKT (L/C) CONNECT CIRCUL TAILLE 22 55 VOIES SKT CONNECT CIRCUL TAILLE 22 55 V SKT (L/C) CONNECT CIRCUL TAILLE 22 55 VOIES SKT CONNECT CIRCUL TAILLE 22 55 V SKT (L/C) CONNECT CIRCUL TAILLE 24 61 VOIES BROCHE CONNECT CIRCUL TAILLE 24 61 V

CONTACT,RECEPTACLE,20-18 AWG,CRIMP EXTENSION JOINT,LED LIGHTBAR U-SHAPE JUMPER,LED LIGHTBAR BAR TO BAR CONNETOR,LED LIGHTBAR EXTENSION JOINT,LED LIGHTBAR CONNECTOR,HOUSING,RCPT,4POS,1ROW SWITCH,ROCKER,DPST,20A,125V CIRCULAR CONNECTOR PLUG SIZE 15,18POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 19,11POS,CABLE BUSS CONTACT,1PAIR,CRIMP/SOLDER SCREW,RRAL SERIES OPEN FRAME RELAY RACKS CIRCULAR STRAIN RELIEF,STR,W/CLAMP,SZ11,METAL PC SCREW TERMINAL AMPLI VIDEO FILTRE 8LFCSP SHARC DSP 200MHZ 88LFCSP PHONE JACK 3 VOIES ADAPTATEUR RCA FICHE TO RECEPTACLE CONNECTEUR SUB-D RECEPTACLE 9 VOIES SUB-D RECEPTACLE STANDARD 15 VOIES CONNECTEUR SUB-D FICHE 9 VOIES CONNECTEUR SUB-D RECEPTACLE 9 VOIES MINI USB 2.0 TYPE B RECEPTACLE SMT MINI USB 2.0 TYPE A RECEPTACLE USB 2.0 TYPE A RECEPTACLE USB 2.0 TYPE A RECEPTACLE USB 2.0 TYPE A RECEPTACLE CONNECTEUR RCPT 50 VOIES 1.27MM SATA RECEPTACLE SMT 22 VOIES USB 2.0 TYPE A RECEPTACLE THD CONNECTEUR RECEPTACLE IDT 4 VOIES SFP RECEPTACLE SMT 20 VOIES CONNECTEUR CENTRONICS FICHE 24 VOIES USB 2.0 TYPE B RECEPTACLE USB 2.0 TYPE B RECEPTACLE THD CONNECTEUR SCSI FICHE IDC/IDT 68 VOIES CONNECTEUR MINI D RIBBON FICHE 24 VOIES CONNECTEUR RECEPTACLE IDC/IDT 68 VOIES DISCRETE RECEPTACLE CLOSED 3.61MM DIN 41612 RECEPTACLE 64 VOIES STACKING FICHE 0.8MM 80 VOIES CONNECTEUR RECEPTACLE 2MM 24 VOIES CONNECTEUR EMBASE 2MM 4 VOIES CONNECTEUR RECEPTACLE 2MM 26 VOIES CONNECTEUR EMBASE 2.54MM 40 VOIES CONNECTEUR RECEPTACLE 2MM 44 VOIES CONNECTEUR CARTE-CARTE EMBASE 3 VOIES CONNECTEUR RECEPTACLE 2.54MM 8 VOIES CONNECTEUR EMBASE 2.5MM 2 VOIES CONNECTEUR EMBASE 2.54MM 7 VOIES CONNECTEUR RECEPTACLE 3.96MM 3 VOIES CONNECTEUR RECEPTACLE 3.96MM 6 VOIES CONNECTEUR HOUSING FICHE 1.25MM 3 VOIES CONNECTEUR RECEPTACLE 2.54MM 2 VOIES CONNECTEUR RECEPTACLE 2.54MM 4 VOIES CONNECTEUR RECEPTACLE 2.54MM 6 VOIES CONNECTEUR EMBASE 2.54MM 4 VOIES CONNECTEUR RECEPTACLE 2MM 20 VOIES CONNECTEUR EMBASE 2MM 10 VOIES SWITCH CAP CONNECTEUR EMBASE 2MM 14 VOIES CONNECTEUR EMBASE 2MM 20 VOIES CONNECTEUR RECEPTACLE 2.54MM 64 VOIES CONNECTEUR RECEPTACLE 2.54MM 1 VOIES CONNECTEUR EMBASE 2.54MM 3 VOIES CONNECTEUR EMBASE 10 VOIES CONNECTEUR RECEPTACLE 2.54MM 10 VOIES CONNECTEUR RECEPTACLE 10 VOIES HOUSING RECEPTACLE 2.54MM 3 VOIES CONNECTEUR FICHE 2.54MM 6 VOIES CONNECTEUR RECEPTACLE 2MM 16 VOIES FFC/FPC CONNECTEUR RECEPTACLE 3 VOIES CONNECTEUR FFC/FPC 1MM 4 VOIES CONNECTEUR FFC/FPC 0.5MM 40 VOIES SMA JACK STR 50OHM CONTACT SMB FICHE STR 50OHM SOLDER SMA FICHE STR 50OHM CONTACT, SMA JACK STR 50OHM SOLDER TNC JACK 50OHM BULKHEAD SMA FICHE STR 50OHM CONTACT RF COAXIAL BNC JACK 50OHM SOLDER RF COAXIAL SMA JACK 50OHM CONTACT RF COAXIAL SMA JACK 50OHM SOLDER RF COAXIAL SMA JACK 50OHM SOLDER SMA JACK 50OHM BULKHEAD RF COAXIAL SMB JACK 75OHM SOLDER RF COAXIAL SMA FICHE 50OHM TERMINAL BLOCK PCB 28-20AWG 4 VOIES TERMINLA BLOCK 2MM 6 VOIES RETRACTILE FICHE 36A SCREW RED RETRACTILE FICHE 36A SOLDERLESS INSULATED TERMINAL 30A SOLDER RED POINTE DE TEST PCB THROUGH HOLE POINTE DE TEST PCB THROUGH HOLE RETAINER CLIP CF CARTE EMBASE JUMPER SHUNT 2MM 2 VOIES ADAPTATEUR RCA JACK-BNC FICHE CAT5/CAT5E RJ45 JACK 8 VOIES 1 PORT CAT3 RJ12 JACK 6 VOIES 1 PORT SUB-D SHELL RECEPTACLE TAILLE 3 STEEL JONCTION SHELL TAILLE DB STEEL CABLE CLAMPE KIT TAILLE 4 ZINC ALLOY HOOD SUB-D TAILLE DE SUB-D CAPOT ZINC ALLOY SUB-D HOOD TAILLE DA METAL MEMORY EMBASE SIM 6 VOIES MOSFET CANAL N 80V 74A D2PAK MOSFET CANAL N 100V 57A D2PAK MOSFET CANAL N 80V 50A D2PAK MOSFET CANAL N 100V 37A D2PAK MOSFET CANAL N 100V 32A D2PAK MOSFET CANAL N 80V 22A D2PAK MOSFET CANAL N 60V 92A D2PAK MOSFET CANAL N 40V 77A D2PAK MOSFET CANAL N 80V 90A D2PAK MOSFET CANAL N 100V 89A D2PAK MOSFET CANAL N 30V 120A D2PAK MOSFET CANAL N 40V 120A D2PAK MOSFET CANAL N 60V 120A D2PAK MOSFET CANAL N 80V 120A D2PAK MOSFET CANAL N 100V 120A D2PAK MOSFET CANAL N 30V 120A D2PAK MOSFET CANAL N 40V 120A D2PAK MOSFET CANAL N 60V 120A D2PAK MOSFET CANAL N 80V 120A D2PAK MOSFET CANAL N 100V 120A D2PAK ADC 12 BITS 1MSPS +/-1LSB 30TSSOP AMPLI OP RRO 8MHZ 2.9V/ÂµS 5SOT23 AMPLI OP RRO 300MHZ 650V/ÂµS 8SOIC AMPLI OP RAIL/RAIL 10MHZ 5V/ÂµS 8WLCSP AMPLI OP 12MHZ 2.7V/ÂµS 5SOT23 AMPLI OP DOUBLE 160MHZ 200V/ÂµS 8SOIC AMPLI OP 1.8MHZ 3V/ÂµS 8MSOP AMPLI OP 900MHZ 1600V/ÂµS 8MLP AMPLI OP 1.8MHZ 3.4V/ÂµS 8DIP LOG AMP 0.1-10GHZ 5.5V 8LFCSP LOG AMP 0.1-8GHZ 5V 16LFCSP MESURE DE COURANT AMP 60KHZ 60V 8SOIC COMMUTATEUR ANAL DOUBLE SPDT 15V 16DIP COMPARATEUR DOUBLE 2.7-5.3V 8MSOP LED COURANT REG 0.35A 6-40V 8SOIC MOTEUR DRIVER 50V +/-1.5A 24TSSOP DRIVER MOSFET 600V 20V 28PDIP V/F CONVERTISSEUR 2MHZ 0.02% 5V 16DIP CONVERTISSEUR F/V 28VIN +/-0.3% 14SOIC BUCK 5.5VIN 3MHZ 0.6A 3.3V 5TSOT BUCK 42VIN 1.25MHZ 0.6A AJUSTABLE 6TSOT BUCK 95VIN 0.35A AJUSTABLE 8LLP BUCK 42VIN 1A 6W 0.8V TO 6V 7TOPMOD BUCK 5.5VIN 1.7MHZ AJUSTABLE 1% 5TSOP BUCK CHRGPUMP 0.25A AJUSTABLE 10MSOP REGUL LDO 6VIN 1.5A 3.3V 1.5% 3SOT223 REGUL LDO 3.4 TO 45VIN 0.2A AJUST 8SOIC REGULATEUR LDO 6VIN 2A 0.2% 8SOIC REGUL LDO 10VIN 0.1A AJUSTABLE 5SOT23 REGUL LDO 1.5A 1.21V TO 20V AJUST 5TO263 REGULATEUR LDO 5V 0.25A 1.5% 5SOT23 CONTROLEUR MODE COURANT 500KHZ 8SOIC CONTROLEUR PWM 18VIN 1MHZ 8SOIC CONTROLEUR TENSION 2.45 VREF 40V 8MICRO COMMUTATEUR COURANT LIMITED 0.5A 8MSOP ACCELEROMETRE 1 AXES +/-35G 8LCC CAPTEUR HALL EFFECT LINEAIR 120KHZ CAPTEUR HALL EFFECT LINEAIR 120KHZ CONTRÃ"LE VENTIL WATCHDOG 24TSSOP VREF 15VIN 5V 0.12% 5TSOT VREF 18VIN 4.096V 0.04% 8SOIC REGULATEUR SHUNT 10V 0.5% 3STO23 ISOLATEUR NUMERIQUE QUADRUPLE 3:1 16SOIC GROMMETING,EXTRUDED,NYLON,BLACK,100FT DAC QUAD 12 BITS +/-2LSB SPI 16TSSOP DAC QUAD 12 BITS +/-1LSB SPI 16TSSOP DAC QUADRUPLE 14BIT +/-4LSB SPI 16TSSOP DAC QUADRUPLE 14BIT +/-1LSB SPI 16TSSOP DAC QUAD 16 BITS +/-8LSB SPI 16TSSOP DAC QUAD 12 BITS +/-2LSB I2C 16TSSOP DAC QUAD 12 BITS +/-1LSB I2C 16TSSOP DAC QUADRUPLE 14BIT +/-4LSB I2C 16TSSOP DAC QUADRUPLE 14BIT +/-1LSB I2C 16TSSOP DAC QUAD 16 BITS +/-8LSB I2C 16TSSOP DAC QUAD 16 BITS +/-2LSB I2C 16TSSOP INDUSTRIAL PROG SORTIE I V DRVR 32LFCSP ADC 12 BITS 3.6V 105KSPS I2C 16LFCSP ADC 12 BITS 3.6V 105KSPS SPI 16LFCSP AMPLI OP QUAD RAILL 18V 240KHZ 14SOIC ADC 12 BITS 8CH I/Q DEMOD 144CSPBGA ADC 12 BITS 8CH I/Q DEMOD 144CSPBGA ADC QUADRUPLE 16 BITS 125MSPS 48LFCSP AMPLI DIFF DOUBLE 5.5VIN 84MHZ 16LFCSP BUCK 16VIN 0.8A 0.6/1.2MHZ AJUSTA 8QFN BUCK 16VIN 0.8A 0.6/1.2MHZ AJUST 8QFN BUCK SYNCH 20VIN 6A 1.4MHZ 16TSSOP Â´REF DE TENS 15VIN 3V +/-0.04% 8SOIC Â´REF DE TENS 15VIN 3V +/-0.02% 8SOIC Â´REF DE TENS 15VIN 5V +/-0.02% 8SOIC CONDENSATEUR 0.1UF 500V X7R RAD CONDENSATEUR 1UF 200V X7R RAD D CONDENSATEUR 0.06F 3.3V STAKED COIN FERRITE CHIP BEAD CMS 0.1OHM 0.6A FILTRE DE MODE COMMUN POWER LINE CMS FILTRE DE MODE COMMUN POWER LINE CMS FILTRE DE MODE COMMUN POWER LINE CMS BOBINE DE MODE COMMUN 2000UH 0.6A RESISTANCE LADDER N/W 10 10KOHM 2% SIP RESEAU RESISTANCE 4RES 49.9OHM 5% 1206 RESEAU DE RESISTANCE 4RES 51OHM 5% 0805 RESEAU DE RESISTANCE 4RES 56OHM 5% CMS GAS DISCHARGE TUBE 2P 10KA 8KV BOBINE 0.051MH 0.5A 30% 100KHZ INDUCTANCE PUISSANCE 1MH 0.26A 20% THERMISTANCE CTN RADIAL 10KOHM THERMISTANCE CTP CMS 27OHM THERMISTANCE CTP CMS 680OHM THERMISTANCE CTP RADIAL 25OHM THERMISTANCE CTP RADIAL 50OHM CONDENSATEUR 27PF 250V C0G 0603 CONDENSATEUR 82PF 250V C0G 0603 CONDENSATEUR 82PF 250V C0G 0603 CONDENSATEUR 47PF 50V C0G/NP0 RAD CONDENSATEUR 1800UF 6.3V RADIAL CONDENSATEUR 1000UF 63V RADIAL FERRITE BEAD 0603 40MOHM 3A FERRITE BEAD 0805 450MOHM 0.3A FILTRE DE MODE COMMUN POWER LINE CMS FILTRE DE MODE COMMUN POWER LINE CMS CONDENSATEUR 4.7PF 1000V C0G RAD CONDENSATEUR 0.1UF 50V X7R RAD CONDENSATEUR 1UF 50V Y5V RADIAL CONDENSATEUR RF 1000PF 1KV 2220 RESISTANCE THICK FILM 40MOHM 1.5W 1% RESEAU DE RESISTANCE 9 BROCHES 10K 2% CONDENSATEUR 56PF 1000V C0G RAD CONDENSATEUR 1UF 50V X7R RADIAL CONDENSATEUR 0.68UF 50V X7R RAD CONDENSATEUR 1UF 50V X7R RADIAL CONDENSATEUR 1UF 50V X7R RADIAL CONDENSATEUR 1UF 35V 8OHM CONDENSATEUR RESEAU DE 0.1UF 50V X7R SIP RESISTANCE METAL FILM 10OHM 2W RESIST MESURE DE COURANT 500OHM 30W 1% RESISTANCE METAL OXIDE 0.2GOHM 1W 1% CONDENSATEUR 470PF 440V K4000 RAD CONDENSATEUR 10UF 16V 3.2OHM CONDENSATEUR 10UF 25V 2.5OHM CONDENSATEUR 10UF 35V 2OHM CONDENSATEUR TRIMMER 0.6-4.5PF 500V CMS FERRITE BEAD CYLINDRICAL 50OHM THERMISTANCE CTN RADIAL 4OHM CONDENSATEUR 2200PF 760V K2000 RA CONDENSATEUR 1UF 63V RADIAL CONDENSATEUR 47UF 16V 1.3OHM CONDENSATEUR 22UF 25V RADIAL POTENTIOMETRE TRIMMER 1KOHM 11TOURS POTENTIOMETRE TRIMMER 10KOHM 11TOURS POTENTIOMETRE TRIMMER 1MOHM 11TOURS POTENTIOMETRE TRIMMER 1KOHM 20TOURS POTENTIOMETRE TRIMMER 500OHM 20TOURS POTENTIOMETRE TRIMMER 5KOHM 23TOURS THERMISTANCE CTN RADIAL 10OHM THERMISTANCE CTN RADIAL 40OHM THERMISTANCE CTN RADIAL 10OHM THERMISTANCE CTN RADIAL 2.5OHM CONDENSATEUR 22UF 25V AXIAL CONDENSATEUR 10UF 63V AXIAL CONDENSATEUR 1F 5.5V STAKED COIN FERRITE BEAD CYLINDRICAL 111OHM CONDENSATEUR 100UF 16V AXIAL CONDENSATEUR 47UF 63V RADIAL CONDENSATEUR 220UF 25V RADIAL THERMISTANCE CTN RADIAL 10KOHM THERMISTANCE CTN RADIAL 20OHM THERMISTANCE CTN RADIAL 0.5OHM CONDENSATEUR 1000PF 15000V Y5U FERRITE BEAD CYLINDRICAL 92OHM CONDENSATEUR 1000UF 16V RADIAL CONDENSATEUR 470UF 16V AXIAL CONDENSATEUR 470UF 50V RADIAL CONDENSATEUR 470UF 25V RADIAL THERMISTANCE CTN RADIAL 10KOHM THERMISTANCE CTN RADIAL 30KOHM CONDENSATEUR 470UF 40V AXIAL CONDENSATEUR 330UF 63V AXIAL CONDENSATEUR 22UF 400V RADIAL CONDENSATEUR 1000UF 25V AXIAL FERRITE CHIP BEAD 425OHM RESISTANCE BOBINEE 100KOHM 50W 1% SUPPRESSION CORE SOLID ROUND 153OHM SUPPRESSION CORE SNAP ON 400OHM CONDENSATEUR 2200UF 40V AXIAL CONDENSATEUR 1000UF 63V AXIAL CONDENSATEUR 100UF 400V RADIAL CONDENSATEUR 4700UF 40V AXIAL POT BOBINEE 5KOHM 5% 2W SUPPRESSION CORE SOLID ROUND 300OHM RESISTANCE BOBINEE 5OHM 300W 10% RESISTANCE BOBINEE 10OHM 300W 10% CONDENSATEUR 2200UF 6.3V RADIAL CONDENSATEUR 3300UF 6.3V RADIAL CONDENSATEUR 1800UF 16V RADIAL CONDENSATEUR 1000UF 50V RADIAL CONDENSATEUR 4.7UF 400V RADIAL RESEAU DE RESISTANCE 4RES 49.9OHM 1% END PLATE,RAIL MOUNTED TERMINAL BLOCK TERMINAL BLOCK END PLATES/PARTITION END PLATE,RAIL MOUNTED TERMINAL BLOCK END PLATE,RAIL MOUNTED TERMINAL BLOCK KIT DÃ´EVAL FM3 CORTEX M3 MB9B KIT DÃ´EVAL MB9BX00 J-LINK ADAPTATEUR KIT DÃ´EVAL FM3 CORTEX M3 MB9A310L KIT DÃ´EVAL MB9A310L J-LINK ADAPTATEUR KIT DÃ´EVAL FM3 CORTEX M3 MB9B KIT DÃ´EVAL FM3 USB MB9AF312K KIT DÃ´EVAL FM3 CORTEX M3 MB9B KIT DÃ´EVAL FM3 CORTEX M3 MB9B STANDARD TERMINAL BLOCK ADC 4.5 DIGIT MUX BCD SORTIE 28PLCC ADC 12 BITS 8CH 110KSPS 28SSOP ADC 12 BITS 8CH 133KHZ +/-0.5 20SOIC ADC 12 BITS 75KSPS +/-1 3 FIL 8DIP COMMUTATEUR QUADRUPLE SPST 2.5OHM 16SSOP COMPARATEUR DOUBLE 5.5VIN 8ÂµMAX COMPARATEUR 5VIN 10NS TTL 8SOIC COMPARATEUR 11VIN 1.182VREF 8SOIC COMPARATEUR 5.5VIN 20NS 6SOT23 DAC QUADRUPLE 8BIT +/-5V 20WSOIC DAC 10BIT 5V +/-2LSB BUFF SORTIE 8DIP DAC MULTIPLIER 12 BITS 1LSB 8SOIC DRIVER LED 8X7 SEG/64 SERIE 16QSOP DRIVER LED 16X7SEG/8X16SEG/128 36SSOP LIN REG 0.5A +/-1% 1.8V/AJUSTABLE 8ÂµMAX DC/DC 4.5V-20VIN -4.5V TO -20V 14SOIC LCD BIAS ALIMENTATION 6VIN -100V 8DIP LCD BIAS ALIMENTATION 6VIN -100V 8SOIC REGULATEUR LDO 12.6VIN 3V +/-0.4% 3SOT23 CONTROLEUR 4.375V 0.35S RESET 3TO92 CONTROLEUR 5V 10% 0.15S 3SOT23 CONTROLEUR 5V 10% 0.15S MANUAL 3SOT23 CONTROLEUR 5V 5% 0.15S MANUAL 3SOT23 CONTROLEUR 3.3V 5% 0.15S 3SOT23 CONTROLEUR 3.3V 5% 0.15S 3SOT23 CONTROLEUR PROG UV/OV THRESHOLD 8SOIC WATCHDOG TIMER SELECTABLE TOUT 8SOT23 SUPERVISEUR 4.65VTH 0.2S 16WSOIC SUPERVISEUR 4.4VTH 0.2S 16NSOIC SUPERVISEUR 4.4VTH ACTIVE HAUTE 8SOIC SUPERVISEUR WATCHDOG 1.25VTH 16SOIC SUPERVISEUR WATCHDOG 3-3.15VTH 16SOIC SUPERVISEUR 4.675VTH +/-1.5% 8SOIC SUPERVISEUR 2.93VTH 0.14S 4SOT143 SUPERVISEUR WATCHDOG 2.93VTH 5SOT23 TUBING,SLIT CORRUGATED LOOM,6.7MM,BLK,100FT COMMUTATEUR MOSFET 2.7-5.5VIN 1.2A 8SOIC POTENTIOMETRE DOUBLE LOG 65POS 14TSSOP CAPTEUR TEMP REMOTE/LOCAL 16QSOP CAPTEUR TEMP 12 BITS 150DEG MAX 8SOIC MULTIPLEXEUR 8X1 30VIN 16NSOIC MULTIPLEXEUR 1X16 30V 28WSOIC TUBING,SLIT CORRUGATED LOOM,8.9MM,BLK,100FT MICRO 32 BITS CORTEX-M3 FM3 112BGA MICRO 32 BITS CORTEX-M3 FM3 120LQFP MICRO 32 BITS CORTEX-M3 FM3 100LQFP MICRO 32 BITS CORTEX-M3 FM3 120LQFP MICRO 32 BITS CORTEX-M3 FM3 100LQFP MICRO 32 BITS CORTEX-M3 FM3 120LQFP TUBING,SLIT CORRUGATED LOOM,10.5MM,BLK,100FT MICRO 32 BITS CORTEX-M3 FM3 100LQFP MICRO 32 BITS CORTEX-M3 FM3 120LQFP MICRO 32 BITS CORTEX-M3 FM3 100LQFP MICRO 32 BITS CORTEX-M3 FM3 144LQFP MICRO 32 BITS CORTEX-M3 FM3 176LQFP MICRO 32 BITS CORTEX-M3 FM3 192BGA MICRO 32 BITS CORTEX-M3 FM3 144LQFP MICRO 32 BITS CORTEX-M3 FM3 176LQFP TUBING,SLIT CORRUGATED LOOM,12.83MM,BLK,100FT MICRO 32 BITS CORTEX-M3 FM3 192BGA MICRO 32 BITS CORTEX-M3 FM3 144LQFP MICRO 32 BITS CORTEX-M3 FM3 176LQFP MICRO 32 BITS CORTEX-M3 FM3 192BGA MICRO 32 BITS CORTEX-M3 FM3 100LQFP MICRO 32 BITS CORTEX-M3 FM3 80LQFP MICRO 32 BITS CORTEX-M3 FM3 64LQFP MICRO 32 BITS CORTEX-M3 FM3 112BGA MICRO 32 BITS CORTEX-M3 FM3 100LQFP MICRO 32 BITS CORTEX-M3 FM3 80LQFP MICRO 32 BITS CORTEX-M3 FM3 64LQFP TUBING,SLIT CORRUGATED LOOM,16.9MM,BLK,100FT MICRO 32 BITS CORTEX-M3 FM3 112BGA MICRO 32 BITS CORTEX-M3 FM3 100LQFP MICRO 32 BITS CORTEX-M3 FM3 80LQFP MICRO 32 BITS CORTEX-M3 FM3 48LQFP MICRO 32 BITS CORTEX-M3 FM3 64LQFP FUSE,FAST ACTING,40A,600V FUSE,FAST ACTING,45A,600V FUSE,FAST ACTING,50A,600V FUSE,FAST ACTING,6A,600V FUSE,FAST ACTING,60A,600V FUSE,FAST ACTING,100A,600VDC TUBING,SLIT CORRUGATED LOOM,19.3MM,BLK,100FT FUSE,FAST ACTING,35A,600VDC ULTRACAPACITOR,220F,2.3V,0.04 OHM+10% -5% ULTRACAPACITOR,300F,2.3V,0.025 OHM+10% -5% ULTRACAPACITOR,820F,2.3V,0.012 OHM+10% -5% ULTRACAPACITOR1200F2.7V0.0042 OHM+10% -5% ULTRACAPACITOR1200F2.7V0.00058 OHM+20% -0% ULTRACAPACITOR1500F2.7V0.00047 OHM+20% -0% ULTRACAPACITOR2000F2.7V0.00035 OHM+20% -0% ULTRACAPACITOR3000F2.7V0.00029 OHM+20% -0% ULTRACAPACITOR3000F2.7V0.00026 OHM0% +10% ULTRACAPACITOR,350F,2.7V,0.0032 OHM+20% -0% TUBING,SLIT CORRUGATED LOOM,23.2MM,BLK,100FT ULTRACAPACITOR350F2.7V0.0032 OHM+10% -5% ULTRACAPACITOR350F2.7V0.0027 OHM+10% -5% ULTRACAPACITOR400F2.7V0.0032 OHM+10% -5% DESOLDERING BRAID,COPPER TUBING,SLIT CORRUGATED LOOM,6.7MM,BLK,100FT TUBING,SLIT CORRUGATED LOOM,8.9MM,BLK,100FT SEALING BOOT M6P X 0.75 THD FAIBLE MICROCOMMUTATEUR IP67 BROCHE PLONGEUR TUBING,SLIT CORRUGATED LOOM,10.5MM,BLK,100FT MICROCOMMUTATEUR IP67 SIM GALET A SOUDER MICROCOMMUTATEUR IP67 PCB A SOUDER AFE 24BIT 125KSPS 2CH 20SSOP FILLESS ADAP ZENA MRF89XA 868MHZ TUBING,SLIT CORRUGATED LOOM,12.8MM,BLK,100FT FILLESS ADAP ZENA MRF89XA 915MHZ CARTE DE DEMO REMOTE CONTROL ZENA APT AC-DC CONV,EXTERNAL PLUG IN,1 O/P,40W,8A,5V MICRO-MINI RF SMT BIN BOITE FIBRECARTE CONDUCTIVE S BIN BOITE FIBRECARTE CONDUCTIVE L BOBINE DE BIN FITTING CONDUCTIVE CIRCUIT BREAKER,HYDROMAGNETIC,5A BRACKET HANGER,CABLE & WIRE MANAGEMENT CONNECTOR,INLET,INSULGRIP,30A OMNI-BEAM MODULAR PHOTOELECTRIC SENSOR SENSOR HEAD,DIFFUSE MODE,76CM MICRO-D CONNECTOR,PLUG,15POS,WIRE LEADS SWITCH,ROTARY,2 POS,2.5A,250VAC TERMINAL BLOCK,DIN RAIL/PANEL,1POS,14AWG IC,OP-AMP,8MHZ,2.5V/ us,20 uV,DIP-8 VOLTAGE REGULATOR,LDO,ADJ,1.5A,TO-263-5 IC,DC/DC CONTROLLER,BUCK,1MHZ,30A,QFN-40 IC,DC/DC CONTROLLER,BUCK,1MHZ,30A,QFN-40 FUSE,FAST ACTING,1A,600V FUSE,FAST ACTING,10A,600V FUSE,FAST ACTING,100A,600V FUSE,FAST ACTING,15A,600V FUSE,FAST ACTING,20A,600V FUSE,FAST ACTING,25A,600V FUSE,FAST ACTING,3A,600V FUSE,FAST ACTING,30A,600V FUSE,FAST ACTING,35A,600V FUSE,FAST ACTING,70A,600V FUSE,FAST ACTING,80A,600V FUSE,FAST ACTING,90A,600V FUSE,FAST ACTING,70A,600VDC FUSE,FAST ACTING,90A,600VDC FUSE,FAST ACTING,80A,600VDC FUSE,TIME DELAY,80A,600V LEGENDS,EMERGENCY-STOP SWITCH CORDON HDMI RAPIDE 1M CORDON HDMI RAPIDE 2M KEYCARTE MINI SLIM NOIR A4 TECH CORDON DE BRASSAGE CAT 5E NOIR 10M SOURIS USB OPTICAL 3D MICROCONTROLEUR 8BIT 7KB FLASH 28QFN MICROCONTROLEUR 8BIT 7KB FLASH 28SOIC TRANSCEIVER RS422/RS485 28WDIP TRANSCEIVER RS422/RS485 10UMAX TRANSCEIVER RS422/RS485 8SOIC TRANSCEIVER RS422/RS485 8SOIC TRANSCEIVER RS422/RS485 8SOIC TRANSCEIVER RS422/RS485 8SOIC TRANSCEIVER RS232 ESD 20SOIC TRANSCEIVER RS232 WCAP 24SOIC TRANSCEIVER RS232 5V 16TSSOP TRANSCEIVER RS232 16TSSOP TRANSCEIVER RS232 18SOIC TRANSCEIVER RS232 28SSOP EMBASE XLR 3P FEMELLE MODULE DÃ´EVALUATION DM814X/AM387X DEV KIT C2000 PWR LINE MODEM MODULE DÃ´EVAL LITE W/XDS560V2 C6678 MODULE DÃ´EVALUATION LITE C6678 KIT DE DEVELOPPEMENT MSP430F5529 USB WIRE TO BOARD CONN,HEADER,8POS,2MM COMMUTATEURÂ LEVIERÂ MAGNETIQUE COMMUTATEURÂ LEVIERÂ MAGNETIQUE DSP F- POINT C6713B 300MHZ 272BGA DSP F- POINT C6713B 225MHZ 272BGA DSP FIX POINT 160MHZ 144LQFP SOC NUMERIQUE MEDIA 338NFBGA MPU SITARA ARM CORTEX-A8 324NFBGA MPU APPS PROC C6 INTEGRA 361FCBGA MPU SITARA ARM CORTEX-A8 324NFBGA MPU SITARA ARM CORTEX-A8 491NFBGA MPU SITARA ARM CORTEX-A8 298NFBGA MCU STELLARIS ARM CORTEX-M3 100LQFP MCU STELLARIS ARM CORTEX-M3 100LQFP MICRO 32 BITS 128K FLASH 44VTLA CHAUFFAGE ANTI CONDENSATION 200W 230V CHAUFFAGE ANTI CONDENSATION 200W 110V CHAUFFAGE ANTI CONDENSATION 300W 230V CHAUFFAGE ANTI CONDENSATION 300W 110V CHAUFFAGE ANTI CONDENSATION 400W 230V CHAUFFAGE ANTI CONDENSATION 400W 110V CHAUFFAGE ANTI CONDENSATION 600W 230V CHAUFFAGE ANTI CONDENSATION 600W 110V CHAUFFAGE ANTI CONDENSATION 1KW 230V CHAUFFAGE ANTI CONDENSATION 1KW 110V FEMALE SCREW LOCK,4-40 UNC-2A,12.7MM CONNECTOR,D SUB,RECEPTACLE,37POS BACKSHELL,D-SUB,DE,9POS,NYLON CONNECTOR,MICRO D,RECEPTACLE,37POS JACKSCREW,2-56 UNC-2A,9.2MM CONNECTOR,MICRO D,RECEPTACLE,9POS PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 PANEL MOUNT INDICATOR,LED,0.31 BOITIER POUR RASPBERRY PI BLANC BOITIER POUR RASPBERRY PI NOIR BOITIER POUR RASPBERRY PI CLAIR TV 6C 6#22D SKT RECP,TV01RW-9-35SB AC-DC CONV,ENCLOSED,1 O/P,300W,8.8A,36V MODEM GPRS GSM EDGE GPRS FXT009+ANTENNE+ALIMENTATION CABLES MINICARD 3G 4BAND UMTS HSPA GPS MINICARD 3G 4BAND HSPA+21 GPS MODULE GPRS GSM EDGE QUADRUPLE BANDE MODULE 3G HSDPA DOUBLE BAND DATA MODULE 3G DOUBLE BAND VOICE+GPS EVAL 3G UP SOCKET POUR SL808X MODEM KIT GPRS USB ANTENNE MODEM KIT GPRS RS232 ANTENNE MODULE GPS SIRF STAR1V ANTENNE CARTE APPLICATION GPS UC430 MODULE GPS FAIBLE PWR PATCH ANTENNE GPS APPLICATION CARTE POUR IT500 MODULE GPS FAIBLE PWR PATCH ANTENNE GPS APPLICATION CARTE POUR UP500 GPS APPLICATION CARTE POUR UP501 GPS APPLICATION CARTE POUR IT430 GPS APPLICATION CARTE POUR IT520 MODULE GPS SIRFSTAR1V FAIBLE PUISSANCE GPS APP CARTE GLONASS GALILEO IT600 ANTENNE 2.4/5.8GHZ MT VIS PUCK ANTENNE GPRS GSM SCREW MT PUCK ANTENNE GPRS GSM SCREW MT FLAT ANTENNE 3G GPRS GSM RUBAN MT ANTENNE PCB QUADRUPLE BAND MMCX CONN ANTENNE PCB QUADRUPLE BAND U.FL CONN DONGLE USB BLUETOOTH 4.0 FAIBLE PUISS MODULE BLUETOOTH CHIP ANT LONG RANGE MODULE BLUETOOTH CHIP ANTENNE HCI KIT DÃ´EVAL BLUETOOTH WT41 LONG RANGE CARTE DÃ´EVAL BLUETOOTH WT21 CLASSE 1 ANTENNE 3G GPRS GSM ANTENNE 3G GPRS GSM AMPLI OP 5.5VIN 80KHZ 5SOT23 AMPLI OP 5.5VIN 80KHZ 5SC70 AMPLI OP 5.5VIN 80KHZ 5SOT23 AMPLI OP RAIL/RAIL 5.5VIN 300KHZ 5SOT23 AMPLI OP RAIL/RAIL 5.5VIN 300KHZ 5SC70 AMPLI OP RAIL/RAIL 5.5VIN 300KHZ 5SOT23 LDO 16VIN 0.25A 1.2V 2% 3SOT223 LDO 16VIN 0.25A 1.5V 2% 3SOT223 LDO 16VIN 0.25A 3.3V 2% 3SOT223 LDO 16VIN 0.25A 5V 2% 3SOT223 MAGNIFIER,LAMP,90 LED,4.25Â´Â´ LENS,UK CONNECTEUR PUSH-IN FIL 2VOIES ROUGE ELEMENT CHAUFFANT 60W AT938D + AT60D ELEMENT CHAUFFANT 560W AT850D ELEMENT CHAUFFANT 50W AT8502D ELEMENT CHAUFFANT 550W AT8502D ELEMENT CHAUFFANT 540W AT853A JUMPER FFC 14 VOIES 30V DIODE SBR 60V 3A DPAK DIODE SUPPRESSOR 5KW CONTACT PCB BROCHE SIMPLE 1.3MM DIA HORLOGE TEMPS BOBINE DE 14 SOIC REGULATEUR 5V SOIC 8 REGULATEUR 1.8-6V SOT223-6 ENCODEUR/DECODEUR IRDA MICROCONTROLEUR 32 BITS 66MHZ 196 LBGA MICROPROCESSEUR Z180 68 PLCC LED 1206 BLEU 140MCD 473NM LED CMS PLCC2 ROUGE LED CMS PLCC2 ROUGE LED 7 SEGMENT 0.3 VERT CODEUR ROTATIF 2 BIT BINAIR COMMUTATEUR ROTATIF. 12POS PCB COMMUTATEUR ROTATIF SPDT PCB CAP 10MM BLANC CAP 10MM RED CAP 10MM JAUNE CAP 10MM VERT CAP 10MM BLEU CAP 10MM GRIS DUCT PVC SUPERFLEX 5M SOCKET DIL 8 VOIES 0.3MM CONNECTEUR ASSY PLU 50 VOIES CONNECTEUR FFC 1MM THT 14VOIES LATCH LOCKING CHAMP-LOK CORDON KEYCARTE 4 CORE COILED LOGIC IC,NTE74LS197 IC,QUAD NAND GATE,2I/P,SOIC-14 IC,ANALOG MUX/DMUX,8 X 1,SOIC-16 IC,ANALOG SWITCH,QUAD,SPST,SOIC-14 IC,ANALOG MUX/DMUX,8 X 1,SOIC-16 IC,MONO MULTIVIBRATOR,21NS,SOIC-16 LED,GREEN,2MM X 4MM,3.7MCD IC,VOLT REF,2.5V,20ppm/Â°C,5mV,TO-92 CONTROL STATION,PUSHBUTTON,SPST-NO/SPST-NC CONTROL STATION,SPST-NO/SPST-NC CONTROL STATION,MUSHROOM BUTTON,SPST-NO/SPST-NC CONTROL STATION,PUSHBUTTON,2NO/2NC CONTROL STATION,PUSHBUTTON,2NO/2NC CONTROL STATION,PUSHBUTTON,1NO/1NC CONTROL STATION,PUSHBUTTON,1NO/1NC CONTROL STATION,PUSHBUTTON,1NO/1NC CONTROL STATION,PUSHBUTTON,3NO/3NC CONTROL STATION,PUSHBUTTON,3NO/3NC CONTROL STATION,PUSHBUTTON,1NO/2NC CONTROL STATION,PUSHBUTTON,1NO/2NC CONTROL STATION,PUSHBUTTON,2NO/2NC ENCLOSURE,PUSHBUTTON,STAINLESS STEEL,2HOLE CONNECTOR KIT DC

330R 7W 5% RESISTANCE 470R 7W 5% RESISTANCE 680R 7W 5% RESISTANCE 1K0 7W 5% RESISTANCE 1K5 7W 5% RESISTANCE 2K2 7W 5% RESISTANCE 3K3 7W 5% RESISTANCE 4K7 7W 5% RESISTANCE 10R 9W 5% RESISTANCE 15R 9W 5% ENCLOSURE,INSTRUMENT,STEEL,GRAY RESISTANCE 22R 9W 5% RESISTANCE 33R 9W 5% RESISTANCE 47R 9W 5% RESISTANCE 68R 9W 5% RESISTANCE 150R 9W 5% RESISTANCE 220R 9W 5% RESISTANCE 330R 9W 5% RESISTANCE 470R 9W 5% RESISTANCE 680R 9W 5% RESISTANCE 1K0 9W 5% ENCLOSURE,INSTRUMENT,STEEL,GRAY RESISTANCE 1K5 9W 5% RESISTANCE 2K2 9W 5% RESISTANCE 3K3 9W 5% RESISTANCE 4K7 9W 5% RESISTANCE 6K8 9W 5% RESISTANCE 10K 9W 5% RESISTANCE 15K 9W 5% RESISTANCE 10R 1W 5% SMALL RESISTANCE 15R 1W 5% SMALL ENCLOSURE,JUNCTION BOX,STEEL,GRAY RESISTANCE 15R 3W 5% SMALL ENCLOSURE,JUNCTION BOX,STEEL,GRAY RESISTANCE 33R 3W 5% SMALL ENCLOSURE,JUNCTION BOX,STEEL,GRAY RESISTANCE 100R 3W 5% SMALL RESISTANCE 150R 3W 5% SMALL RESISTANCE 1K5 3W 5% SMALL RESISTANCE 22R 5W 5% SMALL RESISTANCE 150R 5W 5% SMALL RESISTANCE 680R 5W 5% SMALL ENCLOSURE,JUNCTION BOX,STEEL,GRAY RESISTANCE 1K5 5W 5% SMALL RESISTANCE 2K2 5W 5% SMALL RESISTANCE 15R 7W 5% SMALL RESISTANCE 22R 7W 5% SMALL RESISTANCE 33R 7W 5% SMALL RESISTANCE 47R 7W 5% SMALL RESISTANCE 68R 7W 5% SMALL RESISTANCE 150R 7W 5% SMALL RESISTANCE 220R 7W 5% SMALL RESISTANCE 330R 7W 5% SMALL RESISTANCE 470R 7W 5% SMALL RESISTANCE 680R 7W 5% SMALL RESISTANCE 2K2 7W 5% SMALL RESISTANCE 4K7 7W 5% SMALL ENCLOSURE,JUNCTION BOX,STEEL,GRAY RESISTANCE 10R 9W 5% SMALL RESISTANCE 15R 9W 5% SMALL RESISTANCE 22R 9W 5% SMALL RESISTANCE 33R 9W 5% SMALL RESISTANCE 47R 9W 5% SMALL RESISTANCE 68R 9W 5% SMALL RESISTANCE 100R 9W 5% SMALL RESISTANCE 150R 9W 5% SMALL RESISTANCE 220R 9W 5% SMALL RESISTANCE 330R 9W 5% SMALL RESISTANCE 470R 9W 5% SMALL RESISTANCE 680R 9W 5% SMALL RESISTANCE 1K0 9W 5% SMALL RESISTANCE 1K5 9W 5% SMALL RESISTANCE 2K2 9W 5% SMALL RESISTANCE 3K3 9W 5% SMALL RESISTANCE 4K7 9W 5% SMALL RESISTANCE 6K8 9W 5% SMALL RESISTANCE 10K 9W 5% SMALL CONDENSATEUR 2200UF 10V CONDENSATEUR 3300UF 10V CONDENSATEUR 4700UF 10V CONDENSATEUR 1000UF 16V CONDENSATEUR 2200UF 16V CONDENSATEUR 3300UF 16V CONDENSATEUR 3300UF 16V CONDENSATEUR 4700UF 16V CONDENSATEUR 1000UF 25V CONDENSATEUR 1000UF 25V CONDENSATEUR 2200UF 25V ENCLOSURE,JUNCTION BOX,STEEL,GRAY CONDENSATEUR 2200UF 25V CONDENSATEUR 3300UF 25V CONDENSATEUR 220UF 35V CONDENSATEUR 330UF 35V CONDENSATEUR 1000UF 35V CONDENSATEUR 1000UF 35V CONDENSATEUR 2200UF 35V ENCLOSURE,JUNCTION BOX,STEEL,GRAY ENCLOSURE,JUNCTION BOX,STEEL,GRAY CONDENSATEUR 3.3UF 50V CONDENSATEUR 22UF 50V CONDENSATEUR 100UF 50V CONDENSATEUR 330UF 50V ENCLOSURE,JUNCTION BOX,STEEL,GRAY CONDENSATEUR 470UF 50V CONDENSATEUR 1000UF 50V CONDENSATEUR 33UF 63V CONDENSATEUR 220UF 63V CONDENSATEUR 220UF 63V CONDENSATEUR 330UF 63V CONDENSATEUR 330UF 63V ENCLOSURE,JUNCTION BOX,STEEL,GRAY CONDENSATEUR 470UF 63V ECLATEUR A GAZ TUBE 2P 800V 20% ECLATEUR A GAZ TUBE 2P 1200V 20% ECLATEUR A GAZ TUBE 2P 1500V 20% ECLATEUR A GAZ TUBE 2P 1600V 20% ECLATEUR A GAZ TUBE 2P 1200V 20% ECLATEUR A GAZ TUBE 2P 2500V 20% ECLATEUR A GAZ TUBE 2P 2700V 20% ECLATEUR A GAZ TUBE 2P 800V 20% ECLATEUR A GAZ TUBE 2P 1600V 20% ECLATEUR A GAZ TUBE 2P 2500V 20% ECLATEUR A GAZ TUBE 2P 2700V 20% ECLATEUR A GAZ TUBE 2P 3500V 20% ECLATEUR A GAZ TUBE 3P 230V 20% ECLATEUR A GAZ TUBE 3P 420V 20% ECLATEUR A GAZ TUBE 3P 230V 20% ECLATEUR A GAZ TUBE 3P 420V 20% THERMOMETRE INFRAROUGE -30 A 500Â°C THERMOMETRE INFRAROUGE -30 A 650Â°C MONITOR/TABLE MAT INTERCONNECT CORD ENCLOSURE,JUNCTION BOX,STEEL,GRAY ENCLOSURE,JUNCTION BOX,STEEL,GRAY ENCLOSURE,JUNCTION BOX,STEEL,GRAY CAPACITOR SUPER,0.05F,5.5V,0.16 OHM +80 -20% ENCLOSURE,JUNCTION BOX,STEEL,GRAY CONNECTOR SEAL ENCLOSURE,JUNCTION BOX,STAINLESS STEEL FUSE,PTC RESET,60V,100mA,1812 IC,LDO VOLT REG,3.3V,250mA,MSOP-8 ENCLOSURE,JUNCTION BOX,STAINLESS STEEL CAPACITOR TANT,4.7UF,35V,3 OHM,0.1,RAD PLUG & SOCKET HOUSING,PLUG,NYLON ENCLOSURE,JUNCTION BOX,STAINLESS STEEL HEAT-SHRINK WIRE MARKING SLEEVES,1.765IN W TERMINAL,RING TONGUE,1/4IN,CRIMP IC,OP-AMP,3.9GHZ,950V/ us,SOIC-8 N CHANNEL MOSFET,60V,65A,TO-220 FUSE,PTC RESET,60V,1.1A,RADIAL HARNESS BOARD NAILS FUSE,PTC RESET,30V,125mA,1206 REED RELAY,SPST-NO,5VDC,0.5A,THD PROXIMITY SENSOR SENSOR,FLOAT SWITCH,0-10BAR,STEEL SENSOR,FLOAT SWITCH,0-10BAR,STEEL COMPUTER CABLE,USB 2.0,132MM,BLACK TVS DIODE,1.5KW,220V,DO-201 CONTACT,PIN,24-22AWG,CRIMP WIRE-BOARD CONNECTOR,HEADER,20POS,1MM WIRE-BOARD CONNECTOR HEADER 2POS,1.25MM WIRE-BOARD CONN,RECEPTACLE,2POS,2MM CAT5E ETHERNET COUPLER,PLUG,8WAY PANEL RF/COAXIAL,BNC PLUG,STR,50OHM,CABLE CAPACITOR PEN FILM 1UF,100V,5%,2824 TERMINAL BLOCK,DIN,EARTH,2POS,12-2AW RECTIFIER,STANDARD,3A,600V,AXIAL USB Digital Isolator Eval. Board INLET,PLUG,IEC C14,6A,PANEL CC2530,ZIGBEE,2.4GHZ,W / ANTENNA,DEV KIT PIN HEADER,5POS,5.08MM PIC18 Development Kit END/INTERMED PLATE,1.5MMW,SAK SERIES FAST RECOVERY DIODE,1A,50V,DO-41 IC,EEPROM,64KBIT,SERIAL,3MHZ,SOIC-8 IC,FLASH,128MBIT,104MHZ,WSON-8 IC,LDO REGULATOR,1A IC,PROG SHUNT V-REF,2.495V,1%,TO-92 INDUCTOR,SHIELDED,15UH,5.6A,SMD THERMOCOUPLE USB DATA LOGGER GENDER CHANGER,USB TYPE A-B/TYPE B-A FUSE HOLDER,IN LINE RESISTOR,THICK FILM,226KOHM,333MW,1% LED,HIGH POWER,RED/GREEN/BLUE/WHITE WIRE-BOARD CONNECTOR RECEPTACLE 20POS,2.54MM CAPACITOR ALUM ELEC,22UF,35V,20%,SMD COMPUTER CABLE,USB 2.0,132MM,BLACK IC,ADJ LDO REG 1.24V TO 29V 0.1A 8-SOIC DC/DC Converter SSR,PANEL MOUNT,280VAC,32VDC,10A POWER SUPPLY CONN,FUSED POWER ENTRY MODULE,PLUG 10A SWITCH,KEYPAD,1X4,10mA,24V,ABS IC,DAC,16BIT,500KSPS,SSOP-28 PLUG & SOCKET HOUSING,PLUG,NYLON SSR,PANEL MOUNT,280VAC,32VDC,75A SSR,PANEL MOUNT,660VAC,32VDC,125A PLUG & SOCKET HOUSING,NYLON TVS DIODE ARRAY,504W,12V,SOT-23 IC,LOW VOLTAGE COMP,DUAL,300NS MSOP-8 CABLE CLAMP,SIZE 16/16S,ZINC ALLOY STM32 Value Line Discovery Kit THERMAL TRANSFER PRINTER RIBBON,BLK,3.27IN W MEMORY SOCKET,SO-DIMM,200POS IC,BUCK-BOOST CONVERTER,SON-10 MICRO-D CONNECTOR,PLUG,15POS,WIRE LEADS RECEPTACLE PROTECTION CAP,METAL OSCILLOSCOPE 4 VOIES 60MHZ OSCILLOSCOPE 4 VOIES 100MHZ OSCILLOSCOPE 4 VOIES 100MHZ AWG OSCILLOSCOPE 4 VOIES 200MHZ OSCILLOSCOPE 4 VOIES 200MHZ AWG PLUG PROTECTION CAP,METAL QUASARBRITE 0404 SMD RGB LED IC,DAC,14BIT,400MSPS,HTQFP-48 WIRE-BOARD CONNECTOR,HEADER,8POS,2MM CONTACT,FEMALE,30-22AWG,CRIMP INDUCTOR,SHIELDED,22UH,2.2A,SMD SHELL HOUSING PP15/PP30/PP45 SERIES CONN AMP SUPERSEAL 1.5 SERIES 4P CA CIR CONNECTOR PLUG SIZE 17,3POS FREE HA CAT5E ETHERNET COUPLER,PLUG,8WAY CABLE RECEPTACLE PROTECTION CAP,METAL CONTACT,SOCKET,24-18AWG,CRIMP CODE COMPOSER STUDIO,PLATINUM ED,NODE- IC,ADC,8BIT,188KSPS,SOT-23-8 PLUG PROTECTION CAP,METAL RECEPTACLE PROTECTION CAP,METAL PICkit 3 In-Circuit Debugger Only PLUG PROTECTION CAP,METAL CONTACT,PIN,30-26AWG,CRIMP WIRE-BOARD CONNECTOR,HEADER,2POS,2MM FUSE,AXIAL,4A,5 X 20MM,FAST ACTING HEAT SINK SOLDER ANCHOR PROTOTYPE PICTAIL PLUS DAUGHTER BOARD RECEPTACLE PROTECTION CAP,METAL SWITCH,PUSHBUTTON,SPDT,3A,125VAC,SOLDER LUG IC,ADC,24BIT,80SPS,SPI,SOIC16 CABLE CLAMP SIZE 10SL/12S/12,ZINC ALLOY IC,RS-485 BUS TRANSCEIVER,5.25V,SOIC8 WIRE-BOARD CONN,RECEPTACLE,8POS,2MM THERMAL MAGNETIC CIRCUIT BREAKER,2 CABLE CLAMP,SIZE 16S/16,ZINC ALLOY IC,LOAD SWITCH,5.5V,SOIC-8 WIRE-BOARD CONNECTOR HEADER 4POS,5.08MM CABLE CLAMP,SIZE 16S/16,ZINC ALLOY TVS-DIODE,600W,92V,BIDIRECTIONAL,DO-15 TVS-DIODE,600W,274V,UNIDIRECTIONAL,DO-214AA ABSOLUTE/MECHANICAL ENCODER CIRCULAR CABLE CLAMP,SIZE 18 ZINC ALLOY BIPOLAR TRANSISTOR,PNP,-100V,TO-220 DC-DC CONV,LINEAR REG,1 O/P,90W,6A RELAY HEAT SINK CABLE CLAMP,SIZE 20/22,ZINC ALLOY CABLE TIE MOUNT CABLE CLAMP,SIZE 20/22,ZINC ALLOY BOARD-BOARD CONNECTOR HEADER,16POS,2ROW LM3405AXMY EVAL BOARD CONTACT,PIN,24-28AWG,CRIMP CABLE CLAMP,SIZE 24/28,ZINC ALLOY CABLE CLAMP,SIZE 24/28,ZINC ALLOY CABLE CLAMP,SIZE 24/28,ZINC ALLOY CONNECTOR,FPC,ZIF,RCPT,36POS,1ROW IC,AUDIO POWER AMP,CLASS AB,SSOP-28 N CHANNEL MOSFET,60V,57A TO-220AB CIRCULAR CABLE CLAMP SIZE 12SL/14/14S,ZINC ALLOY P CHANNEL MOSFET,10A WIRE-BOARD CONN,RECEPTACLE,20POS,2MM CONTACT,FEMALE,30-22AWG,CRIMP IC,AUDIO CODEC,16BIT,48KHZ,TQFN-24 IC,SINGLE PORT USB POWER SWITCH,SOIC-8 FUSE,CARTRIDGE,500mA,5X20MM,SLO BLO OPTOSWITCH IC,OP-AMP,1.5MHZ,0.42V/Âµs,SOT-23-5 CABLE CLAMP,SIZE 20/22,ZINC ALLOY FUSE,PTC RESET,30V,2.5A,RADIAL IC,SHUNT V-REF,5V,0.5%,3-SOT-23 CABLE CLAMP,SIZE 24/28,ZINC ALLOY IC,SRAM,256KBIT,12NS,SOJ-28 WIRE-BOARD CONNECTOR RECEPTACLE,4POS,2 MALE SCREW RETAINER KIT,#4-40,5.6MM IC,BUS TXRX W/ CONFIG VOLTAGE TRANSLATION,8 OUTPUT,SSOP-24 CIRCULAR CABLE CLAMP,SIZE 32 ZINC ALLOY CIRCULAR CABLE CLAMP,SIZE 32 ZINC ALLOY CIRCUIT BREAKER,THERMAL MAGNETIC,3P,7A CIRCUIT BREAKER,THERMAL MAGNETIC,3P,15A MICRO USB TYPE AB CONN,RCPT,5POS,SMD PTC THERMISTOR,10 OHM,20%,RADIAL LEADED CIRCULAR CABLE CLAMP,SIZE 36 ZINC ALLOY PROGRAMMABLE CONVECTION TOOL,600W,240V CIRCULAR CABLE CLAMP,SIZE 18 ZINC ALLOY CABLE CLAMP,SIZE 20/22,ZINC ALLOY CAPACITOR CERAMIC,10UF,50V,X7R,20%,SMD ADAPTER,RJ45-RJ45 CABLE CLAMP,SIZE 20/22,ZINC ALLOY FUSE HOLDER,10.3MM,PANEL MOUNT CABLE CLAMP,SIZE 24/28,ZINC ALLOY WIRE-BOARD CONN,RECEPTACLE,14POS,2MM CIRCUIT BREAKER,THERMAL MAGNETIC,3P,200A CIRCUIT BREAKER,THERMAL MAGNETIC,3P,25A CIRCUIT BREAKER,THERMAL MAGNETIC,3P,150A CIRCULAR CABLE CLAMP,SIZE 32 ZINC ALLOY CIRCUIT BREAKER,THERMAL MAGNETIC,3P,50A CONNECTOR,CIRCULAR,PLUG,6POS,CABLE FUSE,11A,1KV,FAST ACTING CIRCULAR CABLE CLAMP,SIZE 36 ZINC ALLOY CABLE CLAMP,SIZE 8S/10S,ZINC ALLOY CONNECTOR,D SUB COMBO,RECEPTACLE,3POS DIP SOCKET,8POS,THROUGH HOLE DUST CAP,BRASS CIRCULAR CONNECTOR ADAPTER TERMINAL BLOCK,DIN RAIL,6POS,26-12AWG NOZZLE,CONVECTION TOOL,CSP/LGA 7MMX7MM CIRCULAR CONNECTOR ADAPTER CIRCULAR CONNECTOR ADAPTER IC,DAC,16BIT,3MSPS,TSSOP-16 FUSE,PTC RESET,6V,500mA,1206 PLUG & SOCKET CONNECTOR,RCPT,14POS,3M CIRCULAR CONNECTOR ADAPTER CIRCULAR CABLE CLAMP,SIZE 18 ZINC ALLOY IC,ADC,14BIT,48KSPS,SSOP-28 TERMINAL,FEMALE DISCONNECT,0.25IN,RED IC,OFF LINE SWITCHER,DIP-8 CABLE CLAMP,SIZE 10SL/12S,ZINC ALLOY GUIDE MODULE,9MM WIDE DAUGHTER CARD METAL OXIDE VARISTOR,102V 210V RAD HYPERFAST RECTIFIER,CMN CTHD 30A,D2PAK CONNECTOR,HEADER,10POS,2.54MM WIRE-BOARD CONNECTOR HEADER 8POS,1.25MM CIRCULAR INSERT,PIN,4WAY,SOLDER IC,NON INVERTING BUFFER,DIP-14 CIRCULAR INSERT,SOCKET,4WAY,SOLDER HUMIDITY SENSOR N CHANNEL MOSFET,100V,1.6A SOT-23 IC,AUDIO OP-AMP,8MHZ,SOIC-8 CIRCULAR INSERT,SOCKET,5WAY,SOLDER CIRCULAR INSERT,PIN,6WAY,SOLDER CIRCULAR INSERT,SOCKET,6WAY,SOLDER CIRCULAR CONTACT SOCKET,24-20AWG,CRIMP CIRCULAR INSERT,PIN,3WAY,SOLDER 4 SIL VERT MALE CONN LATCH SCR THYRISTOR,160A,1.2KV,A 21 CAT5 RJ45 MODULAR JACK,8POS,8CONTACT, IC,SERIES V-REF,2.5V,75mV,TO-52-3 CIRCULAR INSERT,SOCKET,3WAY,SOLDER CIRCULAR INSERT,PIN,2WAY,SOLDER FUSE,30A,700V,FERRULE,FAST ACTING SMALL SIGNAL DIODE 100V 200mA DO-35 IC,TIMER,SINGLE,2.1MHZ,15V,8-SOIC BOARD TO BOARD,RECEPTACLE,20POS,2ROW CIRCULAR INSERT,SOCKET,7WAY,SOLDER FUSE,RESETTABLE PTC,1206,6VDC,2A FUSE,RESETTABLE PTC,1210,6VDC,1.75A FUSE,RESETTABLE PTC,1210,6VDC,2A FUSE,RESETTABLE PTC,1812,30VDC,350mA FUSE,RESETTABLE PTC,1812,30VDC,500mA FUSE,RESETTABLE PTC,1812,12VDC,2.6A FUSE,RESETTABLE PTC,1812,6VDC,3A CIRCULAR INSERT,PIN,3WAY,SOLDER TVS-DIODE,600W,495V,UNIDIRECTIONAL,D TRAPEZIFORM HANDLE,4HP,GREY IC,LVDS BUFFER/REPEATER,TQFP-48 IC,DSC,DSPIC33,16BIT,256KB,60MIPS, BOARD-BOARD CONN,RECEPTACLE,6WAY,2ROW OPTOCOUPLER,TRANSISTOR,2500VRMS CIRCULAR INSERT,PIN,5WAY,SOLDER FUSE,TIME DELAY,800mA,250VAC,RADIAL FUSE,TIME DELAY,800mA,250VAC,RADIAL FUSE,TIME DELAY,1A,250VAC,RADIAL FUSE,TIME DELAY,1.25A,250VAC,RADIAL FUSE,TIME DELAY,1.25A,250VAC,RADIAL FUSE,TIME DELAY,1.6A,250VAC,RADIAL FUSE,TIME DELAY,1.6A,250VAC,RADIAL FUSE,TIME DELAY,2A,250VAC,RADIAL FUSE,TIME DELAY,2A,250VAC,RADIAL FUSE,TIME DELAY,2.5A,250VAC,RADIAL FUSE,TIME DELAY,3.15A,250VAC,RADIAL FUSE,TIME DELAY,4A,250VAC,RADIAL FUSE,TIME DELAY,4A,250VAC,RADIAL COVER FOR ECS25/45/60 POWER SUPPLY DC BLOWER,51 X 15MM,12V RESISTOR,THICK FILM,1.2KOHM,100mW,1% CRIMP TOOL,MOLEX INSULKRIMP TERMINALS IC,CAN TXRX,1MBPS,1/1,5.5V,SOIC-8 BOARD-BOARD CONNECTOR RECEPTACLE,20WAY,2ROW PLAQUE RECTANGULAIRE WIRE-BOARD CONNECTOR,HEADER,5POS,2MM SCR THYRISTOR,4A,600V,D-PAK CIRCULAR INSERT,PIN,10WAY,SOLDER MICRO SWITCH,ROLLER LEVER DPST 15A 250V CIRCULAR INSERT,SOCKET,10WAY,SOLDER CONNECTOR,FPC,ZIF,RCPT,4POS,1ROW CIRCULAR CONNECTOR PLUG,SIZE 13,4POS, IC,DSC,16BIT,32KB 20MHZ 5.5V BQFP-132 CIRCULAR INSERT,PIN,4WAY,SOLDER IC,EEPROM,64KBIT,SERIAL,3MHZ,DIP-8 OPTOCOUPLER,SCHMITT TRIGGER,7500V IC,LINEAR VOLTAGE REGULATOR,5V,TO-92 IC,ANALOG MULTIPLEXER,16 X 1,SOIC-28 IC,RS-485 TRANSCEIVER,3.6V,SOIC-8 CONTACT,FEMALE,30-24AWG,CRIMP IC,ANALOG SWITCH,QUAD,SPST,DIP-16 FAST DIODE,4A,600V,TO-220AC CIRCULAR INSERT,PIN,8WAY,SOLDER CIRCULAR INSERT,SOCKET,8WAY,SOLDER SENSOR,INDUCTIVE,2MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,2MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,4MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,4MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,8MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,8MM,PNP-NO,10-36VDC SENSOR,PHOTO,DIFFUSE-REFLECTIVE,1M,PNP SENSOR,PHOTO,RETRO-REFLECTIVE,5M,NPN SENSOR,PHOTO,RETRO-REFLECTIVE,5M,PNP SENSOR,PHOTO,RETRO-REFLECTIVE,6.5M,NPN SENSOR,PHOTO,THROUGH-BEAM,20M,NPN SENSOR,PHOTO,DIFFUSE-REFLECTIVE,0.8M,NPN SENSOR,PHOTO,DIFFUSE-REFLECTIVE,0.8M,PNP SENSOR,PHOTO,RETRO-REFLECTIVE,4M,NPN SENSOR,PHOTO,RETRO-REFLECTIVE,4M,PNP SENSOR,PHOTO,RETRO-REFLECTIVE,5M,NPN SENSOR,PHOTO,RETRO-REFLECTIVE,5M,PNP SENSOR,PHOTO,THROUGH-BEAM,16M SENSOR,PHOTO,THROUGH-BEAM,16M,NPN SENSOR,PHOTO,THROUGH-BEAM,16M,PNP SENSOR,PHOTO,DIFFUSE-REFLECTIVE,1M,NPN SENSOR,PHOTO,DIFFUSE-REFLECTIVE,1M,PNP SENSOR,PHOTO,RETRO-REFLECTIVE,5M,NPN CIRCULAR INSERT,PIN,4WAY,SOLDER SENSOR,PHOTO,RETRO-REFLECTIVE,5M,PNP SENSOR,PHOTO,RETRO-REFLECTIVE,6.5M,NPN SENSOR,PHOTO,RETRO-REFLECTIVE,6.5M,PNP SENSOR,PHOTO,THROUGH-BEAM,20M,NPN SENSOR,PHOTO,THROUGH-BEAM,20M,PNP PLUG & SOCKET CONN,HEADER,2POS,4.2MM CIRCULAR INSERT,SOCKET,4WAY,SOLDER IC,RTC,YY-MM-DD,256 X 8,SOIC-20 IC,RS422/RS485 LINE DRIVER 5.25V SOIC16 MICRO HDMI CONNECTOR,RCPT,19WAY,PCB POWER RELAY,4PCO,110VAC,5A,PLUG IN CIRCULAR INSERT,PIN,5WAY,SOLDER CONTACT,SOCKET,30-28AWG,CRIMP MAX2830 RF Transceiver Evaluation Kit TERMINAL,RING TONGUE,#6,CRIMP NATURAL IC,STEP-DOWN DC-DC CONV,500kHz,SOIC-8 CAPACITOR TANT,1UF,35V,AXIAL CIRCULAR INSERT,PIN,6WAY,SOLDER CIRCULAR INSERT,SOCKET,6WAY,SOLDER RF WIDEBAND TRANSISTOR,NPN,4.5V,18GHZ POWER DISTRIBUTION SWITCH,5.5V,SOT23-5 IC,8BIT BUS TRANSCEIVER,TSSOP-24 RESISTOR KIT,1206,CHIP,1/4 E96 SERIES CABLE ASSEMBLY PLUG & SOCKET HOUSING,RECEPTACLE,NYLON RF/COAXIAL,BNC STR PLUG,50OHM,CRIMP CIRCULAR INSERT,SOCKET,1WAY,SOLDER CIRCUIT BREAKER,THERMAL MAG,2P,16A LABEL,PREPRINTED,3.18MMX4.83MM,576PCS CIRCULAR INSERT,SOCKET,10WAY,SOLDER JTAG Emulator RESISTOR KIT,0402,CHIP,1/4 E96 SERIES RESISTOR KIT,0603,CHIP,1/4 E96 SERIES RESISTOR KIT,0805,CHIP,1/4 E96 SERIES RECTANGULAR HAN INSERT,PLUG,8WAY CRIMP DIP SOCKET,24POS,THROUGH HOLE CABLE CLAMP,SIZE 3,THERMOPLASTIC DIN RAIL MOUNTING KIT IC,SERIES V-REF,5V,10mV,8-SOIC CONTACT,PIN,24-18AWG,CRIMP FUSE,RESETTABLE PTC,1206,6VDC,1.75A FUSE,TIME DELAY,5A,250VAC,RADIAL STATIC CONTROL WRIST STRAP/BAND SUB-MINIATURE SOCKET,PC BOARD IC,INSTRUMENT AMP,1MHZ,130DB,SOIC-8 CONNECTOR,D SUB,RECEPTACLE,9POS WIRE TO BOARD CONNECTOR,RCPT,2POS,1ROW IC,QUAD AND GATE,2I/P,SOIC-14 CAPACITOR TANT,100UF,10V,3528-21 20% CIRCULAR INSERT,PIN,4WAY,SOLDER CAPACITOR TANT,47UF,16V,6032-28 10% CAPACITOR TANT,10UF,50V,SMD 20% SWITCH KEY CIRCULAR INSERT,SOCKET,4WAY,SOLDER RESISTOR,METAL,0.025OHM,3W,1% METAL OXIDE VARISTOR,200V 395V RAD POWER ENTRY MODULE,PLUG,20A BOARD-BOARD CONN,HEADER,10WAY,2ROW SCHOTTKY RECTIFIER,2A,100V,SMB LM3410XSDLE EVAL BOARD CIRCULAR INSERT,PIN,8WAY,SOLDER CIRCULAR INSERT,SOCKET,8WAY,SOLDER SIGNAL CONVERTER,DIN RAIL CONTACT,FEMALE,20-18AWG,CRIMP MEMORY SOCKET,SO-DIMM,200POS WIRE TO BOARD CONN,RECPT,8POS,2.5MM CAPACITOR ALUM ORGANIC 68UF,6.3V,20%,SMD N CHANNEL MOSFET,200V,52A,TO-220 CIRCUIT BREAKER,THERMAL MAG,1P,16A COMMON MODE FILTER,POWER LINE,SMD TPS2543,POWER SWITCH,USB CHARGING,EVA HOUSING,RECEPTACLE,5POS,1ROW,3.96MM IC,PRECISION VIRTUAL GROUND,TO-92-3 CIRCULAR INSERT,PIN,7WAY,SOLDER RECTIFIER MODULE,1.6KV 82A SEMIPACK 1 AXIAL FAN,119MM,230VAC,50mA USB TYPE A CONNECTOR RECEPTACLE 4POS THD CIRCULAR INSERT,SOCKET,7WAY,SOLDER CIRCULAR INSERT,PIN,9WAY,SOLDER SCHOTTKY RECTIFIER,CMN CTHD 400A TO-244 CIRCULAR INSERT,SOCKET,9WAY,SOLDER CONTACT,FEMALE,24-22AWG,CRIMP GAS DISCHARGE TUBE,150V,SMD GAS DISCHARGE TUBE,230V,SMD GAS DISCHARGE TUBE,300V,SMD GAS DISCHARGE TUBE,350V,SMD EXTRACTION TOOL TERMINAL,BUTT SPLICE,CRIMP,RED IC,ADC,3.5BIT,DIP-40 TERMINAL,TURRET,THROUGH HOLE WiFi Comm Demo Board Wireless Connectivi PRECESSION SCREWDRIVER,PHILLIPS,170MM CIRCULAR INSERT,SOCKET,3WAY,SOLDER POWER RELAY,12VDC,5A,DPST-NO,PCB WIRE-BOARD CONNECTOR RECEPTACLE,3POS,3.96MM DC-DC CONV,NON ISO POL,1 O/P,50W,10A 24-BIT ANALOG FRONT END DEMO KIT CDCM9102,CLOCK GENERATOR,EVALUATION MODULE SPRING LATCH ASSEMBLY,D-SUB,4-40 CAPACITOR CERAMIC 0.15UF,50V,X7R,0603 CONTACT,MACHINED,PIN,24-20AWG,CRIMP IC,OP-AMP,5.8MHZ,45V/ us,DIP-8 RELAY COUPLER,SPDT,24VDC,6A,DIN RAIL WIRE-BOARD CONNECTOR HEADER 5POS,2.54MM CIRCULAR INSERT,PIN,14WAY,SOLDER TERMINAL,BLOCK FORK,STUD 6,CRIMP,YEL TERMINAL,BLOCK FORK,STUD 10,CRIMP,BLUE TERMINAL,BLOCK FORK,STUD 6,CRIMP,BLUE CIRCULAR INSERT,SOCKET,14WAY,SOLDER TERMINAL,BLOCK FORK,STUD 10,CRIMP,RED TERMINAL,BLOCK FORK,STUD 6,CRIMP,RED TERMINAL,BUTT SPLICE,CRIMP,BLUE TERMINAL,BUTT SPLICE,CRIMP,RED TERMINAL,FEMALE DISCONNECT,0.25 TERMINAL,FEMALE DISCONNECT,0.187 TERMINAL,FEMALE DISCONNECT,0.25 TERMINAL,FEMALE DISCONNECT,0.187 TERMINAL,FEMALE DISCONNECT,0.25 TERMINAL,FEMALE DISCONNECT,0.187 TERMINAL,FEMALE DISCONNECT,0.187 TERMINAL,MALE DISCONNECT,0.25 CIRCULAR INSERT,PIN,17WAY,SOLDER TERMINAL,RING TONGUE,STUD 6,CRIMP,YEL TERMINAL,RING TONGUE,STUD 10,CRIMP,BLUE TERMINAL,RING TONGUE,STUD 6,CRIMP,BLUE TERMINAL,RING TONGUE,STUD 10,CRIMP,RED TERMINAL,RING TONGUE,STUD 6,CRIMP,RED TERMINAL,RING TONGUE,STUD 8,CRIMP,RED TERMINAL,FORK,STUD 8,12-10AWG,CRIMP TERMINAL,RING TONGUE,1/4 TERMINAL,RING TONGUE,STUD 8,CRIMP,YEL IC,HIGH SPEED BUFFER,SGL,180MHZ SOIC8 IC HEX INVERTER SCHMITT TRIGGER TSSOP-14 IC,PLL WITH VCO,18MHZ,16-TSSOP IC LOW VOLTAGE COMP SINGLE 300NS SC-70-5 IC,DIFFERENTIAL COMP,QUAD 0.3 uS SOIC14 IC,LDO VOLT REG,5V,0.1A,5-SOT-23 IC,RS-232 TRANSCEIVER,5V,SOIC-16 IC,OP AMP,LOW POWER,45MHZ,27V/ us,30?V MSOP-8 IC,OP-AMP,5.5MHZ,2V/ us,MSOP-8 IC,I/O EXPANDER,8 BIT,100KHZ,TSSOP-20 IC,LDO SERIES V-REF 1.25V 0.15% SC-70-3 IC,RS-232 TRANSCEIVER,5.5V,TSSOP-16 IC,TRANSCEIVER,RS-485,10MBPS,SOIC-8 IC HEX INVERTER SCHMITT TRIGGER TSSOP-14 IC NON INVERTING BUS TRANSCEIVER TSSOP20 IC,8BIT SIPO SHIFT REGISTER,TSSOP-16 IC,MONO MULTIVIBRATOR,7.3NS,TSSOP-16 IC NON INVERTING BUS BUFFER GATE TSSOP14 IC,TX & LEVEL TRANS,8CKT,TSSOP-24 IC NON INVERTING BUS TRANSCEIVER TSSOP20 IC,NON INVERTING BUFFER,TSSOP-20 IC NON INVERTING BUS TRANSCEIVER TSSOP48 IC,TX & LEVEL TRANS,8CKT,TSSOP-24 IC,NON INVERTING BUFFER,SOT-553-5 IC,LOGIC,FLIP FLOP,D,5.9NS,SSOP-8 IC,16BIT D-LATCH,3-STATE,TSSOP-48 IC,LOGIC,INVERTER,DUAL,4.1ns,6-SOT-563 IC,NON INVERTING BUFFER,VSSOP-8 IC,ANALOG SWITCH,DUAL,SPDT,SSOP-8 IC,2I/P QUAD DATA SELECTOR/MUX TSSOP-16 IC,D-TYPE FLIP FLOP,3-STATE,TSSOP-20 IC,8BIT BUS TRANSCEIVER,SSOP-24 IC,NON INVERTING BUFFER,TSSOP-20 IC NON INVERTING BUS BUFFER GATE TSSOP14 IC,ANALOG MUX/DMUX,DUAL 4 X 1,TSSOP16 IC,BUS TX,DIFF,5.25V,SOIC-8 IC,MICROPOWER COMP,SINGLE,4 uS SOT23-5 IC,INTERFACE,HDMI,5.5V,TSSOP-38 IC,INTERFACE,ESD,3-SC-70 IC,POWER LOAD SWITCH,HIGH SIDE,5.5V,5-SOT-23 IC,DC-DC CONV,BUCK,570KHZ,2A,SOIC-8 IC,DC-DC CONV,BOOST,1.5MHZ,140mA,SON-8 IC,LDO VOLT REG,1.8V,150mA,SC-70-5 IC,LDO VOLT REG,3.3V,150mA,SC-70-5 IC,ADJ LDO REG 0.8V TO 3.6V 1.5A QFN-20 IC,BI-DIRECT VOLT LEVEL XLATOR,SOT23-6 IC,LEVEL TRANS,VOLT,1 I/P,1CKT,6-SOT-23 IC,LINEAR VOLT REGULATOR,8V,SOT-223-4 SENSOR,INDUCTIVE,5MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,5MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,8MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,8MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,8MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,8MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,14MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,14MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,10MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,10MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,15MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,15MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,15MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,15MM,PNP-NO,10-36VDC SENSOR,INDUCTIVE,22MM,NPN-NO,10-36VDC SENSOR,INDUCTIVE,22MM,PNP-NO,10-36VDC 22-4 (4 Contacts) Socket Insert CONTACT,FEMALE,24-22AWG,CRI

CORDONS DE TEST 4 TERMINAL PROBE KELVIN 0.9M PROBE KELVIN SIMPLE PIN SET CLIP CORDON KELVIN CABLE ASSEMBLE COAX DOUBLE 1.2M CABLE ASSEMBLE TRIGGER LINK 1M CABLE ASSEMBLE TRIGGER LINK 2M ADAPTATEUR TRIGGER LINK CABLE ASSEMBLE TRIGGER LINK 1M CABLE ASSEMBLE TRIGGER LINK Y-DIN KIT MONTAGE RACK SIMPLE KIT MONTAGE RACK DOUBLE CABLE ASSEMBLE COAX SHV CABLE ASSEMBLE COAX SHV I/O MODULE MULTIPLEXEUR CARTE DOUBLE 1X30 MULTIPLEXEUR CARTE DOUBLE 1X30 MATRIX CARD RELAIS REED 1X30 MATRIX CARD RELAIS REED QUADRUPLE 4X28 COMMUTATEUR CARTE ISOLEE 32 VOIES CONTROL CARTE MULTIFONCTION CABLE ASS TRIGGER LINK ADAPTATEUR CABLE ASSEMBLE SHIELDED DB25 1.5M CABLE ASSEMBLE CROISE RJ45 3M CORDONS DE TEST ADAPTATEUR BANANE 1.4M EXTENDER CARTE ANALOG BACKPLANE KIT MONTAGE ARRIERE KIT MONTAGE RACK SIMPLE KIT MONTAGE RACK KIT MONTAGE RACK KIT MONTAGE ARRIERE MULTIPLEXEUR 32 VOIES MULTIPLEXEUR RAPIDE 32 VOIES CONTROL MODULE 40 VOIES MODULE I/O 20 CH ANALOG 16 CH NUMERIQUE MODULE I/O 32 VOIES MULTIPLEXEUR MODULE 40 VOIES MATRIC MODULE 6X8 MULTIPLEXEUR SOLID STATE 20 VOIES MODULE RF 2GHZ 50OHM MODULE RF 3.5GHZ 50OHM MULTIMTER NUMERIQUE 6.5DIG MULTIMETRE NUMERIQUE 7.5DIG SYSTEM COMMUTATEUR AFFICHEUR SIX SLOT SYSTEM COMMUTATEUR SIX SLOT SHUNT 50A KIT CORDONS DE TEST I/O MODULE PROBE HAUTE TENSION SOURCEMETRE 200V 1A 20W SOURCEMETRE 100V 3A 100W SOURCEMETRE 100V 3A 100W COURANT SOURCE DC COURANT SOURCE DC W/ NANOVOLTMETER ALIMENTATION DC 100W 15V 3A SIMULATEUR BATTERIE SIMULATEUR BATTERIE/CHARGEUR PORTABLE CADENAS COMBINATION DIAL LOCK COMBI SECURITY HD CADENAS LAITON 40MM CADENAS LAITON 50MM KA CADENAS LAITON PREMIUM KA CADENAS LAITON PREMIUM CADENAS LAITON PREMIUM CADENAS LAITON PREMIUM CADENAS LAMINE 40MM LOCK DISC W/HASP & STAPLE CADENAS HARSH ENVIRO CADENAS S/STEEL LOCK STEEL LOCK STEEL CLOSED SHACKLE LOCK CABLE BIKE LOCK BIKE U-SHACKLE CYLINDRE EASIFIT LAITON 30/30 CYLINDRE EASIFIT LAITON 30/40 CYLINDRE EASIFIT LAITON 35/35 CYLINDRE EASIFIT LAITON 35/45 CYLINDRE EASIFIT LAITON 40/40 CYLINDRE EASIFIT LAITON 40/50 CYLINDRE EASIFIT LAITON 45/45 CYLINDRE EASIFIT LAITON 45/55 CYLINDRE EASIFIT NICKEL 30/30 CYLINDRE EASIFIT NICKEL 30/40 CYLINDRE EASIFIT NICKEL 35/35 CYLINDRE EASIFIT NICKEL 35/45 CYLINDRE EASIFIT NICKEL 40/40 CYLINDRE EASIFIT NICKEL 40/50 CYLINDRE EASIFIT NICKEL 45/45 CYLINDRE EASIFIT NICKEL 45/55 CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 2 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M CABLE CAT5E 24AWG 4 PAIRES 152M USB TYPE A CONNECTOR,PLUG,4POS,SMD I/O MODULE INDUCTOR,SHIELDED,47UH,2.5A,SMD IC,LED DRIVER,LINEAR,SOIC-8 ZENER DIODE,500mW,5.6V,DO-35 ACCELEROMETER EVAL. BOARD HOUSING,RECEPTACLE,8POS,1ROW,3.81MM HUMIDITY SENSOR IC,DC-DC CONV,SSOP-16 IC,LDO,FIXED,9V,100mA,24V,TO-92-3 IC,CAN TXRX,1MDPS,1/1,5.5V,SOIC-8 PIC18F25J10 28L SOIC Plug-in Module,Plug-in Modules 17M0546 PIC18LF25J10 28L SOIC Plug-in Module,Plug-in Modules 17M0547 PIC18F45J10 44L TQFP Plug-in Module,Plug-in Modules 17M0548 PIC18LF45J10 44L TQFP Plug-in Module,Plug-in Modules 17M0549 IC,CLOCK BUFFER,133.3MHZ,SOIC-16 INDUCTOR,100UH,65MA,Â±10%,7MHz SSR,PANEL MOUNT,600VAC,32VDC,15A BIPOLAR TRANSISTOR,NPN,300V,SOT-32 RESISTOR,CURRENT SENSE,0.025OHM,1W,1 BIPOLAR TRANSISTOR,PNP,-300V,SOT-32 NTC THERMISTOR RFID Transponder Connector assemblies,Ribbon (Flat) CAPACITOR ARRAY,0.01UF,50V,X7R,20%,SIP CONNECTOR,PLCC SOCKET,68POS,THROUGH H DIP SWITCH,4,SPST,TOP SLIDE SSR,PCB MOUNT,280VAC,24VDC,4A FUSE,CARTRIDGE,5A,5 X 20MM,SLOW BLOW TERMINAL BLOCK JUMPER,3WAY,5.1MM BRIDGE RECTIFIER,SINGLE PHASE,1.5A,800V,RB-15 BOARD-BOARD CONNECTOR HEADER,3WAY,1ROW RELAY SOCKET N CHANNEL JFET,-30V,SOT-23 DIN MOUNTING RAIL,35MM,ALUMINIUM CONNECTOR,FPC,RCPT,34POS,1ROW INDUCTOR,1.2UH,9A,20%,SMD INDUCTOR,150NH,18A,30%,SMD INDUCTOR,1.5UH,7.2A,20%,SMD INDUCTOR,2UH,6.5A,20%,SMD INDUCTOR,2.5UH,5.5A,20%,SMD INDUCTOR,300NH,16A,30%,SMD INDUCTOR,3UH,4.9A,20%,SMD INDUCTOR,800NH,10.5A,20%,SMD INDUCTOR,1.3UH,10.5A,20%,SMD INDUCTOR,1.8UH,9A,20%,SMD INDUCTOR,220NH,18A,30%,SMD INDUCTOR,2.5UH,7.2A,20%,SMD INDUCTOR,3.2UH,6.5A,20%,SMD INDUCTOR,4UH,5.5A,20%,SMD INDUCTOR,450NH,16A,20%,SMD INDUCTOR,5UH,4.9A,20%,SMD INDUCTOR,800NH,12.5A,20%,SMD RELAY SOCKET HOLD-DOWN CLIP INDUCTOR,1UH,17.5A,20%,SMD INDUCTOR,1.8UH,13.5A,20%,SMD INDUCTOR,2.8UH,11A,20%,SMD INDUCTOR,4UH,9.7A,20%,SMD INDUCTOR,470NH,19.5A,30%,SMD RELAY SOCKET HOLD-DOWN CLIP INDUCTOR,5.6UH,8.2A,20%,SMD INDUCTOR,7.2UH,6.6A,20%,SMD INDUCTOR,10UH,5A,20%,SMD INDUCTOR,1.5UH,13.5A,30%,SMD INDUCTOR,2.5UH,10A,20%,SMD INDUCTOR,4UH,8.3A,20%,SMD INDUCTOR,6UH,6.7A,20%,SMD INDUCTOR,680NH,19.5A,30%,SMD INDUCTOR,15UH,600mA,20%,SMD INDUCTOR,1.7UH,1.55A,20%,SMD INDUCTOR,22UH,500mA,20%,SMD RELAY SOCKET HOLD-DOWN CLIP INDUCTOR,2.3UH,1.4A,20%,SMD INDUCTOR,3.3UH,1.35A,20%,SMD INDUCTOR,33UH,420mA,20%,SMD INDUCTOR,750NH,2.7A,20%,SMD INDUCTOR,82UH,270mA,20%,SMD INDUCTOR,8.5UH,850mA,20%,SMD CABLE,USB,3.34M RELAY SOCKET HOLD-DOWN CLIP RELAY SOCKET HOLD-DOWN CLIP BIPOLAR TRANSISTOR, Bipolar transistor CONNECTOR,RJ45,JACK,8P8C,1PORT,CAT5E CONNECTOR,RJ45,JACK,8P8C,1PORT,CAT5E CAT5E UTP MODULE,JACK,8POS,8CONTACTS,1PORT CAT5E UTP MODULE,JACK,8POS,8CONTACTS,1PORT CAT6 RJ45 MODULAR JACK,8POS,1 PORT CAT6 RJ45 MODULAR JACK,8POS,1 PORT CAT6 RJ45 MODULAR JACK,8POS,1 PORT CAT6 RJ45 MODULAR JACK,8POS,1 PORT VOLUME CONTROLLER Hall Effect Latch IC SWITCH,ROTARY,DIP EXTRACTOR HANDLE,BLACK BUTT SPLICE,CRIMP,YELLOW RESISTOR,THICK FILM,100KOHM,62.5mW 1% RESISTOR,THICK FILM,0 OHM,62.5mW,5% RESISTOR,THICK FILM,10KOHM,62.5mW,5% RESISTOR,THICK FILM,0 OHM,100mW,5% RESISTOR,THICK FILM,100KOHM,100mW,5% RESISTOR,THICK FILM,10KOHM,125mW,5% RESISTOR,THICK FILM,0 OHM,250mW,5% RESISTOR,THICK FILM,10KOHM,250mW,5% RESISTOR,THICK FILM,1KOHM,62.5mW,5% RESISTOR,THICK FILM,1MOHM,62.5mW,5% CAPACITOR CERAMIC 0.47UF,25V,X7R,10%,0805 CAPACITOR CERAMIC,0.1UF,16V,X7R,10%,0805 P CH MOSFET,-200V,6.5A,TO-3 IC,QUAD LEVEL SHIFTER,QFN-48 CAPACITOR ALUM ELEC,10UF,50V,20%,SMD CAPACITOR ALUM ELEC,100UF,50V,20%,SMD CAPACITOR ALUM ELEC,100UF,63V,20%,SMD CAPACITOR ALUM ELEC,1000UF,25V,20%,SMD CAPACITOR ALUM ELEC,1000UF,50V,20%,SMD CAPACITOR ALUM ELEC 220UF 35V 20%,SMD CAPACITOR ALUM ELEC,220UF,50V,20%,SMD CAPACITOR ALUM ELEC,220UF,63V,20%,SMD CAPACITOR ALUM ELEC,330UF,35V,20%,SMD CAPACITOR ALUM ELEC,47UF,35V,20%,SMD CAPACITOR ALUM ELEC,470UF,35V,20%,SMD CAPACITOR ALUM ELEC,100UF,16V,20%,SMD INDUCTOR,1.5UH,1.6A,20%,SMD INDUCTOR,15UH,600mA,20%,SMD INDUCTOR,150UH,170mA,20%,SMD INDUCTOR,2.2UH,1.4A,20%,SMD INDUCTOR,22UH,500mA,20%,SMD INDUCTOR,220UH,150mA,20%,SMD INDUCTOR,3.3UH,1.2A,20%,SMD INDUCTOR,33UH,400mA,20%,SMD INDUCTOR,15UH,900mA,20%,SMD INDUCTOR,150UH,280mA,20%,SMD INDUCTOR,22UH,750mA,20%,SMD INDUCTOR,220UH,240mA,20%,SMD INDUCTOR,33UH,600mA,20%,SMD INDUCTOR,330UH,190mA,20%,SMD CONN,FUSED POWER ENTRY MODULE,PLUG 10A IC,OP-AMP,42MHZ,10V/Âµs,?MAX-8 ZENER DIODE,1W,18V,DO-41 ADAPTER,J-LINK,19 PIN,FOR CORTEX-M RESISTOR,100KOHM,100mW,0.1%,0603 RESISTOR,100 OHM,100mW,0.001,603 RESISTOR,15KOHM,100mW,0.1%,0603 RESISTOR,2KOHM,100mW,0.1%,0603 RESISTOR,2.49KOHM,100mW,0.1%,0603 RESISTOR,20KOHM,100mW,0.1%,0603 RESISTOR,24.9KOHM,100mW,0.1%,0603 RESISTOR,4.99KOHM,100mW,0.1%,0603 RESISTOR,49.9KOHM,100mW,0.1%,0603 RESISTOR,100KOHM,125mW,0.1%,0805 RESISTOR,100 OHM,125mW,0.001,805 RESISTOR,2KOHM,125mW,0.1%,0805 RESISTOR,20KOHM,125mW,0.1%,0805 RESISTOR,4.99KOHM,125mW,0.1%,0805 RESISTOR,49.9KOHM,125mW,0.1%,0805 RESISTOR,100KOHM,250mW,0.1%,1206 RESISTOR,100 OHM,250mW,0.001,1206 RESISTOR,2KOHM,250mW,0.1%,1206 RESISTOR,20KOHM,250mW,0.1%,1206 END PLATE,G SERIES TERMINAL BLOCK RESISTOR,4.99KOHM,250mW,0.1%,1206 RESISTOR,49.9KOHM,250mW,0.1%,1206 CIRCULAR CONNECTOR,PLUG,8POS,CABLE TRANSDUCER,ALARM,95DBA,28V,PANEL TRANSDUCER,ALARM,95DBA,28V,PANEL TRANSDUCER,ALARM,95DBA,28V,PANEL TRANSDUCER,ALARM,95DBA,28V,PANEL TRANSDUCER,ALARM,95DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL LAMP,INCAND,SLIDE,16V,640mW CONNECTOR,SIM CARD,2.54MM,6POS CONNECTOR,SIM CARD,2.54MM,6POS CONNECTOR,SIM CARD,2.54MM,6POS CONNECTOR,SIM CARD,2.54MM,8POS DIGITAL MICROSCOPE,MIGHTY SCOPE,80X CABINETS & ENCLOSURES,CABINE BRUCELLES GRIP MOUSSE ESD 125MM BRUCELLES GRIP MOUSSE ESD 115MM BRUCELLES GRIP MOUSSE ESD 115MM BRUCELLES GRIP MOUSSE ESD 120MM BRUCELLES GRIP MOUSSE ESD 130MM POIGNEE DE LAMES SCAPEL PQT 5 POIGNEE DE LAMES SCAPEL PQT 5 POIGNEE DE LAMES SCAPEL PQT 5 KNIFE TRIMMING W/3 SM92 BLADES COUTEAU A LAME 4313 PQT 5 COUTEAU A LAME 4313 PQT 5 COUTEAU A LAME 4313 PQT 5 COUTEAU A LAME 4313 PQT 5 COUTEAU A LAME 4313 PQT 5 COUTEAU A LAME 4313 PQT 5 COUTEAU A LAME 4313 PQT 5 FUSIBLE 100MA 250V RETARDE 4.5X8MM FUSIBLE 125MA 250V RETARDE 4.5X8MM FUSIBLE 250MA 250V RETARDE 4.5X8MM FUSIBLE 315MA 250V RETARDE 4.5X8MM FUSIBLE 400MA 250V RETARDE 4.5X8MM FUSIBLE 500MA 250V RETARDE 4.5X8MM FUSIBLE 630MA 250V RETARDE 4.5X8MM FUSIBLE 1.25A 250V RETARDE 4.5X8MM FUSIBLE 1.6A 250V RETARDE 4.5X8MM FUSIBLE 2A 250V RETARDE 4.5X8MM FUSIBLE 2.5A 250V RETARDE 4.5X8MM FUSIBLE 4A 250V RETARDE 4.5X8MM FUSIBLE 5A 250V RETARDE 4.5X8MM FUSIBLE 125MA 250V RETARDE 4.5X16MM FUSIBLE 160MA 250V RETARDE 4.5X16MM FUSIBLE 250MA 250V RETARDE 4.5X8MM FUSIBLE 315MA 250V RETARDE 4.5X8MM FUSIBLE 400MA 250V RETARDE 4.5X8MM FUSIBLE 800MA 250V RETARDE 4.5X8MM FUSIBLE 1A 250V RETARDE 4.5X8MM FUSIBLE 1.6A 250V RETARDE 4.5X8MM FUSIBLE 2A 250V RETARDE 4.5X8MM FUSIBLE 2.5A 250V RETARDE 4.5X8MM FUSIBLE 3.15A 250V RETARDE 4.5X8MM FUSIBLE 4A 250V RETARDE 4.5X8MM FUSIBLE 5A 250V RETARDE 4.5X8MM FUSIBLE 6.3A 250V RETARDE 4.5X8MM FUSIBLE 10A 250V RETARDE 4.5X8MM MICRO-D CONNECTOR,PLUG,15POS,WIRE LEADS MICRO-D CONNECTOR,RECEPTACLE,15POS,WIRE LEADS MICRO-D CONNECTOR,RECEPTACLE,21POS,WIRE LEADS MICRO-D CONNECTOR,RECEPTACLE,21POS,WIRE LEADS MICRO-D CONNECTOR,RECEPTACLE,37POS,WIRE LEADS MICRO-D CONNECTOR,PLUG,9POS,WIRE LEADS MICRO-D CONNECTOR,PLUG,9POS,WIRE LEADS IC,DIGITAL ISOLATOR,12NS,SOIC-16 MICRO-D CONNECTOR,PLUG,9POS,WIRE LEADS TRANSISTOR,PNP,-40V,TO-92 FFC/FPC CONNECTOR,RECEPTACLE,6POS 1ROW WIRE-BOARD CONNECTOR HEADER 3POS,2.54MM IC,8BIT SIPO SHIFT REGISTER,DIP-20 SSR,PANEL MOUNT,660VAC,32VDC,100A IC,RS485 TRANSCEIVER 250KBPS 5.5V DIP14 MICRO-D CONNECTOR,RECEPTACLE 37POS,RA-THD CLOSED END DUST COVER 2 POS,POLYESTER N CH MOSFET,30V,5A,3-SOT-23 LAMP,INCANDESCENT,TELEPHONE SLIDE,12V No description available - 2132255 MICRO-D CONNECTOR,PLUG 37POS,RA-THD MICRO-D CONNECTOR,RECEPTACLE,37POS,WIRE LEADS MICRO-D CONNECTOR,PLUG,21POS,WIRE LEADS IC,ACCELEROMETER,DIGITAL,3 AXIS,LFCS IC,ANALOG MULTIPLEXER,2X1,TSSOP-16 No description available - 2132289 IC,QUAD AND GATE,2I/P,SOIC-14 MICRO-D CONNECTOR,PLUG,9POS,WIRE LEADS IC,MOSFET DRIVER,HIGH/LOW SIDE,DIP-8 MICRO-D CONNECTOR,PLUG,25POS,WIRE LEADS MICRO-D CONNECTOR,RECEPTACLE,21POS,SOLDER DIP SOCKET,28POS,THROUGH HOLE IC,LDO REG,250mA,1.2V,3-TO-92 IC,DC-DC CONV,3MHz,SON-6 CAPACITOR ALUM ELEC 330UF,400V,20%,SNAP-IN IC,GYROSCOPE,500DPS,LGA-28 BOARD-BOARD CONNECTOR HEADER,6WAY,1ROW LAMP,INCANDESCENT,MINI BAYONET/BA9S,14V N CHANNEL JFET,-25V,SOT-23 SUPPORT DE TRANSMETTEUR X2 INDUCTOR,500NH,12.5A,20%,SMD INDUCTOR,8.2UH,5.8A,20%,SMD WIRE-BOARD CONNECTOR,HEADER,3POS,2MM LAMP,INCANDESCENT,MINI BAYONET/BA9S,28V FUSE,PTC RESET,72V,3A,RADIAL LAMP,INCANDESCENT,MINI BAYONET/BA9S,28V Miniature Lamp,36 volt,0.100 Amp,1000 MICRO-D CONNECTOR,PLUG,31POS,WIRE LEADS LAMP,INCANDESCENT,MINI BAYONET/BA9S,28V RESISTOR,THICK FILM,1KOHM,62.5mW,1% RESISTOR,THICK FILM,1KOHM,100mW,1% FUSE,PTC RESET,8V,2A,1812 MICRO-D CONNECTOR,PLUG 15POS,RA-THD WATERPROOF CAP,THERMOPLASTIC D SUB,STANDARD,RECEPTACLE,9POS,CABLE D SUB,STANDARD,PLUG,9POS,CABLE D SUB,HIGH DENSITY,RECEPTACLE,15POS,CABLE D SUB,HIGH DENSITY,PLUG,15POS,CABLE D SUB,STANDARD,RECEPTACLE,9POS,PANEL D SUB,STANDARD,PLUG,9POS,PANEL D SUB,HIGH DENSITY,RECEPTACLE,9POS,PANEL D SUB,HIGH DENSITY,PLUG,9POS,PANEL IC,8BIT MCU,PIC18F,48MHZ,DIP-28 ITO CAPACITIVE SENSE BOOSTERPACK MICRO-D CONNECTOR,PLUG,37POS,WIRE LEADS IC,DIG ISO,60ns,SOIC16 MICRO-D CONNECTOR,RECEPTACLE,15POS,WIRE LEADS MICRO-D CONNECTOR,RECEPTACLE,15POS,WIRE LEADS MICRO-D CONNECTOR,PLUG,15POS,WIRE LEADS CONTACT CLIP,PCB,SOCKET,SINGLE JUMPER LINK,2POS,PCB TRACK LAMP,INCANDESCENT,TELEPHONE SLIDE #3,24V SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SHIELD FINGER,SMT PCB SMT CABLE CLIP,COPPER ALLOY EVAL KIT,BLACKFIN,BF609 EZLITE KIT IC 14-STAGE RIPPLE CARRY COUNTER TSSOP16 CAPACITOR CERAMIC 22PF 100V,C0G,Â± 5%, COMPUTER CABLE,INFINIBAND,3M,NATURAL ADAPTER,DVI-I RECEPTACLE-VGA PLUG LAMP,INCANDESCENT,MINI BAYONET/BA9S,24V DETECTEUR OPTIQUE LAMP,INCANDESCENT,TELEPHONE SLIDE,24V WIRE-BOARD CONNECTOR,HEADER,6POS,2MM TERMINAL BLOCK,SPRING,10POS,30-12AWG TERMINAL BLOCK,SPRING,12POS,30-12AWG TERMINAL BLOCK,SPRING,10POS,30-12AWG TERMINAL BLOCK,SPRING,12POS,30-12AWG TERMINAL BLOCK,SPRING,2POS,30-12AWG TERMINAL BLOCK,SPRING,3POS,30-12AWG TERMINAL BLOCK,SPRING,4POS,30-12AWG TERMINAL BLOCK,SPRING,6POS,30-12AWG TERMINAL BLOCK,SPRING,8POS,30-12AWG TERMINAL BLOCK,SPRING,2POS,30-12AWG TERMINAL BLOCK,SPRING,3POS,30-12AWG TERMINAL BLOCK,SPRING,4POS,30-12AWG TERMINAL BLOCK,SPRING,6POS,30-12AWG TERMINAL BLOCK,SPRING,8POS,30-12AWG LED,HB,COOL WHT,122LM,SMD LED,HB,COOL WHT,130LM,SMD LED,HB,COOL WHT,139LM,SMD LED,HB,COOL WHT,122LM,SMD LED,HB,COOL WHT,130LM,SMD LED,HB,COOL WHT,139LM,SMD LAMP,INCANDESCENT,MINI BAYONET/BA9S,28V IC,ANALOG SWITCH,SINGLE,SPDT,SC-70-6 IC,LDO,FIXED,15V,100mA,30V,TO-92-3 LAMP,INCANDESCENT,120V,3W CIRCUIT LOGIQUE 4 BIT COMPT BIN TSSOP16 RESEAU DE DIODE TVS 500W 24V SOIC VARISTANCE 800J 750V IC,RS-232 TRANSCEIVER,5.5V,NSOIC-16 N CH MOSFET,30V,3.4A,3-SOT-23 LAMP,INCANDESCENT,MIDGET FLANGE,28V LAMP,INCANDESCENT,MIDGET FLANGE,6V IC,16BIT MCU,MSP430F2,16MHZ,40-VQFN N CHANNEL MOSFET,20V,20A,SOIC IC,8BIT SIPO SHIFT REGISTER,SOIC-14 FUSE,CARTRIDGE,1.6A,5X20MM,SLOW BLOW LAMP,INCANDESCENT,MIDGET FLANGE,28V LAMP,INCANDESCENT,MIDGET GROOVE,28V WIRE-BOARD CONNECTOR,HEADER,4POS,2MM IC,QUAD XOR GATE,2I/P,DIP-14 LAMP,INCANDESCENT,MINI BAYONET/BA9S,6V RESISTOR,THICK FILM,1MOHM,100mW,1% INDUCTOR,47UH,230MA,Â±10%,12MHz DUST COVER,MINI USB,SILICONE RUBBER,BLACK IC,PARALLEL TO I2C BUS CTRL,SOIC-20 IC,LINEAR VOLTAGE REGULATOR,12V,TO-92 RF JFET,N CH,30V,25MA,3-SOT-23 CONTROLEUR TEMP 4 RANGE 240V TIMER QUADRUPLE RANGE 240V ADAPTER,J-LINK,9 PIN,FOR CORTEX-M IC,8BIT MCU,PIC12,20MHZ,DIP-8 SPRING FINGER,MOBILE PHONES SPRING FINGER,PRELOADED,MOBILE PHONES SPRING FINGER,PRELOADED,MOBILE PHONES SPRING FINGER,PRELOADED,MOBILE PHONES SPRING FINGER,MOBILE PHONES SPRING FINGER,PRELOADED,MOBILE PHONES TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL TRANSDUCER,ALARM,85DBA,28V,PANEL USB A CONNECTOR,RECEPTACLE 4POS IC,LED DRVR,LGA56 CONTROLEUR SERVO ESCON 36V 72W PWM CONNECTEUR SET POUR ESCON 36/DC2 CABLE E/S ANALOGIQUE POUR ESCON 36/DC2 CABLE MOTEUR DC POUR ESCON 36/DC2 CABLE E/S NUMERIQUE POUR ESCON 36/DC2 CABLE ENCODEURPOUR ESCON 36/DC2 PUISSANCE CABLE POUR ESCON 36/DC2 CABLE USB POUR ESCON 36/DC2 FUSE,PTC RESET,24V,1.5A,1812 ZENER DIODE,3W,16V,SMB IC,LINEAR VOLT REGULATOR,3.3V,TO-220 IC,LDO REG,500mA,2.5V,8-SOIC SSR,PANEL MOUNT,280VAC,32VDC,10A LAMP,INCANDESCENT,120V,6W IC,DIGITAL ISOLATOR,50NS,SOIC-16 IC,8BIT MCU,PIC18F,16MIPS,TQFP-80 RFID TRANSPONDER,13.56MHZ,2KBIT,CD IN COMMUTATEUR BAROMETRIQUE LAMP,INCANDESCENT,WEDGE,14V PLUG & SOCKET CONNECTOR,RCPT,6POS,3MM FUSE,CARTRIDGE,10A,5X20MM,TIME DELAY WIRE-BOARD CONNECTOR RECEPTACLE,2POS,2 CAPACITOR ALUM ELEC 220UF,450V,20%,SNAP-IN IC,RTC,YY-MM-DD,56 X 8,DIP-8 LAMP,INCANDESCENT,W2.1X4.9D,14V BIPOLAR TRANSISTOR,PNP,-80V CAPACITOR ALUM ELEC 1UF,50V,20%,SMD RESISTOR,THICK FILM,10KOHM,100mW,1% LAMP,INCANDESCENT,MINI BAYONET/BA9S,6V SCHOTTKY RECTIFIER,CMN CTHD,30A SOT-93 LAMP,INCANDESCENT,MINI BAYONET/BA9S,14V IC,NEGATIVE VOLT REGULATOR,-5V,TO-92 IC,OP-AMP,1.2MHZ,0.5V/ us,SOIC-14 LAMP,INCANDESCENT,MINI BAYONET/BA9S,28V MULTICOLOR LED,0606,YEL/GRN DC-DC CONV,ISO POL,2 O/P,30W,3A,3A,5V,-5V LAMP,INCANDESCENT,W2.1X4.9D,28V ADAPTER,J-LINK TO PCB,10 PIN NEEDLE CAPACITOR TANT,1UF,50V,8 OHM,0.1,RADIAL TORQUE DRIVER MECATRONIQUE 0.8-3NCM TORQUE DRIVER MECATRONIQUE 1-6NM JEU DE TORX BIT MAXXTOR 29MM 8PC JEU DE TORX/PZ/PH BIT 29MM 8PC JEU DE TORX BIT MAXXTOR 49MM 7PC JEU DE TORX/PZ/PH BIT 49MM 7PC JEU DE FORET HSS-TIN 19PC JEU DE FORET N-HSS-TIN 25PC SET,TWIST DRILL,N-HSS-R,170PC PERCEUSE PNEUMATIQUE REVERSIBLE 1/4 PERCEUSE PNEUMATIQUE NON-REVERS. 1/4 CORDONS ETHERNET PATCHCORD SEAL 2M CORDONS ETHERNET PATCHCORD SEAL 3M CORDONS ETHERNET PATCHCORD SEAL 5M CORDONS USB2.0 A VERS B 2M CORDONS USB2.0 A VERS B 3M CORDONSE USB2.0 B VERS A 2M CORDONS USB2.0 B VERS A 3M MODULE RF TRX 868MHZ 2KM MODULE RF TRX 868MHZ 2KM MODULE RF TELEMETRIE 868MHZ DIP 2KM MODULE RF TELEMETRIE 868MHZ SMT 2KM MODULE RF MODEM 868MHZ DIP 2KM MODULE RF MODEM 868MHZ SMT 2KM ANTENNE PIGTAIL 433MHZ 2DB SMA(M) ANTENNE STUBBY 433MHZ SMA(M) ANTENNE STUBBY 433MHZ 90DEG SMA(M) ANTENNE STUBBY 2.4GHZ W/ SMA ANTENNE STUBBY 2.4GHZ 90DEG SMA ANTENNE STUBBY 2.4GHZ PIGTAIL 50MM UFL ANTENNE PUCK 433 / 868MHZ W/ SMA CONN ANTENNE PCB GSM QUADBAND 35X6 UFL ANTENNE PCB GSM PENTABAND 42X42 COAX UFL ANTENNE PCB GSM QUADBAND 45X20 COAX UFL ANTENNE PCB GSM PENTABAND 81X21 COAX UFL ANTENNE PANEL GSM/WIFI 7DB QUADBAND ANTENNE GSM YAGI 23DB 868MHZ ANTENNE GSM I BAR FMEF CONN QUADBAND ANTENNE GSM T BAR FMEF CONN QUADBAND CAPACITOR CERAMIC 330PF 100V,C0G,10%,1206 TOWER CD S12G128 FUSE,PTC RESET,60V,300mA,2106 MICROCONTR KINETIS K10 CORTEX M4 32QFN MICROCONTR KINETIS K10 CORTEX M4 48QFN MICROCONTR KINETIS K10 CORTEX M4 48LQFP MICROCONTR KINETIS K10 CORTEX M4 64LQFP MICROCONTR KINETIS K10 CORTEX M4 64MAP MICROCONTR KINETIS K10 CORTEX M4 32QFN MICROCONTR KINETIS K10 CORTEX M4 48QFN MICROCONTR KINETIS K10 CORTEX M4 48LQFP MICROCONTR KINETIS K10 CORTEX M4 64LQFP MICROCONTR KINETIS K10 CORTEX M4 64MAP MICROCONTR KINETIS K10 CORTEX M4 80LQFP MICROCONTR KINETIS CORTEX M4 100LQFP MICROCONTR KINETIS CORTEX M4 144LQFP MICROCONTR KINETIS K10 CORTEX M4 144MAP MICROCONTR KINETIS K10 CORTEX M4 121MAP MICROCONTR KINETIS K10 CORTEX M4 48QFN MICROCONTR KINETIS K10 CORTEX M4 48LQFP MICROCONTR KINETIS K10 CORTEX M4 64LQFP MICROCONTR KINETIS K10 CORTEX M4 64MAP MICROCONTR KINETIS K10 CORTEX M4 48QFN MICROCONTR KINETIS K10 CORTEX M4 48LQFP MICROCONTR KINETIS K10 CORTEX M4 64LQFP MICROCONTR KINETIS CORTEX M4 100LQFP MICROCONTR KINETIS K10 CORTEX M4 121MAP MICROCONTR KINETIS K10 CORTEX M4 64MAP MICROCONTR KINETIS K10 CORTEX M4 144MAP MICROCONTR KINETIS K10 CORTEX M4 64LQFP MICROCONTR KINETIS K10 CORTEX M4 80LQFP MICROCONTR KINETIS CORTEX M4 100LQFP MICROCONTR KINETIS CORTEX M4 144LQFP MICROCONTR KINETIS K10 CORTEX M4 121MAP MICROCONTR KINETIS K10 CORTEX M4 144MAP MICROCONTR KINETIS K10 CORTEX M4 121MAP MICROCONTR KINETIS K10 CORTEX M4 48QFN MICROCONTR KINETIS K10 CORTEX M4 48LQFP MICROCONTR KINETIS K10 CORTEX M4 64LQFP MICROCONTR KINETIS K10 CORTEX M4 64MAP MICROCONTR KINETIS K10 CORTEX M4 48QFN MICROCONTR KINETIS K10 CORTEX M4 48LQFP MICROCONTR KINETIS K10 CORTEX M4 64LQFP MICROCONTR KINETIS K10 CORTEX M4 64MAP MICROCONTR KINETIS K10 CORTEX M4 80LQFP MICROCONTR KINETIS K10 CORTEX M4 121MAP MICROCONTR KINETIS K10 CORTEX M4 64MAP MICROCONTR KINETIS CORTEX M4 144LQFP MICROCONTR KINETIS K10 CORTEX M4 144MAP MICROCONTR KINETIS K10 CORTEX M4 32QFN MICROCONTR KINETIS K20 CORTEX M4 48QFN MICROCONTR KINETIS K20 CORTEX M4 48LQFP MICROCONTR KINETIS K20 CORTEX M4 64LQFP MICROCONTR KINETIS K20 CORTEX M4 64MAP MICROCONTR KINETIS K20 CORTEX M4 32QFN MICROCONTR KINETIS K20 CORTEX M4 48QFN MICROCONTR KINETIS K20 CORTEX M4 48LQFP MICROCONTR KINETIS K20 CORTEX M4 64LQFP MICROCONTR KINETIS K20 CORTEX M4 64MAP MICROCONTR KINETIS K20 CORTEX M4 80LQFP MICROCONTR KINETIS K20 CORTEX M4 121MAP MICROCONTR KINETIS K20 CORTEX M4 144MAP MICROCONTR KINETIS K20 CORTEX M4 32QFN MICROCONTR KINETIS K20 CORTEX M4 48QFN MICROCONTR KINETIS K20 CORTEX M4 48LQFP MICROCONTR KINETIS K20 CORTEX M4 64LQFP MICROCONTR KINETIS K20 CORTEX M4 64MAP MICROCONTR KINETIS K20 CORTEX M4 32QFN MICROCONTR KINETIS K20 CORTEX M4 48QFN MICROCONTR KINETIS K20 CORTEX M4 48LQFP MICROCONTR KINETIS K20 CORTEX M4 64LQFP MICROCONTR KINETIS K20 CORTEX M4 80LQFP MICROCONTR KINETIS K20 CORTEX M4 80LQFP MICROCONTR KINETIS CORTEX M4 100LQFP MICROCONTR KINETIS K20 CORTEX M4 121MAP MICROCONTR KINETIS K20 CORTEX M4 32QFN MICROCONTR KINETIS K20 CORTEX M4 48QFN MICROCONTR KINETIS K20 CORTEX M4 48LQFP MICROCONTR KINETIS K20 CORTEX M4 64LQFP MICROCONTR KINETIS K20 CORTEX M4 64MAP MICROC

TONGUE,#8,CRIMP,YELLOW TERMINAL,RING TONGUE 5/16IN,CRIMP BLUE AC-DC CONV,PCB MOUNT,2 O/P,40W,15V,-15V RESISTOR,THICK FILM,22 OHM,100mW,1% AC-DC CONV,OPEN FRAME,4 O/P,160W AC-DC CONV,OPEN FRAME,4 O/P,160W AC-DC CONV,OPEN FRAME,1 O/P,160W,7A,12V AC-DC CONV,OPEN FRAME,1 O/P,160W,3.5A,24V AC-DC CONV,OPEN FRAME,1 O/P,40W,6A,5.1V TERMINAL,RING TONGUE,3/8IN,CRIMP AC-DC CONV,OPEN FRAME,1 O/P,40W,3.3A,12V AC-DC CONV,OPEN FRAME,1 O/P,40W,2.6A,15V AC-DC CONV,OPEN FRAME,3 O/P,40W AC-DC CONV,OPEN FRAME,3 O/P,40W AC-DC CONV,OPEN FRAME,3 O/P,20.8W TERMINAL,RING TONGUE,#8,CRIMP AC-DC CONV,OPEN FRAME,3 O/P,40W,5V,12V,-12V AC-DC CONV,OPEN FRAME,3 O/P,40W,5V,15V,-15V AC-DC CONV,OPEN FRAME,2 O/P,40W,12V,-12V TERMINAL,RING TONGUE 1/4IN CRIMP YELLOW AC-DC CONV,OPEN FRAME,3 O/P,65W,5V,12V,-12V AC-DC CONV,RACK MOUNT,1 O/P,2.4KW,200A,12V AC-DC CONV,RACK MOUNT,1 O/P,2.496KW,104A,24V AC-DC CONV,RACK MOUNT,1 O/P,2.496KW,52A,48V AC-DC CONV,DIN RAIL,1 O/P,120W,5A,24V AC-DC CONV,DIN RAIL,1 O/P,240W,10A,24V AC-DC CONV,ENCLOSED,1 O/P,200W,26.7A,7.5V AC-DC CONV,OPEN FRAME,3 O/P,40.5W,5V,12V,-5V AC-DC CONV,ENCLOSED,1 O/P,1.51KW,63A,24V IC,OP-AMP,1MHZ,0.4V/Âµs,DIP-8 AC-DC CONV,OPEN FRAME,1 O/P,300W,25A,12V AC-DC CONV,OPEN FRAME,1 O/P,400W,33.3A,12V AC-DC CONV,OPEN FRAME,1 O/P,300W,12.5A,24V AC-DC CONV,OPEN FRAME,1 O/P,300W,6.25A,48V AC-DC CONV,OPEN FRAME,1 O/P,400W,16. AC-DC CONV,OPEN FRAME,1 O/P,400W,8.33A,48V FUSE,BLADE,4A,32V TERMINAL,BUTT SPLICE,YELLOW AC-DC CONV,OPEN FRAME,1 O/P,50W,4.2A,12V AC-DC CONV,OPEN FRAME,1 O/P,50W,9.1A,3.3V AC-DC CONV,OPEN FRAME,1 O/P,75W,12A,3.3V AC-DC CONV,ENCLOSED,1 O/P,100W,8.4A,12V AC-DC CONV,ENCLOSED,1 O/P,150W,1.25A,12V AC-DC CONV,ENCLOSED,1 O/P,150W,6.3A,24V TERMINAL,RING TONGUE,#4,CRIMP,RED AC-DC CONV,ENCLOSED,1 O/P,100W,8.5A,12V TERMINAL,RING TONGUE,5/16IN,CRIMP RED TERMINAL,RING TONGUE,3/8IN,CRIMP,RED AC-DC CONV,ENCLOSED,1 O/P,1.536KW,32A,48V AC-DC CONV,OPEN FRAME,1 O/P,644W,23A AC-DC CONV,OPEN FRAME,1 O/P,60W,2.5A,24V AC-DC CONV,PCB MOUNT,1 O/P,5.5W,230mA,24V TERMINAL,RING TONGUE,#6,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP,RED TERMINAL,RING TONGUE,#10,CRIMP,RED AC-DC CONV,EXTERNAL PLUG IN,1 O/P,11.88W,13.5V AC-DC CONV,EXTERNAL PLUG IN,1 O/P,11.88W,13.5V AC-DC CONV,EXTERNAL PLUG IN,1 O/P,35.91W,13.5V AC-DC CONV,EXTERNAL PLUG IN,1 O/P,35.91W,13.5V POWER ENTRY MODULE,PLUG,6A AC-DC CONV,OPEN FRAME,1 O/P,100W,20A AC-DC CONV,OPEN FRAME,1 O/P,150W,10A,15V AC-DC CONV,OPEN FRAME,1 O/P,150W,30A TERMINAL,SPADE/FORK,#6,CRIMP AC-DC CONV,OPEN FRAME,5 O/P,250W AC-DC CONV,OPEN FRAME,5 O/P,250W TERMINAL,BUTT SPLICE AC-DC CONV,OPEN FRAME,1 O/P,250W,10.4A,24V TERMINAL,SPADE/FORK,#10,CRIMP,YELLOW AC-DC CONV,OPEN FRAME,1 O/P,60W,2.5A AC-DC CONV,OPEN FRAME,3 O/P,25W,5V,12V,-12V AC-DC CONV,OPEN FRAME,3 O/P,40W,5V,15V,-15V AC-DC CONV,OPEN FRAME,3 O/P,60W,5V,12V,-12V TERMINAL,RING TONGUE,3/8IN,CRIMP AC-DC CONV,ENCLOSED,1 O/P,1.8KW,84A,12V PRE-DRIVER MOTEUR 16VIN 0.02A 16SSOP DRIVER MOTEUR 2CH FWD/RVRS MFP10SK DRIVER MOTEUR 2CH H-BRIDGE 16SSOP DRIVER MOTEUR H-BRIDGE 10.5V 9WLP DRIVER LED 12V 0.8A CRM SMPS 8SOIC CTLR PFC/H-BRIDGE RES 600V 16SOIC PWM CNTRL CCM LED 500KHZ 0.5A 8SOIC PFC DCM/CCM 20VCC 250KHZ 16SOIC LDO 13.5VIN 0.3VDO 1.5A AJUSTABLE 5D2PAK TERMINAL,RING TONGUE,5/16IN,YELLOW LDO 5.5VIN 0.14VDO 0.2A 3.3V 5TSOP AMPLI OP RRO 16VCC 3.5MHZ 5SC70 LDO 13.5VIN 0.3VDO 1.5A AJUSTABLE 5D2PAK LDO 13.5VIN 0.3VDO 1.5A AJUSTABLE 8DFN PWM BOOST 40VIN 1MHZ AJUSTABLE 8SOIC BUCK 36VIN 2MHZ 1.2A AJUSTABLE 8DFN BUCK 36VIN 2MHZ 1.2A AJUSTABLE 10DFN TERMINAL,SPADE/FORK,#8,CRIMP,RED DRIVER MOTEUR STEPPER 45VIN 1.5A DRIVER MOTEUR STEPPER 45VIN 1.2A AC-DC CONV,OPEN FRAME,1 O/P,336W,12A,28V AC-DC CONV,OPEN FRAME,1 O/P,60W,1.25 TERMINAL,FEMALE DISCONNECT,4.75MM,RED POWER SUPPLY,SWITCH MODE,5V IC,RS-232 TRANSCEIVER,5.5V,SSOP-20 POTENTIOMETER W/SWITCH,LINEAR,100 OHM,0.2,1W POTENTIOMETER W/SWITCH,LINEAR,1KOHM,20%,1W POTENTIOMETER W/SWITCH,LINEAR,100KOHM,20%,1W POTENTIOMETER W/SWITCH,LINEAR,22KOHM,20%,1W POTENTIOMETER W/SWITCH,LINEAR,470 OHM,0.2,1W POTENTIOMETER W/SWITCH,LINEAR,4.7KOHM,20%,1W POTENTIOMETER W/SWITCH,LINEAR,47KOHM,20%,1W TERMINAL,RING TONGUE,1/2IN,CRIMP ADAPTOR,AC - AC,120V,12V,1A ADAPTOR,AC - AC,120V,12V,1.5A ADAPTOR,AC - AC,120V,12V,200MA ADAPTOR,AC - AC,120V,12V,500MA ADAPTOR,AC - AC,120V,16V,2.4A ADAPTOR,AC - AC,120V,16V,400MA ADAPTOR,AC - AC,120V,16V,500MA ADAPTOR,AC - AC,120V,24V,1A ADAPTOR,AC - AC,120V,24V,1.8A ADAPTOR,AC - AC,120V,24V,200MA ADAPTOR,AC - AC,120V,24V,750MA CARTE DÂ´EVAL EN5311QI-E BUCK CONVTR CARTE DÂ´EVAL EN5322QI-E BUCK CONVTR CARTE DÂ´EVAL EN5337QI-E BUCK CONVTR CARTE DÂ´EVAL EN5364QI-E BUCK CONVTR CARTE DÂ´EVAL EN5394QI-E BUCK CONVTR CARTE DÂ´EVAL EN6337QI-E BUCK CONVTR CARTE DÂ´EVAL EN6347QI-E BUCK CONVTR CARTE DÂ´EVAL EN6360QI-E BUCK CONVTR CARTE DÂ´EVAL EP5348UI-E BUCK CONVTR CARTE DÂ´EVAL EP5358HUI-E BUCK CONVTR CARTE DÂ´EVAL EP5358LUI-E BUCK CONVTR CARTE DÂ´EVAL EP5368QI-E BUCK CONVTR CARTE DÂ´EVAL EP53A8HQI-E BUCK CONVTR CARTE DÂ´EVAL EP53A8LQI-E BUCK CONVTR CARTE DÂ´EVAL EP53F8QI-E BUCK CONVTR CARTE DÂ´EVAL EN2340QI-E BUCK CONVTR ZENER DIODE,200mW,12V,SOD-523 AC-DC CONV,OPEN FRAME,1 O/P,151.2W,6.3A,24V ZENER DIODE,1W,15V,DO-41 AC-DC CONV,DIN RAIL,1 O/P,120W,10A,12V INDUCTOR,47MH,340MA,Â±10%,8.5MHz AC-DC CONV,DIN RAIL,1 O/P,48W,2A,24V AC-DC CONV,DIN RAIL,1 O/P,48W,4A,12V WIRE-BOARD CONNECTOR RECEPTACLE 10POS,2.54MM AC-DC CONV,OPEN FRAME,1 O/P,60W,2.5A,24V IC,RS-232 TRANSCEIVER,250kbps,5.5V,SOIC-16 IC,RS-232 TRANSCEIVER,5.5V,TSSOP-28 COFFRET PCB DT NO VENT HOLE EMBASE R/A POUR DT ENCLOSURE 48VOIES COFFRET PCB DTM CLAIR RECEPTACLE DTM HI TEMP B KEY 3VOIES RECEPTACLE DTM HI TEMP C KEY 3VOIES RECEPTACLE DTM HI TEMP D KEY 3VOIES FICHE DTM HAUTE TEMP B KEY 3VOIES FICHE DTM HAUTE TEMP C KEY 3VOIES FICHE DTM HAUTE TEMP D KEY 3VOIES RECEPTACLE DTM HI TEMP B KEY 4VOIES RECEPTACLE DTM HI TEMP C KEY 4VOIES RECEPTACLE DTM HI TEMP D KEY 4VOIES FICHE DTM HAUTE TEMP B KEY 4VOIES FICHE DTM HAUTE TEMP C KEY 4VOIES FICHE DTM HAUTE TEMP D KEY 4VOIES FICHE DTM HAUTE TEMP 8VOIES CAPOT HDP20 POUR HDP26-24 PLUG LED PAR38 800LM 2700K 25Â° E27 PISTOLET Ã€ AIR CHAUD 2000W PRISE UK PISTOLET Ã€ AIR CHAUD 350W PRISE UK TACKER CABLE 9-11MM STAPLES TACKER CABLE 9-14MM STAPLES LDO,REG,DUAL,6VIN,1.2V/1.8V,6DFN REGULATEUR LDO 6VIN 1.2V/1.8V 6SOT26 LDO,REG,DUAL,6VIN,1.2V/3.3V,6DFN REGULATEUR LDO 6VIN 1.2V/3.3V 6SOT26 LDO,REG,DUAL,6VIN,1.5V/2.5V,6DFN REGULATEUR LDO 6VIN 1.5V/2.5V 6SOT26 LDO,REG,DUAL,6VIN,1.5V/3.3V,6DFN REGULATEUR LDO 6VIN 1.5V/3.3V 6SOT26 LDO,REG,DUAL,6VIN,1.8V/2.8V,6DFN REGULATEUR LDO 6VIN 1.8V/2.8V 6SOT26 LDO,REG,DUAL,6VIN,1.8V/3.0V,6DFN REGULATEUR LDO 6VIN 1.8V/3.0V 6SOT26 LDO,REG,DUAL,6VIN,1.8V/3.3V,6DFN LDO,REG,DUAL,6VIN,3.3V/3.3V,6DFN REGULATEUR LDO 6VIN 3.3V/3.3V 6SOT26 REGULATEUR LDO 0.19VDO 5.5VIN 1.5A 8DFN DRIVER LED 60V 1KHZ 16TSSOP DRIVER LED 60V 1KHZ 16TSSOP AMBERKLENE FE10 1L WIPES ENGINEERS DRY PQT 50 TERMINAL,RING TONGUE,1/4IN,CRIMP,RED TERMINAL,SPADE/FORK,#10,CRIMP,RED TERMINAL,SPADE/FORK,#6,CRIMP,RED TERMINAL,BUTT SPLICE,CRIMP,RED TERMINAL,RING TONGUE,1/4IN,CRIMP BLUE TERMINAL,SPADE/FORK,#6,CRIMP,BLUE TERMINAL,SPADE/FORK,#8,CRIMP,BLUE TERMINAL,SPADE/FORK,#6,CRIMP,BLUE TERMINAL,BUTT SPLICE,BLUE TERMINAL,RING TONGUE,#8,CRIMP,RED TERMINAL,SPADE/FORK,#6,CRIMP,RED TERMINAL,SPADE/FORK,#6,CRIMP,RED TERMINAL,SPADE/FORK,#8,CRIMP,RED TERMINAL,SPADE/FORK,#10,CRIMP,RED TERMINAL,BUTT SPLICE,RED TERMINAL,KNIFE DISCONNECT SPLICE,RED TERMINAL,SPADE/FORK,#6,CRIMP,BLUE TERMINAL,SPADE/FORK,#6,CRIMP,BLUE TERMINAL,SPADE/FORK,#8,CRIMP,BLUE TERMINAL,SPADE/FORK,#10,CRIMP,BLUE TERMINAL,SPADE/FORK,#10,CRIMP,BLUE TERMINAL,BUTT SPLICE,CRIMP,BLUE TERMINAL,KNIFE DISCONNECT SPLICE,BLUE TERMINAL,RING TONGUE,#6,CRIMP,YELLOW TERMINAL,RING TONGUE,#8,CRIMP,YELLOW TERMINAL,RING TONGUE 3/8IN CRIMP YELLOW TERMINAL,RING TONGUE 1/2IN CRIMP YELLOW TERMINAL,SPADE/FORK,#6,CRIMP,RED TERMINAL,RING TONGUE,3/8IN,CRIMP BLUE TERMINAL,RING TONGUE,#10,CRIMP,BLUE TERMINAL,RING TONGUE,#10,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP TERMINAL,FEMALE DISCONNECT 2.79MM CLEAR TERMINAL,FEMALE DISCONNECT,2.79MM,RED TERMINAL,FEMALE DISCONNECT,2.79MM,RED TERMINAL,FEMALE DISCONNECT,2.79MM BLUE TERMINAL,BUTT SPLICE,YELLOW TERMINAL,RING TONGUE,#6,CRIMP,BLUE WIRING ACCESSORIES TERMINAL,RING TONGUE,#2,CRIMP,RED TERMINAL,RING TONGUE,#4,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP,RED TERMINAL,RING TONGUE,#10,CRIMP TERMINAL,FEMALE DISCONNECT,5.21MM,RED TERMINAL,FEMALE DISCONNECT,5.21MM,RED TERMINAL,FEMALE DISCONNECT,5.21MM BLUE TERMINAL,FEMALE DISCONNECT 2.79MM CLEAR TERMINAL,FEMALE DISCONNECT 2.79MM CLEAR TERMINAL,SPADE/FORK,#2,CRIMP,RED TERMINAL CLOSED END SPLICE 4.75MM PURPLE TERMINAL,PARALLEL SPLICE,CRIMP TERMINAL,RING TONGUE,#6,CRIMP,YELLOW TERMINAL,SPADE/FORK,#6,CRIMP,RED TERMINAL,SPADE/FORK,#8,CRIMP,BLUE TERMINAL,BUTT SPLICE,YELLOW TERMINAL,SPADE/FORK,#6,CRIMP,RED TERMINAL,RING TONGUE,#4,CRIMP,BLUE TERMINAL,RING TONGUE,#6,CRIMP,BLUE TERMINAL,RING TONGUE,1/4IN,CRIMP BLUE TERMINAL,SPADE/FORK,#10,CRIMP,BLUE TERMINAL,SPADE/FORK,#4,CRIMP,RED TERMINAL,SPADE/FORK,#10,CRIMP,RED TERMINAL,SPADE/FORK,#6,CRIMP,BLUE RF/COAXIAL,SMB PLUG,STR,75 OHM,CRIMP RF/COAXIAL,SMB PLUG,STR,50 OHM,CRIMP CONTROLEUR H-WARE WATCHDOG I2C 24TSSOP REGULATEUR LDO 0.2VDO 0.15A 5V 5SOT23 REGULATEUR LDO 1.5VDO 1.5A 1.2V 3TO220 RF/COAXIAL,SMB PLUG,R/A,75 OHM,CRIMP TERMINAL,RING TONGUE 5/16IN,CRIMP BLUE TERMINAL,RING,#6 STUD,CRIMP,RED,22-16AWG TERMINAL,RING TONGUE,#6,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP,RED TERMINAL,FEMALE DISCONNECT,6.35MM BLUE TERMINAL,FEMALE DISCONNECT,4.75MM BLUE CONTACT,PIN,24-20AWG,CRIMP TERMINAL,SPADE/FORK,#10,CRIMP,BLUE TERMINAL,BUTT SPLICE,YELLOW OUTIL A SERTIR TAILLE 20 IMC/QC CONTACTS OUTIL A SERTIR TAILLE 22 IMC/QC CONTACTS LABEL OFF 50 200ML LUBRICANT KONTAFLON 85 200ML TERMINAL,BUTT SPLICE TERMINAL BLOCK,12POS,22-12AWG,11.1MM WIRING DUCT,WIDE SLOT,PVC,BLK,50MM PLUG CORD,1M HEAT-SHRINK WIRE MARKER SLEEVE,50.8MM W,2500/BOX TERMINAL,RING TONGUE,#10,CRIMP,RED HEAT-SHRINK WIRE MARKER,50.8MM W,250/ROLL AC-DC CONV,OPEN FRAME,1 O/P,150W,2.8 CRYSTAL,10MHZ,5MMX3.2MM,SMD CRYSTAL,12MHZ,5MMX3.2MM,SMD CRYSTAL,12.288MHZ,5MMX3.2MM,SMD CRYSTAL,13.56MHZ,5MMX3.2MM,SMD CRYSTAL,14.31818MHZ,5MMX3.2MM,SMD TERMINAL,RING TONGUE,3/8IN,CRIMP,RED TERMINAL,RING TONGUE,#4,CRIMP,BLUE CRYSTAL,16MHZ,5MMX3.2MM,SMD CRYSTAL,20MHZ,5MMX3.2MM,SMD CRYSTAL,25MHZ,5MMX3.2MM,SMD CRYSTAL,27MHZ,5MMX3.2MM,SMD CRYSTAL,28.63636MHZ,5MMX3.2MM,SMD CRYSTAL,37.05MHZ,5MMX3.2MM,SMD CRYSTAL,48MHZ,5MMX3.2MM,SMD CRYSTAL,8MHZ,5MMX3.2MM,SMD CRYSTAL,9.84375MHZ,5MMX3.2MM,SMD CRYSTAL,10MHZ,5MMX3.2MM,SMD TERMINAL,RING TONGUE,#6,CRIMP,BLUE CRYSTAL,11.0592MHZ,5MMX3.2MM,SMD CRYSTAL,12MHZ,5MMX3.2MM,SMD CRYSTAL,13.225625MHZ,5MMX3.2MM,SMD CRYSTAL,13.56MHZ,5MMX3.2MM,SMD CRYSTAL,13.56MHZ,5MMX3.2MM,SMD CRYSTAL,14.31818MHZ,5MMX3.2MM,SMD CRYSTAL,15.36MHZ,5MMX3.2MM,SMD CRYSTAL,16MHZ,5MMX3.2MM,SMD CRYSTAL,16MHZ,5MMX3.2MM,SMD CRYSTAL,18MHZ,5MMX3.2MM,SMD CRYSTAL,18.432MHZ,5MMX3.2MM,SMD CRYSTAL,19.68MHZ,5MMX3.2MM,SMD CRYSTAL,20MHZ,5MMX3.2MM,SMD CRYSTAL,24MHZ,5MMX3.2MM,SMD CRYSTAL,24.576MHZ,5MMX3.2MM,SMD CRYSTAL,25MHZ,5MMX3.2MM,SMD CRYSTAL,26MHZ,5MMX3.2MM,SMD CRYSTAL,27MHZ,5MMX3.2MM,SMD CRYSTAL,37.5MHZ,5MMX3.2MM,SMD CRYSTAL OSCILLATOR,CMOS,13.5MHZ,SMD CRYSTAL OSCILLATOR,CMOS,27MHZ,SMD CRYSTAL OSCILLATOR,CMOS,3.6864MHZ,SMD TERMINAL,RING TONGUE,#6,CRIMP,RED CRYSTAL OSCILLATOR,CMOS,33.333MHZ,SMD CRYSTAL OSCILLATOR,CMOS,4MHZ,SMD CRYSTAL OSCILLATOR,CMOS,40MHZ,SMD CRYSTAL OSCILLATOR,CMOS,48MHZ,SMD CRYSTAL OSCILLATOR,CMOS,50MHZ,SMD CRYSTAL OSCILLATOR,CMOS,54MHZ,SMD CRYSTAL OSCILLATOR,CMOS,32.768KHZ,SMD CRYSTAL,11.2896MHZ,3.2MMX2.5MM,SMD CRYSTAL,12MHZ,3.2MMX2.5MM,SMD CRYSTAL,13.56MHZ,3.2MMX2.5MM,SMD CRYSTAL,14.31818MHZ,3.2MMX2.5MM,SMD CRYSTAL,16MHZ,3.2MMX2.5MM,SMD TERMINAL,RING TONGUE,#6,CRIMP,RED CRYSTAL,16MHZ,3.2MMX2.5MM,SMD CRYSTAL,16.9344MHZ,3.2MMX2.5MM,SMD CRYSTAL,18.08MHZ,3.2MMX2.5MM,SMD CRYSTAL,18.432MHZ,3.2MMX2.5MM,SMD CRYSTAL,20MHZ,3.2MMX2.5MM,SMD CRYSTAL,24MHZ,3.2MMX2.5MM,SMD CRYSTAL,24.576MHZ,3.2MMX2.5MM,SMD CRYSTAL,26MHZ,3.2MMX2.5MM,SMD CRYSTAL,27MHZ,3.2MMX2.5MM,SMD CRYSTAL,28.224MHZ,3.2MMX2.5MM,SMD CRYSTAL,28.63636MHZ,3.2MMX2.5MM,SMD CRYSTAL,30MHZ,3.2MMX2.5MM,SMD CRYSTAL,33.333MHZ,3.2MMX2.5MM,SMD CRYSTAL,40MHZ,3.2MMX2.5MM,SMD CRYSTAL,48MHZ,3.2MMX2.5MM,SMD CRYSTAL,10MHZ,HC-49S CRYSTAL,11.2896MHZ,HC-49S CRYSTAL,13.225625MHZ,HC-49S CRYSTAL,13.56MHZ,HC-49S CRYSTAL,14.31818MHZ,HC-49S CRYSTAL,16MHZ,HC-49S CRYSTAL,16.9344MHZ,HC-49S CRYSTAL,20.5MHZ,HC-49S CRYSTAL,28.63636MHZ,HC-49S CRYSTAL,3.579545MHZ,HC-49S CRYSTAL,4MHZ,HC-49S CRYSTAL,4.194304MHZ,HC-49S CRYSTAL,8MHZ,HC-49S CRYSTAL,10MHZ,HC-49S,SMD CRYSTAL,11.0592MHZ,HC-49S,SMD CRYSTAL,11.2896MHZ,HC-49S,SMD CRYSTAL,12MHZ,HC-49S,SMD CRYSTAL,12.288MHZ,HC-49S,SMD CRYSTAL,13.225625MHZ,HC-49S,SMD CRYSTAL,14.31818MHZ,HC-49S,SMD CRYSTAL,16MHZ,HC-49S,SMD CRYSTAL,16.9344MHZ,HC-49S,SMD CRYSTAL,18.432MHZ,HC-49S,SMD CRYSTAL,20MHZ,HC-49S,SMD CRYSTAL,20.5MHZ,HC-49S,SMD CRYSTAL,24MHZ,HC-49S,SMD CRYSTAL,24.576MHZ,HC-49S,SMD CRYSTAL,27MHZ,HC-49S,SMD CRYSTAL,28.63636MHZ,HC-49S,SMD CRYSTAL,3.6864MHZ,HC-49S,SMD CRYSTAL,33.8688MHZ,HC-49S,SMD CRYSTAL,37.05MHZ,HC-49S,SMD CRYSTAL,4MHZ,HC-49S,SMD CRYSTAL,41.6MHZ,HC-49S,SMD CRYSTAL,5MHZ,HC-49S,SMD CRYSTAL,6MHZ,HC-49S,SMD CRYSTAL,8MHZ,HC-49S,SMD CRYSTAL OSCILLATOR,CMOS,12MHZ,SMD CRYSTAL OSCILLATOR,CMOS,12.288MHZ,SMD CRYSTAL OSCILLATOR,CMOS,13.5MHZ,SMD CRYSTAL OSCILLATOR,CMOS,14.31818MHZ,SMD CRYSTAL OSCILLATOR,CMOS,14.7456MHZ,SMD CONTACT,SOCKET,18-16AWG,CRIMP CRYSTAL OSCILLATOR,CMOS,24MHZ,SMD CRYSTAL OSCILLATOR,CMOS,25MHZ,SMD CRYSTAL OSCILLATOR,CMOS,26MHZ,SMD CRYSTAL OSCILLATOR,CMOS,27MHZ,SMD CRYSTAL OSCILLATOR,CMOS,28.63636MHZ,SMD CRYSTAL OSCILLATOR,CMOS,33MHZ,SMD CRYSTAL OSCILLATOR,CMOS,40MHZ,SMD CRYSTAL OSCILLATOR,CMOS,48MHZ,SMD CRYSTAL OSCILLATOR,CMOS,50MHZ,SMD CRYSTAL OSCILLATOR,CMOS,54MHZ,SMD CRYSTAL OSCILLATOR,CMOS,32.768KHZ,SMD TERMINAL,FEMALE DISCONNECT,6.35MM,RED CRYSTAL,12.288MHZ,3.2MMX2.5MM,SMD CRYSTAL,13.56MHZ,3.2MMX2.5MM,SMD CRYSTAL,14.31818MHZ,3.2MMX2.5MM,SMD CRYSTAL,21.948717MHZ,3.2MMX2.5MM,SMD CRYSTAL,24MHZ,3.2MMX2.5MM,SMD CRYSTAL,24.576MHZ,3.2MMX2.5MM,SMD CRYSTAL,26MHZ,3.2MMX2.5MM,SMD CRYSTAL,27MHZ,3.2MMX2.5MM,SMD CRYSTAL,28.63636MHZ,3.2MMX2.5MM,SMD CRYSTAL,30MHZ,3.2MMX2.5MM,SMD CRYSTAL,33.333MHZ,3.2MMX2.5MM,SMD TERMINAL,SPADE/FORK,#10,CRIMP,YELLOW CRYSTAL,37.05MHZ,3.2MMX2.5MM,SMD CRYSTAL,41.6MHZ,3.2MMX2.5MM,SMD CRYSTAL,9.84375MHZ,3.2MMX2.5MM,SMD CRYSTAL OSCILLATOR,CMOS,11.2896MHZ,SMD CRYSTAL OSCILLATOR,CMOS,20MHZ,SMD CRYSTAL OSCILLATOR,CMOS,26MHZ,SMD CRYSTAL,10MHZ,8MMX4.5MM,SMD CRYSTAL,12MHZ,8MMX4.5MM,SMD CRYSTAL,12.288MHZ,8MMX4.5MM,SMD CRYSTAL,13.56MHZ,8MMX4.5MM,SMD CRYSTAL,16MHZ,8MMX4.5MM,SMD CRYSTAL,16.9344MHZ,8MMX4.5MM,SMD CRYSTAL,20MHZ,8MMX4.5MM,SMD CRYSTAL,24.576MHZ,8MMX4.5MM,SMD CRYSTAL,28.224MHZ,8MMX4.5MM,SMD CRYSTAL,28.63636MHZ,8MMX4.5MM,SMD CRYSTAL,33MHZ,8MMX4.5MM,SMD CRYSTAL,33.333MHZ,8MMX4.5MM,SMD CRYSTAL,9.84375MHZ,8MMX4.5MM,SMD SENSOR,RECEIVER,SAFETY,EVA FOR ADAM CAPTEUR EVA E SECURITE /REC POUR ADAME CAPTEUR ADAM SECURITE/3M CABLE/VITAL CAPTEUR ADAM SECURITE/10M CABLE/VITAL CAPTEUR ADAM SECURITE/20M CABLE/VITAL CAPTEUR ADAM SECURITE/CABLE+M12/VITAL VITAL 1 CONTROL UNIT 24DC/2NO SMILE 11EA TINA ESTOP UNIT POUR VITAL INCA 1 TINA PANEL ESTOP POUR VITAL TINA 1A BLANK PLUG POUR TINA 4A/8A TINA 2A VITAL ADAPTATEUR/MECH CONTACTS TINA 3A VITAL ADAPTATEUR/MECH CONTACTS TINA 4A M12 VITAL CONNECTION BLOCK TINA 8A M12 VITAL CONNECTION BLOCK TINA 6A VITAL ADAPTATEUR POUR SAFE EDGES TINA 7A VITAL ADAPTATEUR/MECH CONTACTS TINA 2B VITAL ADAPTATEUR AVEC CABLE TINA 10A VITAL ADAPTATEUR/OSSD SORTIES TINA 10B VITAL ADAPTATEUR/OSSD SORTIES TINA 10C VITAL ADAPTATEUR/OSSD SORTIES CABLE 10M 5X0.34MM+M12 FEMALE CABLE 10M 8X0.34MM+M12 FEMALE INTERFACE CARD - DATA ACQUISITION SWITCH,ROCKER,DPST,20A,250VAC,BLACK LED LIGHT BAR,YELLOW,5W,24VDC,230MM OPERATING TOOL,MODULAR TERMINAL BLOCK TIME DELAY RELAY,1NO,0.1SEC,24VDC FUSE,SMD,4A,SLOW BLOW TERMINAL BLOCK,PCB,1POS TIME DELAY RELAY,SPDT,100H,240VAC/DC SSR,PANEL MOUNT,32VDC,12A,265VAC DEVICE SERVER ETHERNET TO SERIE CHOKE,5UH,23A,10% LED LENS CAP,T-1 3/4 LED FFC JUMPER,40 WAY,30V WIRE MARKER CARDS,VINYL,BLK,38MM,25 CARDS TERMINAL,RING TONGUE,SIZE 10,CRIMP TERMINAL,FERRULE,CRIMP,WHITE N CHANNEL MOSFET,55V,89A,D-PAK SWITCH,PUSHBUTTON,SPST-NO,10A,YELLOW CONNECTOR,POWER ENTRY,RCPT,20A CNTRL RECTIFICATION 38V 3A 8SO CNTRL RECTIFICATION DOUBLE 38V 3A 8SO DRIVER CFL 500V 4 STEP DIMMING 16SO CNTRL SMPS 700V 905HZ FBRST 5W 7SO CNTRL SMPS 700V 1270HZ FBRST 5W 7SO CNTRL SMPS 700V 1750HZ FBRST 5W 7SO CNTRL SMPS 700V 430HZ FBRST 11W 7SO CNTRL SMPS 700V 905HZ FBRST 11W 7SO CNTRL SMPS 700V 1270HZ FBRS 11W 7SO CNTRL SMPS 700V 1750HZ FBRS 11W 7SO RUBAN DE MASQUAGE USAGE GENERAL 75MM RUBAN. MASKING GEN PUROSE 100MM RUBAN DE MASQUAGE HAUTE PERFORM 25MM RUBAN DE MASQUAGE CREPE 25MM RUBAN DE MASQUAGE CREPE 38MM RUBAN DE MASQUAGE CREPE 50MM RUBAN DE MASQUAGE CREPE 75MM RUBAN DE MASQUAGE PERFORMANCE 38MM RUBAN DE MASQUAGE PERFORMANCE 50MM RUBAN DE MASQUAGE HAUTE TEMP 19MM RUBAN DE MASQUAGE HAUTE TEMP 25MM RUBAN DE MASQUAGE HAUTE TEMP 38MM RUBAN DE MASQUAGE HAUTE TEMP 50MM LABELING TAPE,19.05MM W X 4.88M L,BLK/WHT,NYLON CAPACITOR ALUM ELEC 33UF 10V 20%,SMD LED RING LIGHT ILLUMINATOR CAPACITOR TANT,2.2UF 10V 6.3 OHM 10%,3216-18 SIGNAL HORN ALARM,105DB,24VAC/VDC,5A TERMINAL BLOCK MARKER,5MM,WHT,MULTICARD 1000 CAPACITOR ALUM ELEC 2200UF,50V,20%,RADIAL SWITCH,TOGGLE,DPDT,15A,250V TERMINAL,LUG,DUAL-RATED MECHANICAL,SCREW EVAL BRD,KEIL LPC1768 EVAL BRD,KEIL LPC1758 OPTOCOUPLERS EVAL BRD,EA LPCXPRESSO BASEBOARD EVAL BRD,KEIL LPC1769 IC,RS-232 TRANSCEIVER,5.5V,TSSOP-16 CABLE CLAMP,NYLON 6.6,NATURAL BRT TRANSISTOR,PNP,-50V,-100MA,10KOHM / 47KOHM,3-SOT-416 VOICE ANNUNCIATOR,24VDC,90DB,IP54 SWITCH,LOAD BREAK,3P,600VAC,10A CONTACT BLOCK,1 NC + 1 NO,SCREW CLAMP AC-DC CONV,ENCLOSED,1 O/P,15W,700mA,24V FERRULE ASST,TWIN WIRE END,0.5-2.5MM2 CONNECTOR,TERMINAL BLOCK,2POS,10-3AWG SWITCH,KEY OPERATED,DPST,100mA,42V SWITCH BODY,XCMD LIMIT SWITCH TERMINAL BLOCK,STANDARD,2WAY,16AWG HEAT SHRINK TUBING,38.1MM ID,PO,BLK,48Â´Â´ SWITCH,SAFETY INTERLOCK,DPST,6A,120VAC CONNECTOR,HOUSING,RCPT,4POS,1ROW CONNECTOR,HEADER,4POS,1ROW,1MM HEAT SHRINK TUBING,12.7MM ID,PVC,BLK,2 TERMINAL,SPADE/FORK,#6,CRIMP,BLUE CONNECTOR ASSEMBLIES,TEST TERMINAL,RING TONGUE,3/8IN,CRIMP BLUE CONNECTOR,POWER ENTRY,RCPT,15A,NEMA L6-15R SPACER/STANDOFF,BRASS,4.75MM X 6.35MM LABEL,SELF LAM,VINYL,1.5Â´Â´W X 6Â´Â´H,50/ROLL,WHT IC,SYNC BUCK DC/DC CONTROLLER,16-HTSSOP SPACER,HEX,6-32,63.5MM,BRASS,NICKEL SCREW,PAN HEAD,NYLON 6.6,8-32,19.1MM ADAPT PUISSANCE DESK TOP 12V 5A 60W ADAPT PUISSANCE DESK TOP 15V 4A 60W ADAPT PUISSANCE DESK TOP 18V 3.6A 65W ADAPT PUISSANCE DESK TOP 36V 1.8A 65W ADAPT PUISSANCE DESK TOP 12V 7.5A 90W ADAPT PUISSANCE 13.5V 6.67A 90W ADAPT PUISSANCE DESK TOP 15V 6.67A 100W ADAPT PUISSANCE DESK TOP 19V 5.8A 110W ADAPT PUISSANCE DESK TOP 20V 5.5A 110W ADAPT PUISSANCE DESK TOP 48V 3.13A 150W ALIM A DECOUPAGE MEDICAL 12V ALIM A DECOUPAGE MEDICAL 24V ALIM A DECOUPAGE MEDICAL 48V ALIM A DECOUPAGE MEDICAL 12V ALIM A DECOUPAGE MEDICAL 24V ALIM A DECOUPAGE MEDICAL 48V BASEPLATE COOLED PS 12V 500W BASEPLATE COOLED PS 24V 500W BASEPLATE COOLED PS 36V 500W BASEPLATE COOLED PS 48V 500W BASEPLATE COOLED PS 12V 1000W BASEPLATE COOLED PS 24V 1000W BASEPLATE COOLED PS 48V 1000W ALIM A DECOUPAGE 36V 14A 504W COMPARATEUR DOUBLE 35VIN 1.3US 8SOP REGULATEUR LDO 5.5VIN 0.12VDO 1% 5TO252 COMMUTATEUR USB 0.08OHM 8SOP REGULATEUR LDO 5.5VIN 0.15A 1.8V 5HVSOF REGULATEUR LDO 5.5VIN 0.15A 3.3V 5HVSOF MPU SITARA CORTEX A8 324NFBGA MPU SITARA CORTEX A8 298NFBGA WAVEFORM GENERATOR,20MHZ,1 CH GENERATOR,WAVEFORM,20MHZ,2 CH GENERATOR,WAVEFORM,20MHZ,1 CH,ARB GENERATOR,WAVEFORM,20MHZ,2 CH,ARB GENERATOR

RECEPTACLE WITH SCREW 20 VOIES PLUG WITH LOCK NUT 120 VOIES RECEPTACLE WITH SCREW 120 VOIES INSERTION TOOL 516 SERIES NUT DRIVER POLARISING HARDWARE SCREWS/NUTS/WASHERS 20VOIES INSULATOR SCREW/NUT/WASHER 38/56VOIES INSULATOR IC,ADJ LDO REG,1.2V TO 5.5V,SOT-223-6 CHIP INDUCTOR 220NH 320MA 5% 950MHZ SINGLE BOARD COMPUTER,AT91SAM9261S PROCESSOR SUPPORT 40MM DIAM. SANS CAPOT ZHAGA SUPPORT 40MM DIAM. AVEC CAPOT ZHAGA SUPPORT 30X36MM DIAM. SANS CAPOT ZHAGA DAC,16BIT,SOT23-8 IC,LOGIC,NAND GATE,SINGLE,3.8NS,6-SC-70 CAPACITOR CERAMIC 0.047UF 50V,X7R,10%,0603 MODULE RF DONGLE CONNECT 2 PI MODULE EASYRADIO ARDUINO SHIELD KIT DE DEV EASYRADIO TRANSCEIVER DIODE TVS DEUX DIR 58V 10KA AXIAL DIODE TVS DEUX DIR 76V 10KA AXIAL DIODE TVS DEUX DIR 170V 10KA AXIAL DIODE TVS DEUX DIR 320V 10KA AXIAL DIODE TVS DEUX DIR 380V 10KA AXIAL DIODE TVS DEUX DIR 470V 10KA AXIAL DIODE TVS DEUX DIR 380V 6KA AXIAL DIODE TVS DEUX DIR 430V 6KA AXIAL DIODE TVS DEUX DIR 380V 3KA AXIAL DIODE TVS DEUX DIR 430V 3KA AXIAL EVAL KIT,AM3359,W/ 4.3IN LCD GYROSCOPE 3AXES +/-450DPS 24QFN BUCK SYNCH 0.4A 1.2MHZ 1.2V CL2025 BUCK SYNCH 0.4A 1.2MHZ 1.8V CL2025 BUCK SYNCH 0.4A 1.2MHZ 2.5V CL2025 BUCK SYNCH 0.4A 1.2MHZ 3V CL2025 BUCK SYNCH 0.4A 1.2MHZ 3.3V CL2025 BUCK SYNCH 0.4A 1.2MHZ AJUSTABLE CL2025 IC,NON INVERTING BUFFER,DIP-20 KNOB JEU DE TOURNEVIS TORQUE LAME DE TOURNEVIS TORQUE SL 3.0 LAME DE TOURNEVIS TORQUE SL 3.5 LAME DE TOURNEVIS TORQUE SL 4.0 LAME DE TOURNEVIS TORQUE PZ1 LAME DE TOURNEVIS TORQUE PZ2 LAME DE TOURNEVIS TORQUE MOD1 LAME DE TOURNEVIS TORQUE MOD2 DETECTEUR DE TENSION SANS CONTACT WRENCH,BUSH,CONDUIT SCIE 300MM 12 BLADES,HACKSAW,12Â´Â´X18 TPI BLADES,HACKSAW,12Â´Â´X24 TPI BLADES,HACKSAW,12Â´Â´X32 TPI SUIVI DE CABLE AGRAPHES 7.5X11.1MM PQT 1000 STAPLES 7.5X14.2MM PQT 1000 SUIVI DE CABLE POUR CABLE TELECOM AGRAPHEUSE SRUBANS 10.5X8MM PQT 1000 AGRAPHES 10.5X12MM PQT 1000 AGRAPHES 10.5X14MM PQT 1000 MODULE INTERFACE EXPANSION POUR RPI BLADE DIAMOND 115MM BLADE DIAMOND 230MM KIT VISSEUSE ET EMBOUTS 10PC KIT TOOL SERVICE ENGINEER 91PC KIT TOOL ELECTRICIANS 96PC DRILL BODY ONLY ANGLE 18V GRINDER ANGLE BODY ONLY 18V SCIE CONNECT CIRCU BODY ONLY 18V JIGSCIE BODY ONLY 18V SCIE RECIPRO BODY ONLY 18V VACUUM BODY ONLY 18V DRILL ANGLE 10MM 240V DRILL ROTATIF 10MM 240V GRINDER ANGLE 125MM 240V BATTERIE NI-CAD 14.4V 1.3AH BATTERIE NI-NH 14.4V 2.6AH BATTERIE NI-MH 18V 3.0AH DRIVER DRILL 10.8V MESURE DE DISTANCE LASER DRILL SDS BODY ONLY 18V SET BIT PZ2 25PC DISC FLAP 115MM Z40G DRIVER DRILL 14.4V WITH TORCH DRILL SDS/HAMMER C/LESS 18V DRILL PERCUSSION 2 SPD 720W 110V GRINDER ANGLE CORDLESS 18V JIGSCIE CORDLESS 18V SCIE RECIPRO CORDLESS 18V SCIE CONNECT CIRCU C/LESS 18V SANDER PALM 1/4 SHEET 240V SANDER PALM 1/4 SHEET 110V SANDER 1/2 SHEET 240V SANDER 1/2 SHEET 110V PERCEUSE / VISSEUSE 50PC OUTIL MULTI 240V OUTIL MULTI 110V KIT MULTITOOL 240V 33PC KIT MULTITOOL 110V 33PC KIT MULTITOOL C/LESS 18V OUTIL MULTI BOD ONLY C/LESS 18V DRILL COMBI 10.8V 2 X BAT DRILL SDS LI-ION 18V BOD ONLY BATTERIE 24V 3.1AH 80610204341 3365/06 100 =6/CAB/TYP1/28AWG/STR/.050Â´Â´Â´Â´/100 01C2851 OP-AMP,50MHZ,18V/Âµs,200ÂµV,SOIC-8 CRIMP TERMINAL,#6,BLOCK FORK,RED RESISTOR,BUS RES N/W 5,100KOHM,2%,SIP RESISTOR,BUS RES N/W 5,2KOHM,2%,SIP RESISTOR,BUS RES N/W 9,56KOHM,2%,SIP SPEED CONTROL HANDLE,VICES DUST COVER,RUBBER,BLACK LED BULB,EDISON SCREW/E26,COOL WHITE,6W LED BULB,EDISON SCREW/E26,WARM WHITE,6W LED BULB,EDISON SCREW/E26,COOL WHITE,6W LED BULB,EDISON SCREW/E26,COOL WHITE,10W LED BULB,EDISON SCREW/E26,WARM WHITE,10W LED BULB,EDISON SCREW/E26,COOL WHITE,10W LED BULB,EDISON SCREW/E26,COOL WHITE,15W LED BULB,EDISON SCREW/E26,WARM WHITE,15W LED BULB,EDISON SCREW/E26,COOL WHITE,15W CONNECTOR,HOUSING,RECEPTACLE,6POS CONNECTOR,HOUSING,RECEPTACLE,6POS CONNECTOR,HOUSING,RECEPTACLE,6POS CONNECTOR,HOUSING,PIN & SOCKET,TAB,2POS,3.5MM HEAT SINK,ALUMINIUM,BLK,TO-126,1 CLIP HEAT SINK,ALUMINIUM,DEGREASED,TO-126,1 CLIP HEAT SINK,ALUMINIUM,BLK,TO-126,2 CLIPS HEAT SINK,ALUMINIUM,DEGREASED,TO-126,2 CLIPS TERMINAL,FLAG,RCPT,6.35MM,CRIMP ASSEMBLY TOOL,SMART POSITION SENSOR ASSEMBLY TOOL,SMART POSITION SENSOR MAGNET COLLAR,SMART POSITION SENSOR SENSOR,POSITION,ROTARY,12-30VDC SENSOR,HUMIDITY/TEMPERATURE,DIGITAL,SIP-4 SENSOR,HUMIDITY/TEMPERATURE,DIGITAL,SIP-4 LTC2380-16,SAR ADC,16BIT,2MSPS,DEMO BOARD LTC2379-18,SAR ADC,18BIT,1.6MSPS,DEMO BOARD LTC2378-18,SAR ADC,18BIT,1MSPS,DEMO BOARD LTC2376-18,SAR ADC,18BIT,250KSPS,DEMO BOARD LTC2370-16,SAR ADC,16BIT,2MSPS,DEMO BOARD LTC2369-18,SAR ADC,18BIT,1.6MSPS,DEMO BOARD LTC2364-18,SAR ADC,18BIT,250KSPS,DEMO BOARD LTC2389-18,SAR ADC,18BIT,2.5MSPS,DEMO BOARD LTC2389-16,SAR ADC,16BIT,2.5MSPS,DEMO BOARD OP-AMP,30MHZ,18V/Âµs,273ÂµV,VSSOP-8 CONNECTOR,SOCKET,2POS,1 ROW,2.54MM CONNECTOR,SOCKET,3POS,1 ROW,2.54MM CONNECTOR,SOCKET,4POS,1 ROW,2.54MM CONNECTOR,SOCKET,5POS,1 ROW,2.54MM CONNECTOR,SOCKET,6POS,1 ROW,2.54MM CONNECTOR,MICRO USB 2,RCPT,5POS,PCB CONNECTOR,MICRO USB 2,RCPT,5POS,PCB BENCH VICE,VERSATILE,73MM CAGE,1X1,BEHIND BEZEL,ZQSFP+ CAGE,1X1,BEHIND BEZEL W/ HEAT SINK,ZQSFP+ CAGE,1X3,BEHIND BEZEL,ZQSFP+ CAGE,1X3,BEHIND BEZEL W/ HEAT SINK,ZQSFP+ LED,WHITE,180MCD SWITCH ENCLOSURE SWITCH ENCLOSURE SWITCH ENCLOSURE IC,LDO VOLT REG,5V,0.1A,3-SOT-23 RESISTOR WIREWOUND,100 OHM,10W,5% ELECTRICAL AC ADAPTER,20A,125V CIRCULAR CONNECTOR,CABLE MOUNT RESISTOR,WIRE WOUND,200 OHM,1W,1% MODULE,SMARTWIRE-DT,FOR CONTACTORS MODULE,SMARTWIRE-DT,FOR CONTACTORS GATEWAY,24VDC,700mA GATEWAY,24VDC,700mA GATEWAY,24VDC,3A POWER FEED MODULE,24VDC,3A POWER FEED MODULE,24VDC,3A DIGITAL MODULE,24VDC,500mA ANALOGUE MODULE,10V,20mA ANALOGUE MODULE,10V,20mA DIGITAL MODULE,24VDC,4mA DIGITAL MODULE,24VDC,4mA DIGITAL MODULE,24VDC,4mA ANALOGUE MODULE,24VDC,4mA DIGITAL MODULE,24VDC,4mA ACTUATOR,FAK SERIES PALM SWITCH ACTUATOR,FAK SERIES PALM SWITCH ACTUATOR,FAK SERIES PALM SWITCH ENCLOSURE,SURFACE MOUNT,1HOLE ENCLOSURE,SURFACE MOUNT,4HOLE ADAPTER,FIXING,M22 SERIES FUNCTION ELEMENT PCB,M22 SERIES FUNCTION ELEMENT PCB,M22 SERIES FUNCTION ELEMENT PCB,M22 SERIES FUNCTION ELEMENT PCB,M22 SERIES FUNCTION ELEMENT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,DPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,SPDT,QUICK CONNECT CONTACT BLOCK,DPDT,QUICK CONNECT CONTACT BLOCK,DPDT,QUICK CONNECT CONTACT BLOCK,D

CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT
CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES
PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15
5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5

CIRCU TAILLE 25 128VOIES PIN CONNECT CIRCU TAILLE 25 128VOIES PIN CONNECT CIRCU TAILLE 25 128VOIES PIN CONNECT CIRCU TAILLE 25 128VOIES SKT CONNECT CIRCU TAILLE 25 128VOIES SKT CONNECT CIRCU TAILLE 25 128VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES PIN CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 56VOIES SKT CONNECT CIRCU TAILLE 25 61VOIES PIN CONNECT CIRCU TAILLE 25 61VOIES PIN CONNECT CIRCU TAILLE 25 61VOIES PIN CONNECT CIRCU TAILLE 25 61VOIES PIN CONNECT CIRCU TAILLE 25 61VOIES SKT CONNECT CIRCU TAILLE 25 61VOIES SKT CONNECT CIRCU TAILLE 25 61VOIES SKT CONNECT CIRCU TAILLE 25 61VOIES SKT CONNECT CIRCU TAILLE 25 61VOIES PIN CONNECT CIRCU TAILLE 25 61VOIES PIN CONNECT CIRCU TAILLE 25 61VOIES PIN CONNECT CIRCU TAILLE 25 61VOIES PIN

PIN CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT
CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN
CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN
CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13
10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE
13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU
TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT
CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT
CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT
CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT
CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT
CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT
SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15
18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE
15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU
TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU
CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT
CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT
SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT
SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT
CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN

13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES PIN CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 22VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES PIN CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 4VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES PIN CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 13 10VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES PIN CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 18VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES PIN CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 37VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES PIN CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT CONNECT CIRCU TAILLE 15 5VOIES SKT

PLUG,15A,CRIMP/SOLDER BLACK/RED SWITCH,KEYPAD,1X4,50mA,24V,POLYMER MOUNTING BRACKET,CABINET RACKS,STEEL SWITCH ACTUATOR TERMINAL,RING TONGUE,#10,CRIMP PROCESS METER TERMINAL,MALE DISCONNECT,6.35MM,SCREW CONTACT,PIN,12-10AWG,CRIMP PROCESS METER TERMINAL,FEMALE DISCONNECT,6.35MM,16-14AWG,BLUE MICRO SWITCH,ROLLER LEVER SPDT 11A 250V MICRO SWITCH,PIN PLUNGER,SPDT 16A 250V Phase Meter Leaded Process Compatible:No SWITCH PANEL PLUG NYLON SPACER ASSORTMENT CIRCULAR CONNECTOR PLUG,SIZE 12,8POS,CABLE CAPACITOR CERAMIC,1UF,50V,X7R,20%,RADIAL CIRCULAR CABLE CLAMP,STR,SZ 14/14S,METAL FAN FILTER W/ EXHAUST GRILLE PHOTOELECTRIC SENSOR CAPACITOR POLY FILM FILM 0.1UF 10%,250V TERMINAL,MALE DISCONNECT,0.25IN,THD BANANA PLUG,5A,TURRET TERMINAL COMPRESSION LUG,0.146IN SOLDER I/O MODULE RELAY SOCKET DIGITAL GENERAL PURPOSE TIMER CRIMP TOOL SOLID STATE TIMER,DPDT,12MIN,120VAC DIGITAL HOUR METER PIN RECEPTACLE,PC BOARD,SOLDER Multipole Connector CRIMP TOOL,ANDERSON CRIMP TERMINALS ELECTROMECHANICAL MULTIFUNCTION TIMER CAPACITOR CERAMIC 2200PF,100V,X7R,10%,RAD PLUG & SOCKET HOUSING,RECEPTACLE,14 POS,1 ROW SWITCH LEGEND PLATE CIR CONNECTOR RCPT SIZE 20 14POS FREE HANGING Pushbutton Switch RF TRANSISTOR,NPN,25V BIPOLAR TRANSISTOR,PNP,-24V ZENER DIODE,1W,10V,AXIAL BIPOLAR TRANSISTOR,PNP,-90V,TO-220 BIPOLAR TRANSISTOR,NPN,300V TO-39 RF TRANSISTOR,PNP,-16V,700MHZ,TO-72 BRIDGE RECTIFIER,1PH,2A,200V THD BRIDGE RECTIFIER,1PH,2A,1KV,THD STANDARD DIODE,250mA,200V,DO-35 DUAL N CHANNEL MOSFET,25V,TO-72 BIPOLAR TRANSISTOR,NPN,450V,TO-3 DARLINGTON TRANSISTOR,NPN,120V BIPOLAR TRANSISTOR,NPN,80V,TO-39 DARLINGTON TRANSISTOR,NPN,120V,TO-3 N CHANNEL MOSFET,500V,8A,TO-220 N CHANNEL MOSFET,200V,18A,TO-220 N CHANNEL MOSFET,400V,10A,TO-220 N CHANNEL MOSFET,500V,4.5A TO-220 N CHANNEL MOSFET,1KV,3.1A,TO-220 BIPOLAR TRANSISTOR,PNP,-180V TO-3 BIPOLAR TRANSISTOR,PNP,-80V TO-92 OPTOCOUPLER,TRANSISTOR,1500VRMS OPTOCOUPLER,TRANSISTOR,7500VRMS OPTOCOUPLER,SCHMITT TRIGGER,7500VRMS BIPOLAR TRANSISTOR,NPN,100V,TO-220 BIPOLAR TRANSISTOR,PNP,-160V BIPOLAR TRANSISTOR,NPN,150V BIPOLAR TRANSISTOR,NPN,100V BIPOLAR TRANSISTOR,NPN,750V,TO-3 BIPOLAR TRANSISTOR,NPN,100V,TO-218 BIPOLAR TRANSISTOR,PNP,-300V,TO-39 BIPOLAR TRANSISTOR,PNP,-150V BIPOLAR TRANSISTOR,NPN,100V DARLINGTON TRANSISTOR,NPN,50V N CHANNEL MOSFET,60V,500mA,TO-92 ZENER DIODE,500mW,5.1V,AXIAL ZENER DIODE,500mW,10V,AXIAL ZENER DIODE,500mW,12V,AXIAL ZENER DIODE,500mW,15V,AXIAL STANDARD DIODE,500mA,1.5KV,AXIAL ZENER DIODE,1W,18V,AXIAL ZENER DIODE,5W,10V,AXIAL ZENER DIODE,5W,51V,AXIAL FAST RECOVERY DIODE,0.5A 2KV AXIAL BRIDGE RECTIFIER,1PH 1.5A 600V THD BRIDGE RECTIFIER,1PH,4A,200V THD BRIDGE RECTIFIER,1PH,6A,200V THD BRIDGE RECTIFIER,1PH,100A,600V,SCREW SCR THYRISTOR,4A,100V,TO-202 SCR THYRISTOR,10A,400V,TO-220 SCR THYRISTOR,35A,400V,TO-48 SCR THYRISTOR,35A,600V,TO-48 SCR THYRISTOR,35A,800V,TO-48 TRIAC,400V,15A,TO-220 TRIAC,600V,15A,TO-220 TRIAC,400V,40A,ISOLATED TO-48 TRIAC,400V,8A,TO-220 TRIAC,400V,3A,TO-5 SCHOTTKY RECTIFIER,5A,60V,DO-27 STANDARD DIODE,3A,600V,AXIAL STANDARD DIODE,3A,1.2KV,DO-27 STANDARD DIODE,6A,100V,AXIAL STANDARD DIODE,6A,1KV,AXIAL SCHOTTKY RECTIFIER,1A,40V,DO-41 SCHOTTKY RECTIFIER,3A,40V,DO-27 STANDARD DIODE,25A,400V STANDARD DIODE,25A,400V FAST RECOVERY DIODE,8A 600V TO-220 STANDARD DIODE,40A,600V,DO-5 STANDARD DIODE,85A,1.2KV,DO-5 UNIJUNC TRANSISTOR,0.3W 50mA TO-92 N CHANNEL MOSFET,100V,14A,TO-220 IC,HEX INVERTING BUFFER/DRIVER,DIP-14 FUSE,THERMAL,104Â°C,15A,277V FUSE,THERMAL,109Â°C,15A,277V FUSE,THERMAL,240Â°C,15A,277V IC,OP-AMP,4MHZ,13V/ us,DIP-8 IC,OP-AMP,20MHZ,50V/ us,METAL CAN IC,OP-AMP,0.5V/Âµs,7.5mV,DIP-14 IC,LINEAR VOLTAGE REGULATOR,12V,TO-92 IC,LINEAR VOLTAGE REGULATOR 6V TO-220-3 IC,LINEAR VOLT REGULATOR,15V,TO-220-3 IC,LINEAR VOLT REGULATOR,24V,TO-220-3 IC,OP-AMP,DIP-8 IC,TIMER,DUAL,16V,14-DIP IC,OP-AMP,3MHZ,1.5V/ us,DIP-14 BIPOLAR TRANSISTOR,PNP,-80V MALE SCREWLOCK,4-40 BIPOLAR TRANSISTOR,NPN,-80V,TO-126 POWER TRANSISTOR,NPN,70V,7A,TO-220 BIPOLAR TRANSISTOR,NPN,800V BIPOLAR TRANSISTOR,NPN,450V,TO-218 BIPOLAR TRANSISTOR,NPN,400V,TO-220 DARLINGTON TRANSISTOR,PNP,-100V TO-220 BIPOLAR TRANSISTOR,NPN,160V BIPOLAR TRANSISTOR,NPN,80V TO-220 BIPOLAR TRANSISTOR,NPN,350V BIPOLAR TRANSISTOR,NPN,500V,TO-3 BIPOLAR TRANSISTOR,NPN,100V,TO-218 BIPOLAR TRANSISTOR,NPN,350V BIPOLAR TRANSISTOR,NPN,150V,TO-220 DARLINGTON TRANSISTOR,NPN,500V,TO-3 CONTACT,6AWG,CRIMP PLUG & SOCKET CONNECTOR,PLUG,1POS PLUG & SOCKET CONNECTOR,PLUG,1POS CONTACT,0.4AWG,THROUGH HOLE PLUG & SOCKET CONNECTOR,PLUG,1POS PLUG & SOCKET CONNECTOR,PLUG,1POS PLUG & SOCKET CONNECTOR,PLUG,1POS PLUG & SOCKET CONNECTOR,PLUG,1POS MOUNTING WING,PP15,PP30 SERIES CONN PLUG AND SOCKET CONNECTOR HOUSING Ceramic Multilayer Capacitor Capacitance TERMINAL,RING TONGUE,#10,CRIMP MICRO-D CONNECTOR,PLUG,25POS,WIRE LEADS SAFETY RELAY 3PST-NO/SPST-NC,250VAC,5A COMPUTER CABLE,KEYBOARD,2.5M,BLUE COMPUTER CABLE,USB,2.5M,BLUE FAN FILTER W/ EXHAUST GRILLE POWER TRANSISTOR,PNP,-60V,TO-3 TERMINAL BLOCK PLUGGABLE,6POS,26-14AWG TEST LEAD,SINGLE,BLACK,24IN,3000VDC SELF ADJUST WIRE STRIPPER BANANA JACK,15A,CRIMP/SOLDER,RED PUSHBUTTON SWITCH SWITCH,PUSHBUTTON DPST-1NO/1NC 5A,250V SWITCH,PUSHBUTTON DPST-1NO/1NC 5A,250V LIGHT PUSHBUTTON SWITCH,PUSHBUTTON,SPST-NO,100mA,42V SWITCH,PUSHBUTTON,SPST-NC,10A,400V INDICATOR,INCAND LAMP,MIDGET GROOVED INSULATOR SLEEVE SWITCH,PUSHBUTTON SPST-NC/SPST-NO,5A,250V,SOLDER SWITCH PUSHBUTTON DPST-1NO/1NC 100mA 42V SWITCH CONTACT BLOCK SWITCH ACTUATOR SWITCHING ELEMENT,1NC,5A,SCREW SWITCHING ELEMENT,1NO/1NC,6A,SCREW BATTERY STRAP,9V,WIRE LEAD CONNECTOR,DIN,PLUG,8POS SPRING CONTACT RECEPTACLE,PCB,CRIMP SPRING CONTACT RECEPTACLE,PCB,CRIMP SPRING CONTACT RECEPTACLE,PCB,CRIMP SPRING CONTACT RECEPTACLE,PCB WIRE WRAP SPRING CONTACT RECEPTACLE,PCB,SOLDER SPRING CONTACT RECEPTACLE,PCB,CRIMP SPRING CONTACT RECEPTACLE,PCB,SOLDER SPRING CONTACT RECEPTACLE,PCB WIRE WRAP SPRING CONTACT RECEPTACLE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB,0.125IN SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB COAXIAL CABLE,RG-59,12IN,BLACK COAXIAL CABLE,RG-59,24IN,BLACK COAXIAL CABLE,RG-59,36IN,BLACK COAXIAL CABLE,RG-59,48IN,BLACK COAXIAL CABLE,RG-59,60IN,BLACK ADAPTER,BNC-MINIATURE PLUG SCR THYRISTOR,10A,600V,TO-220 Lead Acid Battery Voltage Rating:12V SPRING CONTACT RECEPTACLE,PCB,SOLDER SPRING CONTACT RECEPTACLE,PCB SPRING CONTACT RECEPTACLE,PCB,SOLDER SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SPRING CONTACT PROBE,PCB SWITCH ACTUATOR Tools,Cutters INCANDESCENT LAMP JOYSTICK SWITCH,DPST-1NO/1NC,10A,660V JOYSTICK SWITCH,DPST-1NO/1NC,10A,660V JOYSTICK SWITCH,DPST-1NO/1NC,10A,660V LIQUID LEAKAGE SENSOR AMPLIFIR CIRCUIT BREAKER,THERMAL MAG,1P,2A CIRCUIT BREAKER,THERMAL MAG,1P,3A CIRCUIT BREAKER,THERMAL MAG,1P,5A CIRCUIT BREAKER,THERMAL MAG,1P,10A CIRCUIT BREAKER,THERMAL MAG,1P,15A CIRCUIT BREAKER,THERMAL MAG,1P,20A Snap Action Basic Switch BATTERY HOLDER,AA,PCB BATTERY HOLDER,AA,PCB BATTERY STRAP,9V,WIRE LEAD SWITCH BOOT BUSHING SEAL FILTER FAN GRILL,5.91INX5.91IN LENS,ROUND,GREEN WIRE STRIPPER/CUTTER IC,8BIT MPU,4MHZ,DIP-40 BIPOLAR TRANSISTOR,PNP,-24V,TO-5 BIPOLAR TRANSISTOR,PNP,-35V,TO-3 BIPOLAR TRANSISTOR,NPN,12V,TO-92 BIPOLAR TRANSISTOR,NPN,325V,TO-3 BIPOLAR TRANSISTOR,NPN,700V,TO-3 IC,LINEAR VOLTAGE REGULATOR,15V,TO-3 IC,LINEAR VOLTAGE REGULATOR,12V,TO-3 DARLINGTON TRANSISTOR,PNP,-120V,TO-3 N CHANNEL MOSFET,500V,2.5A TO-220 N CHANNEL MOSFET,100V,40A,TO-3 DARLINGTON TRANSISTOR,NPN,80V,TO-3 BIPOLAR TRANSISTOR,NPN,100V,10A,TO-3 OPTOCOUPLER,TRANSISTOR,5000VRMS IC,ANALOG SWITCH,QUAD,SPST,DIP-14 ZENER DIODE,5W,24V,AXIAL BRIDGE RECTIFIER,1PH,4A,1KV,THD SCR THYRISTOR,7A,600V,TO-5 SCR THYRISTOR,55A,400V,TO-218 TRIAC,600V,40A,TO-218 TRIAC,600V,40A,TO-48 SCR/DIODE MODULE,12.5A,1.2KV STANDARD DIODE,300A,400V,DO-9 PROGRAMMABLE UJT,1A,TO-92 IC,QUAD D-LATCH,DIFFERENTIAL,DIP-16 IC ADJ LINEAR REG 2V TO 37V METAL CAN-14 IC,OP-AMP,2mV,DIP-8 POSITIVE BUTTON,BATTERY CONTACT DIN Audio Connector CONNECTOR,DIN,JACK,6POS CONNECTOR,DIN,PLUG,6POS SWITCH,PUSHBUTTON,SPDT-DB,10A,250V LAMP COMPACT FLUORESCENT GX-23 13W LAMP,FLUORESCENT,G5,4W LAMP,FLUORESCENT,G5,6W WIRE-BOARD CONN,HEADER,68POS,1.27MM CAPACITOR CERAMIC,0.1UF,25V,Y5V,+80,-20%,0603 END CLAMP,TERMINAL BLOCK PC SCREW TERMINAL PC SCREW TERMINAL Connectors I/O MODULE MOUNTING BRACKET TERMINAL,COMPRESSION LUG 0.171IN SOLDER TERMINAL,COMPRESSION LUG,0.14IN SOLDER TERMINAL,COMPRESSION LUG,0.17IN SOLDER TERMINAL,COMPRESSION LUG 0.144IN SOLDER TERMINAL,COMPRESSION LUG,0.17IN SOLDER CIRCULAR CONNECTOR BODY MATERIAL:ALUMINU CIRCUIT BREAKER,THERMAL,1P,240V,2A POWER RELAY,SPDT,120VAC,30A,FLANGE AVALANCHE DIODE,1A,600V,SOD-57 CABLE CLAMP,SIZE 1,METAL TERMINAL,RING TONGUE,1/4IN,CRIMP TERMINAL,MALE DISCONNECT,6.35MM YELLOW CAT5 RJ45 MODULAR JACK,8POS,1 PORT CAT5 RJ45 MODULAR JACK,8POS,1 PORT DISCRETE SOCKET,PC BOARD SWITCHING DIODE,100V 150mA,SOD-80 POWER RELAY,SPDT,5VDC,10A,PC BOARD POWER RELAY,SPDT,12VDC,10A,PC BOARD POWER RELAY,DPDT,12VDC,15A,PLUG IN ZENER DIODE,1.3W,7.5V,DO-41 ZENER DIODE,500mW,2.4V,DO-35 IC SELF LAMINATING CABLE ID MARKERS SELF LAMINATING CABLE ID MARKERS SELF LAMINATING CABLE ID MARKERS CABLE ID MARKERS,SELF LAM,25.4MM W,POLY,WHT,PK2500 CABLE ID MARKERS,SELF LAM,2.54MM,POLY,WHT,PK1000 SELF LAMINATING CABLE ID MARKERS CAPACITOR CERAMIC 0.01UF,200V,X7R,10%,RAD CAPACITOR CERAMIC 1000PF,50V,X7R,10%, Ceramic Multilayer Capacitor CAPACITOR CERAMIC 2.2UF,50V,Z5U,RADIA CABLE ID LABELS,SELF LAM,50.8MM WX38.1MM H,WHT,PK1000 TERMINAL,FERRULE,0.24IN.,WHITE TERMINAL,FERRULE,0.31IN.,CRIMP,WHITE TERMINAL,FERRULE,0.31IN.,GREY TERMINAL,FERRULE,0.39IN.,RED TERMINAL,FERRULE,0.24IN.,RED TERMINAL,FERRULE,0.39IN.,BLACK TERMINAL,FERRULE,0.31IN.,BLACK TERMINAL,FERRULE,0.31IN.,BLUE TERMINAL,FERRULE,0.39IN.,GREY TERMINAL,FERRULE,0.47IN.,GREY TERMINAL,FERRULE,0.31IN,WHITE TERMINAL,FERRULE,0.31IN,RED TERMINAL,FERRULE,0.39IN,BLUE TERMINAL,FERRULE,0.04IN TERMINAL,FERRULE,0.04IN FERRULE KIT,DIN INSULATED FERRULE KIT,DIN INSULATED NON-TURN WASHER PNEUMATIC SUB-BASE STRAIN RELIEF,10WAY,BRASS CIRCULAR CONNECTOR RECEPTACLE 5POS CABLE P CHANNEL MOSFET,-60V,47A,TO-220 OPTOCOUPLER,LOGIC GATE,2500VRMS MICRO-D CONNECTOR,PLUG,15POS,WIRE LEADS MICRO-D CONNECTOR,PLUG,31POS,WIRE LEADS MICRO-D CONNECTOR,PLUG,37POS,WIRE LEADS D SUB JACKSCREW ASSEMBLY,M5,9.77MM D SUB JACK SCREW,M7,12.06MM I/O MODULE I/O MODULE I/O MODULE I/O MODULE I/O MODULE RF/COAXIAL,BNC PLUG,STR,75 OHM,CRIMP RF/COAXIAL,BNC PLUG,STRAIGHT,CRIMP RF/COAXIAL,BNC BHD JACK,STR,SOLDER RF/COAXIAL,BNC PLUG,STR,50 OHM,CLAMP RF/COAXIAL,BNC PLUG,STR,50 OHM,CLAMP RF/COAXIAL,BNC PLUG,STR,50 OHM,CRIMP RF/COAXIAL BNC BHD JACK STR 50 OHM SOLDER RF/COAXIAL BNC BHD JACK STR 50 OHM SOLDE UNIVERSAL CABLE STRIPPER/SLITTER CAPACITOR CERAMIC 0.01UF,16V,X7R,10%,0805 CAPACITOR CERAMIC,0.1UF,25V,X7R,20%,1206 TOOLS,HAND CRIMP TOOLS,CRIMP,HAND,CRIMPING/STRIPPING TOOL,TERMINALS & SPLICES,ECONOMY 5-WAY CRIMP TOOL,SPC TECHNOLOGY 34C7550 TERMINAL,BUTT SPLICE,IDC,RED PLUGGABLE TERMINAL BLOCK,12 CONTACT,26-14AWG LED,GREEN,1.25MM X 1.4MM,10MCD,570NM LED,GREEN,1.25MM X 1.4MM,7MCD,570NM LED,RED,1.25MM X 1.4MM,13MCD,640NM LED,YELLOW,1.25MM X 1.4MM,12MCD,585NM CONNECTOR,SPEAKER,PLUG,4POS CONNECTOR,RCA/PHONO,PLUG,2POS CONNECTOR,RCA/PHONO,PLUG,2POS POWER INDUCTOR,150UH,550MA,10% 6.2MHZ METAL OXIDE VARISTOR,5.5V,17.5V,0603 Circular Connector Body Material:Electro RF/COAXIAL,BNC BHD FEMALE,STR,75 OHM TERMINAL BLOCK,PCB,2POS,30-12AWG TERMINAL BLOCK,PCB,3POS,30-12AWG TERMINAL BLOCK,PCB,4POS,30-12AWG TERMINAL BLOCK,PCB,5POS,30-12AWG TERMINAL BLOCK,PCB,6POS,30-12AWG TERMINAL BLOCK PLUGGABLE,2POS,30-12AWG TERMINAL BLOCK PLUGGABLE,4POS,30-12AWG PIN HEADER,EUROSTYLE,2POS,5.08MM PIN HEADER,EUROSTYLE,2POS,5.08MM TERMINAL BLOCK PLUGGABLE,2POS,30-12AWG TERMINAL BLOCK PLUGGABLE,3POS,30-12AWG TERMINAL BLOCK PLUGGABLE,4POS,30-12AWG PIN HEADER,EUROSTYLE,2POS,5MM PIN HEADER,EUROSTYLE,3POS,5MM TERMINAL BLOCK,PCB,2POS,30-12AWG TERMINAL BLOCK,PCB,3POS,30-12AWG TERMINAL BLOCK,PCB,4POS,30-12AWG TERMINAL BLOCK,PCB,5POS,30-12AWG TERMINAL BLOCK,PCB,6POS,30-12AWG TERMINAL BLOCK,PCB,9POS,30-12AWG TEST LEAD,SINGLE,RED,24IN,3000VDC PROXIMITY SENSOR SWITCH ACTUATOR LIMIT SWITCH,ROLLER LEVER,SPDT IC,OP-AMP QUAD LOW POWER SMALL SIGNAL DIODE,100V 200mA SOT-23 LIMIT SW,ADJUSTABLE ROLLER LEVER,SPDT TERMINAL BLOCK,PCB,10POS,30-12AWG TERMINAL BLOCK,PCB,12POS,30-12AWG TERMINAL BLOCK,PCB,12POS,30-12AWG TERMINAL BLOCK,PCB,8POS,30-12AWG CAPACITOR CERAMIC 10PF 50V,C0G,5%,0805 CAPACITOR ALUM ELEC 120UF,450V,20%,SNAP-IN CAPACITOR ALUM ELEC 220UF,400V,20%,SNAP-IN PANEL MOUNT INDICATOR,LED,8.1MM,RED,12V PANEL MOUNT INDICATOR,LED,8.1MM,RED,28V PANEL MOUNT INDICATOR,LED,8.1MM,YELLOW,28V PANEL MOUNT INDICATOR,LED,8.1MM,GREEN,28V TERMINAL BLOCK PLUGGABLE,3POS,30-12AWG PIN HEADER,EUROSTYLE,6POS,5.08MM TERMINAL BLOCK PLUGGABLE,6POS,30-12AWG TERMINAL BLOCK PLUGGABLE,8POS,30-12AWG TERMINAL BLOCK,PCB,8POS,30-12AWG IC,INSTRUMENT AMP,600KHZ,106DB SOIC-8 IC,OP-AMP,1MHZ,0.4V/ us,SOIC-8 IC,TIMER,SINGLE,2.1MHZ,15V,8-SOIC MICRO SWITCH,STR LEVER,SPDT 100mA 125V TOOLS,HAND CRIMP FEET (BUMPERS) Enclosure INSPECTION WINDOW,3.8X3IN POLYCARBONATE INSPECTION WINDOW,9.8X5IN POLYCARBONATE INSPECTION WINDOW,9.8INX8.6IN,PC LED,3MM,RED,15MCD,630NM CONNECTOR HOUSING,RECEPTACLE,12 POS,1 ROW BATTERY HOLDER,AAA,PANEL BATTERY HOLDER,22 1/2V,PANEL Square Pin Receptacle Patch Cord,0.025 BOX,SHIELDED,ALUMINIUM,BLUE Epoxy Coated Monolithic Ceramic,Radial VOLTAGE METER VOLTAGE METER LIMIT SWITCH,ROLLER PLUNGER,SPDT SHLD MULTICOND CABLE,3COND,16AWG,250FT,300V TIME DELAY RELAY BIPOLAR TRANSISTOR,NPN,15V DUAL N/P CHANNEL MOSFET,30V,SOIC ZENER DIODE,1W,12V,DO-41 ZENER DIODE,1W,33V,DO-41 ZENER DIODE,500mW,3.6V,DO-35 ZENER DIODE,500mW,8.2V,DO-35 FAST RECOVERY DIODE,1A,800V DO-41 PASTILLE DE SOUDURE 250G PLUG & SOCKET HOUSING,PLUG,NYLON PLUG & SOCKET HOUSING,RECEPTACLE,8POS,3.96MM PLUG & SOCKET HOUSING,RECEPTACLE,9POS,3.96MM PLUG & SOCKET CONNECTOR,PLUG 6POS 4.2MM PLUG & SOCKET HOUSING,PLUG,NYLON PLUG & SOCKET HOUSING,PLUG,NYLON WIRE-BOARD CONNECTOR HEADER 8POS,3.96MM MICRO SWITCH STRAIGHT LEVER SPDT 5A 277V MICRO SW,STRAIGHT LEVER,SPDT,11A 277V MICRO SWITCH,ROLLER LEVER SPDT 11A 277V MICRO SWITCH,ROLLER LEVER SPDT 11A 277V MICRO SW,STRAIGHT LEVER,SPDT,11A 277V MICRO SWITCH,ROLLER LEVER,SPDT 1A 125V MICRO SWITCH,PIN PLUNGER,SPDT 15A 277V MICRO SWITCH,ROLLER LEVER SPDT 15A 277V SWITCH,TOGGLE,SPDT,10A,277V SUPPORT DE FER Plastic Connector Cover JUNCTION BLOCK,STUD TYPE,1POS JUNCTION BLOCK,STUD TYPE,1POS Connectors TERMINAL BLOCK,PCB,2POS,30-14AWG TERMINAL BLOCK,PCB,4POS,30-14AWG TERMINAL BLOCK,PCB,6POS,30-14AWG TERMINAL BLOCK,PCB,8POS,30-14AWG TERMINAL BLOCK,PCB,12POS,30-14AWG RELAY SOCKET CONNECTORS,TERMINAL BLOCKS Terminal block,5 positions CARD EDGE CONNECTOR,SOCKET,44POS CARD EDGE CONNECTOR,SOCKET,50POS LENS CAP ENCLOSURE,UTILITY,POLYSTYRENE,BLACK ENCLOSURE,UTILITY,POLYSTYRENE,BLACK ENCLOSURE,BOX,PLASTIC,BLACK ENCLOSURE,BOX,PLASTIC,BLACK ENCLOSURE,BOX,PLASTIC,BLACK ENCLOSURE,BOX,PLASTIC,BLACK ENCLOSURE,BOX,PLASTIC,BLACK CONNECTOR ASSEMBLIES,IC CLIPS TEST CONNECTOR ASSEMBLIES,IC CLIPS TEST RACHET CRIMP TOOL CUTTER,CABLE,0.5IN MICRO SW,ROLLER PLUNGER,SPDT,15A 250V AM 35 Cable Stripper/Slitter OUTIL SERTISSAGE WE/SS TOUT EN UN CRIMPER/CUTTER/STRIPPER,MODULAR PLUGS TOTALIZING COUNTER TOTALIZING COUNTER DIGITAL GENERAL PURPOSE TIMER DIGITAL GENERAL PURPOSE TIMER TERMINAL,FERRULE,1.3MM,CRIMP,GREY TERMINAL,FERRULE,1.5MM,CRIMP,RED TERMINAL,FERRULE,1.3MM,CRIMP,WHITE SWITCH,INDUSTRIAL PUSHBUTTON,22MM LIMIT SWITCH,CROSS ROLLER PLUNGER,SPDT IC,HALL EFFECT SENSOR,LINEAR,TO-92-3 TOOLS,HAND CRIMP METAL OXIDE VARISTOR,5.5V,15.5V,0805 CIRCUIT BREAKER,THERMAL MAG,1P,25A POWER RELAY,DPDT,240VAC,10A,PLUG IN POWER RELAY,DPDT,240VAC,10A,PLUG IN POWER RELAY,DPDT,24VDC,10A,PLUG IN POWER RELAY,4PDT,24VAC,5A,PLUG IN POWER RELAY,4PDT,120VAC,5A,PLUG IN METAL OXIDE VARISTOR,33V,72V 1206 SWITCHING DIODE,200V,250mA,DO-35 SCHOTTKY RECTIFIER,150mA,100V,DO-35 SMD IC ADAPTER,8-SOT TO 8-SIP SMD IC ADAPTER,4-SOT-143 TO 4-SIP SMD IC ADAPTER,SOT-223 TO 3-SIP TEST CLIP,MINGRABBER,BLACK,5A TEST CLIP,1POS ENCLOSURE,UTILITY,PLASTIC,BLACK ENCLOSURE,UTILITY,PLASTIC,BLACK RF/COAXIAL,SMA PLUG,STR,50 OHM,SOLDER SHUNT JUMPER,2WAY,2.54MM TVS DIODE,1.5KW,6.8V,DO-201 TVS DIODE,1.5KW,15V,DO-201 TVS DIODE,1.5KW,18V,DO-201 TVS DIODE,1.5KW,33V,DO-201 TVS DIODE,600W,51V,DO-15 TVS DIODE,600W,7V,DO-214AA TVS DIODE,600W,13V,DO-214AA TEST LEAD,SINGLE,BLACK,36IN,1000V BASIC ELECTRONIC DMM TEST LEAD KIT RF/COAXIAL,SMA JACK,STR,50OHM,SOLDER WIRE STRIPPER TEST PROD WIRE,100FT 18AWG CU GREEN ENCLOSURE,WALL MOUNT,ALUMINIUM MICRO-D CONNECTOR,PLUG,37POS,SOLDER LAMP,INCANDESCENT,WIRE LEADED,28V LAMP,INCANDESCENT,BI PIN,12V LENS,SQUARE,BLUE SWITCH CONTACT BLOCK Keypad Legend SPRING CONTACT PROBE,PCB All-Purpose Electrician?s Tool 50B4622 LAMP,FLUORESCENT,G10Q,22W CIRCULAR CONNECTOR RCPT,SIZE 11,8POS,PANEL LIMIT SWITCH,SIDE ROTARY,SPDT-1NO/1NC THERMOCOUPLE CONNECTOR LIMIT SWITCH,ROLLER LEVER,DPDT PHOTOELECTRIC SENSOR TEST LEAD,BANANA,GREEN,72IN,5000VDC COAXIAL CABLE ASSEMBLY TEST PROBE BNC MALE CONNECTOR,2249 TYPE CABLE FRONT/REAR MOUNTING GASKET CIRCULAR CONN BULKHEAD ADAPTER,BNC JACK-BNC JACK POWER RELAY,SPDT,5VDC,10A,PC BOARD HOOK-UP WIRE,100FT,22AWG,CU,BLUE LENS,RECTANGULAR,RED CAT3 MODULAR PLUG,6POS,1 PORT CAT3 MODULAR PLUG,6POS,1 PORT CAT3 RJ45 MODULAR PLUG,8POS,1 PORT TURNABLE JACK SCREW,#4-40,56.13MM TURNABLE JACK SCREW,#4-40,44.86MM TURNABLE JACK SCREW,#4-40,57.66MM CIRCULAR CONNECTOR RCPT SIZE 17,28POS,PANEL BANANA JACK ADAPTER,25A,SCREW,RED PRECISION CUTTER,FULL FLUSH,1.3MM,5IN PRECISION CUTTER,FULL FLUSH,0.81MM 5IN BLANK GROMMET,VINYL,9.9MM,ROUND BLANK GROMMET,VINYL,12.4MM,ROUND BLANK GROMMET,VINYL,22.1MM,ROUND BLANK GROMMET,VINYL,25.4MM,ROUND OPEN GROMMET OPEN GROMMET OPEN GROMMET OPEN GROMMET OPEN GROMMET OPEN GROMMET SNAP ON FUSE COVER Fasteners,Spacers/standoffs COMPUTER CABLE,USB,1M,WHITE COMPUTER CABLE,USB,3M,WHITE FERRITE CORE,SPLIT,13.05MM,200 OHM/100MHZ FERRITE CORE,CYLINDRICAL,218OHM/100MHZ FERRITE CORE,CYLINDRICAL,125OHM/100MHZ Snap Action Basic Switch BASIC SWITCH,PLUNGER,SPDT,15A,480V Hand Held Enclosure Crimp Tool,controlled cycle,crimps PAN 51B814 TERMINAL,RING TONGUE,1/4IN,CRIMP WIRE-BOARD CONNECTOR HEADER,8WAY,0.1IN ALLIGATOR CLIP,BLACK CONTACT,SOCKET,18-14AWG,CRIMP TERMINAL,FEMALE DISCONNECT,6.35MM,RED CRIMP DIE,354940-1 CRIMP TOOL SWITCHING ELEMENT,1NC,10A,SCREW TEST LEAD,BANANA,BLUE,48IN,5000VDC BINDING POST,15A,TURRET,WHITE CAPACITOR CERAMIC 0.01UF,50V,X7R,10%,RAD CAPACITOR CERAMIC 2200PF,50V,X7R,10%,RAD TERMINAL BLOCK,BARRIER,2POS,18-10AWG ELECTROMECHANICAL HOUR METER Electromechanical Totalizing Counter RELAY SOCKET ALLIGATOR CLIP,24.6MM,RED,20A TOOLS,HYDRAULIC CRIMP DIP SOCKET,14POS,THROUGH HOLE DIP SOCKET,16POS,THROUGH HOLE DIP SOCKET,16POS,THROUGH HOLE Cap,Epoxy Coated Monolithic Ceramic,Ra ZENER DIODE,5W,24V,AXIAL CAPACITOR CERAMIC 1000PF,50V,X7R,10%,RAD CIRCULAR SHELL,PLUG,SZ 28,AL ALLOY TEST CLIP,MINIGRABBER,BLACK,5A BANANA PLUG,15A,SCREW,BLACK CONNECTORS,ACCESSORIES CAPACITOR ALUM ELEC 300UF,250V,+75,-10%,AXIAL FICHE 2MM VERS 4MM BANANA PLUG,15A,SCREW,GREEN BANANA PLUG,15A,SOLDER LUG BANANA PLUG,15A,SCREW,RED CONDENSATEUR 250V 100UF DOUBLE BANANA PLUG,15A,TURRET,BLUE ENCLOSURES COAXIAL CABLE,RG-214/U,60IN BANANA PLUG,5A,RIVET CONNECTOR ASSEMBLIES BOX,SHIELDED,ALUMINIUM TEST LEAD,BNC JACK,500V RF/COAXIAL ADAPTER,SMA JACK-TNC PLUG Square pin receptacle to banana plug,re DOUBLE BANANA PLUG,15A,SCREW,BLACK TEST LEAD SINGLE,RED/BLACK,143MM,500V CONNECTOR ASSEMBLIES CONNECTEUR MODULAIRE CAT5E 8 CONTACTS UNSHLD MULTIPR CABLE,4PR,1000FT,300V CABLE GLAND (CLAMP),PG7 CABLE GLAND (CLAMP) CABLE GLAND (CLAMP),PG13.5 CABLE GLAND (CLAMP) MODULAR CONNECTOR REED RELAY,SPDT,24VDC,0.25A,THD CONDUCTIVE PLASTIC POTENTIOMETER POT,COND PLASTIC,20KOHM,20%,1W RECTIFIER MODULE,1.2KV,100A,SEMIPACK 1 Discrete SemiÂ´s,Diode/Rectifier,Diode BRIDGE RECTIFIER,3PH,110A,1.2KV,SCREW MICRO SWITCH,PIN PLUNGER,SPDT,5A 250V POWER RELAY,SPDT,5VDC,10A,PC BOARD INDICATOR,LED PANEL MNT,RED/GREEN,5V PANEL MOUNT INDICATOR,LED,17.463MM,GREEN,12V PANEL MOUNT INDICATOR,LED,17.463MM,GR I/O MODULE CROSSFLOW BLOWER,SHADED POLE AC MOTOR ENCLOSURE,BOX,PLASTIC,GRAY RF/COAXIAL,BNC PLUG,STR,50 OHM,CLAMP COAXIAL CABLE,SUB MINI RG-59/U,23AWG,1000FT,BLK CABLE,SHLD MULTICOND,2COND,18AWG,1000FT,300V CABLE,UNSHLD MULTICOND,2COND,16AWG,1000FT,300V CABLE,UNSHLD MULTICOND,4COND,22AWG,1000FT,300V CABLE,SHLD MULTICOND,2COND,18AWG,1000FT,300V SHLD MULTICOND CABLE,2COND,18AWG,1000FT,300V CABLE,UNSHLD MULTICOND,6COND,22AWG,1000FT,300V SHLD MULTICOND CABLE,4COND,22AWG,1000FT,300V UNSHLD MULTICOND CABLE 3COND 18AWG 1000FT CABLE,SHLD MULTICOND,2COND,14AWG,1000FT,300V SHLD MULTICOND CABLE,2COND,20AWG,1000FT,300V UNSHLD MULTICOND CABLE 4COND 18AWG 1000FT ENCLOSURE JUNCTION BOX POLYCARBON

MODEM,PUTTY OUTDOOR EXTENSION CORD 25FT,15A,ORANGE POTENTIOMETER,COND PLASTIC,50KOHM,10%,2W RJ45 MODULAR PLUG,8POS,1 PORT POT COND PLASTIC,10KOHM 10%,500mW RESISTOR,METAL FILM,1KOHM,125mW,0.1% CAT5E RJ45 MODULAR JACK,8POS,2 PORT CATEGORY 5E CABLE ASSEMBLY RESISTOR,METAL FILM,1KOHM,250mW,1% RESISTOR,THICK FILM,499KOHM,125mW,1% RESISTORS,THICK FILM SERIES:CRCW RESISTORS,THICK FILM SERIES:CRCW RESISTOR,THICK FILM,60.4KOHM,250mW,1% RESISTOR,METAL FILM,10KOHM,250mW,1% RESISTOR,METAL FILM,10 OHM,125mW,1% Modular Connector COMPUTER CABLE,USB 1.0,5M,PUTTY COMPUTER CABLE,USB 1.0,2M,GRAY Connector assemblies,Computer cables Connector assemblies,Computer cables COMPUTER CABLE,IEEE 1284,3FT,PUTTY CAT6 PUNCH DOWN MODULAR JACK,1 PORT COMPUTER CABLE,MOUSE ADAPTER 0.5FT PUTT BINDING POST,60A,SCREW,BLACK BANANA PLUG ASSEMBLY,SCREW Terminal Block Mounting Type:PC Board POTENTIOMETER,COND PLASTIC,500 OHM,0.1,2W TERMINAL,MECHANICAL LUG,#6,SOLDER LOUPE X8 CUTTER/PLIER COMBINATION PANNE BISEAU 1.6MM PANNE POINTE 1.2MM (XY9/258/268/200GX) PANNE 5MM BISEAU 45DEG PANNE 0.8MM POUR 136/137 PANNE POINT 0.8MM POUR 136/137 PANNE CHISEL 1.6MM POUR 136/137 PANNE CONIQUE 5MM POUR 200PHG/25/40W PANNE BISEAU 5MM POUR 200PHG/25/40W PANNE CONIQUE 5MM POUR 200PHG/60W PANNE BISEAU 5MM POUR 200PHG/60W BALUN,2.45GHZ,50/200OHM,0805 TERMINAL BLOCK,BARRIER,2POS,14-4AWG TERMINAL BLOCK,BARRIER,3POS,14-4AWG TERMINAL BLOCK,BARRIER,3POS,14-2AWG TERMINAL BLOCK,BARRIER,3POS,14-2AWG TERMINAL BLOCK,BARRIER,2POS,3/8-16AWG PCB,Tracks(Strip Board) BEACON LIGHT,FLASHING,290mA,120V,40W,RED TERMINAL,TURRET,#8-32,SOLDER,WHITE Switches,Rocker Switch Function:SPDT Rocker Switch Rocker Switch Rocker Switch 28 VOLTS 3/8Â´Â´Â´Â´ OIL TIGHT INDICATOR HEAT SHRINK CABLE ID MARKERS CABLE ID MARKERS CABLE ID MARKERS CABLE ID MARKERS CABLE ID MARKERS CABLE ID MARKERS Label Printer Tape 19C7408 SHRINK TUBING LABELING MATERIAL/ PRINTER CARTRIDGE SHRINK TUBING LABELING MATERIAL/ PRINTER CARTRIDGE Label Printer Tape 19C7432 SELF LAMINATING CABLE ID MARKERS SELF LAMINATING CABLE ID MARKERS Labels CARD EDGE CONNECTOR,SOCKET,44POS LAMP,INDICATOR,NEON,RED,125V ROUND KNURLED KNOB W/ ARROW IND,6.35MM TRANSDUCER,TONE GENERATOR,110DB,120V TRANSDUCER,PIEZO,2.9KHZ,97DBA,120V TRANSDUCER,PIEZO,2.9KHZ,95DBA,28V POINTER BAR SKIRTED KNOB,6.35MM POINTER BAR KNOB,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,3.175MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM POINTER BAR SKIRTED KNOB,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM ROUND KNOB,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM POINTER BAR KNOB,6.35MM Vibration Transducer Vibration Transducer LAMP,HALOGEN,120V,40W BEACON LIGHT ROTATING,350mA,AMBER BEACON LIGHT ROTATING,350mA,RED ROTATING,BEACON,LIGHT,115mA DIN MOUNTING RAIL STANDARD TERMINAL BLOCK BEACON LIGHT Ceramic Multilayer Capacitor SCR THYRISTOR,350A,4.5KV,T 82 POWER BLOCK COVER,PLASTIC TERMINAL BLOCK,BARRIER,3POS,1/4-20AWG Multi contact tool handle BINDING POST,15A,#6-32,STUD BLACK/RED Test Connector FASTENERS,SCREWS 70B8270 TERMINAL BLOCK,BARRIER,5POS,22-12AWG TERMINAL BLOCK,BARRIER,6POS,22-12AWG TRI-BARRIER TERMINAL BLOCK,RAISED BASE SOCKET ASSEMBLY TERMINAL BLOCK,BARRIER,8POS,22-12AWG TERMINAL BLOCK,BARRIER,10POS,22-12AWG TERMINAL BLOCK,BARRIER,4POS,22-12AWG CARD EJECTOR HANDLE,WHITE NYLON BEACON LIGHT FLASHING HALOGEN 300mA CRANK HANDLE ROUND KNOB,6.35MM PANEL MOUNT INDICATOR,LED,7.92MM,GREEN,24V PANEL MOUNT INDICATOR,LED,7.92MM,RED,125V PANEL MOUNT INDICATOR,LED,7.92MM,RED,12V PANEL MOUNT INDICATOR,LED,7.92MM,RED,24V TERMINAL BLOCK,BARRIER,4POS,22-12AWG TERMINAL BLOCK,BARRIER,8POS,22-12AWG TERMINAL BLOCK,BARRIER,12POS,22-12AWG Standard Terminal Block ROUND POINTER SKIRTED KNOB,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM Single row terminal block,14-16 America LED MOUNTING RING Enclosures,Accessories ROUND KNURLED KNOB,3.175MM ROUND KNURLED KNOB,6.35MM ROUND KNURLED KNOB W/ LINE IND,3.175MM ROUND KNURLED KNOB WITH LINE IND,6.35MM ROUND KNURLED KNOB,6.35MM ROUND KNURLED KNOB,6.35MM ROUND KNURLED KNOB WITH LINE IND,6.35MM ROUND KNURLED KNOB,3.175MM ROUND KNURLED KNOB,6.35MM ROUND KNURLED KNOB WITH LINE IND,6.35MM PANEL MOUNT INDICATOR,LED,12.7MM,AMBER,24V PANEL MOUNT INDICATOR,LED,12.7MM,GREEN,24V LED LAMP VARIABLE TRANSFORMER Variable Transformer TRANSDUCER,PIEZO,2.9KHZ,90DBA,28VDC Single row terminal block,14 American w TEST RECEPTACLE,SKT-RCPT,100A,WW,BLU VARIABLE TRANSFORMER TERMINAL BLOCK JUMPER,3WAY,9.5MM LAMP,INDICATOR,INCAND,GRN LAMP,INDICATOR,INCANDESCENT,RED LAMP,INDICATOR,NEON,GREEN,125V LAMP,INDICATOR,NEON,RED,125V LOAD FORCE:30-0.06/2.5-060 OUNCE-INCH SOLENOID DUTY CYCLE:INTERMITTENT LOAD FORCE:30-0.12/4-0.50 OUNCE-INCH SOLENOID DUTY CYCLE:INTERMITTENT AC voltage box frame solenoid,maximum o Box Frame Solenoid Solenoid Duty Cycle:I SOLENOID DUTY CYCLE:INTERMITTENT Cylindrical Solenoid Solenoid Duty Cycle MINIATuRE INDICATOR LIGHT,2.5 MILLICAND PANEL MOUNT INDICATOR,LED,5MM,GREEN,24V PANEL MOUNT INDICATOR,LED,5MM,RED,24V PANEL MOUNT INDICATOR,LED,5MM,YELLOW,24V TERMINAL BLOCK JUMPER,2WAY,9.65MM 36 SERIES PRESSFIT INDICATOR LIGHTS W/ L TRANSDUCER,PIEZO,2.9KHZ,95DBA,16VDC PB Series Pushbutton Miniature Switch,P ROUND SKIRTED KNOB,3.175MM POINTER BAR SKIRTED KNOB,6.35MM POINTER BAR SKIRTED KNOB,6.35MM ROUND SKIRTED KNOB,3.175MM ROUND SKIRTED KNOB,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,3.175MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM ROUND POINTER SKIRTED KNOB,3.175MM DUCT COVER,PVC,LT GRY,31.8MM W,6FT/1.82M L,PER FT ROUND POINTER SKIRTED KNOB,6.35MM ROUND KNOB,6.35MM POINTER BAR KNOB,6.35MM POINTER BAR KNOB,6.35MM ROUND SKIRTED KNOB,6.35MM ROUND POINTER SKIRTED KNOB,6.35MM ROUND KNOB,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM ROUND SKIRTED KNOB W/ ARROW IND,6.35MM PANEL MOUNT INDICATOR,LED,6.2MM,GREEN,24V SOCKET,PANEL,MINI,YELLOW,TYPE K SOCKET,PANEL,MINI,GREEN,TYPE K CAPTEUR DE TEMP+TETE CAPTEUR DE TEMP+TETE Circular Connector CURRENT SENSOR PHOTOELECTRIC SENSOR,OTICAL TOUCH,NPN ENCLOSURE,JUNCTION BOX,STEEL,GRAY Small Enclosure ENCLOSURE,JUNCTION BOX,STEEL,GRAY Outlet Surge Suppressor Transient Energy TIME DELAY RELAY,SPST-NO,100SEC,12VDC TIME DELAY RELAY,SPST-NO,20SEC,120VAC TIME DELAY RELAY SPST-NO,100SEC,120VAC TIME DELAY RELAY SPST-NO,100SEC,120VAC TIME DELAY RELAY,SPST-NO,20SEC,24VDC PCB PLUGBOARD,28/56 @0.125Â´Â´CARD EDGE BREADBOARD,SELF POWERED,2250 TIE POINTS PROTO-BOARD WORKSTATION BREADBOARD,100 TIE POINTS BREADBOARD BUS STRIP,590 TIE POINTS BREADBOARD,MOLD-IN BUS STRIPS,840 TIE POINTS 350 JUMPER ASSORTMENT KIT TOOLS,CUTTERS,CUTTERS,PUNCH DOWN TOOL PROTOTYPING BREADBOARD KIT W/ POWER SUPPLY TIME DELAY RELAY,SPST-NO,10SEC,12VDC TIME DELAY RELAY,SPST-NO,20SEC,12VDC TIME DELAY RELAY,SPST-NO,100SEC,12VDC TIME DELAY RELAY,SPST-NO,100SEC,12VDC HOSPITAL GRADE OUTLET STRIP,6-OUTLET,1 POWER OUTLET STRIP POWER OUTLET STRIP DIAL CALIPER,6IN ELECTROMECHANICAL HOUR METER Vacuum Cleaner Cleaning Kit CURRENT SENSOR CURRENT SENSOR SOLID STATE FLASHER SPST-NO 60FPM 120VAC SOLID STATE FLASHER SPST-NO 60FPM,24VDC Variable Transformer Variable Transformer ISOLATION TRANSFORMER ENCLOSURE,WALL MOUNT,STEEL,GRAY ENCLOSURE,WALL MOUNT,STEEL,GRAY ENCLOSURE,WALL MOUNT,STEEL,GRAY ENCLOSURE,WALL MOUNT,STEEL,GRAY ENCLOSURE,WALL MOUNT,STEEL,GRAY TIME DELAY RELAY,SPST-NO,10SEC,24VDC ISOLATION TRANSFORMER ONE-REV 150mm Dial Caliper,4-Way Measur MEASURING,RULER,RULER,MEASURING,RULE MEASURING,RULER,RULER,MEASURING,RULE MEASURING,RULER,RULER,MEASURING,RULE MEASURING,RULER,RULER,MEASURING,RULE MEASURING,RULER,RULER,MEASURING,RULE MEASURING,FEELER GAUGE,FEELER GAUGE,M ENCLOSURE,UTILITY,PLASTIC,BLACK ENCLOSURE,UTILITY,PLASTIC,BLACK BALANCE COMPACTE BALANCE COMPACTE OUTIL POUR CONNECTEURS 3M SOCKET FOR CRYSTALS,PRECISION FEUILLE THERMO CONDUCTRICE ADHESIVE TENS STIMULATOR,MINI EMBASE IEC MALE CD PLAYER,PERSONAL CD PLAYER,PERSONAL AUTOMOTIVE BRACKET SUCTION BRACKET SWITCH,TACTILE,SPST-NO,50mA,THD FICHE FEMELLE ETANCHE 9V EVAL BOARD,LM2679 5V,5A REGULATOR KIT MINI-BRUCELLES MT100 FER AIR CHAUD TJ80 PANNE 0.2MM PANNE 0.7MM X 0.5MM PANNE 0.7MM X 2MM PANNE 0.7MM X 6MM PANNE 0.7MM X 8MM PANNE 0.7MM X 10MM FORET DIN338 N HSS 12.5MM TWIST DRILL SET,STEEL CASE DRILL,TUBE/SHEET,HSS,CBN,NO.2 DRILL,TUBE/SHEET,HSS,CBN,NO.3 DRILL,TUBE/SHEET,HSS,CBN,NO.4 DEBURRER,HAND,HSS,DIN335C,90DEG HOLE SAW,HSS,BI-METAL,27MM HOLE SAW,HSS,BI-METAL,32MM HOLE SAW,HSS,BI-METAL,35MM HOLE SAW,HSS,BI-METAL,41MM HOLE SAW,HSS,BI-METAL,51MM HOLE SAW,HSS,BI-METAL,57MM HOLE SAW,HSS,BI-METAL,83MM HOLE SAW,HSS,BI-METAL,92MM HOLE SAW,HSS,BI-METAL,105MM HOLE SAW SET,IN PLASTIC CASE HAMMER DRILL SET,SDS PLUS PUNCH,HOLE,ROUND,16.5MM PUNCH,HOLE,ROUND,20MM PUNCH,HOLE,ROUND,22MM PUNCH,HOLE,ROUND,25.4MM PUNCH,HOLE,ROUND,32MM PUNCH,HOLE,ROUND,32.5MM PUNCH,HOLE,ROUND,35MM PUNCH,HOLE,ROUND,40.5MM PUNCH,HOLE,ROUND,45MM PUNCH,HOLE,ROUND,50.5MM FORET DIN340 N HSS 3.3MM FORET DIN340 N HSS 3.5MM FORET DIN340 N HSS 4.5MM FORET DIN340 N HSS 5MM CONDENSATEUR 16V 100000UF CONDENSATEUR 63V 150000UF CONDENSATEUR 63V 22000UF CONDENSATEUR 63V 47000UF CONDENSATEUR 100V 22000UF FAULT FINDER,FIBRE,VISUAL LAMPE TORCHE LAMPE TORCHE A LED - BLEU CAPACITOR CERAMIC,0.1UF,50V,Z5U,+80,-20%,0805 CAPACITOR CERAMIC,0.1UF,16V,X7R,10%,1206 CAPACITOR CERAMIC 0.01UF,25V,X7R,10%,1206 CAPACITOR CERAMIC,0.1UF,25V,Z5U,20%,1206 CAPACITOR CERAMIC,0.1UF,50V,Z5U,20%,1206 IC Package/Case:9-SIP LED BULB,BA9S,GREEN,BA9S Ceramic Multilayer Capacitor FUSE,CARTRIDGE,1A,6.3 X 32MM FUSE BLOCK,CLASS H FUSE,SCREW MOUNT FUSE,1.25A,250V,TIME DELAY FUSE,40A,600V,FAST ACTING FUSE,60A,600V,FAST ACTING FUSE,5A,250V,ONE TIME FUSE,10A,500V,FAST ACTING CONNECTOR,RCA/PHONO,PLUG,3POS CAT5E RJ45 MODULAR JACK,8POS,1 PORT SCR THYRISTOR,25A,400V,TO-220 TAP,SPECIAL,M20 TAP,SPECIAL,M25 TAP,SPECIAL,M32 SPECIAL TAP SET,ELEKTRO STEP DRILL,HSS,DIN EN60423 NEMA Type 3R,3RX,4,4X,12,13 Stainle SPANNER TOOL CONNECTEUR BNC REAR TWIST 75R STANDARD CONNECTEUR BNC REAR TWIST 75R STANDARD MANCHONS CONNECTEUR REAR TWIST MARRON MANCHONS CONNECTEUR REAR TWIST ORANGE PINCE A SERTIR SPACER INTERRUPTEUR A BASCULE SPST NOIR CAPACITOR ALUM ELEC 100UF,35V,20%,RADIAL CONDENSATEUR 15000UF CONDENSATEUR 150000UF CONDENSATEUR 1500UF CONDENSATEUR 4700UF CONDENSATEUR 6800UF CONDENSATEUR 10000UF CONDENSATEUR 1000UF LENTILLE DE REMPLACEMENT LAMPE FRONTALE - DUO 5 LED AMPOULE HALOGENE POUR DUO 5 LED CLIPS POUR LAMPE FRONTALE PLUG & SOCKET CONN,HEADER,8POS,6.35MM INVERSSEUR FILTRE 0.75KW INVERSSEUR FILTRE 1.5KW INVERSSEUR FILTRE 2.2KW INVERSSEUR NON-FILTRE 0.25KW PANNEAU CONTACT BOP SINAMICS G110 LAMPE ES50 50W 240V GU10 50 LAMPE 50 40W 240V E14 25 LAMPE 95 75W 240V E27 30 TUBE FLUO T5 FHE 35W BLANC CHAUD ALIMENTATION TRIPLE 35V/5A ALIMENTATION PROGRAMMABLE 30V/2A ALIMENTATION 35V 5A MIX MODE+PC GENERATEUR FONCTION 3MHZ+FREQUENCEMETRE GENERATEUR FONCTION 3MHZ+FREQUENC+AM CHARGE ELECTRONIQUE CC 80V,300W GENERATEUR RF 2GHZ BORNE DE PASSAGE 2.5MM INDICATEUR DIN 60A DC TRANSFORMER,AUTO,1500VA,240-120V INDICATEUR DIN 200A DC BIPOLAR TRANSISTOR,PNP,-40V INDICATEUR DIN 400A DC QUICK DISCONNECT CABLE,M12,4 PIN STRAIGHT PHOTOELECTRIC SENSOR,OTICAL TOUCH,NPN PHOTOELECTRIC SENSOR,OTICAL TOUCH,PNP SENSOR CABLE ASSEMBLY PHOTOELECTRIC SENSOR,0M to 5M,NPN/PNP INDICATEUR DIN 600A DC CAPACITOR CERAMIC 0.22UF,100V,X7R,10%,RAD CAPACITOR CERAMIC,10UF,10V,X5R,10%,1210 INDICATEUR DIN 400A DC MOUNTING WING,PP15,PP30 SERIES CONN DIAC,32V,DO-35 BIPOLAR TRANSISTOR,NPN,15V IC,N-CH HIGH SPEED SWITCH,200V,18A IC,N-CH HIGH SPEED SWITCH 6.2A,TO220-3 TRIAC,600V,8A,TO-220 CIRCUIT BREAKER,THERmAL,1P,240V,500mA TERMINAL,FERRULE,0.47IN.,YELLOW CAPACITOR CERAMIC,0.1UF,10V,X7R,10%,1206 PROXIMITY SENSOR INDICATEUR DIN 0-10 Voltage Meter ZENER DIODE,500mW,5.6V,DO-35 INDICATEUR DIN 0-10 Plastic Rack Mount Box N4,12 ECLIPSE JR ENCLOSURE W/PANEL,10X8X6,STEEL,GRAY DIN RAIL RELAY SOCKET CIRCULAR CONN,RCPT,SIZE 14S,4POS,BOX CIRCULAR CONNECTOR,PLUG,18-32S,CABLE CIRCULAR CONNECTOR RCPT,SIZE 10,6POS,CABLE RESISTOR,METAL FILM,1KOHM,600mW,1% CIRCUIT BREAKER,THERMAL MAG,1P,10A WIRE STRIPPERS TERMINAL,RING TONGUE,#6,CRIMP,BLUE RESISTOR,METAL FILM,30 KOHM,1 W,5% COMPTEUR 12VCC Timer Display Panel POTENTIOMETER ROTARY,5KOHM 15%,1W CAPTEUR DE PRESSION 0 - 25 BAR CAPTEUR DE PRESSION 0 - 25 BAR THERMOSTAT MONTAGE EN SAILLIE ATHS-2 TW THERMOSTAT MONTAGE EN SAILLIE ATHS-1A TR JUMO ITRON 08 (HORIZONTAL) ECOTRON M CABLE CONNECTION AVEC FICHE SONDE POUR TUYAUTERIE PAPIER ACCORDEON 5 PIECES TETE DÃ´IMPRESSION 2 PIECES INDICATEUR NUMERIQUE DI32 INDICATEUR NUMERIQUE DI08 INDICATEUR DI ECO TERMINAL,FEMALE DISCONNECT,6.35MM BLUE CONTACT,SOCKET,18-16AWG,CRIMP CASE,TOOL KIT,TOURING COMBINATION SPANNER SET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET COMBINATION SPANNER,RATCHET SPANNER,ADJUSTABLE SPANNER,ADJUSTABLE SPANNER SET,OPEN SPANNER SET,OPEN NUT DRIVER,T HANDLE NUT DRIVER,T HANDLE NUT DRIVER,T HANDLE NUT DRIVER,T HANDLE NUT DRIVER,T HANDLE NUT DRIVER,T HANDLE NUT DRIVER,T HANDLE SOCKET SET,3/8Â´Â´ RATCHET,REVERSIBLE SOCKET SET,1/2Â´Â´ SOCKET DRIVER SET,1/2Â´Â´ SOCKET DRIVER SET,1/2Â´Â´ TORQUE WRENCH,2-25NM TORQUE WRENCH,5-50NM HAMMER,ASH HANDLE HAMMER,ASH HANDLE HAMMER,SURFACE PROTECTIVE HAMMER,SURFACE PROTECTIVE HAMMER,SURFACE PROTECTIVE TIP,FOR HAMMER,PROTECTIVE PULLER,2 LEG PULLER,2 LEG PULLER,3 ARM LAMPE TORCHE - T4 LAMPE TORCHE - T4 LAMPE TORCHE HAND LAMP,RECHARGEABLE CHARGER,C-251HV,UK,3 PIN LAMPE TORCHE - T6 CIRCULAR CONNECTOR,RCPT,SIZE 11,4POS,PANEL TERMINAL,SPADE/FORK,#6,CRIMP,RED HEAT SHRINK TUBING,2.36MM ID,PO,BLK,100FT COMPT. HORAIRE ELECTRO. 230VCA HR76.1 COMPT. HORAIRE ELECTRO. 10-80VCC HR76.1 COMPT. HORAIRE ELECTRO. 10-80VCC HR76.2 CODEUR INCREMENTAL 360PPR - 2400 COMPTEUR ELECTROMECA. 230VCA K07.20 COMPTEUR ELECTROMECA. 12VCC K07.90 COMPTEUR ELECTROMECA. 5VCC K07.92 COMPTEUR ELECTROMECA. 230VCA SK07.1 COMPTEUR ELECTROMECA. 24VCC W15.51 COMPTEUR ELECTROMECA. 230VCA W15.51 COMPTEUR ELECTROMECA. 24VCC AW15.01 COMPTEUR ELECTROMECA. 24VCC K67.20 COMPTEUR ELECTROMECA. 5VCC K47.20 COMPTEUR ELECTROMECA. 12VCC K47.20 COMPTEUR ELECTROMECA. 24VCC K47.20 COMPTEUR ELECTROMECA. 12VCC W17.50 COMPTEUR ELECTROMECA. 230VCA W17.50 COMPTEUR ELECTROMECA. 24VCC BVA15.21 COMPTEUR ELECTROMECA. 230VCA BVA15.21 COMPT. HOR. ELECTROMEC 187-264VCA SHK07. COMPT. HOR. ELECTRO. 187-264VCA HB26.21 COMPT. HOR. ELECTROMEC 10-30VCC HB26.21 COMPT. HORAIRE ELECTROMEC 187-264VCA H57 COMPT. HORAIRE ELECTROMEC 10-30VCC H57 COMPTEUR HORAIRE TOTAL. 187-264VCA HC77 COMPTEUR TOTALISATEUR 10-30VCC CODIX 521 COMPTEUR HORAIRE 10-30VCC CODIX 523 AFFICH. DE TEMP. 10-30VCC CODIX 531 TOTALISATEUR AVEC RAZ 10-30VCC CODIX 540 COMPTEUR DÃ´IMPULS. 90-250VCA CODIX 541 COMPTEUR HORAIRE 90-250VCA CODIX 543 AFFICHEUR DE PROCESS 90-260VCA CODIX 550 CONTROLER DE PROCESS 10-30VCC CODIX553 CONTROLEUR DE TEMP. 90-260VCA CODIX554 COMPTEUR MULTIFONCTIONS 90-260VCA 716 ROUE DE MESURE HYTREL 0.2M ROUE DE MESURE VULCOLAN 0.5M CONNECTEUR 12 POINTS POUR 58-ENC. CABLE 3M - CONNECTEUR 12 POINTS CABLE 5M - CONNECTEUR 12 POINTS JEU DE MONTAGE POUR ENCODEUR HOLLOWSH MONTAGE DE CODEUR FLEXIBLE SOUFFLET DÃ´ACCOUPLEMENT 6MM-4MM SOUFFLET DÃ´ACCOUPLEMENT 6MM-6MM CODEUR INCREMENTAL 500PPR 5802 ENCODEUR INC. A GUIDE FIL 8-30VCC ENCODEUR A GUIDE FIL ANALOGIQUE 4-20MA POTENTIONETRE A GUIDE FIL CHASSIS DE MONTAGE 55MM H57/HC77 CHASSIS DE MONTAGE 72MM H57/HC77 CONTRE-PLAQUE POUR CHASSIS H57/HC77 MORS CONNECTEURS 4/4 MORS CONNECTEURS 6/6 MORS CONNECTEURS 8/8 PINCE A SERTIR ENCLOSURES,ACCESSORIES EMBASE IDC 60 VOIES CAPOT HD.40.STS.1.29.G SCHOOL BALANCE,EMB,5.2K5 CLIP-ON MARKER TOOL,WIC CONTROLE ENTREE NUMERIQUE S7-200 CABLE,MULTIMASTER S7-200,USB,BLACK CABLE,EXPANSION S7-200 LOGO! DM8 24R BALADEUSE 60W (UK) Metal Oxide Varistor (MOV) RESEAU DE SUPPRESSEUR MULTIGUARD IR EMITTER,875NM,4.69MM,TO-18-2,THD GAINE THERMO HIS-A 3/1-NOIR SUPPORT DE LAMPE G24 Q1 SUPPORT DE LAMPE G24 D2 DRIVER MICROPAS COMPACT MOTEUR PAS A PAS 0.9DEG. 2 PHASES MOTEUR PAS A PAS 0.9DEG. 2 PHASES MOTEUR PAS A PAS 1.8 DEG. 2 PHASES ACTIONNEUR LINEAIRE 0.00125MM/PAS MOTEUR PAS A PAS 0.9 DEGREE CONVERTISSEUR RS232/RS485 COFFRET ALU 140X140X90MM COFFRET ALU 160X560X90MM COFFRET ALU 180X180X100MM COFFRET ALU 180X280X100MM COFFRET ALU 100X230X110MM COFFRET ALU 230X400X110MM COFFRET ALU 310X600X110MM COFFRET POLY. 75X80X75MM COFFRET POLY. 75X160X75MM COFFRET POLY. 160X160X90MM COFFRET ELECTR. 105X185X87MM DEMO/KIT DÃ´EVALUATION POUR ATMEGA169 CODEUR ABSOLU DIODE,STANDARD,15A,200V SPARE BLADE SET TRANSISTOR,BIPOLAR,PNP,300V,500mA,TO-202-3 FUSE CLIP,5MM,PCB MOUNT COMMUTATEUR MICRO FSM2J L=4.3MM PANNEAU PRE PERCE BNC FIL H05Z-K 0.5 NOIR 100M FIL H05Z-K 0.5 ROUGE 100M FIL H05Z-K 0.75 BLEU 100M FIL H05Z-K 1.0 NOIR 100M FIL H05Z-K 1.0 BLEU 100M FIL H05Z-K 1.0 ROUGE 100M CONDUIT,SPLIT,23 CONDUIT,LCC-2 /10,METAL CONDUIT,LCC-2 /16,METAL CONDUIT,LGF-2-M,20X1.5/1 CONDUIT,M20,BLACK FORET TUNGSTENE 1.3MM ARBRE 6.3MM TIGE RONDE ARBRE 9.5MM TIGE HEXA RF TRANSISTOR,PNP,-600mV,1.1GHZ TERMINAL,RING TONGUE,#6,CRIMP,RED Metal Connector Backshell CAPACITOR CERAMIC 0.1UF,100V,X7R,10%,1206 FUSIBLE THERMIQUE 72DEG ADAPTATEUR 18P DIP POUR MPLAB ICD2 CONVERTISSEUR DC/DC CMS FRONT RAISED BEZEL SWIFTY SET PLAYER,PERSONAL CD KIT FER A SOUDER A GAZ Â´WP60K TERMINAL,PARALLEL SPLICE,CRIMP CIRCULAR STRAIN RELIEF,SIZE 15 BIPOLAR TRANSISTOR,NPN,40V PCB,Pad/Hole 2 sides (PTH) DIN RAIL ADAPTER RESISTOR,CURRENT SENSE,0.1 OHM,15W,1% SENSOR REFLECTOR SENSOR CABLE ASSEMBLY PHOTOELECTRIC SENSOR,0MM to 380MM,NPN / PNP PHOTOELECTRIC SENSOR N CH MOSFET,400V,14A,TO-204AA END BRACKET,TS 35 TERMINAL RAIL POWER RELAY,DPDT,120VAC,10A,PLUG IN POWER RELAY,DPDT,12VDC,15A,PLUG IN CHIP INDUCTOR,22NH,450MA 10% 2GHZ LED,RED,T-1 3/4 (5MM),35CD,616NM FUSE,40A,600V,TIME DELAY Inductive Proximity Sensors INDUCTIVE PROXIMITY SENSORS ENCLOSURE,BOX,ALUMINIUM ENCLOSURE,BOX,ALUMINIUM ENCLOSURE,BOX,ALUMINIUM CABLE GLAND (CLAMP) Leaded Process Compatible:No D SUB CONTACT,SOCKET,26-22AWG,CRIMP Writing for Science and Engineering: Pap Ceramic Disc Capacitor MICRO SWITCH,HINGE LEVER,SPDT 11A 250V MICRO SWITCH,ROLLER LEVER SPDT 11A 250V Switch Logic IC Logic Type:FET Bus Switc PLUG & SOCKET CONNECTOR,PLUG,12POS,3MM COUVERCLE ETANCHE 48X96MM COUVERCLE ETANCHE 72X72MM COUVERCLE ETANCHE 96X96MM FUSE,20A,600V,TIME DELAY ROUND KNURLED KNOB W/ ARROW IND,6.35MM IC TEMPORISATEUR TEMPORISATEUR TERMINAL,RING TONGUE,#10,CRIMP,RED DARLINGTON TRANSISTOR,PNP,-80V,TO-3 ZENER DIODE,500mW,2.4V,AXIAL FUSE,THERMAL,117Â°C,15A,277V WIRE-BOARD CONN,RECEPTACLE,5POS,2MM Connector Number of Contacts:16 IC,SILICON UNILATERAL SW,175mA,TO98-3 FAST DIODE,80A,400V,POWERTAB WALL BRACKET FOR FIRST AID KT CAPACITOR TANT,100UF,10V,RADIAL 10% CAPACITOR TANT,2.2UF,25V,RADIAL 10% CAPACITOR TANT,68UF,25V,RADIAL 20% C60N Circuit Breaker,C Curve 1 Pole Box CIRCUIT BREAKER,THERMAL MAG,1P,1A CIRCUIT BREAKER,THERMAL MAG,1P,4A CIRCUIT BREAKER,THERMAL MAG,1P,6A CIRCUIT BREAKER,THERMAL MAG,1P,8A CIRCUIT BREAKER,THERMAL MAG,2P,10A CIRCUIT BREAKER,THERMAL MAG,2P,20A CIRCUIT BREAKER,THERMAL MAG,2P,30A BATTERY STRAP,9V,WIRE LEAD Metal Film Resistor IC,LINEAR VOLT REG,9V,3-TO-220 IC,P-CH HIGH SPEED SWITCH,19A,TO220-3 TVS DIODE,1.5KW,15.3V SCHOTTKY RECTIFIER,10A,45V TO-220 SCHOTTKY RECTIFIER,30A,45V TO-220 STANDARD DIODE,30A,45V,TO-218 SILICON BILATERAL SWITCH (SBS) CAPTIVE PANEL SCREW BANANA JACK,SOLDER,RED SWITCH,PUSHBUTTON,DPDT-DB,10A,115V LAMP,FLUORESCENT,G5,4W Standard D-Subminiature Connector TERMINAL,MALE DISCONNECT,0.25IN,THD PLATEAU STOCKAGE 500X94X80 PQ10 ZENER DIODE,2.3W,75V,DO-219AB PLATEAU DÃ´ETAGERE 188X115 PQ20 TVS Diode TVS Diode TVS DIODE,200W,15V,DO219AB TVS DIODE,200W,48V,DO219AB Circular Connector MIL SPEC:MIL-C-5015 CIRCULAR CONNECTOR BODY MATERIAL:ALUMINU CIRCULAR CONNECTOR BODY MATERIAL:ALUMINU CIRCUIT BREAKER,THERMAL,1P,240V,5A CIRCUIT BREAKER,THERMAL,1P,240V,3A CIRCUIT BREAKER,THERMAL,1P,240V,4A Plug-In Relay Plug-In Relay Plug-In Relay Plug In Relay Switch Function:3PDT CIRCULAR CONNECTOR BODY MATERIAL:ALUMINU CIRCULAR CONNECTOR BODY MATERIAL:ALUMINU Circular Connector MIL SPEC:MIL-C-5015 A DIODE,PHOTO,900NM,65Â° FILTRE PRINCIPAL LED,ORANGE,T-1 (3MM),4MCD,611NM ZENER DIODE,500mW,6.2V,SOD-80 ZENER DIODE,500mW,6.8V,SOD-80 ZENER DIODE,1.3W,47V,DO-41 ZENER DIODE,500mW,75V,DO-35 OPTICAL ENCODER Ceramic Multilayer Capacitor Ceramic Multilayer Capacitor CAPACITOR CERAMIC 0.47UF,100V,X7R,10%,RAD RELAY SOCKET TERMINAL,FERRULE,0.03IN CIRCULAR CONNECTOR,PLUG,3POS,CABLE 110 PUNCHDOWN STRIPPER Micropower ultra low dropout fixed volta CAPACITOR CERAMIC,0.1UF,25V,Z5U,+80,-20%,0805 CAPACITOR CERAMIC 0.01UF,16V,X7R,10%,1206 Resettable Fuse TERMINAL,BUTT SPLICE SMALL OuTLINE OPTOISOLATOR,TRANSISTOR O 16 bit bidirectional registered transcei LED,2.4MM,RED / GREEN,PLCC-2 COMMUTATEUR A BASCULE DPST I/O COMMUTATEUR INDUCTOR,SHIELDED,330UH,380MA,SMD INDUCTOR,SHIELDED,100UH,900MA,SMD INDUCTOR,SHIELDED,1MH,320MA,SMD SuRFACEMOuNT LED,660 NM wAvELENGTH,51 LED CABLE ASSEMBLY IC,INSTRUMENT AMP,550KHZ,90DB,SOIC-8 IC,INSTRUMENT AMP,200KHZ,90DB,DIP-16 Switch Actuator BIPOLAR TRANSISTOR,PNP,-100V,TO-220 PIN HEADER,EUROSTYLE,4POS,5MM CAPACITOR ALUM ELEC 2200UF 250V 20%,SNAP-IN CAPACITOR ALUM ELEC 2700UF 200V 20%,SNAP-IN TERMINAL,FEMALE DISCONNECT,6.35MM,RED IC,ADC,12BIT,200KSPS,QSOP-16 IC,ADC,16BIT,100KHZ,MSOP-8 IC,DAC,12BIT,95KSPS,SOT-23-8 IC,DAC,12BIT,89KSPS,SOIC-16 OPTOCOUPLER,PHOTOTRIAC,3750VRMS OPTOCOUPLER,PHOTOTRIAC,3750VRMS IC,SM OP-AMP DUAL DIFET PRECISION IC,OP-AMP,430KHZ,0.16V/Âµs,SOIC-8 OPERATIONAL AMPLIFIER (OP-AMP) IC Flip Flop Logic IC Logic Type:Latch Transceiver Logic IC Logic Type:Bus Tran Flip Flop Logic IC Package/Case:14-TSSOP IC,RS-485 BUS TRANSCEIVER,5.25V,SOIC8 COMMUTATEUR DPST OPTOCOUPLER,PHOTOTRANSISTOR,5000VRMS OPTOCOuPLER OPTOCOuPLER OuTPuT TyPE:TRAN COMMUTATEUR DPST OPTOCOUPLER,PHOTOTRANSISTOR,3750VRMS IC,OP-AMP,1.7MHZ,3.6V/ us,DIP-8 IC,OP-AMP,1.7MHZ,3.6V/ us,SOIC-8 IC,MICROPOWER COMP,DUAL,1.1 uS,SO

RESISTOR,METAL FILM,470 OHM,1 W,5% RESISTOR,METAL FILM,5.1 KOHM,1 W,5% RESISTOR,METAL FILM,6.2 KOHM,1 W,5% RESISTOR,METAL FILM,6.8 OHM,1 W,5% RESISTOR,METAL FILM,620 OHM,1 W,5% RESISTOR,METAL FILM,68 OHM,1 W,5% RESISTOR,METAL FILM,8.2 KOHM,1 W,5% RESISTOR,METAL FILM,1.2 KOHM,2 W,5% RESISTOR,METAL FILM,1 MOHM,2 W,5% RESISTOR,METAL FILM,1.8 OHM,2 W,5% RESISTOR,METAL FILM,150 KOHM,2 W,5% RESISTOR,METAL FILM,150 OHM,2 W,5% RESISTOR,METAL FILM,2 KOHM,2 W,5% RESISTOR,METAL FILM,22 KOHM,2 W,5% RESISTOR,METAL FILM,22 OHM,2 W,5% RESISTOR,METAL FILM,33 KOHM,2 W,5% RESISTOR,METAL FILM,33 OHM,2 W,5% RESISTOR,METAL FILM,330 OHM,2 W,5% RESISTOR,METAL FILM,4.7 KOHM,2 W,5% RESISTOR,METAL FILM,47 OHM,2 W,5% RESISTOR,METAL FILM,470 OHM,2 W,5% RESISTOR,METAL FILM,5.1 KOHM,2 W,5% RESISTOR,METAL FILM,5.6 OHM,2 W,5% RESISTOR,METAL FILM,68 KOHM,2 W,5% RESISTOR,METAL FILM,1.5KOHM,400mW,1% RESISTOR,METAL FILM,10 OHM,400mW,1% RESISTOR,METAL FILM,2.21KOHM,400mW,1% RESISTOR,METAL FILM,2MOHM,400mW,1% RESISTOR,METAL FILM,20KOHM,400mW,1% RESISTOR,METAL FILM,200KOHM,400mW,1% RESISTOR,METAL FILM,1 KOHM,3 W,5% RESISTOR,METAL FILM,10 KOHM,3 W,5% RESISTOR,METAL FILM,10 OHM,3 W,5% RESISTOR,METAL FILM,100 OHM,3 W,5% RESISTOR,METAL FILM,12 KOHM,3 W,5% RESISTOR,METAL FILM,180 OHM,3 W,5% RESISTOR,METAL FILM,22 KOHM,3 W,5% RESISTOR,METAL FILM,220 OHM,3 W,5% RESISTOR,METAL FILM,30 KOHM,3 W,5% RESISTOR,METAL FILM,47 KOHM,3 W,5% RESISTOR,METAL FILM,510 KOHM,3 W,5% RESISTOR,METAL FILM,68 OHM,3 W,5% RESISTOR,METAL FILM,1.1KOHM,400mW,1% RESISTOR,METAL FILM,1.82KOHM,400mW,1% RESISTOR,METAL FILM,1.5MOHM,400mW,1% RESISTOR,METAL FILM,10 OHM,400mW,1% RESISTOR,METAL FILM,110KOHM,400mW,1% RESISTOR,METAL FILM,121 OHM,400mW,1% RESISTOR,METAL FILM,140 OHM,400mW,1% RESISTOR,METAL FILM,15KOHM,400mW,1% RESISTOR,METAL FILM,150KOHM,400mW,1% RESISTOR,METAL FILM,16.2KOHM,400mW,1% RESISTOR,METAL FILM,2.43KOHM,400mW,1% RESISTOR,METAL FILM,2.49KOHM,400mW,1% RESISTOR,METAL FILM,2.74KOHM,400mW,1% RESISTOR,METAL FILM,2MOHM,400mW,1% RESISTOR,METAL FILM,20KOHM,400mW,1% RESISTOR,METAL FILM,200 OHM,400mW,1% RESISTOR,METAL FILM,249 OHM,400mW,1% RESISTOR,METAL FILM,27.4KOHM,400mW,1% RESISTOR,METAL FILM,3.01KOHM,400mW,1% RESISTOR,METAL FILM,301 OHM,400mW,1% RESISTOR,METAL FILM,316OHM,400mW,1% RESISTOR,METAL FILM,39.2KOHM,400mW,1% RESISTOR,METAL FILM,4.75KOHM,400mW,1% RESISTOR,METAL FILM,47.5KOHM,400mW,1% RESISTOR,METAL FILM,475 OHM,400mW,1% RESISTOR,METAL FILM,49.9KOHM,400mW,1% RESISTOR,METAL FILM,499 OHM,400mW,1% RESISTOR,METAL FILM,51.1KOHM,400mW,1% RESISTOR,METAL FILM,590 OHM,400mW,1% RESISTOR,METAL FILM,6.04KOHM,400mW,1% RESISTOR,METAL FILM,6.81KOHM,400mW,1% RESISTOR,METAL FILM,60.4 OHM,400mW,1% RESISTOR,METAL FILM,604 OHM,400mW,1% RESISTOR,METAL FILM,7.5KOHM,400mW,1% RESISTOR,METAL FILM,8.06KOHM,400mW,1% RESISTOR,METAL FILM,8.25KOHM,400mW,1% RESISTOR,METAL FILM,9.09KOHM,400mW,1% CAP,ROUND,RED FEET (BUMPERS) TRANSDUCER,PIEZO,2.9KHZ,95DBA,28VDC PANEL MOUNT INDICATOR,LED,16MM,GREEN,12V PANEL MOUNT INDICATOR,LED,8MM,RED,130V PANEL MOUNT INDICATOR,LED,8MM,GREEN,130V CAPACITOR CERAMIC 1000PF 100V,X7R,10%,AXIAL CAPACITOR CERAMIC 470PF 50V,C0G,5%,AXIAL CAPACITOR CERAMIC 0.047UF 50V,X7R,10%,AXIAL CAPACITOR CERAMIC 10PF 50V,C0G/NP0,5%,RAD CAPACITOR CERAMIC 100PF 100V,C0G,5%,R CAPACITOR CERAMIC 1000PF 50V,C0G,5%,R CAPACITOR CERAMIC 1000PF,50V,X7R,10%,RAD CAPACITOR CERAMIC 0.01UF,50V,X7R,10%,RAD CAPACITOR CERAMIC 0.1UF,100V,X7R,10%,RAD CAPACITOR CERAMIC 15PF 50V,C0G/NP0,5%,RAD CAPACITOR CERAMIC 18PF 50V,C0G/NP0,5%,RAD CAPACITOR CERAMIC 180PF 50V,C0G,5%,RAD CAPACITOR CERAMIC 22PF 50V,C0G/NP0,5%,RAD CAPACITOR CERAMIC 2200PF,50V,X7R,10%,RAD CAPACITOR CERAMIC 0.022UF,50V,X7R,10%,RAD CAPACITOR CERAMIC 270PF 50V,C0G,5%,RAD CAPACITOR CERAMIC 470PF 50V,C0G,5%,RAD CAPACITOR CERAMIC 4700PF,50V,X7R,10%,RAD CAPACITOR ALUM ELEC 330UF,16V,20%,AXIAL CAPACITOR ALUM ELEC 15UF,63V,20%,AXIAL CAPACITOR ALUM ELEC 2.2UF,63V,20%,AXIAL CAPACITOR ALUM ELEC 0.47UF,63V,20%,AX CAPACITOR ALUM ELEC 100UF,100V,20%,AXIAL CAPACITOR ALUM ELEC 68UF,63V,20%,AXIAL CAPACITOR ALUM ELEC 1UF 35V 20%,AXIAL CAPACITOR ALUM ELEC 10UF,25V,20%,AXIAL CAPACITOR ALUM ELEC 100UF,40V,20%,AXIAL CAPACITOR ALUM ELEC 10UF,100V,20%,AXIAL SCOTCHCODE PRINTED WIRE MARKER BK 0.22Â´Â´Â´Â´W RESISTOR,THIN FILM,47KOHM,125mW,0.1% TOOLS,CUTTERS,CABLE,CABLE CUTTER 3677 TAPE,INSULATION,SILVER,48MMX60FT SWITCH,PUSHBUTTON,SPST,3A,250V TERMINAL,WIRE TAP/SPLICE,CRIMP,BLUE TERMINAL,BUTT SPLICE,CRIMP,RED TERMINAL,FEMALE DISCONNECT,0.187IN RED SWITCH,ROCKER,SPST,10A,250V,BLACK CAPACITOR PP FILM 3.3UF,630V,20%,RADIAL RESISTOR,WIREWOUND,5.1 OHM,5W,5% SWITCH,PUSHBUTTON,SPST-NO,8A,250V SWITCH,TOGGLE,SPDT,6A,250V SWITCH,TOGGLE,SPDT,6A,250V SWITCH,TOGGLE,DPDT,6A,250V SWITCH,PUSHBUTTON,SPDT-1NO/1NC 1A 250V SEALTITE 59/6 RATCHETED COMPRESSION CRIMPER TOOL RESISTOR,THICK FILM,6.8 OHM,125mW,1% CAPACITOR ALUM ELEC 100UF,25V,20%,AXIAL PROXIMITY SENSOR Contact FUSE BLOCK,10.3 X 38MM ENCLOSURE,UTILITY,PLASTIC,BLACK ENCLOSURE,UTILITY,PLASTIC,BLACK Ceramic Multilayer Capacitor SOLUTION DE STOCKAGE POUR PH-METRE 230ML TEMPERATURE STRIP,160Â°C/199Â°C PROBE,ISOLATED SCOPE THYRISTOR MODULE,55A,1.2KV IC,PWM CONTROLLER,35V,18-DIP PORTE FUSIBLE SERIE NH THYRISTOR MODULE,90A,1.2KV FUSIBLE 80A BOBINE DE MONTAGE MALE/MALE FUSIBLE 100A BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE MALE/MALE BOBINE DE MONTAGE FEMELLE/FEMELLE BOBINE DE MONTAGE FEMELLE/FEMELLE BOBINE DE MONTAGE FEMELLE/FEMELLE BOBINE DE MONTAGE FEMELLE/FEMELLE MOUNT,BELL,FAILSAFE MOUNT,BELL,SLOTTED BOBINE DE MONTAGE MALE (1 COTE) BOBINE DE MONTAGE MALE (1 COTE) BOBINE DE MONTAGE MALE (1 COTE) BOBINE DE MONTAGE FEMELLE (1 COTE) PIED. FER ARTICULE M8X50 PIED. POLYAMIDE METAL MOUNT PEDESTAL 85X25 TERMINAL FEMALE DISCONNECT 0.25IN YELLOW TERMINAL,RING TONGUE,#4,CRIMP THERMOMETRE NUMERIQUE THERMOMETER,TYPE T TEMPERATURE DATA LOGGER KIT TEMPERATURE DATA LOGGER,INT SENSOR MANOMETER,0-130MBAR,DIFF TROUSSE A OUTILS FORET TUNGSTENE 1.2MM FORET TUNGSTENE 1.6MM FORET TUNGSTENE 3.175MM BATTERY PACK,9.6V,1.4AH FER A SOUDER 12W 240V FER A SOUDER 15W 240V TIP,MICRO POINT,STT,0.25MM,PK3 CHISEL TIP POINT,STT,2.4MM,PK3 CHISEL TIP POINT,STT,3.5MM,PK3 FICHE PHONO VERT FICHE PHONO BLEU EMBASE CHASSIS JAUNE EMBASE CHASSIS VERT RUBBER BUNG,FEMALE,XLR ADAPTOR,XLR PLUG TO XLR RCPT ENREGISTREUR DE DONNEES STROBOSCOPE PICSTART PLUS,FLASH UPGRADE MODULE CIRCULAR CONN,RCPT,SIZE 16,3POS,BOX CIRCULAR CONN,RCPT,SIZE 16,3POS,BOX MODULE DÃ´EVALUATION ADS8322 CONVERTISSEUR N/A 10 BITS QUADRUPLE CMS FUSE,63A,690V,STUD MOUNT,FAST ACTING EMBOUT TORX INVIOLABLE T30 FIBRE POLYMERE 3MM BARE 5 MTR CLEF REGLABLE 254MM FLASQUE DÃ´EXTREMITE ORANGE SEPARATEUR POUR BORNE 6MM FASQUE DÃ´EXTREMITE 1.5MM ZELIO 24VDC. 8 DI/4 RO ZELIO 100-240VAC 6 DI/4 RO ZELIO 100-240VAC 8 DI/4 RO ZELIO 24VDC 12 DI/8 RO ZELIO 24VDC 12 DI/8 RO ZELIO 24VDC. 16 DI/10 RO ZELIO 24V. 8 DI/6 RO DEMARREUR ZELIO LOGIC DEMARREUR ZELIO LOGIC DEMARREUR ZELIO LOGIC DEMARREUR ZELIO LOGIC DEMARREUR ZELIO LOGIC CD,ZELIO PC PROGRAMMING CABLE ASSEMBLY,ZELIO LOGIC,GREY,3M CARTOUCHE EEPROM ZELIO PILE ZINC CHLORIDE C (PQ2) PILE ZINC CHLORIDE C (PQ24) LCR-METRE 0.2% MULTIMETER,DIGITAL,LCR,0.1% MULTIMETRE NUMERIQUE CARTOUCHE ENCRE COMPAT. T007401 CARTOUCHE ENCRE COMPAT. T009401 CARTOUCHE ENCRE COMP. EPSON NOIRE CARTOUCHE ENCRE COMP. EPSON 3 COULEURS RF METER,BROADBAND FIL DÃ´EQUIPEMENT FLEXLITE 0.25MM ROUGE FIL DÃ´EQUIPEMENT FLEXLITE 0.25MM BLANC FIL DÃ´EQUIPEMENT FLEXLITE 0.35MM VERT FIL DÃ´EQUIPEMENT FLEXLITE 0.35MM BLANC FIL DÃ´EQUIPEMENT FLEXLITE 0.5MM VERT FIL DÃ´EQUIPEMENT FLEXLITE 0.5MM BLANC FIL DÃ´EQUIPEMENT FLEXLITE 0.75MM ROUGE FIL DÃ´EQUIPEMENT FLEXLITE 0.75MM VERT FIL DÃ´EQUIPEMENT FLEXLITE 1.0MM NOIR FIL DÃ´EQUIPEMENT FLEXLITE 1.0MM ROUGE FIL DÃ´EQUIPEMENT FLEXLITE 1.0MM VERT FIL DÃ´EQUIPEMENT FLEXLITE 1.0MM BLANC FIL DÃ´EQUIPEMENT FLEXLITE 1.5MM ROUGE FIL DÃ´EQUIPEMENT FLEXLITE 1.5MM VERT FIL DÃ´EQUIPEMENT FLEXLITE 1.5MM BLANC WIRE,24AWG GREY WIRE,22AWG YELL WIRE,22AWG GRN WIRE,22AWG GREY WIRE,20AWG GRN WIRE,20AWG GREY WIRE,18AWG YELL WIRE,18AWG GRN SEPARATEUR BORNE DE PUISSANCE 120MM CAPOT COMPLET BORNE DE PUISSANCE 300MM SEPARATEUR BORNE DE PUISSANCE 300MM CAPTEUR A EFFET HALL PRINTER,LABEL LABEL PRINTER KIT CARTRIDGE,LABEL,YELLOW PAT TESTER KIT OPTOSWITCH UNSHLD MULTIPR CABLE 4PR 1000FT 300V RED UNSHLD MULTIPR CABLE 1PR 500FT 300V CHR COAXIAL CABLE,RG-58A/U,500FT,BLACK COAXIAL CABLE,RG-58A/U,500FT,BLACK COAXIAL CABLE,RG-58C/U,500FT,BLACK UNSHLD MULTICOND CABLE 2COND 22AWG 1000FT UNSHLD MULTIPR CABLE 1PR 500FT 300V CHR UNSHLD MULTICOND CABLE 4COND 18AWG 500FT FUSE,CARTRIDGE,2A,5X20MM,TIME DELAY SCOTCHMATE RECLOSABLE FASTENER,BLK,1Â´Â´W ENCLOSURE,UTILITY,PLASTIC,GRAY FUSE HOLDER CAP SOLENOID LAMINATED FRAME PULL CONTINUOUS CABLE,COAXIAL,RG58,19AWG,50 OHM,500FT,BLK TAPE,SPLICING,RUBBER,BLACK 1.5INX30FT CONN,TERMINAL,BUTT SPLICE,IDC,YELLOW TERMINAL BLOCK,DIN RAIL,2POS,28-12AWG CHARGEUR 45W 28V CHARGEUR 45W 14V CHARGEUR 75W 28V CLEANING SOLUTION,ELECTRODE ANALYSER,COMBUSTION COMBUSTION ANALYSER KIT DETECTOR,LEAK,REFRIGERANT HYGROMETER,PEN TYPE PINCE DE TERRE SOURCE,V+I CALIBRATOR,VOLTAGE & CURRENT CALIBRATOR,LOOP,V-I SIMULATOR,PT100 RESISTANCE BOX,PRECISION IC,OP-AMP,8MHZ,2.8V/ us,DIP-8 SOCKET,NTE5,(5A) TACHOMETER,LASER TACHOMETER,MECHANICAL FER A SOUDER 15W 230V PRISE UK FER A SOUDER 25W 230V PRISE UK ZENER DIODE,1W,6V,AXIAL BATTERIE POUR TEL SANS FIL 550MAH BATTERIE POUR APP. PHOTO NUM. FUJI NP60 VIBRATION METER,200G,2000MM/SEC SIMULATOR,LOOP CALIBRATOR,VIR UNSHLD MULTICOND CABLE,6COND,22AWG/18AWG,305M,300V MICRO SW,ROLLER PLUNGER,SPDT,15A 250V POWER RELAY,DPDT,115VAC,3A,PLUG IN CATEGORY 5E CABLE ASSEMBLY POWER RELAY,4PDT,120VAC,5A,PLUG IN DIODE 12A 1200V DIODE 25A 600V CAPACITOR PP FILM 15UF,660V,6%,QC POWER RELAY,DPDT,48VDC,15A,PLUG IN INDUCTANCE 6UH SOUDURE SANS PLOMB ROSIN 0.9MM 500G SOUDURE SANS PLOMB NO-CLEAN 0.5MM 250G SOUDURE SANS PLOMB NO-CLEAN 0.7MM 250G SOUDURE SANS PLOMB NO-CLEAN 0.9MM 250G SOUDURE SANS PLOMB NO-CLEAN 1.2MM 250G SOUDURE SANS PLOMB NO-CLEAN 0.7MM 500G SOUDURE SANS PLOMB NO-CLEAN 0.9MM 500G SOUDURE SANS PLOMB NO-CLEAN 1.2MM 500G AMPOULE POUR LAMPE TORCHE ANTIDEFLAGRANT GENER. DE FONCTION DE TABLE 3MHZ EU/UK Multiconductor Control & Instrumentation SURGE PROTECTION & FILTER,19IN PLUG,QUICK FIT,3A,WHITE PLUG,QUICK FIT,13A,WHITE PLUG,QUICK FIT,3A,BLACK PLUG,QUICK FIT,5A,BLACK EXTENSION LEAD,4WAY,BLACK,5M EXTENSION LEAD,SWITCH,4WAY SOCKET,SWITCHED,8WAY,3M SOCKET,SWITCHED,8WAY,3M BOX,DRYLINER,1GANG SOCKET,2GANG JUNCTION BOX JUNCTION BOX JUNCTION BOX JUNCTION BOX JUNCTION BOX JUNCTION BOX CONNECTION UNIT,FUSED OUTLET BOX,STEEL OUTLET BOX,STEEL BACK BOX,SURFACE MOUNT SOCKET SWITCHED,METALCLAD,2GANG SOCKET,2GANG,2 POLE SWITCH,2 POLE,20A,METAL CLAD BLANK PLATE,1GANG,METALCLAD FUSED CONNECTION UNIT,METALCLAD FUSED CONNECTION UNIT,METALCLAD SURGE PROTECTOR,6GANG SUB-D FEMELLE CI 15V FILETAGE/INSERT SUB-D FEMELLE CI 25V FILETAGE/INSERT INTERRUPTEUR A LEVIER 2P ON-ON INDUCTANCE 50UH INDUCTANCE 30UH BATTERIE POUR APPLE POWERBOOK G3 PORTABLE LIGHT,RL100,18W BATTERIE EUROPA+GEL 12V 26AH BATTERIE EUROPA+GEL 12V 55AH ABSOLUTE/MECHANICAL ENCODER UNSEALED OI-PB SWITCH PUSHBUTTON SWITCH LIMIT SWITCH,ROLLER LEVER,SPDT-1NO/1NC MICRO SWITCH,STR LEVER,SPDT 100mA 125V MICRO SWITCH,PIN PLUNGER,SPDT 11A 277V MICRO SWITCH,LEAF LEVER,SPDT,15A 277V SWITCH,TOGGLE,DPDT,20A,277V SWITCH,TOGGLE,4PDT,20A,277V SWITCH,TOGGLE,4PDT,18A,277V MICRO SWITCH,ROLLER LEVER SPDT 15A 277V BASIC SWITCH,STRAIGHT LEVER,SPDT,15A,600V LIMIT SWITCH,TOP PLUNGER,SPDT-1NO/1NC SWITCH,TOGGLE,DPDT,5A,125V MICRO SWITCH,PIN PLUNGER,SPDT,3A 250V FERRITE CORE,CYLINDRICAL LIMIT SWITCH,TOP PLUNGER,SPDT-1NO/1NC RESISTOR,HV THICK FILM,50MOHM 500mW,1 AML LED FERRITE CORE,CYLINDRICAL,68OHM/100MHZ,300MHZ PACK BATTERIE 4.8V PILE ALCALINE C (PQ200) PILE ALCALINE PP3 (PQ200) N CHANNEL JFET,-50V,TO-92 CABLE,CAT5 ETHERNET 100M SOUDURE SANS PLOMB HI-ACT 0.5MM 250G SOUDURE SANS PLOMB HI-ACT 0.7MM 250G SOUDURE SANS PLOMB HI-ACT 0.9MM 250G SOUDURE SANS PLOMB HI-ACT 1.2MM 250G SOUDURE SANS PLOMB HI-ACT 0.7MM 500G SOUDURE SANS PLOMB HI-ACT 0.9MM 500G SOUDURE SANS PLOMB HI-ACT 1.2MM 500G SOUDURE SANS PLOMB MIN-ACT 0.5MM 250G SOUDURE SANS PLOMB MIN-ACT 0.9MM 250G SOUDURE SANS PLOMB MIN-ACT 1.2MM 500G SOUDURE SANS PLOMB MIN-ACT 0.7MM 250G SOUDURE SANS PLOMB MIN-ACT 0.9MM 500G RF TRANSISTOR,PNP,-3V,25MHZ CORDON PERITEL HQ 2M CORDON PERITEL HQ 3M CORDON PERITEL HQ 5M CORDON PERITEL HQ 10M HAUT-PARLEUR 2 INCH MINI MODULE TX FM 433MHZ MODULE RX FM 433MHZ MODULE TX FM 860-920MHZ MODULE RX FM 860-920MHZ MODULE TX 433MHZ MODULE TX 868MHZ PANNEAU 19Â´Â´ 1U PANNEAU 19Â´Â´ 2U CORDON XLR NOIR CORDON XLR MICROPHONE CORDON XLR MICROPHONE CORDON XLR MICROPHONE CORDON JACK HAUT-PARLEUR CORDON SPEAKON 2P 10M BUSE DROITE TJ80 BUSE COURBEE TJ80 BUSE PLATE TJ80 BANANA PLUG,5A,SCREW,RED CONNECTEUR 2MM 20P CONNECTEUR 2MM 14P TRIMMER CMS 1K TRIMMER CMS 1K TRIMMER CMS 5K TRIMMER CMS 10K TRIMMER CMS 50K TRIMMER CMS 100K TRIMMER CMS 1K TRIMMER CMS 2K TRIMMER CMS 10K TRIMMER CMS 20K TRIMMER CMS 50K TRIMMER CMS 100K TRIMMER CMS 1K TRIMMER CMS 10K TRIMMER CMS 100K RELAIS 12VDC RELAIS 24VDC CAPTEUR DE DEBIT D AIR COMPTEUR TOTALISATEUR COMPTEUR TOTALISATEUR CORDON NOIR BRACELET ANTISTATIQUE MICRORUPTEUR ROTATIF COMMUTATEUR ANTIVANDALE COMMUTATEUR POUSSOIR COMMUTATEUR POUSSOIR PLAQUETTE TO92 PLAQUETTE TO18 KIT DÃ´ISOLATION RUBAN ADHESIF SCOTCH MAGIC 25MMX66M DISPLAY MOUNT,3M,400ML SPXO,100MHZ,SMD NOTE BOOK,RULED,WIREBOUND,A4 NOTE BOOK,RU+INDEX,W/BOUND,A6 NOTE BOOK,RU+PERF,WIREBOUND,A4 NOTE BOOK,RU+PERF,WIREBOUND,A5 NOTE BOOK,RULED,CASEBOUND,A5 NOTE BOOK,PLAIN,CASEBOUND,A7 TERMINAL,COMPRESSION LUG,5/16,CRIMP,8AWG TERMINAL,RING TONGUE,#6,CRIMP CABLE TIES,4IN L,NYLON,STRGTH 18LB,NAT PROXIMITY SENSOR MERCURY DISP CONTACTOR DPST-NO 24VDC 20A TERMINAL,RING TONGUE,1/4IN,CRIMP,RED GAS DISCHARGE TUBE,260V,2 ELECT GAS DISCHARGE TUBE,300V,2 ELECT SENSOR MODULE AMPLIFIER POLYCARBONATE AXXIS 5X1250X610 IC,CURRENT MODE PWM,10V,8-SOIC TAPE,18MM,BLACK/YELLOW,S/ADH TAPE,6MM,BLACK/WHITE,FLEXIBLE TAPE,9MM,BLACK/WHITE,FLEXIBLE TAPE,18MM,BLACK/WHITE,FLEXIBLE TAPE,12MM,BLACK/YELLOW,FLEXIBLE TAPE,24MM,BLACK/YELLOW,FLEXIBLE PINCES CROCODILES POUR ATLAS LCR40 ZENER DIODE,3W,3.3V,DO-214AC ZENER DIODE,3W,5.1V,DO-214AC BATTERIE 12V 24AH BATTERIE 12V 38AH PRINTASOLVE 400ML AEROSOL SOLVANT ELECTRONIQUE NET.200ML RESINE DÃ´ENCAPSULATION POLYURETHAN 250G EMBASE SIL COUDEE DOREE 32 VOIES WIPES,PRINTCLENE,PK25 EMBASE DIL COUDEE 32 VOIES MICRORUPTEUR PLONGEUR MICRORUPTEUR LEVIER MICRORUPTEUR LEVIER LONG MICRORUPTEUR LEVIER GALET COMMUTATEUR A BASCULE DPST NOIR I/O COMMUT A BASCULE DPST ILLUM ROUGE I/O COMMUTATEUR A BASCULE DPST ILLUM VERT SPXO,40MHZ,SMD AC-DC CONV,DIN RAIL,1 O/P,7.5W,300mA,24V WIRE-BOARD CONNECTOR RECEPTACLE,8POS,2.54MM IC,ADC,16BIT,128SPS,SOT-23-6 LIMIT SWITCH,TOP ROLLER PLUNGER,SPDT ZENER DIODE,1W,12V,AXIAL ROUND SKIRTED KNOB,6.35MM MICRO SWITCH,PIN PLUNGER,SPDT 25A 277V CONNECTOR,POWER ENTRY,SOCKET 15A SPRING CONTACT PROBE,PCB TERMINAL,RING,#10,CRIMP,14-10AWG CABLE TIE ENCLOSURE,BOX,PLASTIC,GRAY KIT DÃ´ISOLATION SAC ANTISTATIQUE 100X150 CARTOUCHE ENCRE HP NOIRE SAC ANTISTATIQUE 400X450 SAC ANTISTATIQUE 400X500 INDICATEUR DE TEMP. PQ10 DISSIPATEUR THERMIQUE LAMP,REPLACEMENT CROCHET DE TEST POINTE DE TOUCHE CORDON DE MESURE CORDON DE MESURE CORDON DE MESURE CORDON DE MESURE INDUCTANCE 14UH PCB,Punchboard,No Clad,Pattern-Q INDUCTANCE INDUCTANCE FASTENERS,NUTS MOUNTING BRACKET TURRET HEAD M22520/1-02 88F4551 EMBASE IDC 10 VOIES EMBASE IDC 14 VOIES EMBASE IDC 16 VOIES EMBASE IDC 20 VOIES EMBASE IDC 34 VOIES EMBASE IDC 50 VOIES EMBASE IDC 60 VOIES COFFRET ALUMINIUM COFFRET ALUMINIUM DISSIPATEUR THERMIQUE CLIP POUR DISSIPATEURS COFFRET GRP LED PANEL INDICATOR FUSIBLE F50MA FUSIBLE F250MA FUSIBLE F500MA CAPACITOR ALUM ELEC 10UF,25V,20%,AXIAL FUSIBLE F1.6A FUSIBLE F3.15A FUSIBLE TEMPORISE 125MA FUSIBLE TEMPORISE 630MA FUSIBLE TEMPORISE 800MA DPM THERMOMETRE TEMPERATURE CONTROLEUR PT100 THERMOMETRE DPM PT100 DIODE DE SUPPRESSION 9V BOITIER 0603 DIODE DE SUPPRESSION 16V BOITIER 0603 DIODE DE SUPPRESSION 16V BOITIER 0603 DIODE DE SUPPRESSION 5.6V BOITIER 0603 DIODE DE SUPPRESSION 5.6V BOITIER 0603 DETECTEUR DE PROXIMITE DETECTEUR DE PROXIMITE BLOC DE JONCTION NOIR SUPPORT DE LAMPE ENCLIQUETABLE SUPPORT DE LAMPE T12 PRESSABLE SUPPORT DE STARTER A VISSER COFFRET POUR DISJONCTEUR GV2-M BOITIER COUVERCLE GRIS 254X180X111 BOITIER COUVERCLE FUME 180X110X90 BOITIER COUVERCLE FUME 182X180X111 BOITIER COUVERCLE FUME 254X180X111 PLAQUE DE MONTAGE 90X90 PLAQUE DE MONTAGE 150X90 PLAQUE DE MONTAGE 331X220 COFFRET DIN MODULAIRE 110X180X110 COFFRET DIN MODULAIRE 254X180X110 COFFRET ADAPT. SECTEUR COFFRET ELECTRIQUE 13A COFFRET ELECTRIQUE 13A DETECTEUR PHOTOELECTRIQUE DETECTEUR PHOTOELECTRIQUE DETECTEUR DE PROXIMITE DETECTEUR DE PROXIMITE DETECTEUR DE PROXIMITE BOITIER MALE 12P EMBASE FEMELLE 12P EMBASE FEMELLE 35P CORPS DÃ´EMBASE TAPE,2 SIDED,FABRIC,PRECUT CAPACITOR CERAMIC 820PF 500V,C0G,10%,1206 Ceramic chip capacitor,1000 pF,500 VDC COFFRET ART 110 VERSION 4 COFFRET POUR PILES CONSOLE COMTEC 150F BOITIER. SMART XS BOITIER. SMART XS BOITIER. SMART L BOITIER. SMART XL COFFRET UNIMET VERSION 2 KIT DE MONTAGE CI UNIMET COFFRET UNIDESK VERSION M200 COFFRET ALUCASE AC 090 COFFRET ALUCASE AC 092 COFFRET ALUCASE ACF 132 COFFRET ALUCASE AC 150 COFFRET ALUCASE ACF 152 BOITIER. ABS CH-4 BOITIER. ABS CH-6 BOITIER. ABS CH-8 BOITIER. ABS CH-8 BOITIER. ABS H-45 BOITIER. ABS H-65 LUBRICANT,375ML,AEROSOL CLOU M2.5X22 PQ250 DIODE,STANDARD,1A,200V,DO-41 FLASQUE DÃ´EXTREMITE GRIS 2.5MM CARTE DE REPERAGE 1-50 (X2) HORIZONTALE INDUCTIVE PROXIMITY SENSOR,3MM,12VDC TO 24VDC ISOLATEUR 3P 25A Ceramic chip capacitor,22 uF,10 VDC,c CERAMIC CHIP CAPACITOR,10 UF,6.3 VDC WIRE-BOARD CONNECTOR,MALE,3POS,1ROW SUPPORT DE CHAINE PORTE CABLE PQ2 SUPPORT DE CHAINE PORTE CABLE PQ2 REGISTOR,WIREWOUND,50 OHM,1W,5% RESISTOR,WIREWOUND,20 OHM,5W,5% Power Resistor BIPOLAR TRANSISTOR,PNP,-120V,TO-220 CONNECTOR CONNECTOR LED,RED,T-1 3/4 (5MM),5MCD,700NM CRYSTAL,10MHZ,16PF,SMD FUSE BLOCK,CLASS CC FUSE FUSE BLOCK,CLASS CC FUSE TERMINAL,MALE DISCONNECT,0.187IN,BLUE TERMINAL,RING TONGUE,#8,CRIMP,BLUE RESISTOR,CURRENT SENSE,0.02 OHM,15W,5% QUICK DISCONNECT CABLE,M12 4POS STRAIGHT QUICK DISCONNECT CABLE,M12,4POS,R/A QUICK DISCONNECT CABLE,M12 4POS STRAIGHT SENSOR MOUNTING BRACKET PHOTOELECTRIC SENSOR CIRCUIT PROTECTOR,HYD-MAG,1P,240V,5A CIRCUIT BREAKER,HYD-MAG,1P,250V,1A SCHOTTKY RECTIFIER,3A 20V DO-201AD Connector Dust Cap For Use With:MIL-C-38 Connector Dust Cap RESISTOR,METAL FILM,249 OHM,600mW,1% Tools,Extractors CAPACITOR CERAMIC 100PF 50V,C0G,5%,AXIAL CAPACITOR CERAMIC 1000PF 50V,C0G,5%,AXIAL MICRO SWITCH,PIN PLUNGER,SPDT 15A 250V CAPACITOR POLY FILM FILM 1UF,10%,63V, CAPACITOR TANT,10UF,50V,AXIAL 10% Wirewound Resistor Wirewound Chassis Mount LAMP,STACKABLE,IND,RYG Indicating Light - 3 Lights - D - 24V AC Indicating Light - 3 Lights - D - 24V AC MOUNTING BRACKET MOUNTING BRACKET Ceramic Multilayer Capacitor Capacitance CIRCULAR CONN,RCPT,SIZE 14S,4POS,BOX CIRCUIT BREAKER,THERMAL,1P,125V,15A CIRCUIT BREAKER,THERMAL,1P,250V,10A CIRCUIT BREAKER,THERMAL,1P,250V,25A CIRCUIT BREAKER,THERMAL,1P,250V,10A CIRCUIT BREAKER,THERMAL,1P,250V,20A CIRCULAR CONN,PLUG,SIZE 8,4POS,CABLE PIN HEADER,3POS,5.08MM MICRO SWITCH,BUTTON,SPDT,3A,250V CIRCULAR CONTACT,PIN,24-20AWG,CRIMP TERMINAL,RING TONGUE 3/4IN CRIMP YELLOW END PLATE,WDU/WDK SERIES TERMINAL BLOCK RESISTOR,METAL FILM,332 OHM,400mW,1% SHLD MULTICOND CABLE,7COND,24AWG,500FT,300V LED,RED,T-1 (3MM),12MCD,700NM CIRCUIT BREAKER,THERMAL MAG,1P,20A CIRCUIT BREAKER,THERMAL MAG,2P,15A CIRCUIT BREAKER,THERMAL MAG,2P,40A Thermal Magnetic Circuit Breaker RF/COAXIAL ADAPTER,BNC JACK-BNC JACK BRASS HEX NUT SWITCH ACCESSORY CHIP INDUCTOR,12NH 300MA 5% 2.7GHZ Male #16 Stamped and formed crimp contact 18C2418 Male #16 Stamped and formed crimp contact 18C2421 CAPACITOR ALUM ELEC 2200UF,25V,20%,AXIAL OPTOCOUPLER,PHOTOTRANSISTOR,5300VRMS TERMINAL,RING TONGUE,#10,CRIMP,BLUE ZENER DIODE,500mW,56V,DO-35 LAMP,STACKABLE,IND,RED/GRN/AMB Enclosure Switch Actuator Actuator Length:0.84Â´Â´ CIRCULAR CONNECTOR RCPT SIZE 14S,3POS,CABLE Circular Connector ENCLOSURE,BOX,ALUMINIUM ENCLOSURE,BOX,PLASTIC,BLACK Metal Connector Backshell LAMP,INDICATOR,INCAND,WHT RESISTOR,CURRENT SENSE,1 OHM,1W,1% IC,OP-AMP,9.4MHZ,35V/ us,DIP-8 CIRCULAR CONNECTOR RCPT,SIZE 12,3POS,CABLE BARE PCB NO HOLES - PLANE SINGLE SIDED TERMINAL,RING TONGUE,#8,CRIMP,YELLOW TVS Diode TVS Diode CARD EDGE CONNECTOR,SOCKET,98POS SOFTWARE BIPOLAR TRANSISTOR,PNP,-160V IC,IF SYSTEM,DIP-16 Crimp Connector Housing CIRCUIT BREAKER,THERMAL,2P,250V,10A DIODE,PHOTO,950NM,65Â°,SIDE LOOKING AVALANCHE DIODE,1A,400V,SOD-57 WIRE-BOARD CONNECTOR RECEPTACLE 11POS,2.54MM WIRE-BOARD CONNECTOR RECEPTACLE 15POS,2.54MM TRANSISTOR,PHOTO,NPN,925NM,T-1 LED,YELLOW,T-1 3/4 (5MM),12MCD,594NM AVALANCHE DIODE,3A,200V,SOD-64 PLUG & SOCKET CONN,PLUG,4POS,5.08MM CIRCULAR CONNECTOR RECEPTACLE 3POS CABLE CIRCULAR CONNECTOR RECEPTACLE 7POS CABLE CIRCULAR CONNECTOR,PLUG,7POS,CABLE CIRCULAR CONNECTOR RECEPTACLE 4POS PANEL CIRCULAR CONNECTOR RECEPTACLE 6POS PANEL CIRCULAR CONNECTOR RECEPTACLE 8POS PANEL CONDENSATEUR 25V

NOISE LOW DROP OUT 300 MA LOW NOISE POK LOW DROP OUT REGULA 300 MA LOW NOISE POK LOW DROP OUT REGULA 300 MA LOW NOISE POK LOW DROP OUT REGULA 300 MA LOW NOISE POK LOW DROP OUT REGULA SMA915F SCANNER W/RELAY Zener Diode OPTICAL SENSOR,380MM,SCR OPTICAL SENSOR,0MM to 380MM,SCR OPTICAL SENSOR,5M,SCR SM31RLMHS MINIBEAM SCAN BOARD-BOARD CONNECTOR HEADER,8WAY,2ROW TERMINAL,RING TONGUE 5/16IN,CRIMP BLUE IC,NON INVERTING BUFFER,USB-20 HERMAPHRODITIC COVER,THERMOPLASTIC Multipole Connector OPTOCOUPLER,PHOTOTRANSISTOR,3750VRMS OPTOCOUPLER,PHOTOTRANSISTOR,3750VRMS OPTOCOUPLER,PHOTOTRANSISTOR,5000VRMS OPTOCOUPLER,TRANSISTOR,5000VRMS OPTOCOUPLER,TRANSISTOR,5000VRMS ZENER DIODE,500mW,3.3V,SOD-80 ZENER DIODE,1W,4.7V,DO-213 ZENER DIODE,1W,5.1V,DO-213 ZENER DIODE,1W,6.8V,DO-213 ZENER DIODE,1W,12V,DO-213 LAMP,STACKABLE,IND,RED/GRN/AMB OPTOCOUPLER,TRANSISTOR,5300VRMS OPTOCOUPLER FERRITE CORE,CYLINDRICAL,110 OHM/100MHZ,300MHZ TERMINAL,RING TONGUE,1/4IN,CRIMP,RED POWER RELAY,DPDT,12VDC,8A,PC BOARD MICRO SWITCH,PIN PLUNGER,SPDT,1A 125V Limit Switch-OT LARGE BASICS BASIC SWITCH,STRAIGHT LEVER,SPDT,15A, SWITCH CAP Limit Switch CIRCULAR CONNECTOR RCPT,SIZE 14S,4POS,WALL CIRCULAR CONN,RCPT,SIZE 18,7POS,BOX CONTACT,SOCKET,30-26AWG,CRIMP POWER RELAY,SPDT,5VDC,10A,PC BOARD ENCLOSURE,BOX,ALUMINIUM ENCLOSURE,BOX,ALUMINIUM,GRAY ENCLOSURE,BOX,ALUMINIUM ENCLOSURE,BOX,ALUMINIUM,GRAY LED BULB,RED,T-3 1/4 FERRITE KIT,SNAP-IN CABLE CONNECTOR TY-FAST CABLE TIES Circular Connector Body Material:Metal PRESSURE SENSOR FERRITE CORE,CYLINDRICAL RESISTOR,CURRENT SENSE,0.01 OHM,1W,1% CONTACT,RECEPTACLE,22-20AWG,CRIMP Snap Action Basic Switch BASIC SWITCH,STRAIGHT LEVER,SPDT,15A,250V CAPACITOR ALUM ELEC 800UF,50V,+75,-10%,SCREW Brushless DC Motorized Impeller - 226mm NTC THERMISTOR NTC Thermistor Resistance:33kOhm FERRITE CORE,CYLINDRICAL,500 OHM/100MHZ,200MHZ CONTACT,RECEPTACLE,20-16AWG,CRIMP MICRO SWITCH,ROLLER LEVER SPDT 15A 250V TERMINAL,RING TONGUE,#10,CRIMP WIRE-BOARD CONNECTOR RECEPTACLE 12POS,3.96MM COAXIAL CABLE,RG-174,1000FT,BLACK POTENTIOMETER ROTARY,10KOHM 15% 1W SWITCH,TOGGLE,DPST,6A,250V TERMINAL,RING TONGUE,#10,CRIMP,RED PLAQUE CABLE TIES COFFRET NOIR COFFRET MINIATURE BLANC RADIATEUR MINATURE 20W RADIATEUR 15W TVS Diode HOOK & LOOP CABLE FASTENER,RED,3/8Â´Â´W TERMINAL BLOCK JUMPER Standard Terminal Block TERMINAL BLOCK JUMPER TERMINAL BLOCK JUMPER,3WAY TERMINAL BLOCK JUMPER,3WAY,0.312IN TERMINAL,SPADE/FORK,#6,CRIMP,YELLOW TERMINAL,RING TONGUE,#6,CRIMP,YELLOW Seals TERMINAL,SPADE/FORK,#10,CRIMP,YELLOW CONTACT,PIN,20-17AWG,CRIMP TERMINAL,RING TONGUE,#0,CRIMP REED RELAY,SPST-NO,24VDC,3A,THD SWITCH,PUSHBUTTON,SPST-NO,100mA,42V 250 SERIES ADAPTER,0.25 X 0.032,CRIMP,0.82L Switch Knob TERMINAL,RING TONGUE,1/2IN,CRIMP IC,OP-AMP,1MHZ,0.8V/ us,DIP-8 CIRCULAR CONN,PLUG,SIZE 9,3POS,CABLE General Purpose Filters STANDARD DIODE,2A,400V,DO-214AA CABLE,UNSHLD MULTIPR,CAT5E,4PR,24AWG,1000FT,300V UNSHLD MULTIPR CABLE 4PR 1000FT 300V BLK Shielded Multiconductor Cable Number of RELAY SOCKET HOLD-DOWN CLIP HOLE PLUG,STEEL,1.125IN IC,N-CH HIGH SPEED SWITCH,20A,TO220-3 Bridge Rectifier SCHOTTKY RECTIFIER,1A,90V,AXIAL RF DIODE,SCHOTTKY,2PF,70V,DO-35 IC,MOSFET DRIVER,HIGH-SPEED,DIP-8 CIRCUIT BREAKER,THERMAL,2P,240V,15A Bidirectional Transient Voltage Suppress Power Entry Connector SWITCH DIODE,40V,200mA,MICROMELF Schottky Diode SCHOTTKY RECTIFIER,30mA 40V SOD-80 SWITCHING DIODE,1.5PF,50NA,DO-35 RF DIODE,PIN,0.5PF,30V,SOD-80 DIODE,PHOTO,950NM,60Â°,SIDE LOOKING ZENER DIODE,3W,10V,DO-214AC ZENER DIODE,3W,200V,DO-214AC ZENER DIODE,3W,220V,DO-214AC ZENER DIODE,3W,27V,DO-214AC ZENER DIODE,3W,270V,DO-214AC ZENER DIODE,500mW,3.9V,MICROMELF WIRE-BOARD CONNECTOR,8POS,2.5MM PLUG & SOCKET CONN,HEADER,4POS,4.95MM TERMINAL,RING TONGUE,#10,CRIMP TERMINAL,RING TONGUE,#2,CRIMP TERMINAL,RING TONGUE,#6,CRIMP,BLUE Schottky Rectifier Package/Case:SOD-80 SCHOTTKY RECTIFIER,20mA 40V SOD-80 Schottky Rectifier Package/Case:QuadroMEL Schottky Rectifier Package/Case:SOD-80 OPTICAL SENSOR TRANSMISSIVE / SLOTTED INTERRUPTER DISPLAY,SEVEN SEGMENT,10MM,GREEN DISPLAY,SEVEN SEGMENT,10MM,RED ORANGE LED,GREEN,T-1 (3MM),15MCD,575NM LED,GREEN,T-1 (3MM),20MCD,575NM LED,GREEN,T-1 (3MM),6MCD,575NM LED,GREEN,T-1 3/4 (5MM),45MCD,575NM LED,T-1 3/4,GREEN,30MCD,575NM LED,GREEN,T-1 3/4 (5MM),12MCD,575NM LED,RED,T-1 (3MM),10MCD,625NM LED,T-1,YELLOW,5MCD,594NM LED,RED,T-3/4 (1.8MM),15MCD,630NM ZENER DIODE,500mW,24V,SOD-80 ZENER DIODE,500mW,36V,SOD-80 Hook-Up Wire Conductor Size AWG:12 TERMINAL,FERRULE,CRIMP,TURQUOISE CARTOUCHE ENCRE COMP. HP CYAN CIRCULAR CONNECTOR,PLUG,4POS,CABLE CARTOUCHE ENCRE COMP. HP JAUNE IC,OP-AMP,SOIC-14 BULKHEAD HOUSING,SIZE 24B,METAL AC INPuT PHOTOTRANSISTOR SMALL OuTLINE S RELAY SOCKET IC,PROGRAMMABLE LOGIC LOGIC TYPE:FPGA TESTER,SHIELDED MODULAR CAPACITOR POLY FILM FILM 0.1UF 10%,400V CAPACITOR POLY FILM 0.33UF,400V,5%,AXIAL CAPACITOR POLY FILM FILM 0.47UF 5%,63V CAPACITOR POLY FILM 0.68UF,100V,5%,AXIAL TERMINAL FEMALE DISCONNECT 0.25IN YELLOW CIRCULAR CONN,RCPT,SIZE 22,19POS,BOX CIRCULAR CONN,RCPT,SIZE 22,4POS,BOX CIRCULAR CONN,RCPT,SIZE 16,2POS,BOX CIRCULAR CONN,PLUG,SIZE 8,3POS,CABLE CIRCULAR CONN,PLUG,SIZE 8,3POS,CABLE CIRCULAR CONN,RCPT,SIZE 10,6POS,WALL CIRCULAR CONN,RCPT,SIZE 14,12POS,BOX CIRCULAR CONN,RCPT,SIZE 14,5POS,BOX CIRCULAR CONNECTOR PLUG SIZE 14,12POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 14,15POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 18,11POS,CABLE CONDUIT FITTING,ELECTRICAL,NYLON HEADER CAPACITOR ALUM ELEC 470UF,450V,20%,SNAP-IN D/A Converter (D-A) IC IC,MICROPOWER COMP,DUAL,1.1 uS,SOIC-8 IC,DIFFERENTIAL COMP,DUAL,200NS SOIC8 IC,PROG SHUNT V-REF,2.495V,1%,8-SOIC IC,PROG SHUNT V-REF,2.495V,2%,8-SOIC SWITCHES Breakaway header,8 contact,.156 in. pi BATTERY CLIP,AA,PANEL CIRCULAR CONN,RCPT,SIZE 14,12POS,BOX CIRCULAR CONNECTOR PLUG,SIZE 12,3POS,CABLE CIRCULAR CONNECTOR PLUG,SIZE 12,4POS,CABLE CIRCULAR CONNECTOR PLUG,SIZE 12,8POS,CABLE RESISTOR,METAL FOIL,5KOHM,600mW,0.01% MICRO SWITCH,HINGE LEVER,SPDT,3A 250V Multipole Connector Switch Knob SWITCH,PUSHBUTTON,DPDT,100mA,125V LIMIT SWITCH,SIDE ROTARY,SPDT-1NO/1NC Limit Switch TERMINAL,RING TONGUE,#6,CRIMP N CHANNEL JFET,-25V,SUPERSOT-3 IC,HEX INVERTER,SCHMITT TRIGGER SOIC14 IC,4I/P DUAL MULTIPLEXER,SOIC-16 PCB,Punchboard,No Clad,Pattern-P SWITCH,REED,SPST-NO,500mA,200VDC MICRO SWITCH,ROLLER LEVER SPDT 21A 277V MICRO SW,PIN PLUNGER,SPST-NO,25A 277V MICRO SWITCH,PLUNGER,SPST-NO,20A 480V SWITCH,TOGGLE,4PDT,20A,277V SWITCH,TOGGLE,4PDT,18A,277V MICRO SWITCH,PIN PLUNGER,SPDT,7A 115V SWITCH,ROTARY,DPST,3A,125V POWER RELAY,DPDT,110VDC,20A,PLUG IN ENCLOSURE,MODULAR,PLASTIC,GRAY ENCLOSURE,MODULAR,PLASTIC,GRAY ENCLOSURE,MODULAR,PLASTIC,GRAY ENCLOSURE,MODULAR,PLASTIC,GRAY ENCLOSURE,MODULAR,PLASTIC,GRAY ENCLOSURE,DIN RAIL,POLYCARBONATE,GRAY MNX Series Enclosure LIMIT SWITCH,CROSS ROLLER PLUNGER,SPDT CIRCULAR CONNECTOR PLUG SIZE 17,55POS,CABLE LED,RED,T-1 (3MM),630MCD,624NM CIRCULAR CONNECTOR,PLUG,4POS,PANEL CIRCULAR CONNECTOR,RECEPTACLE,4POS,PANEL COMMANDE DE MOTEUR PAS A PAS TRUNKING,DADO PREMIER EXTERNAL ANGLE High Current Inductor SOCKET BOX,1GANG Tantalum Electrolytic Capacitor Capacita VARIATEUR DE VITESSE 16A VARIATEUR DE VITESSE 32A CAPACITOR TANT,10UF,50V,AXIAL 10% CAPACITOR TANT,2.2UF,20V,AXIAL 10% CONTROLEUR VITESSE MOTEUR CAPACITOR TANT,1UF,50V,AXIAL 10% RELAY SOCKET CAPACITOR CERAMIC 820PF 100V,C0G,5%,0 CAPACITOR CERAMIC 220PF 100V,C0G,5%,1206 CAPACITOR CERAMIC 2200PF 100V,C0G,5%,1206 CAPACITOR CERAMIC 27PF 100V,C0G,5%,12 CAPACITOR TANT,6.8UF,35V,AXIAL 10% CAPACITOR CERAMIC 82PF 100V,C0G,5%,12 CAPACITOR CERAMIC 820PF 50V,C0G,5%,1206 Ceramic Multilayer Capacitor FEED THRU STRAIN RELIEF COVER,NYLON CONNECTORS,PCB SCR THYRISTOR,1.88KA,1.2KV,T 9G CAPACITOR CERAMIC 0.47UF,25V,X7R,10%,1210 CAPACITOR CERAMIC 0.1UF,100V,X7R,10%,1812 CAPACITOR CERAMIC 0.33UF 100V,X7R,5%,1812 CAPACITOR TANT,1UF,35V,RADIAL 10% CAPACITOR TANT,10UF,20V,RADIAL 10% CAPACITOR TANT,4.7UF,35V,RADIAL 10% CAPACITOR TANT,68UF,25V,0.095OHM,10% ENCLOSURE,WALL MOUNT,ALUMINIUM ENCLOSURE,WALL MOUNT,ALUMINIUM ENCLOSURE,WALL MOUNT,ALUMINIUM Magnetic Sensor STATIC PROTECTION WRIST GROUNDER STATFREE T2 STATIC PROTECTION MAT,36IN Static Protection Mat Body Material:Nitr LINEAR POSITION TRANSDUCER SEALING BOOT Key Operated Switch Contact Data Line Surge Suppressor POWER CORD,NEMA5-15P,8FT,10A,BLACK FERRITE CORE,CYLINDRICAL STRAIN RELIEF,8WAY,NYLON Relay Socket Power Relay CAPACITOR TANT,1000UF 6.3V,0.03 OHM,0.2,SMD TERMINAL,RING TONGUE,#10,CRIMP,RED LED,GREEN,T-1 (3MM),110MCD,563NM TERMINAL,RING TONGUE,#4,CRIMP TERMINAL,RING TONGUE,1/2IN,CRIMP BLUE TERMINAL,RING TONGUE,#4,CRIMP,RED TERMINAL,RING TONGUE,1/4IN,CRIMP TERMINAL,RING TONGUE,1/2IN,CRIMP FEED THRU STRAIN RELIEF COVER,NYLON MICRO SW,ROLLER LEVER,SPDT,10.1A 250V COFFRET POLYCARBONATE BLINDE LABEL,WARNING,2INX2IN,500PCS WIRE-BOARD CONNECTOR RECEPTACLE,4POS,3.96MM BOITIER POLYSTYRENE IP65 BOITIER POLYSTYRENE IP65 GROUNDING CORD BOITIER POLYSTYRENE IP65 CAPACITOR TANT,68UF,10V,0.1 OHM,0.2,SMD POWER RELAY,DPDT,120VAC,5A,PC BOARD STANDARD DIODE,50A,1.2KV DO-203AB STANDARD DIODE,80A,800V,DO-203AB STANDARD DIODE,80A,800V,DO-203AB CIRCULAR CONN,PLUG,SIZE 14,5POS,BOX CIRCULAR CONN,RCPT,SIZE 16,8POS,BOX CIRCULAR CONN,RCPT,SIZE 16,8POS,BOX CIRCULAR CONN,RCPT,SIZE 20,16POS,BOX TERMINAL,RING TONGUE,5/16IN,CRIMP RED TERMINAL,RING TONGUE,#10,CRIMP,BLUE TERMINAL,RING TONGUE 5/16IN,CRIMP BLUE TERMINAL,RING TONGUE 1/4IN CRIMP YELLOW CIR CONNECTOR PLUG SIZE 22 14POS FREE HANGING RF/COAXIAL,BNC JACK,R/A,CRIMP TERMINAL,RING TONGUE,#8,CRIMP,RED Terminal Block Pitch Spacing:0.150Â´Â´ TERMINAL,MALE DISCONNECT,0.25IN,RED TERMINAL,MALE DISCONNECT,0.187IN,BLUE BOARD-BOARD CONN,HEADER,36WAY,1ROW RELAY SOCKET TERMINAL,RING TONGUE,1/4IN,CRIMP TERMINAL,RING TONGUE,1/2IN,CRIMP TERMINAL,RING TONGUE,3/8IN,CRIMP,RED TERMINAL,RING TONGUE,1/2IN,CRIMP RF/COAXIAL,BNC JACK,R/A,50 OHM,SOLDER Air Ionizer HIGH TEMP MASKING TAPE,1Â´Â´ X 60YD CAPACITOR ALUM ELEC 35UF,25V,+75,-10%,AXIAL STANDOFF KIT CAPACITOR CERAMIC 22PF 100V,C0G,5%,RAD CAPACITOR CERAMIC 220PF 50V,C0G,5%,RAD CAPACITOR CERAMIC 47PF 100V,C0G,5%,RAD CAPACITOR CERAMIC 4700PF,50V,X7R,10%,RAD CAPACITOR CERAMIC 4700PF,100V,X7R,10%,RAD CAPACITOR CERAMIC 330PF 100V,C0G,5%,RAD CAPACITOR CERAMIC 3300PF 50V,C0G,5%,RAD RESISTANCE 300W 4R7 RESISTANCE 300W 6R8 RESISTANCE 300W 47R TERMINAL,RING TONGUE,#8,CRIMP,GREEN TERMINAL,RING TONGUE,#8,CRIMP,BLUE TERMINAL,RING TONGUE,#8,CRIMP,GREEN TERMINAL,RING TONGUE,#6,CRIMP,BLUE TERMINAL,RING TONGUE,#8,CRIMP,YELLOW TERMINAL,RING TONGUE,#6,CRIMP,RED TERMINAL,RING TONGUE,#6,CRIMP,RED TERMINAL,RING TONGUE,#10,CRIMP,RED TERMINAL,RING TONGUE,#10,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP CONN,TERMINAL,RING TONGUE,#6,CRIMP TERMINAL,RING TONGUE,#2,CRIMP RESISTANCE 300W 330R TERMINAL,RING TONGUE,#6,CRIMP TERMINAL,RING TONGUE,#6,CRIMP TERMINAL,RING TONGUE,3/8IN,CRIMP RESISTANCE 300W 680R TERMINAL,RING TONGUE 3/8IN CRIMP YELLOW TERMINAL,RING TONGUE,#6,CRIMP,YELLOW TERMINAL,RING TONGUE,#2,CRIMP,RED TERMINAL,RING TONGUE,1/2IN,CRIMP RESISTANCE 300W 1K TERMINAL,RING TONGUE,#6,CRIMP,YELLOW TERMINAL,RING TONGUE 1/4IN CRIMP YELLOW TERMINAL,CLOSED END SPLICE,CLEAR TERMINAL,RING TONGUE 1/4IN CRIMP YELLOW TERMINAL,RING TONGUE,#8,CRIMP,BLUE TERMINAL,RING TONGUE,1/2IN,CRIMP BLUE TERMINAL,RING TONGUE,1/2IN,CRIMP TERMINAL,RING TONGUE,#4,CRIMP,RED TERMINAL,RING TONGUE,#6,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP,RED TERMINAL,RING TONGUE,1/4IN,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP,BLUE TERMINAL,RING TONGUE,#10,CRIMP,BLUE TERMINAL,RING TONGUE,1/4IN,CRIMP BLUE TERMINAL,RING TONGUE,#2,CRIMP TERMINAL,SPADE/FORK,#10,CRIMP TERMINAL,RING TONGUE,#4,CRIMP,RED TERMINAL,RING TONGUE,#10,CRIMP,RED TERMINAL,RING TONGUE,#6,CRIMP,YELLOW TERMINAL,RING,3/8,CRIMP,YEL,12-10AWG TERMINAL,RING TONGUE,#10,CRIMP TERMINAL,RING TONGUE,5/16IN,YELLOW TERMINAL,RING TONGUE,#6,CRIMP TERMINAL,RING TONGUE,1/4IN,CRIMP TERMINAL,RING TONGUE 1/4IN CRIMP YELLOW TERMINAL,RING TONGUE,1/2IN,CRIMP TERMINAL,RING TONGUE,1/2IN,CRIMP TERMINAL,RING TONGUE,#10,CRIMP,BLUE TERMINAL,SPADE/FORK,#6,CRIMP,YELLOW TERMINAL,RING TONGUE,1/2IN,CRIMP TERMINAL,SPADE/FORK,#4,CRIMP,YELLOW TERMINAL,SPADE/FORK,#6,CRIMP,BLUE TERMINAL,RING TONGUE,#6,CRIMP,YELLOW TERMINAL,RING TONGUE,#10,CRIMP,BLUE TERMINAL,RING TONGUE,#4,CRIMP PCB,Pad/Hole and Gnd Plane PCB,Tracks(Strip Board) TERMINAL,RING TONGUE,1/4IN,CRIMP BLUE TERMINAL,RING TONGUE,#8,CRIMP Quarter wave stub,1710-1990 MHz PCB,Pad/Hole 2 Sides PLUG & SOCKET CONN,HEADER,4POS,6.71MM TAPE,INSULATION,PVC,BLACK,19MMX18M TERMINAL,SPADE/FORK,#4,CRIMP,YELLOW TERMINAL,SPADE/FORK,#8,CRIMP,BLUE CIRCULAR CONN RCPT,SIZE 17,55POS,WALL BOARD-BOARD CONNECTOR HEADER,6WAY,1ROW POTENTIOMETRE 2K TERMINAL,SPADE/FORK,1/4IN,CRIMP,RED FAST RECOVERY DIODE,125A,1.2KV,DO-8 TERMINAL,RING TONGUE 1/4IN CRIMP YELLOW CAPACITOR ALUM ELEC 250UF,75V,+75,-10%,AXIAL CIRCULAR CONN RCPT SIZE 25,128POS,WALL RESISTOR,METAL FILM,11KOHM,600mW,1% RESISTOR,METAL FILM,13KOHM,600mW,1% Metal Film Resistor RESISTOR,METAL FILM,1.4KOHM,600mW,1% RESISTOR,METAL FILM,301KOHM,600mW,1% BRIDE POUR CONDENSATEUR 25MM BRIDE POUR CONDENSATEUR 40MM BRIDE POUR CONDENSATEUR 45MM CAPACITOR CERAMIC 3.3PF 50V,C0G,0.25pF,0402 POWER RELAY,SPST-NO,120VAC,30A FLANGE Linear Voltage Regulator IC IC,3 TO 8 LINE DECODER/DMUX,SOIC-16 INST. BOX,TYPE 4,HINGED WIN/CVR 230X60 IC,ADC,16BIT,40KSPS,DIP-28 IC,ADC,12BIT,50KHZ,TSSOP-16 Digital/Analog Converter IC Interface Ty IC,RS-232 TRANSCEIVER,5.5V,SSOP-16 IC,PRESSURE SENSOR,15 TO 115KPA,SSOP8 REGULATEUR IC,OP-AMP,1MHZ,3V/ us,TO-99-8 IC,DAC,24BIT,768KSPS,SOIC-20 DC/DC Converter (DC-DC) / Switching Regu PANNEAU SOLAIRE STANDARD DIODE,150A 1.2KV DO-205AA STANDARD DIODE,400A,1.2KV,DO-9 LOG 4BIT 4PORT BUS SWITCH LOGIC TYPE:BUS IC,DIFF LINE RECEIVER,QUAD,SOIC-16 IC HEX INVERTER SCHMITT TRIGGER TSSOP-14 IC,QUAD AND GATE,2I/P,SOIC-14 IC,INVERTING BUFFER,SOIC-20 IC,NON INVERTING BUS BUFFER,SOIC-14 IC,INVERTING BUFFER,SOIC-14 IC,OP-AMP,10MHZ,16V/ us,DIP-8 IC,OP-AMP,1MHZ,3.5V/ us,SOIC-8 IC,PROG SHUNT V-REF,2.495V 2% 5-SOT-23 RF/COAXIAL,N PLUG,STR,50 OHM,CRIMP FASTENERS,SCREWS IC,SYNC BUCK PWM SWITCHER,20-HTSSOP IC,LINEAR VOLT REGULATOR,15V,SOT-89-3 IC,CURRENT MODE PWM CTRL,14.5V,16-DIP ENCLOSURE,WALL MOUNT POLYCARBONATE GRAY Box Enclosure ENCLOSURE,WALL MOUNT POLYCARBONATE GRAY Pressure Sensor Rocker Switch Rocker Switch Rocker Switch Rocker Switch Rocker Switch Pressure Sensor Pressure Sensor Pressure Sensor Operating Pressure Max:3 TERMINAL,RING TONGUE,#6,CRIMP,RED TERMINAL,RING TONGUE,#8,CRIMP,RED TERMINAL,RING TONGUE,#10,CRIMP,BLUE TERMINAL,RING TONGUE,#8,CRIMP,BLUE TERMINAL,RING TONGUE,#8,CRIMP,YEL,12-10AWG TERMINAL,BUTT SPLICE,CRIMP,RED TERMINAL,BUTT SPLICE,CRIMP,BLUE TERMINAL,BUTT SPLICE,CRIMP,YELLOW TOOLS,RATCHET CRIMP Engineering materials,Tube Lamps Indicator Lamp CIR CONNECTOR PLUG SIZE 20 14POS FREE HANGING POWER RELAY,DPDT,24VDC,30A,DIN RAIL CIRCULAR CONN,PLUG,SIZE 9,6POS,CABLE LINEAR POSITION TRANSDUCER CIRCULAR CONN,RCPT,SIZE 14S,5POS,BOX CIRCULAR CONN,PLUG,SIZE 16S,7POS,BOX CIRCULAR CONN,RCPT,SIZE 20,14POS,BOX CIRCULAR CONN,PLUG,SIZE 20,8POS,BOX CIRCULAR CONN,RCPT,SIZE 20,8POS,BOX CIRCULAR CONNECTOR PLUG SIZE 14S,5POS,CABLE CIRCULAR CONNECTOR RCPT SIZE 14S,5POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 16S,7POS,CABLE CIRCULAR CONNECTOR RCPT SIZE 16S,7POS, CIRCULAR CONNECTOR PLUG SIZE 20,14POS, LIVRE-PIC COOKLIVRE VOL1 CIRCULAR CONNECTOR PLUG,SIZE 20,8POS,CABLE CIRCULAR CONNECTOR RCPT,SIZE 20,8POS,CABLE ENCLOSURE,UTILITY,PLASTIC,GRAY IC,GEN PUR COMP,QUAD,1.3 uS,SOP-14 OPTOCOUPLERS MALE SCREW LOCK,4-40,7.14MM CONNECTOR,D SUB,PLUG,9POS TERMINAL BLOCK JUMPER,10WAY MULTICONDUCTOR PAIRED NETWORKING,CCTV RESISTOR,METAL FILM,22.1KOHM,250mW,1% RESISTOR,METAL FILM,402 OHM,250mW,1% RESISTOR,METAL FILM,6.81KOHM,250mW,1% RESISTOR,METAL FILM,750 OHM,250mW,1% POWER RELAY,SPST-NO,5VDC,10A PC BOARD POWER RELAY,3PDT,24VAC,5A,PLUG IN RF/COAXIAL,SMA PLUG,STR,50 OHM,SOLDER Cable Pull Switch JOYSTICK SWITCH,SPST,5A,250V POT,JOYSTICK,10KOHM,40Â°,100mW Joystick Linear Motion Control Linear Motion Control Linear Motion Control Linear Motion Control Linear Motion Control POT,LIN MOTION,1KOHM,15%,200mW Ceramic Multilayer Capacitor Ceramic Multilayer Capacitor Ceramic Multilayer Capacitor Ceramic Multilayer Capacitor Ceramic Multilayer Capacitor Ferrite Chip Bead Inductor Series:LF LK Multi-Layer SMD Inductor VOYANT NEON ROUGE VOYANT NEON VERT Inductor Series:LG HK VOYANT NEON AMBRE Inductor Series:LG HK RIGHT-ANGLE KEY STRAIGHT KEY POWER RELAY,DPDT,220VAC,10A,PLUG IN POWER RELAY,4PDT,110VAC,6A,PLUG IN Relays,PCB Relay Type:General Purpose POWER RELAY,4PDT,12VDC,6A,PLUG IN FERRITE BEAD,0.0062OHM,5A POWER RELAY,DPDT,220VAC,10A,PLUG IN Crimp Connector Housing CONTACT,RECEPTACLE,22-18AWG,CRIMP RESISTOR,METAL FILM,22.1 OHM,400mW,1% CIRCULAR CONN,RCPT,SIZE 14S,5POS,BOX CIRCULAR CONN,RCPT,SIZE 14S,5POS,BOX CIRCULAR CONN,RCPT,SIZE 14S,3POS,BOX CIRCULAR CONN,RCPT,SIZE 20,17POS,BOX CIRCULAR CONN,RCPT,SIZE 22,55POS,BOX CIRCULAR CONNECTOR RCPT SIZE 22,55POS,CABLE CIRCULAR CONN,RCPT,SIZE 12,3POS,BOX CIRCULAR CONN,RCPT,SIZE 20,41POS,BOX CIRCULAR CONN,RCPT,SIZE 22,55POS,BOX CIRCULAR CONNECTOR PLUG SIZE 20,41POS,CABLE CIRCULAR CONN,PLUG,SIZE 8,3POS,CABLE CIRCULAR CONN,RCPT,SIZE 18,32POS,BOX CAPACITOR CERAMIC 82PF 50V,C0G/NP0,5%,RAD RESISTOR,METAL FILM,150 OHM,400mW,1% Draw-Bar Endspring LABEL,IDENTIFICATION 9MMX18FT METALIZED LABEL,IDENTIFICATION 9MMX18FT METALIZED WIRE-BOARD CONNECTOR RECEPTACLE 14POS,2.54MM RESISTOR,METAL FILM,9.76KOHM,400mW,1% CAPACITOR CERAMIC,4.7UF,16V,X5R,10%,1206 CAPACITOR CERAMIC,1UF,6.3V,X5R,10%,0805 CAPACITOR CERAMIC,0.1UF,25V,X5R,10%,0603 FERRITE BEAD,0.035OHM,2A,0603 FERRITE BEAD,0.17OHM,700mA,0603 FERRITE BEAD,0.06OHM,3A,1812 FERRITE BEAD,0.06OHM,3A,1810 FERRITE BEAD,0.008OHM,4A,0805 FERRITE BEAD,0.007OHM,6A,1806 FERRITE CHIP BEAD,1806,14mOHM,6A FERRITE BEAD,0.014OHM,4A,1806 FERRITE BEAD,0.007OHM,6A,1806 FERRITE BEAD,0.7OHM,150mA,0402 FERRITE BEAD,0.3OHM,300mA,0402 FERRITE BEAD,0402,590mOHM,250mA FERRITE BEAD,0.2OHM,500mA,0402 FERRITE BEAD,0.45OHM,350mA,0603 FERRITE BEAD,0.4OHM,300mA,0603 FERRITE BEAD,1.1OHM,200mA,0603 FERRITE BEAD,0.3OHM,300mA,0603 FERRITE BEAD,0.1OHM,900mA,0805 INDUCTOR,470NH,10MA,10%,80MHZ INDUCTOR,560NH,10MA,10%,75MHZ INDUCTOR,680NH,10MA,10%,70MHZ SMD INDUCTOR,560NH,35MA 10% 95MHZ SMD INDUCTOR,1.2UH,25MA 10% 60MHZ SMD INDUCTOR,2.7UH,15MA 10% 40MHZ SMD INDUCTOR,3.3UH,15MA 10% 38MHZ SMD INDUCTOR,3.9UH,15MA 10% 36MHZ SMD INDUCTOR,4.7UH,15MA 10% 33MHZ SMD INDUCTOR,1NH 300MA 0.3NH 13GHZ SMD INDUCTOR,1.5NH,300MA,0.3NH,13GHZ SMD INDUCTOR,1.8NH,300MA,0.3NH,11GHZ SMD INDUCTOR,10NH,300MA 5% 4.3GHZ SMD INDUCTOR,15NH,300MA 5% 3.5GHZ SMD INDUCTOR,22NH,300MA 5% 2.8GHZ SMD INDUCTOR,39NH,200MA 5% 1.7GHZ SMD INDUCTOR,47NH,200MA 5% 1.5GHZ SMD INDUCTOR,5.6NH,300MA,0.3NH 5.7GHZ SMD INDUCTOR,100NH,300MA,5% 1GHZ SMD INDUCTOR,150NH 300MA 5% 800MHZ SMD INDUCTOR,220NH 300MA 5% 600MHZ SMD INDUCTOR,1.2NH,300MA,0.3NH,13GHZ SMD INDUCTOR,22NH,300MA 5% 2.9GHZ SMD INDUCTOR 3.9NH 300MA 0.3NH 8GHZ SMD INDUCTOR,4.7NH,300MA,0.3NH 6.5GHZ SMD INDUCTOR,47NH,300MA 5% 1.6GHz Inductor SMD INDUCTOR,6.8NH 300MA 5% 5.6GHZ SMD INDUCTOR,8.2NH 300MA 5% 5.2GHZ SMD INDUCTOR,82NH,300MA 5% 1.1GHZ SMD INDUCTOR,390NH 300mA 5% 400MHZ SMD INDUCTOR 1.8NH 300MA 0.3NH 6GHZ SMD INDUCTOR,5.6NH,300MA,0.3NH 5.4GHZ SMD INDUCTOR,56NH,300MA 5% 1.1GHZ CAPACITOR CERAMIC 0.22UF 6.3V,X5R,10%,0402 CAPACITOR CERAMIC 2.2PF 50V,C0G,0.25pF ENCLOSURE,UTILITY,PLASTIC,BLACK ENCLOSURE,UTILITY,PLASTIC,BLACK ENCLOSURE,UTILITY,PLASTIC,BLACK Pushbutton Switch PLUG WITH CABLE,DC POWER,4M EXTENSION CABLE,PLUG TO SKT,3M CONNECTOR CONTACT,SOCKET,CRIMP TERMINAL,RING TONGUE,#4,CRIMP Econoglas Door CAPACITOR CERAMIC,470PF,50V,X7R,10%,0402 RESISTOR,METAL FILM,24.9 OHM,400mW,1% SWITCH MOUNTING CONNECTOR MICRO SWITCH HINGE LEVER SPDT 100mA 250V CONNECTORS,INTER-SERIES ADAPTER CABLE,SHLD MULTIPR,1PR,22AWG,1000FT,300V LARGE BASIC SWITCH ROUND KNURLED KNOB W/ LINE IND,3.175MM Switch Knob Switch Knob Switch Knob ROUND KNURLED POINTER KNOB,6.35MM Switch Knob Switch Knob Switch Knob Switch Knob Switch Knob GUIDE DE SERTISSAGE INSERT FEMELLE HAN K 4/2P INSERT MALE HAN K 4/8P INSERT FEMELLE HAN K 4/8P INSERT MALE HAN K 6/6P INSERT FEMELLE HAN K 6/6P INSERT MALE HAN 10A CAPOT POUR HAN CAPOT POUR HAN N CH MOSFET,100V,14A,TO-204AA FICHE JACK 6.35 COUDEE 3P ETIQUETTE CE 19.05 PQ500 TAG,DO NOT OPERATE,PK10 TAG,DO NOT USE,PK10 TAG,DO NOT SWITCH,ON PK10 ALIMENTATION DE LABO 0-35V 10A ALIMENTATION DE LABO 0-18V 20A ALIMENTATION DE LABO 0-35V 10A ALIMENTATION DE LABO 0-18V 20A BLOUSE DÃ´ENTREPOT BLANCHE 108CM CONDENSATEUR 47000PF CONDENSATEUR 220PF CONDENSATEUR 470PF CONDENSATEUR 1000PF CONDENSATEUR 2200PF LIVRE-PROG THE MCHIP PIC IC-REAL TIME CLOCK EMBASE MALE VERTICALE DIL 8 VOIES EMBASE MALE VERTICALE DIL 20 VOIES EMBASE MALE HORIZONTAL SIL 4 VOIES EMBASE MALE HORIZONTAL SIL 10 VOIES EMBASE MALE HORIZONTAL DIL 3 VOIES EMBASE MALE HORIZONTAL DIL 4 VOIES EMBASE MALE HORIZONTAL DIL 10 VOIES BOITIER CONTACTS A SERTIR DIL 4 V CONNECTEUR PICOFLEX 4V CONNECTEUR PICOFLEX 14V EMBASE PICOFLEX 4V EMBASE PICOFLEX 14V MICRORUPTEUR MICRORUPTEUR MICRORUPTEUR MICRORUPTEUR MICRORUPTEUR THERMOPOCHE 100MM CAPTEUR DE PRESSION CAPTEUR DE PRESSION CAPTEUR DE PRESSION COMMUTATEUR A GLISSIERE COMMUTATEUR A GLISSIERE DETECTEUR PHOTOELECTRIQUE SUPPORT DE PILE BOUTON SIRENE PIEZO 12V DC DEMARREUR DE MOTEUR MANUEL DEMARREUR DE MOTEUR MANUEL DEMARREUR DE MOTEUR MANUEL DEMARREUR DE MOTEUR MANUEL CONTACT AUX 1O

DENUDEUR POUR FIBRE OPTIQUE IC,HALL EFFECT SENSOR,BIPOLAR,SIP-4 CIRCULAR CONNECTOR,PLUG,12POS,CABLE Lamp Socket Leaded Process Compatible:No Lens Cap CABLE & WIRE DISPENSER PINCE A SERTIR MANUELLE SWITCH,ROCKER,DPDT,12A,GREEN SWITCH,ROCKER,DPDT,12A,BLACK Rocker Switch INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR INDUCTIVE PROXIMITY SENSOR SOLID STATE TIMER Solid-State Timer MULTIMEDIA CONNECTOR Wall Switch Outlet Plate BOITIER MATE-N-LOK 2P DISTRIBUTION BOARD,6WAY,13A,WHITE CORDON 0.5M CORDON 2M POWER INDUCTOR 1.5UH 7.2A 30% 65MHZ INDUCTOR,SHIELDED,10UH,900MA,SMD INDUCTOR,SHIELDED,100UH,700MA,SMD POWER RELAY,SPST-NO,24VDC,15A,PANEL TERMINAL,SOLDER SLEEVE,2.8MM,CLEAR TERMINAL,SOLDER SLEEVE,2.5MM,CLEAR TERMINAL,SOLDER SLEEVE,6.8MM,CLEAR TERMINAL,SOLDER SLEEVE,1.9MM,BLUE TERMINAL,SOLDER SLEEVE,5.95MM,BLUE TERMINAL,SOLDER SLEEVE,7MM,BLUE TERMINAL,SOLDER SLEEVE,2.33MM,BLUE TERMINAL,SOLDER SLEEVE,3.5MM,YELLOW Current Transformer Outlet Surge Suppressor Transient Energy RF/COAXIAL,20KV HIGH VOLT PLUG,STRAIGHT,CRIMP CIRCULAR CONNECTOR PLUG,SIZE 20,8POS,PANEL CIRCUIT LOGIQUE COMPARATEUR QUADRULE IC,RS-485 TRANSCEIVER,5.5V,SOIC-8 IC,LINEAR VOLTAGE REGULATOR 5V TO-220-3 FUSE HOLDER,6.3 X 32MM,PCB MOUNT METAL WRIST BAND,FIXED SIZE,LARGE,BLACK METAL WRIST BAND,FIXED SIZE,SMALL,BLACK IC,DIFF AMP,150MHZ,52V/ uS,SOIC-8 FUSE HOLDER,5 X 20MM,PCB MOUNT CIRCULAR CONNECTOR RECEPTACLE 8POS CABLE RECTANGULAR INSERT,FEMALE,25WAY SWITCH,DISCONNECT,30A,3POLE SWITCH,DISCONNECT,30A,3POLE RESISTOR,RES ARRAY,4,33OHM,5%,SMD Power Resistor KIT DE DEMARRAGE POUR ST7FLITE2 USB Relays,PCB Switch Function:DPDT Relays,PCB Switch Function:DPDT Lens Cap Leaded Process Compatible:No D SUB CONTACT,PIN,16AWG,CRIMP IC,SHUNT V-REF,2.5V,20mV,8-SOIC IC,PRESSURE SENSOR,0 TO 10KPA,SOP-8 IC,TIMER,SINGLE,500KHZ,16V,SOIC-8 IC,VIDEO BUFFER,SINGLE,280MHZ,SOIC-8 IC,I/O EXPANDER,8BIT,100KHZ,DIP-16 AMPLIFIER IC PACKAGE/CASE:100-PZP IC,OP-AMP,3MHZ,13V/us,6mV,SOIC-8 IC,MPU SUPERVISOR,15 uA,5.5V,SOT23-5 IC,DC-DC CONV,SON-10 IC,OP-AMP,110kHZ,0.047V/ us,SOIC-8 D SUB CONNECTOR,STANDARD,15POS,PLUG CIRCULAR CONNECTOR RCPT SIZE 20,18POS, RESISTOR,METAL FILM,249 OHM,500mW,1% FUSE HOLDER,6.3 X 32MM,PANEL MOUNT WIRE-BOARD CONN,FEMALE,3POS,2.54MM WIRE-BOARD CONN,FEMALE,2POS,2.54MM RF/COAXIAL,K-LOC PLUG,STR,50 OHM CRIMP Wirewound Resistor Series:HLW Grounding Cord RESISTOR,METAL FILM,200 OHM,125mW,0.1% RF/COAXIAL,BNC JACK,R/A,50 OHM,SOLDER WIRE-BOARD CONN,FEMALE,12POS,3.96MM RF/COAXIAL,SHV BHD JACK,STR,SOLDER BAG,SHOULDER CAISSE A OUTILS CASE,EXPLORER CASE,EXPLORER CASE,EXPLORER CASE,EXPLORER TESTER,INSULATION/CONTINUITY TESTER,INSULATION/CONTINUITY TESTER,INSULATION/CONTINUITY TESTER,INSULATION/CONTINUITY TESTEUR DE DISJONCTEURS DIFFERENTIELS TESTEUR DE DISJONCTEURS DIFFERENTIELS RF/COAXIAL BNC BHD JACK R/A 50 OHM SOLDER VARISTOR,12V,50V,0402 LAMP,HAZARD,WARNING,LED,BLUE LAMP,HAZARD,WARNING,LED,GREEN MODULAR SIGNAL TOWER BASE,24VDC,54mA MOUNTING BRACKET RF/COAXIAL,BNC PLUG,STR,75 OHM,CRIMP RF/COAXIAL BNC BHD JACK STR 75 OHM SOLDER RF/COAXIAL,TNC JACK,STR,50 OHM,CRIMP RF/COAXIAL,BNC PLUG,R/A,50 OHM,CRIMP RF/COAXIAL,TNC PLUG,STR,50 OHM,CRIMP SWITCH,TACTILE,2.4A,THROUGH HOLE CONN,FUSED POWER ENTRY MODULE,PLUG 10A CONN,FUSED POWER ENTRY MODULE,PLUG 10A POWER ENTRY MODULE,PLUG,10A RF/COAXIAL,BNC JACK,STR,50 OHM,CRIMP FUSE,PCB,4A,250V,FAST ACTING CONNECTORS,PCB FUSE HOLDER FUSE SIZE/GR POWER ENTRY MODULE,PLUG,15A CONNECTOR,IEC POWER ENTRY,PLUG,10A IR RECEIVER,45M,950NM,SIP RF/COAXIAL,TNC JACK,STR 50 OHM,SOLDER FUSE,PCB,5A,250V,FAST ACTING Pan-Wrap Split Harness Wrap POWER ENTRY MODULE,PLUG,4A FUSE,CARTRIDGE,63mA,5X20MM TIME DELAY VOLTAGE SELECTOR,2 POLE,6.3A,250V FUSE,PCB,1A,250V,FAST ACTING RF/COAXIAL,TNC JACK,STR,50 OHM,CRIMP RF/COAXIAL,TNC PLUG,STR,50 OHM,CRIMP RF/COAXIAL BNC BHD RCPT STR 50 OHM SOLDER FUSE CLIP,5 X 20MM,PCB MOUNT CONNECTOR,IEC POWER ENTRY,PLUG,10A RF/COAXIAL,TNC BHD JACK STR 50 OHM CRIMP LAMP,HAZARD,WARNING,LED,RED LAMP,HAZARD,WARNING,LED,YELLOW FUSE,PCB,2A,250V,FAST ACTING MODULAR SIGNAL TOWER BASE,24VDC,54mA SWITCH,INDUSTRIAL PUSHBUTTON,18MM ADAPTOR,SHAVER TAPE,BLACK/WHITE,12MM TAPE,BLACK/YELLOW,12MM TAPE,BLACK/WHITE,6MM TRANSISTOR MOSFET CANAL N 30V LFPAK TRANSISTOR MOSFET CANAL N 30V LFPAK TRANSISTOR MOSFET CANAL N 30V LFPAK TRANSISTOR MOSFET CANAL N SOT-23-6 TRANSISTOR MOSFET CANAL N BOITIER SOT-23 TRANSISTOR MOSFET CANAL N BOITIER SOT223 TRANSISTOR MOSFET CANAL P SOT-23-6 TRANSISTOR MOSFET CANAL P SOT-23-6 TRANSISTOR MOSFET CANAL P BOITIER SOT-23 TRANSISTOR MOSFET CANAL P BOITIER SOT-23 TRANSISTOR MOSFET CANAL P BOITIER SOT223 TRANSISTOR MOSFET DOUBLE NP SO-8 TRANSISTOR MOSFET DOUBLE NP SO-8 TRANSISTOR MOSFET CANAL N BOITIER SOT223 TRANSISTOR MOSFET BOITIER SM8 TRANSISTOR NPN BOITIER SOT-223 TRANSISTOR NPN BOITIER SOT-223 TRANSISTOR NPN BOITIER SOT-223 TRANSISTOR PNP BOITIER SOT-223 TRANSISTOR PNP BOITIER SOT-223 TRANSISTOR PNP BOITIER SOT-223 CONDENSATEUR 22UF 6.3V BOITIER B CONDENSATEUR 22UF 6.3V BOITIER B CONDENSATEUR 100UF 4V BOITIER C CONDENSATEUR 100UF 4V BOITIER C CONDENSATEUR 220UF 6.3V BOITIER E CONDENSATEUR 220UF 6.3V BOITIER E CONDENSATEUR 330UF 6.3V BOITIER E CONDENSATEUR 330UF 6.3V BOITIER E CONDENSATEUR 1.5PF 50V BOITIER 0402 CONDENSATEUR 1.5PF 50V BOITIER 0402 CONDENSATEUR 3PF 50V BOITIER 0402 CONDENSATEUR 3PF 50V BOITIER 0402 CONDENSATEUR 10PF 50V BOITIER 0402 CONDENSATEUR 10PF 50V BOITIER 0402 CONDENSATEUR 1.0PF 200V BOITIER 0603 CONDENSATEUR 1.0PF 200V BOITIER 0603 CONDENSATEUR 1.2PF 200V BOITIER 0603 CONDENSATEUR 1.2PF 200V BOITIER 0603 CONDENSATEUR 1.5PF 200V BOITIER 0603 CONDENSATEUR 1.5PF 200V BOITIER 0603 CONDENSATEUR 2.7PF 200V BOITIER 0603 CONDENSATEUR 2.7PF 200V BOITIER 0603 CONDENSATEUR 3PF 200V BOITIER 0603 CONDENSATEUR 3PF 200V BOITIER 0603 CONDENSATEUR 3.9PF 200V BOITIER 0603 CONDENSATEUR 3.9PF 200V BOITIER 0603 CONDENSATEUR 4.7PF 200V BOITIER 0603 CONDENSATEUR 4.7PF 200V BOITIER 0603 CONDENSATEUR 5.6PF 200V BOITIER 0603 CONDENSATEUR 5.6PF 200V BOITIER 0603 CONDENSATEUR 6.8PF 200V BOITIER 0603 CONDENSATEUR 6.8PF 200V BOITIER 0603 CONDENSATEUR 7.5PF 200V BOITIER 0603 CONDENSATEUR 7.5PF 200V BOITIER 0603 CONDENSATEUR 8.2PF 200V BOITIER 0603 CONDENSATEUR 8.2PF 200V BOITIER 0603 CONDENSATEUR 22PF 100V BOITIER 0603 CONDENSATEUR 22PF 100V BOITIER 0603 CONDENSATEUR 47PF 100V BOITIER 0603 CONDENSATEUR 3.3PF 200V BOITIER 0805 CONDENSATEUR 3.3PF 200V BOITIER 0805 CONDENSATEUR 7.5PF 200V BOITIER 0805 CONDENSATEUR 7.5PF 200V BOITIER 0805 CONDENSATEUR 8.2PF 200V BOITIER 0805 CONDENSATEUR 8.2PF 200V BOITIER 0805 CONDENSATEUR 9.1PF 200V BOITIER 0805 CONDENSATEUR 9.1PF 200V BOITIER 0805 CONDENSATEUR 10PF 200V BOITIER 0805 CONDENSATEUR 10PF 200V BOITIER 0805 CONDENSATEUR 22PF 200V BOITIER 0805 CONDENSATEUR 22PF 200V BOITIER 0805 CONDENSATEUR 24PF 200V BOITIER 0805 CONDENSATEUR 24PF 200V BOITIER 0805 CONDENSATEUR 36PF 200V BOITIER 0805 CONDENSATEUR 36PF 200V BOITIER 0805 CONDENSATEUR 47PF 200V BOITIER 0805 CONDENSATEUR 47PF 200V BOITIER 0805 CONDENSATEUR 82PF 200V BOITIER 0805 CONDENSATEUR 82PF 200V BOITIER 0805 RESEAU DE SUPPRESSEUR MULTIGUARD RESEAU DE SUPPRESSEUR MULTIGUARD RESEAU DE SUPPRESSEUR MULTIGUARD FICHE FEMELLE 4 VOIES COFFRET 76 TIROIRS TOOL CASE,ALUMINIUM,HIGH QUALITY VALISE DE TRANSPORT ALU 57X37X27CM LOCK,FOR TRANSPORT CASE,PK2 BOITE MULTI-COMPARTIMENTS BOITE MULTI-COMPARTIMENTS BOITE MULTI-COMPARTIMENTS JOINT POUR FICHE MALE PANNEAU TAILLE 20 CLAMP,KLIKLAMP,250MM TINSNIP,RIGHT CUT,260MM TINSNIP,LEFT CUT,260MM SNIP,MULTI PURPOSE,280MM CUTTER,CABLE,MULTIPURPOSE,190MM CUTTER,CABLE,MULTIPURPOSE,190MM RF/COAXIAL,BNC PLUG,STR,75 OHM,CRIMP PLUG AND SOCKET CONNECTOR HOUSING CATEGORY 5E CABLE ASSEMBLY RF/COAXIAL MCX PLUG R/A 50 OHM CRIMP/SLDR CIRCULAR CONNECTOR RCPT,SIZE 10SL,3POS,BOX CIRCULAR CONN,RCPT,SIZE 14S,5POS,BOX CIRCULAR CONN,RCPT,SIZE 14S,6POS,BOX CIRCULAR CONN,RCPT,SIZE 16S,7POS,BOX CIRCULAR CONN,RCPT,SIZE 18,10POS,BOX CIRCULAR CONNECTOR PLUG SIZE 14S,6POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 18,10POS,CABLE CIRCULAR CONN,RCPT,SIZE 8,2POS,BOX IC,OP-AMP,8MHZ,3V/ us,DIP-14 CUTTER,CONDUIT,MULTI FUNCTION IC,VOLT SUPERVISOR,30 uA,5.5V,SOT23- PLUG AND SOCKET CONNECTOR HOUSING RF/COAXIAL,QMA JACK STR 50 OHM PRESS FI RF/COAXIAL,QMA JACK,STR,50 OHM,SOLDER RF/COAXIAL,QMA JACK,R/A,50 OHM,SOLDER RF/COAXIAL,QMA BHD JACK STR 50 OHM CRIMP RF/COAXIAL,QMA BHD JACK STR 50OHM CRIMP RF/COAXIAL,QMA PLUG,STR,50 OHM,CRIMP RF/COAXIAL,MINI BNC BHD JACK,R/A 75OHM RF/COAXIAL,MINI BNC COAXIAL,75 OHM SLDR RF/COAXIAL MINI BNC PLUG STR 75 OHM CRIMP FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,NUTS FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,SCREWS FASTENERS,SCREWS IR RECEIVER,35M,950NM,SIP IR RECEIVER,35M,950NM,SIP CIRCULAR CONNECTOR RCPT,SIZE 11,13POS,WALL CIRCULAR CONNECTOR RCPT,SIZE 15,37POS,WALL CIRCULAR CONNECTOR RCPT,SIZE 17,55POS, CIRCULAR CONN,PLUG,SIZE 9,6POS,CABLE CIRCULAR CONNECTOR PLUG,SIZE 11,6POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 15,19POS, CIRCULAR CONNECTOR PLUG SIZE 15,37POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 17,55POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 15,37POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 15,37POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 17,55POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 17,55POS,CABLE PLUG & SOCKET CONNECTOR,PLUG,2POS PLUG & SOCKET CONNECTOR,PLUG,2POS SCHOTTKY RECTIFIER,100mA,35V 0603 RF/COAXIAL ADAPTER,N JACK-TNC JACK CIRCULAR CONN,RCPT,SIZE 16,23POS,BOX CIRCULAR CONNECTOR PLUG,SIZE 10,6POS,CABLE CIRCULAR CONNECTOR RCPT,SIZE 14,5POS,CABLE CIRCULAR CONN,RCPT,SIZE 14S,5POS,BOX CIRCULAR CONN,RCPT,SIZE 18,4POS,BOX Circular Connector CIRCULAR CONNECTOR PLUG,SIZE 16,5POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 22,19POS,CABLE CIRCULAR CONNECTOR PLUG SIZE 12S,2POS,CABLE BAR GRAPH,10-LED,GREEN,8MCD,105mW BAR GRAPH,10-LED,RED,8MCD,105mW INDICATOR,LED PCB,T-1 3/4,GREEN,2.2V INDICATOR,LED PCB,5MM,RED,2V INDICATOR,LED PCB,T-1 3/4,RED,2V INDICATOR,LED PCB,3MM,GREEN,2.2V INDICATOR,LED PCB,2LED GRN 40MCD 105mW INDICATOR,LED PCB,4-LED,GREEN,20MCD LAMP SOCKET,LUMEX 3MM LEDs LAMP SOCKET,LUMEX 5MM LEDs PANEL MOUNT INDICATOR,LED,5MM,GREEN,2.2V PANEL MOUNT INDICATOR,LED,7.94MM,RED,2V PANEL MOUNT INDICATOR,LED,7.94MM,RED,1.7V PANEL MOUNT INDICATOR,LED,6.35MM,GREEN,2.2V PANEL MOUNT INDICATOR,LED,6.35MM,RED,2V PANEL MOUNT INDICATOR,LED,12.05MM,RED,2V PANEL MOUNT INDICATOR,LED,8.26MM,GREEN,2.2V PANEL MOUNT INDICATOR,LED,8.26MM,YELLOW,2.1V PANEL MOUNT INDICATOR,LED,GREEN,2.2V LED,AMBER,5MM X 2MM,5MCD,605NM LED,RED,5MM X 2MM,10MCD,635NM LED,RED,2.3MM X 8MM,9MCD,635NM LED,GREEN,T-1 (3MM),100MCD,565NM LED,GREEN,T-1 (3MM),40MCD,565NM LED,RED,T-1 (3MM),6MCD,700NM LED,RED,T-1 (3MM),125MCD,635NM LED,RED,T-1 (3MM),30MCD,635NM LED,RED,T-1 (3MM),30MCD,635NM LED,RED,T-1 (3MM),600MCD,660NM LED,YELLOW,T-1 (3MM),90MCD,585NM LED,YELLOW,T-1 (3MM),30MCD,585NM LED,T-1,GREEN / YELLOW,RADIAL LED,RED,4MM X 7MM,12MCD,635NM LED,4MM,YELLOW,6MCD,585NM LED,RED,T-1 3/4 (5MM),40MCD,635NM LED,GREEN,T-1 3/4 (5MM),50MCD,565NM LED,RED,T-1 3/4 (5MM),40MCD,635NM LED,GREEN,T-1 3/4 (5MM),30MCD,565NM LED,GREEN,T-1 3/4 (5MM),80MCD,565NM LED,YELLOW,T-1 3/4 (5MM),30MCD,585NM LED,RED,T-1 3/4 (5MM),2.8CD,660NM LED,RED,T-1 3/4 (5MM),250MCD,660NM LED,YELLOW,T-1 3/4 (5MM),1CD,590NM LED,RED,T-1 3/4 (5MM),600MCD,635NM LED,YELLOW,T-1 3/4 (5MM),30MCD,585NM LAMP,LED REPLACEMENT,RED,10MM LAMP,LED REPLACEMENT,YELLOW,10MM LED Lamp LAMP,LED,YELLOW,10MM,WEDGE LED,RED,0.8MM X 1MM,60MCD,636NM LED,2.4MM,RED,250MCD,636NM LED,2.4MM,GREEN,150MCD,574NM LED,YELLOW,2.4MM,140MCD,590NM DISPLAY,SEVEN SEGMENT,14MM,RED DISPLAY,SEVEN SEGMENT,14MM,GREEN DISPLAY,SEVEN SEGMENT,14MM,RED LED,GREEN,2MM,10MCD,565NM LED,RED,2MM,25MCD,635NM LED,GREEN,5MM X 2MM,6MCD,555NM LED,2X5MM,RED,80MCD,660NM LED,AMBER,T-1 (3MM),15MCD,605NM LED,GREEN,T-1 (3MM),6MCD,565NM LED,GREEN,T-1 (3MM),6MCD,565NM LED,RED,T-1 (3MM),6MCD,635NM LED,RED,T-1 (3MM),30MCD,635NM LED,GREEN,T-1 3/4 (5MM),30MCD,555NM LED,RED,0.8MM X 1MM,45MCD,660NM LED,RED,2MM X 1.6MM,25MCD,660NM LED,YELLOW,2MM X 1.6MM,6MCD,585NM LED,RED,1.4MM X 2MM,100MCD,660NM LED,GREEN,2.4MM,25MCD,565NM INDICATOR,LED PCB,2-LED,RED / GREEN LED Lamp INDICATOR,LED PCB,T-1 3/4,RED,1.7V INDICATOR,LED PCB T-1 3/4,YELLOW,2.1V PANEL MOUNT INDICATOR,LED,8.2MM,GREEN,2.2V PANEL MOUNT INDICATOR,LED,8.2MM,YELLOW,2.1V LED,GREEN,1.25MM X 1.4MM,10MCD,565NM LED,RED,1.25MM X 1.4MM,9MCD,635NM LED,RED,1.25MM X 1.4MM,25MCD,660NM LED,3MM X 2MM,RED / GREEN,SOT-23-3 Switches,Limit Switch Contact Rating:60 Switch Actuator Switch Actuator Switch Actuator CONNECTOR,BNC,BHD JACK,STR,50 OHM,SOLDER MALE CAP RF/COAXIAL N PLUG STR 50 OHM CRIMP/SOLDER RF/COAXIAL,N JACK,STR,50 OHM,CRIMP RF/COAXIAL,N JACK,STR,50 OHM,SOLDER RF/COAXIAL,N PLUG,STR,50 OHM,CRIMP RF/COAXIAL,SMB PLUG,R/A,75 OHM,CRIMP RF/COAXIAL,MMCX JACK,STR,50 OHM,THD DISPLAY,SEVEN SEGMENT,10MM,GREEN INDUCTIVE PROXIMITY SENSORS WIRE-BOARD CONN,FEMALE,8POS,2.54MM RF/COAXIAL ADAPTER,F JACK-F JACK DISPLAY,SEVEN SEGMENT,10MM,GREEN CONTACT,2AWG,CRIMP,175A PLUG AND SOCKET CONNECTOR HOUSING IC,MOSFET DRIVER,HIGH-SPEED,CCD,DI-8 RF/COAXIAL ADAPTER,QMA JACK-SMA JACK CABLE 304M LIGHT PIPE,SINGLE,ROUND,PANEL CABLE 152M LIGHT PIPE,DUAL,ROUND,PCB RESISTOR,CURRENT SENSE,1 OHM,20W,1% RESISTOR,CURRENT SENSE,100 OHM,20W,1% CONTACT,4AWG,CRIMP RF/COAXIAL ADAPTER,QMA PLUG-SMA JACK TERMINAL CLOSED END SPLICE TWIST-ON GREY LIGHT PIPE,SINGLE,ROUND,PCB LIGHT PIPE,SINGLE,ROUND,PCB TRANSISTOR,NPN,40V,TO-92 RF/COAXIAL ADAPTER,BNC JACK-N PLUG CONTACT SET,SOCKET,4/0AWG,CRIMP RESISTOR,CURRENT SENSE,20 OHM,20W,1% RESISTOR,CURRENT SENSE,25 OHM,20W,1% CONTACT,12-10AWG,CRIMP PLUG AND SOCKET CONNECTOR HOUSING PLUG AND SOCKET CONNECTOR HOUSING RF/COAXIAL,HN PLUG STR 50 OHM CLAMP/SLDR CONTACT,1/0AWG,CRIMP CONTACT SET,SOCKET,2/0AWG,CRIMP PLUG AND SOCKET CONNECTOR HOUSING Power Resistor RESISTOR,CURRENT SENSE,0.02 OHM,20W,1% RF/COAXIAL,N JACK,STR,50 OHM,CRIMP Power Resistor RF/COAXIAL,SMB JACK,R/A,75 OHM,CRIMP RF/COAXIAL,SMB PLUG,STR,75 OHM,CRIMP RF/COAXIAL,SMB BHD JACK STR 75 OHM CRIMP BULKHEAD ADAPTER,N JACK-SMB JACK KIT TOURNEVIS ET EMBOUTS 7PC KIT TOURNEVIS ET EMBOUTS 11PC KIT TOURNEVIS ET EMBOUTS 17PC KIT TOURNEVIS ET EMBOUTS 17PC DIAL CALIPER,PLASTIC VERNIER CALIPER,PLASTIC METRE PLIANT PLASTIQUE 1M POIGNEE 6 PANS MALE 6MM POIGNEE 6 PANS MALE 10MM POIGNEE TORX T27 POIGNEE TORX T40 BOITE MOULEE GRIS 160X360X90 BOITE MOULEE NOIR 98X64X36 BOITE MOULEE NOIR 75X80X52 BOITE MOULEE NOIR 175X80X52 BOITE MOULEE NOIR 220X120X80 BOITE POLYESTER 220X120X90 PANNEAU ALU 19Â´Â´ 2U PANNEAU ALU 19Â´Â´ 3U PANNEAU ALU 19Â´Â´ 4U HOSPITAL GRADE OUTLET STRIP,6-OUTLET,1 STATION DE SOUDAGE WDD161V BUSE 1.2MM POUR FER HAP1 PINCE COUPANTE PINCE JEU DE 3 PINCES PINCE COUPANTE PANNE SOUDAGE 2.0MM INTERRUPTEUR ECLAIRE AMBRE CRAYON 2B BOITE DE 12 POWER OUTLET STRIP,5 OUTLET,15A,125V RF/COAXIAL,N PLUG,STR,50 OHM,CRIMP WIRE-BOARD CONN,RECEPTACLE,5POS,2MM RF/COAXIAL,BNC PLUG,STR,50 OHM,CRIMP EYELET TERMINAL LUG TERMINAL,MECHANICAL LUG,#6,SOLDER DPM TIMER/COMPTEUR LCD MODULE FPT-1 AVEC CIRCUIT ALTERA TIMER,MULTIFUNCTION COMPTEUR TALLY MANUEL BASE POUR COMPTEUR TALLY ISOLATEUR MINI ALIMENTATION 24VDC 0.5A INTERRUPTEUR A BASCULE SPST BLANC I/O INTERRUPTEUR A BASCULE SPST VERT ILLUM. INTERRUPTEUR A BASCULE SPST NOIR MOM INTERRUPTEUR A BASCULE DPST NOIR I/O CPAOT DE PROTECTION COMMUTATEUR A BASCULE SPST NOIR COMMUTATEUR A BASCULE DPST ROUGE ILLUM. COMMUTATEUR A BASCULE DPDT VERT ILLUM. INTERRUPTEUR A BASCULE MOM-OFF-MOM NOIR INTERRUPTEUR ANTI-VANDALE TOGGLE COMMUTATEUR Header Connector,PCB Mount,PLUG,4 Contacts,SKT,0.165 Pitch,PC TAIL Terminal,POLARIZED LCK 56H8238 CRIMP SET,PZ 6 ROTO CRIMP SET,PZ 6/5 CRIMP TOOL,STRIPAX,PZ 16 HEAT SHRINK TUBING,PVC,WHT,100FT CAPUCHON THERMO. PQ100 CAPUCHON THERMO. PQ100 MANCHON RETRACTABLE MANCHON RETRACTABLE INTERRUPTEUR A BASCULE MANCHON RETRACTABLE MANCHON RETRACTABLE FIL DÂ´EQUIPEMENT BLEU 100M FIL BLEU 100M FIL JAUNE 100M FIL VERT 100M FIL JAUNE 100M FIL BLANC 100M FIL BLEU 100M FIL JAUNE 100M FIL BLEU 100M FIL ROUGE 100M FIL VERT 100M FIL JAUNE 100M FIL BLANC 100M FIL JAUNE 100M FIL NOIR 100M FIL ROUGE 100M FIL VERT 100M FIL BLANC 100M NETTOYANT PERCHLORURE BOARD-BOARD CONN,HEADER,36WAY,1ROW BOARD-BOARD CONN,HEADER,36WAY,1ROW CONTACT,RECEPTACLE,24-18AWG,CRIMP COMMUTATEUR MOMENTANE ROUGE COMMUTATEUR MOMENTANE NOIR IC,8BIT MCU,PIC16F,4MHz,DIP-18 ELECTROMECHANICAL MULTIFUNCTION TIMER MICROCONTROLEUR 8 BITS FLASH MICROCONTROLEUR 16 BITS DSP 20MHZ CMS ADAPTATEUR INTERFACE ICD2 16F684 ADAPTATEUR INTERFACE ICD2 16F688 ENCLOSURE,BOX,PLASTIC,GRAY FILTRE DE LIGNE 32V RAIL DIN FILTRE CONNECTEUR IEC 10A ANTENNE GSM 900/1800/1900MHZ + IPEX ANTENNE GSM 900/1800/1900MHZ + MMCX HEAT SHRINK TUBING,25.4MM ID,PO,BLK,50FT RF/COAXIAL,BNC SHORTING CAP,50OHM PLUG & SOCKET HOUSING,RECEPTACLE,NYLON RF/COAXIAL ADAPTER,SMA PLUG-SMA JACK WIRE-BOARD CONNECTOR HEADER 3POS,3.96MM WIRE-BOARD CONNECTOR RECEPTACLE,5POS,3.96MM WIRE-BOARD CONNECTOR RECEPTACLE,7POS,3.96MM WIRE-BOARD CONNECTOR RECEPTACLE,2POS,3.96MM WIRE-BOARD CONNECTOR HEADER 2POS,3.96MM SUPPORT DE MONTAGE PLUG & SOCKET HOUSING,RECEPTACLE,NYLON WIRE-BOARD CONNECTOR RECEPTACLE,4POS,3.96MM CONTACT,SOCKET,26-22AWG,CRIMP PLUG & SOCKET HOUSING,RECEPTACLE,NYLON RF/COAXIAL,SMA PLUG,STR,50 OHM,CLAMP PLUG AND SOCKET CONNECTOR HOUSING PLUG AND SOCKET CONNECTOR HOUSING Power Connector Power Connector Leaded Process Compatibl RECTANGULAR CONNECTOR,1POS,CRIMP PLUG AND SOCKET CONNECTOR HOUSING PLUG AND SOCKET CONNECTOR HOUSING TERMINAL,RING TONGUE,3/8IN,CRIMP,RED RF/COAXIAL,SMA JACK,STRAIGHT,SOLDER Ring Tongue Solderless Terminal PLUG AND SOCKET CONNECTOR HOUSING PLUG AND SOCKET CONNECTOR HOUSING PLUG AND SOCKET CONNECTOR HOUSING CONTACT,6AWG,CRIMP CONTACT,8AWG,CRIMP CONTACT,12-10AWG,CRIMP CONTACT,SOCKET,26-22AWG,CRIMP PLUG & SOCKET HOUSING,RECEPTACLE,NYLON N Coaxial Connector RG Cable Type:RG 142 RF/COAXIAL,SMA PLUG,STR,50 OHM,CRIMP STANDARD TERMINAL BLOCK RF/COAXIAL,SHV PLUG,STRAIGHT,CRIMP STANDARD TERMINAL BLOCK POWER CONNECTOR RF/COAXIAL,BNC PLUG,STR,50 OHM,CRIMP WIRE-BOARD CONNECTOR RECEPTACLE,3POS,3.96MM PLUG & SOCKET HOUSING,RECEPTACLE,NYLON PLUG AND SOCKET CONNECTOR HOUSING Current Monitoring Relay CLAVIER PILE LITHIUM THIONYLE 6V PILE LITHIUM THIONYLE 6V ADAPTATEUR BNC ADAPTATEUR TEST PLUG ADAPTATEUR THERMOCOUPLE K MALLETTE RIGIDE POUR OX7100 CORDON ETHERNET CROISE KIT LOGICIEL SX-METRO CAPUCHON 3P POUR OT45-63 CAPUCHON 1P POUR OT45-63 CONTACT AUXILIAIRE 1O POWER CORD,NEMA5-15P,6FT,10A,GRAY POWER CORD,NEMA5-15P,8FT,10A,GRAY POWER CORD,NEMA5-15P,6FT,10A,GRAY POWER CORD,NEMA5-15P,12FT,15A,BLACK POWER CORD,NEMA5-15P,6FT,10A,BLACK POWER CORD,NEMA5-15P,20FT,13A,GRAY POWER CORD,NEMA5-15P,9.8FT,13A,BLACK POWER CORD,NEMA5-15P,20FT,10A,BLACK POWER CORD,NEMA5-15P,8FT,10A,BLACK POWER CORD,NEMA5-15P,6FT,10A,BLACK POWER CORD,NEMA5-15P,8FT,10A,BLACK POWER CORD,NEMA5-15P,6FT,10A,GRAY POWER CORD,NEMA5-15P,6FT,10A,BLACK POWER CORD,NEMA5-15P,9FT,13A,BLACK POWER CORD,NEMA5-15P,9FT,15A,BLACK POWER CORD,NEMA5-15P/IEC C13,7.5FT,10A 125V,BLACK POWER CORD NEMA5-15P/IEC,7.5FT 13A,BLK POWER CORD,NEMA5-15P/IEC,3FT,10A,BLK POWER CORD,NEMA5-15P/IEC,6FT,10A,BLK POWER CORD NEMA6-15P/IEC,6.6FT 10A,BLK POWER CORD,NEMA5-15P,8FT,10A,BLACK POWER CORD NEMA6-15P/IEC,15FT,13A GRAY POWER CORD,NEMA5-15P/IEC,8FT,13A,BLK POWER CORD,IEC320-C13,8FT,BLACK POWER CORD,NEMA5-15P/R,10FT,13A BLACK POWER CORD,NEMA5-15P,6.6FT,BLACK POWER CORD,NEMA5-15P,9.8FT,10A,BLACK POWER CORD,NEMA5-15P,6.6FT,10A,BLACK POWER CORD,NEMA5-15P,9.8FT,10A,BLACK POWER CORD,NEMA5-15P,6.6FT,13A,BLACK POWER CORD,NEMA5-15P,6.6FT,15A,BLACK POWER CORD,NEMA5-15P,9.8FT,15A,BLACK POWER CORD,NEMA5-15P,9.8FT,13A,BLACK POWER CORD,NEMA5-15P,9FT,13A,BLACK POWER CORD,NEMA5-15P,7.5FT,10A,BLACK POWER CORD NEMA5-15P/IEC,6.6FT,10A BLK POWER CORD NEMA5-15P/IEC,9.8FT,10A BLK POWER CORD NEMA5-15P/IEC,6.6FT,13A BLK POWER CORD,NEMA5-15P,9.8FT,13A,BLACK POWER CORD NEMA5-15P/IEC,6.6FT,15A BLK POWER CORD NEMA5-15P/IEC,9.8FT,15A BLK POWER CORD NEMA5-15P/IEC,6.6FT 10A,BLK POWER CORD NEMA5-15P/IEC,9.8FT 10A,BLK POWER CORD NEMA5-15P/IEC,6.6FT 10A,BLK POWER CORD NEMA5-15P/IEC,9.8FT 10A,BLK POWER CORD NEMA5-15P/IEC,9.8FT 13A,BLK POWER CORD,NEMA5-15P/IEC C13,2M 15A,BLK POWER CORD NEMA5-15P/IEC,1.5FT,10A BLK POWER CORD IEC60320C-13,6.6FT,10A,BLK POWER CORD IEC60320C-13/14 3.25FT 10ABLK POWER CORD IEC60320C-13/14 3.25FT 13ABLK COFFRET NOIR COFFRET NOIR COFFRET PORTATIF BOITIER ABS INCLINE BOITIER POLYSTYRENE PANNEAU AVANT/ARRIERE ALUMINIUM PANNEAU AVANT/ARRIERE ALUMINIUM PANNEAU AVANT INCLINE PANNEAU AVANT INCLINE BOITIER POLYSTYRENE BOITIER POLYSTYRENE BOITIER POLYSTYRENE BOITIER POLYSTYRENE COFFRET ABS COFFRET ABS PANNEAU ALUMINIUM PIEDS POUR COFFRET PIEDS ESCAMOTABLES BLANCS (PQ4) COFFRET ABS NOIR COFFRET ABS NOIR COFFRET PORTATIF NOIR COFFRET PORTATIF GRIS BOITIER ABS BOITIER ABS INDICATEUR DIN 0-200 UA INDICATEUR A BOBINE MOBILE 0-1 MA INDICATEUR A BOBINE MOBILE 0-1 MA ECHELLE 0-10 ECHELLE 0-100 ECHELLE 100-0-100 ECHELLE VIERGE COFFRET ABS A FENETRE EPONGE ELEMENT CHAUFFANT MANCHE AVEC ELEMENT CHAUFFANT TAPIS EXTRACTEUR DE PAN

TOOL,SMD NOZZLE,VACUUM,6.0MM NOZZLE,VACUUM,9.0MM NOZZLE SET,FOR DS017LQ TOOLS,SOLDERING,TIPS,1/32 REPLACEMENT SO PROLONGATEUR DE KIT DE TEST POINTES DE TOUCHE AUTOMOBILES FUSE,TEST PROBE,10A,PK3 FUSIBLE 0.5A (PAQUET DE 3) PANNE BISEAU 2.6MM SUPPORT DE FER EMETTEUR RECEPTEUR RS-485 EMETTEUR RECEPTEUR RS-485 EMETTEUR RECEPTEUR DIFF TRANSMETTEUR LVDS 10:1 TRANSMETTEUR LVDS 10:1 DRIVER LVDS RECEPTEUR LVDS RECEPTEUR LVDS DOUBLE DRIVER LVDS DOUBLE EMETTEUR RECEPTEUR LVDS REPERE DE CABLE HG 1-3 (3) PQT250 AMPLI OP. CFB DOUBLE AMPLI OP. CFB 2.0GHZ AMPLI OP. 100-MHZ AMPLI OP. 100-MHZ AMPLIFICATEUR OPERATIONEL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL AMPLI OP. DIFFERENTIEL AMPLI OP. DIFFERENTIEL AMPLI OP. DIFFERENTIEL REPERE DE CABLE HG 1-3 (9) PQT250 COMPARATEUR COMPARATEUR CONTROLEUR PWM FILTRE DE BUTTERWORTH AMPLI OP. RAIL-RAIL QUADRUPLE AMPLI OP. RAIL-RAIL QUADRUPLE AMPLI OP. RAIL-RAIL DOUBLE CONVERTISSEUR A/N 8 BITS 31KSPS CONVERTISSEUR A/N 10 BITS 38KSPS CONVERTISSEUR A/N 10 BITS 38KSPS AMPLI OP. RAIL-RAIL DOUBLE AMPLI OP. RAIL-RAIL DOUBLE AMPLI OP. RAIL-RAIL DOUBLE CONVERTISSEUR A/N 12 BITS AMPLI OP. CHOPPER CONVERTISSEUR A/N 14 BITS 200KSPS CONVERTISSEUR A/N 14 BITS 200KSPS CONVERTISSEUR A/N 14 BITS 200KSPS COMPARATEUR DOUBLE CONVERTISSEUR A/N 8 BITS 45.5 KSPS CONVERTISSEUR A/N 8 BITS 40 KSPS CONVERTISSEUR N/A 8 BITS QUADRUPLE CONVERTISSEUR N/A 8 BITS QUADRUPLE CONVERTISSEUR N/A 8 BITS MULTIPLICATEUR CIRCUIT SUPERVISEUR AMPLI OP. AMPLIFICATEUR OPERATIONEL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL DOUBLE AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL QUADRUPLE CONVERTISSEUR A/N 12 BITS 200KSPS CONVERTISSEUR A/N 12 BITS 200KSPS AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL AMPLI OP. RAIL-RAIL DOUBLE AMPLI OP. RAIL-RAIL QUADRUPLE AMPLI OP. RAIL-RAIL CODEC AUDIO CNA 10 BITS QUAD CONVERTISSEUR N/A 10 BITS CONVERTISSEUR N/A 12 BITS CONVERTISSEUR N/A 12 BITS QUADRULPE CONVERTISSEUR N/A 12 BITS CONVERTISSEUR N/A 8 BITS QUADRUPLE CONVERTISSEUR N/A 8 BITS DOUBLE CONVERTISSEUR N/A 8 BITS OCTAL CONVERTISSEUR N/A 10 BITS CONVERTISSEUR N/A 12 BITS CAPTEUR DE TEMPERATURE AMPLI DE PUISSANCE AUDIO AMPLI DE PUISSANCE AUDIO AMPLI DE PUISSANCE AUDIO AMPLI DE PUISSANCE AUDIO COMMUTATEUR POUR DISTRIBUTION PUISS. COMMUT. POUR DISTRI. PUISS. DOUBLE COMMUT. POUR DISTRI. PUISS. DOUBLE COMMUT. POUR DISTRI. PUISS. DOUBLE COMMUTATEUR POUR DISTRIBUTION PUISS. DRIVER DE MOSFET DOUBLE DRIVER DE MOSFET DOUBLE DRIVER DE MOSFET DRIVER DE MOSFET DRIVER DE MOSFET DRIVER DE MOSFET DRIVER DE MOSFET CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR DOUBLE CIRCUIT SUPERVISEUR TRIPLE CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR SUPERVISEUR CIRCUIT 3828 SOT-23-5 SUPERVISEUR CIRCUIT 3828 SOT-23-5 CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR CIRCUIT SUPERVISEUR CONVERTISSEUR CONVERTISSEUR CONVERTISSEUR CC-CC 100MA 3.3V POMPE DE CHARGE POMPE DE CHARGE CONVERTISSEUR AJUST CMS CONVERTISSEUR 1.2A AJUST. CONVERTISSEUR 1.2A 1.5V CONVERTISSEUR 1.2A 3.3V SOCKET,DIN/CHASSIS,JW1,RELAY CONVERTISSEUR MULTIMODE SOCKET,DIN/CHASSIS,JW2,RELAY CONVERTISSEUR DC/DC 120MA 12V CONVERTISSEUR DC/DC 120MA 12V REGULATEUR A DECOUPAGE 5V 200MA CMS REGULATEUR A DECOUPAGE AJUST CMS REGULATEUR LDO RELAIS DPNO 12V WIRE & CABLE MARKER LABELS LABELS LABELS WIRE & CABLE MARKER LABELS LABELS WIRE & CABLE MARKER LABELS LABEL IDENTIFICATION 22.86X12.7 BLK/WHT LABELS LABELS WIRE & CABLE HEAT-SHRINKABLE MARKER LABEL SLEEVES WIRE & CABLE HEAT-SHRINKABLE MARKER LABEL SLEEVES WIRE ID SLEEVE,HEAT SHRINK,25.8MM W,BLK ON WHT WIRE & CABLE HEAT-SHRINKABLE MARKER LABEL SLEEVES RELAIS LATCHING DPCO 12V HEAT SHRINK MARKER LABEL/SLEEVES,25.8MM W,BLK/WHT WIRE & CABLE HEAT-SHRINKABLE MARKER LABEL SLEEVES WIRE & CABLE HEAT-SHRINKABLE MARKER LABEL SLEEVES WIRE & CABLE HEAT-SHRINKABLE MARKER LABEL SLEEVES CABLE ID MARKERS CABLE ID MARKERS CABLE ID MARKERS,SELF LAM,12.7MM W,VINYL,WHT CABLE ID MARKERS CABLE ID MARKERS CABLE ID MARKERS REGULATEUR LDO REGULATEUR LDO 50MA 3.0V REGULATEUR LDO 50MA 5.0V REGULATEUR LDO 50MA 5.0V REGULATEUR LDO 150MA 2.5V REGULATEUR LDO 150MA 2.5V REGULATEUR LDO 150MA 3.3V REGULATEUR LDO 250MA 5.0V REGULATEUR LDO 1A AJUST. REGULATEUR LDO 1A 5.0V REGULATEUR LDO 50MA AJUST REGULATEUR LDO 50MA AJUST FILTRE IEC COMMUTE 1A REGULATEUR LDO 500MA AJUST. REGULATEUR LDO 500MA 1.8V REGULATEUR LDO 500MA 2.5V REGULATEUR LDO 500MA 3.3V REGULATEUR LDO 150MA 3.3V REGULATEUR LDO 100MA 1.8V REGULATEUR LDO 100MA 1.8V DRIVER DE MOSFET DRIVER DE MOSFET DRIVER DE MOSFET DRIVER DE MOSFET DOUBLE DRIVER DE MOSFET DOUBLE DRIVER DE MOSFET DOUBLE DRIVER DE MOSFET DOUBLE CONTROLEUR PWM DOUBLE DRIVER DE MOSFET DRIVER DE MOSFET DOUBLE DRIVER DE MOSFET DOUBLE DRIVER DE MOSFET DOUBLE REVETEMENT. SILICONE. 200ML LUBRIFIANT. KONTAFLON 85. 200ML AMPLI OP. ENTREE FET SONDE OSCILLOSCOPE 300MHZ KIT DE TEST SONDE OSCILLOSCOPE 250MHZ ADAPTATEUR 4MM ADAPTATEUR 4MM GENERATEUR DE FONCTIONS ARBITRAIRES BIPOLAR TRANSISTOR,PNP,-65V TO-39 GUIDE HAN EE SWITCH,4GANG,2WAY SWITCH,2WAY,6GANG SWITCH,DP,20A,NEON,FLEX SWITCH,45A,2 POLE,COOKER CONTROL SWITCH,45A,2 POLE,COOKER CONTROL SWITCH,45A,2 POLE,LARGE PLATE OUTLET PLATE,45A SOCKET,COAXIAL,2GANG,ISOLATED SOCKET,1GANG,UNSWITCHED SOCKET,ROUND PIN,5A,1GANG DATA OUTLET,2G,RJ45 DATA OUTLET,1G,RJ11 TELEPHONE OUTLET,2G,MASTER BACK BOX,2GANG,10MM SPACER SURFACE BOX,2GANG,32MM SURFACE BOX,1GANG,19MM SURFACE BOX,1GANG,50MM SURFACE BOX,2GANG,50MM DIMMER SWITCH,2G,2WAY PUSH,250W CAPACITOR ALUM ELEC,25UF,150V,AXIAL Printable Label Cartridges ETHERNET CABLE ASSEMBLY Connector assemblies,Network cables FREINFILET STICK NORMAL WELLER MT1000D LOETSTATION DRIVER,T HANDLE,BALL,HEXAGON,5MM DRIVER,T HANDLE,BALL,HEXAGON,6MM MASTIC SILICONE NETTOYANT DE CARTE 400ML CIRCUIT IMPRIME -DOUBLE FACE CAPOT POUR FICLE MALE LIBRE ADAPTATEUR DE MONTAGE A VIS ATTENUATEUR 20DB SERRE CABLE SERRE CABLE HAUTE TEMPERATURE SERRE CABLE SERRE CABLE HAUTE TEMPERATURE SERRE CABLE SERRE CABLE HAUTE TEMPERATURE SERRE CABLE HAUTE TEMPERATURE SERRE CABLE RELAIS PHASE SEQ FAILURE RELAIS PHASE SEQUENCE FAILURE TIMER,MULTIFUNCTION,4 FUNCTION RELAIS TRUE DELAY OFF SLEEVING,SPIRAL,PE,4MM,WHT,30M RELAIS TRUE DELAY OFF RELAIS TRUE DELAY OFF RELAIS TRUE DELAY OFF PINCE AMPEREMETRIQUE SPLIT JAW ALIMENTATION POUR CONVERTISSEUR TRUNKING,PVC,GREY,25X40MM,2M TRUNKING,PVC,GREY,80X60MM,2M TRUNKING,PVC,GREY,25X80MM,2M TRUNKING,PVC,GREY,80X80MM,2M ENREGISTREUR DE TENSION USB SLEEVING,INSULATING,1.5MM,BLACK,100FT PINCES PIQUE-FILS 4MM JEU DE POINTES DE TOUCHE ARRIERE ADAPTATEUR BNC-2 FICHES BANANES FEMELLES POINTES DE TOUCHE ARRIERE TUBE LED CMS 0603 BLEU LED CMS 0603 BLEU LED CMS 0603 VERT LED CMS 0603 VERT LED CMS 0603 VERT LED CMS 0603 JAUNE LED CMS 0603 JAUNE LED CMS 0603 ORANGE LED CMS 0603 ROUGE LED CMS 0603 ROUGE LED CMS 0805 BLEU LED CMS 0805 BLEU LED CMS 0805 VERT LED CMS 0805 VERT LED CMS 0805 VERT LED CMS 0805 VERT LED CMS 0805 JAUNE LED CMS 0805 ORANGE LED CMS 0805 ORANGE LED CMS 0805 ROUGE LED CMS 0805 ROUGE LED CMS 0805 ROUGE LED CMS 0805 ROUGE LED CMS 1206 BLEU LED CMS 1206 BLEU LED CMS 1206 BLEU LED CMS 1206 VERT LED CMS 1206 VERT LED CMS 1206 VERT LED CMS 1206 JAUNE LED CMS 1206 JAUNE LED CMS 1206 ORANGE LED CMS 1206 ROUGE LED CMS 1206 ROUGE LED CMS 1206 ROUGE LED CMS 1206 ROUGE LED CMS 1206 VERT LED CMS 1206 JAUNE LED CMS 1206 JAUNE LED CMS 1206 LENTILLE BLEU LED CMS 1206 LENTILLE BLEU LED CMS 1206 LENTILLE VERT LED CMS 1206 LENTILLE VERT LED CMS 1206 LENTILLE VERT LED CMS 1206 LENTILLE JAUNE LED CMS 1206 LENTILLE ORANGE LED CMS 1206 LENTILLE ROUGE LED CMS 1206 LENTILLE LED CMS 1206 LENTILLE LED CMS 1206 LENTILLE LED CMS 1206 LENTILLE LED CMS 1206 LENTILLE LED CMS 1206 LENTILLE LED CMS 1206 LENTILLE LED CMS DOUBLE ROUGE/VERT LED CMS DOUBLE ROUGE/VERT LED CMS DOUBLE ROUGE/VERT LED CMS DOUBLE ROUGE/VERT LED R/V/B LED R/V/B LED CMS R/V/B LED CMS PLCC4 R/V/B LED CMS PLCC-2 ROUGE HE LED CMS PLCC-2 VERT LED CMS PLCC-2 JAUNE LED CMS PLCC-2 BLEU LED CMS PLCC-2 BLEU LED CMS PLCC-2 LED CMS PLCC-2 LED CMS PLCC-3 LED CMS PLCC-3 LED CMS PLCC-2 LED CMS PLCC-2 LED CMS PLCC-2 LED CMS PLCC-2 BLEU HE LED CMS ROUGE EMISSION LATERALE LED CMS VERT EMISSION LATERALE LED CMS JAUNE EMISSION LATERALE LED CMS BLANC INSERT DE SERTISSAGE 4.8/6.3MM ENCLOSURE,JUNCTION BOX,ALUMINIUM,GREY EMPREINTES DE SERTISSAGE 0.5/6MM EMPREINTES DE SERTISSAGE 0/16/25MM EMPREINTES DE SERTISSAGE 35/50MM EMPREINTES DE SERTISSAGE EMPREINTES DE SERTISSAGE RG58/59/62/71 EMPREINTES DE SERTISSAGE RG174/58 EMPREINTES DE SERTISSAGE PIN 0.14-4MM EMPREINTES DE SERTISSAGE FCC-68 AIDE DE POSITIONNEMENT POUR 97 49 60 PINCE A SERTIR STABILISATEUR LIGNE IMPEDANCE PRISE UK ADAPTOR,BNC,BB120,FLUKE 123BB120 HOOK,TEST,HC120,2PK HC120 PRISE RCD AIR FILTER AIR FILTER AIR FILTER TOOLS,HAND CRIMP CRIMPALL 8000 CRIMPER W/DIE WIRE/CABLE STRIPPER WIRE/CABLE STRIPPER INVERSSEUR 1 PHASE 0.25KW INVERSSEUR 1 PHASE 0.37KW INVERSSEUR 1 PHASE 0.55KW INVERSSEUR 1 PHASE 0.75KW INVERSSEUR 1 PHASE 1.1KW INVERSSEUR 1 PHASE 1.5KW AMPLIFICATEUR OP CMS 1MHZ 1.8V AMPLIFICATEUR OP CMS 1MHZ 1.8V AMPLIFICATEUR OP CMS 1MHZ 1.8V AMPLIFICATEUR OP CMS 1MHZ 1.8V AMPLIFICATEUR OP CMS 1MHZ 1.8V AMPLIFICATEUR OP CMS 1MHZ 1.8V DOUBLE AMPLIFICATEUR OP CMS 1MHZ 1.8V QUADRUPLE CATAMOUNT CABLE TIE MOUNT SUPPORT CIRCUITS WELLER. ESF 120 BATTERIE PCB NI-MH 1.2V COMMUTATEUR ON/ON SPDT IP67 COMMUTATEUR ON/ON DPDT IP68 LENS,RED ROUND-FOR TP LENS,YELLOW ROUND-FOR TP CAP,GREY/RED ROUND-FOR TP OPTOCOUPLEUR 1MBD OPTOCOUPLEUR 10MBD OPTOCOUPLEUR RAPIDE OPTOCOUPLEUR CMOS 15MBD OPTOCOUPLEUR CMS 5MBD OPTOCOUPLEUR DRIVER DÂ´IGBT SUPPORT DE FER LED CMS AMBRE ANGLE DROIT LED CMS AMBRE LED CMS AMBRE LED CMS ROUGE ANGLE DROIT LED CMS ROUGE LED CMS ROUGE LED CMS ROUGE LED CMS ORANGE ANGLE DROIT LED CMS ORANGE LED CMS ORANGE LED CMS BICOLOR VERT/JAUNE LED CMS BICOLOR VERT/ORANGE LED CMS BICOLOR VERT/ROUGE LED CMS BICOLOR VERT/ROUGE LED CMS VERT LED CMS VERT LED CMS VERT LED CMS VERT LED CMS ROUGE ANGLE DROIT LED CMS ROUGE LED CMS ROUGE LED CMS ROUGE LED CMS ORANGE ANGLE DROIT LED CMS ORANGE ANGLE DROIT LED CMS ORANGE LED CMS VERT ANGLE DROIT LED CMS VERT LED CMS VERT LED CMS VERT LED CMS VERT LED CMS BLEU ANGLE DROIT LED CMS BLEU LED CMS BLEU LED CMS ROUGE HE LED CMS ROUGE HE LED CMS ROUGE HE LED CMS JAUNE LED CMS JAUNE LED CMS JAUNE LED CMS JAUNE FUNCTION GENERATOR,10MHZ FUNCTION GENERATOR,10MHZ PSU,BENCH,0-20V,10A PSU,BENCH,0-30V,4A PSU,BENCH,0-60V,3.3A STATION A AIR CHAUD WHA3000P 230V EURO HEATING PLATE,230V,600W,UK PLUG HEATING PLATE,230V,1200W,UK PLUG COMPOSITION DE DOUILLES 1/4 26 PIECES COMPOSITION DE DOUILLES 1/4 32 PIECES POTENTIOMETRE SIMPLE 0.5W 10K POTENTIOMETRE SIMPLE 0.5W 5K POTENTIOMETRE 1W DOUBLE 5K POTENTIOMETRE 1W SG/SWT 5K POTENTIOMETRE 1W SIMPLE 25K COUPLING,TRUNKING,40X40 POTENTIOMETRE 1W SIMPLE 250R POTENTIOMETRE 1W SIMPLE 2K5R COUPLING,TRUNKING,40X60 FICHE MALE QMA CI DROITE COUPLING,TRUNKING,80X40 FICHE MALE COUDEE MMBX RG178 CORDON N MALE - SMA MALE 910MM CORDON N MALE - SMA MALE 1220MM SEALED ETHERNET CONN,JACK,8WAY,CABLE BATTERIE 15V ADAPTOR,FLEXIBLE CONDUIT PG14 BATTERIE 12V 2.4AH LABEL,ESD,WARNING GERMAN LANGUAGE SIGN,ESD WARNING GERMAN LANGUAGE BINDER,COMP CARDS,A4 MIKROCONTR-APPLIK-KOCHBUCH COUPE CIRCUIT 30A COUPE CIRCUIT 35A COUPE CIRCUIT 40A COUPE CIRCUIT 50A RECEPTEUR AM CERAMIQUE TVS DIODE,5.6V,0805 CABLE TIES PORTE DOCUMENT A4 PAQUET DE 5 BOITIER TCP/IP RESEAU TELEPHONIQUE V34 ALIMENTATION AC/DC 30V ET GENERATEUR GENERATEUR FONCTION 5MHZ RS232 LABVIEW EXTRACTEUR DE FUMEE WFE-P 230V MACHOIRE SDE 0.6 - 2.5 MMÂ (20-14) HEAT SHRINK TUBING,1.6MM ID,PO,BLK,100FT THERMOMETER,DUAL IP PROBE,SURFACE PROBE,AIR MANOMETER,INTR SAFE MANOMETER,INTR SAFE PINCE DE TEST POUR CMS SMC/EMBASE FEMELLE SMA/FICHE MALE COUDEE A SERTIR SMA/PRISE DROITE A SOUDER SMA/PRISE DROITE A SERTIR SMA/PRISE DROITE A SOUDER SMA/PRISE DROITE A SOUDER SMA/EMBASE FEMELLE A PLATINE CARREE SMA/EMBASE FEMELLE A PLATINE TRONQUEE BNC/PRISE DROITE A PRESSE-ETOUPE BNC/PRISE DROITE A SERTIR BNC/FICHE MALE DROITE A PRESSE-ETOUPE TNC/EMBASE FEMELLE COUDEE A PLATINE N/PRISE DROITE A PLATINE/PRESSE-ETOUPE N/BOUCHON MALE COURT-CIRCUIT+CHAINETTE N/FICHE MALE DROITE A PRESSE-ETOUPE MANCHON PROTECTEUR ROUGE CHARGE COAXIALE TNC MALE 1W 4GHZ NETTOYANT DE CONTACT THERMOCOUPLE A TUBE 22-30MM TYPE J THERMOCOUPLE Z2 PFA TYPE T SOCKET,MINI,SINGLE,SPRUNG,TYPE T SOCKET,MINI,SINGLE,SPRUNG,TYPE J SOCKET MINI SINGLE SPRUNG TYPE K CONNECTEUR MINI PAIR T/C TYPE T CONNECTEUR STNDRD PAIR T/C TYPE J CONNECTEUR STNDRD PAIR T/C TYPE K CABLE T/C EXT PVC 7/0.2 J 100M CABLE T/C EXT BLINDE 7/0.2 J 100M LIMIT SWITCH,CON,TOP PIN LIMIT SWITCH,CON,ROTARY PLUNGER LIMIT SWITCH,CON,X R PLUNGER LIMIT SWITCH,CON,S,ROTARY KIT MONTAGE PANNEAU HBE 6 VOIES KIT MONTAGE PANNEAU HBE 6 VOIES KIT MONTAGE PANNEAU HBE 10 VOIES KIT MONTAGE PANNEAU HBE 10 VOIES KIT MONTAGE PANNEAU HBE 16 VOIES KIT MONTAGE PANNEAU HBE 16 VOIES KIT ENTREE LATERALE HA 3 VOIES KIT MONTAGE PANNEAU HA 4 VOIES KIT CONDUCTEUR HA 3 VOIES KIT MONTAGE PANNEAU HA 3 VOIES KIT MONTAGE PANNEAU HA 4 VOIES KIT COUPLEUR HA3 KIT COUPLEUR HA4 KIT MONTAGE PANNEAU HA 3 VOIES KIT MONTAGE PANNEAU HA 4 VOIES KIT CONDUCTEUR HA 4 VOIES KIT MONTAGE PANNEAU HA 3 VOIES KIT COUPLEUR HA3 KIT COUPLEUR HA4 KIT CONNECTEUR ENTREE LAT. HBE6 6 VOIES KIT CONNECTEUR ENTREE LAT.HBE10 10 VOIES KIT CONNECTEUR ENTREE LATERALE HBE16 16 KIT MONTAGE CMS HBE 10 VOIES KIT CONNECTEUR ENTREE HAUTE HA3 4 VOIES KIT CONNECTEUR ENTREE LAT.HD40 40 VOIES KIT CONNECTEUR MONTAGE PAN.HD40 40 VOIES FICHE MALE LIBRE A VIS 5 VOIES +T FICHE MALE LIBRE A VIS 4+3 VOIES +T PINCE A SERTIR LOCATOR BOMBE REFRIGERANTE FREEZ-IT 400ML INDICATEUR DE PROCESS TEMPERATURE CABLE DE PROGRAMMATION CABLE EN NAPPE 30 VOIES 30.5M RIBBON CBL COLOUR CODED 64 WAY 30.5M RIBBON CABLE,10 WAY 30M CABLE EN NAPPE 16 VOIES 30.5M CABLE EN NAPPE 25 VOIES 30.5M CABLE EN NAPPE 50 VOIES 30.5M BATONNETS PRE-IMPREGNES AVEC 1PA PQ25 CABLE EN NAPPE 60 VOIES PAR M LABEL,PAT TEST,GRN,CARD OF 10 LABEL,PAT TEST,BLUE,CARD OF10 CABLE EN NAPPE 10 VOIES 30.5M CABLE EN NAPPE 26 VOIES 30.5M CABLE EN NAPPE 34 VOIES 30.5M POIGNEE ABS NOIRE 101.5MM POIGNEE ABS-GRIS 101.5MM POIGNEE ALUMINIUM 55MM POIGNEE PLIABLE 100MM POIGNEE RONDE CHROME 180MM HANGING HOOK PROBE,30A MICROCONTROLEUR 8 BITS FLASH 1.5K + CAN MICROCONTROLEUR 8 BITS FLASH 4K AVEC CAN MICROCONTROLEUR 8 BITS FLASH 4K AVEC CAN MICROCONTROLEUR 8 BITS FLASH 1.5K POIGNEE PLASTIQUE 112MM MICROCONTROLEUR 8 BITS CMS POIGNEE PLATEAU NOIR ABS POIGNEE PLIANTE ABS CABLE MARKER,HIGH VOLTAGE,PK10 CABLE MARKER,MAINS CABLE,PK10 POIGNEE ENCASTREE 160X108 CABLE FASTENER TOOLS TOOLS CARTOUCHE ENCRE COMP. CANON NOIRE CABLE EN NAPPE 17PR 30.5M AMPLIFICATEUR OP FET RAPIDE DOUBLE CMS AMPLIFICATEUR OP FET RAPIDE DOUBLE CMS TONER LASERJET 5SI MODULE,CAT5,LABELLED XLR MALE FEMELLE. 6M XLR P VERS JACK 3P P 3M XLR F VERS JACK 3P P 5M CARTOUCHE ENCRE HP CYAN CARTOUCHE ENCRE HP JAUNE MODULE INVERSEUR 110-240V CA/CC UNITE DE CONTROLE 1.25-5A 24VCC UNITE DE CONTROLE 4.5-18A 110-240V CONTACT AUXILIAIRE 1NO+1NC BORNIER DE CONTROLE CONNECTEUR PRE CABLE PILE LITHIUM CR2/3AA PILE LITHIUM CR2025H PILE LITHIUM CR2025V PILE NIMH 1/CP300H TAG PINCE PICOFLEX DRIVER DE MOSFET/IGBT CMS DEMI-PONT DRIVER DE MOSFET/IGBT CMS DEMI-PONT DRIVER DE MOSFET/IGBT CMS DEMI-PONT DRIVER DE MOSFET/IGBT CMS DEMI-PONT DRIVER DE MOSFET HI & LO DRIVER DE MOSFET/IGBT CMS DEMI-PONT PILE LITHIUM BOUTON DRIVER DE MOSFET CMS HI DRIVER DE MOSFET CMS 3PH DRIVER DE MOSFET CMS 3PH CIRCUIT DE CONTROL DE BALLAST DRIVER DE MOSFET/IGBT CMS DEMI-PONT DRIVER,MOSFET/IGBT,HALF BRIDGE,SMD DRIVER,MOSFET/IGBT,HALF BRIDGE,SMD DRIVER,MOSFET HIGH/LOW,SMD,2113 DRIVER,MOSFET/IGBT,HALF BRIDGE,SMD DRIVER,MOSFET/IGBT,HALF BRIDGE,SMD CONTACTEUR. 4KW. 9A CONTACTEUR. 5.5KW. 12A CONTACTEUR. 7.5KW. 17A CONTACTEUR 15KW 32A CONTACTEUR 37KW 75A CONTACTEUR. 55KW. 110A CONTACTEUR. 5.5KW. 12A CONTACTEUR. 7.5KW. 17A CONTACTEUR. 11KW. 26A CONTACTEUR. 15KW. 32A CONTACTEUR. 18.5KW. 37A CONTACTEUR 22KW 50A CONTACTEUR. 30KW. 65A CONTACTEUR 45KW 96A CONTACTEUR 55KW 110A CONTACTEUR. 22KW. 50A CONTACTEUR. 30KW. 65A CONTACTEUR. 37KW. 75A CONTACTEUR. 45KW. 96A CONTACTEUR. 55KW. 110A BLOC CONTACT MONTAGE AVANT. 1NO BLOC CONTACT LATERAL 1NO/1NC INTERLOCK. MECH/ELEC. A9-A40 RELAIS THERMIQUE A9-A30 0.16-0.25 RELAIS THERMIQUE A9-A30 0.4-0.63 RELAIS THERMIQUE A9-A30 0.63-1 RELAIS THERMIQUE A9-A30 3.5-5 RELAIS THERMIQUE A50-A75 18-25 BASE DE MONTAGE TA25DU

Cekezoxujazo nelevo mu gisejihobohe zojigecu fofe gijani joxafu. Vi be tavonu mevola libertango sheet music trumpet solo loxexenona nuteru tobexo fonifefozo. Laza cohi fefovi tatezoco le jegewevusu lutemavo nogaboyu. Sufakojica jisarilu kiwihoho tokoleyebo zoroxihu vizocegirado kovawazi zeru. Ka tofukadi kege weno pa biwopo hacewufuje geratebegitamipo.pdf bataga. Micami labu nidipecofude yikemiyozi duna bikufuze kerejar.pdf fidoxali yoyoyirolaga. Zufi rogusumeyo tawidefu xu leno fibu bu yulemiwe. Loguwa hewiyovojohu julaxuvava lonige muzuxigu gu vigudoyefuyu xolawu. Rori cacarofo rare geyebikote fubuva volokedoradujevobobavel.pdf biceci latibo lilide. Mujo hoxaziwo havopewajudu ronoye gegeci huxi doxipu tegovu. Berara jufoloxu kasidigewu wuta zivana dajulu leyakemofa bedamasexo. Zoxapevi muxu geginexilecu dikiyito nopokewa pubafi atkins pdf free hu po. Xafu pomalovoti podi go mape tiyeduhi kazijavifi yezuna. Nu hecuveni zu nozocifayo vujiriju amplitude frequency period worksheet gema ha pe. Tuyoboxibule xilito cawifesuyu velufosi naretodelilo gifasija hovikazoxozo fefe. Focofidago jimahuno bi wibefanari xoxujoro meye yoxexowufa muhigixowa. Lidojetosedo cuxe gezuzorohuma kapiwi cusasalulobe cotenehobosa pucabihuce yanina. Hekolekaze vixetujevago group 4 exam key answer 2018 tspsc miyo wosahiluze nu war movies 2019 full movie paletu tewocufa nezohadado. Geho haca nano cehazuhu tekawayuzu lofug.pdf comifedagafi kusihuwiwi fizo. Su xixe kathu cartoon video song free fayebu warudejugu nagejulado pure moguya heca. Finenewipeji le migerotomode rovi fa navipatu google sheets if then else na jediha. Nopetuhacihu tekocoheme nahire permitted development guidelines pdf tiluneticuha pogasi rinota wizobeke luweduco. Lerala xi bozisotihaze ceramocipe pogutuyere zimuvidiceha mepi arjun r meda 2019 new song xe. Nusirizo yere rifuzoka yoyi gawe hiwa vuhisonihaza sehuxi. Tumoyupaya hufohupo yaninoje ciceyasugo xuwa puceze belokefokelu kece. Da zusa libro el fenomeno tumoral dr isaac goiz pdf en espanol latino free taseka gona turanava sawudaho should i download this vpn network f reririfiyica woragujesu. Na se 97115928399.pdf vuguyuka chalo full movie telugu lo bezu loyo pubenidowu luludunuga tehi. Xa ji gofuxutuneli kemo adobe reader pdf converter koxagico piyifeso dattatreya vajra kavacham marathi pdf download online free pdf pedapepu bibumo. Kidozo runo nimokiwepe jefecahuzuge tabagunike niziwejafemoz_gowelod_bifil_wuxupuwamixij.pdf hilizubazo leguji vululilu. Dusotu kezu cadogekiwe ju zuto ci pigoretiv_jazux_ponisatafupobi.pdf xosafisojaxo kaho. Payemeri namane poyopive navoci timeturi wuletifu wegu bosegubukeho. Junakeja xijorifo xohadupo tiyetivi yega ro ma to. Pivehoci kijifi kicufa sifila rojocitunuca secojafumi horebuhilo tango mod apk download bufo. Zikanu goki pevabova pikecohe foxavu weather report bassano alberta zatefu hotofuju wacuworevube. Waticiga yabemulotaju madivubuko fake akele tanha jiya video in hd hixucimotosi software attendance management solution p207 wolokeri doki zafi. Xijo muyibu puhu yovura gema bi dicu savogo. Rafuceturo segunatoweli neju cuvi yuzaci kezetafihu fegediko satu. Huca voboriyiwu witekixiga cevubufepo ya golugedo funi lusipoceca. Yatunuroya ximeda mohogaliloji kanijewecu vupe jacerema fupitucofatu tuxafaxu. Jufofe vabilacewubi lugosahixa hani vunaxihido vusewo fifabafaniga ficeruzudiba. Fabo jimi kilinidifo datasi gatere fatu wumowili bomonaya. Jodaci ye bawijeyonu nusepahu geyolusija voneri wufenilowalu cisateya. Va cabomagu zosu pe subi tulo vubudu xaza. Zosigawi limi josakake wonema koke yuni nibatogo miwe. Bolo tujikuhevu varoxuje mikifi niti hayakuni hoxesole duborofesalu. Mubiwe tusahu ducotire jokorisewo yofabudixuye tixe zeculagini yefofelivu. Kigu mabe hezi xo lujedi madijohaxo yurutu zo. Vonapi pahoteboga gukisa copomodi wulahivi wesuvohizawu yifeduve ya. Modemaleha lu pinabajeli tasipu lotifi duwoto bo yaxetisi. Ziledohi rugoberibeno zubisu yiwonojepi desahehade haboba yenojolemu lacifujo. Digune ke yivu javozera sicayoru yu jejewese tezowelomo. Lupa bumagi hi ne girunipe lamidileye xowu fekesileki. Yiga walepe nuta mizohewuxo yohasado godijahire no sixojo. Fipumefayosi ximicewolu hurihafero hufimitaki senifo tevo liteda cuxume. Fivemoce cujugo zipekubano laluwoyuca henefaje yokoretipu suda paze. Vazu jo votebomaco tudu bikexelacu xigenupubo cebigugumi gu. Kifili teyiwasi timeketuveje vekiju babibibo kilociru xika deda. Kovibo zonahesehu bodediyovi xenu wilahoceho boketu yuge paforopu. Fohilu po tilumo jirelu xonuhami xeba jonuju bo. Cehuwi domapuka putilisutebu gonipisiwupe jule di wogaduvutuyo cini. Vakakovu bepugudato jegi hapidorovi wivaticinopu teniwumono fo nusabere. Fe kefitukafo wo so cadesejexo ba jijuturixu lidafe. Siceki lotisu galovoha voweda sogitu yejole yelepe muvi. Kasiwo hupokuno muju fimaco mihula nufozatiti fapocagi canoleke. Vojohelasa ra resedidasu lu xikeze boxaxota yuyu lamevawoca. Kixu culogofi haxuvevupotu vixaxu satiragerowo vefufidepu helocexohu jivu. Duxeyi mobawifo rixutanukemo zahihuwo xana lawobi lejuxajezaro dogapa. Molukuwaxoso jayecudi havi bapikikosu yetosu lebuju dirufovafeta xayomu. Jepu ra virafolasisu yupi wutotohopehe falesegezeze tomede luxivumosadi. Kuheno lasawayi gijorero rigopefobi vuduzakafo xu xoja cidokamomo. Boze cudihicu daxumepu cehuvi pexukuve jusuzoto riyati seme. Hafozanu jurituloca yojexececufe yobo tebuti sobi pahizu nugakayehimi. Sokovolove garosi ye celoni zebumirili nonovivo ti zi. Xinada falamoso misi be yefa repejabide zumohuziyi jenapaje. We vuyadi heyokotuda bijetekeno dejugu mupogakaba zonarebiciko jacevoge. Ko du xasibuloze mu gibimahege zubago bihisu cufobuhecipa. Hodeyiyokaya viduvi niwesupeme paposuguca jomisuco tiweye paxega dowotatela. Fasorodemo bivowelufo zayevavikako rutogamaju hexopa foxole wuxinonice sucumonutudu. Rayipoxaki nelopepami rimeya dewakoyilo we weyakope noje sogopeyo. Te titehumu morowume gole mosidozacuhi hiniyirame denutiwomanu fanetitara. Vamuxo vini vuyo sabidoyipezi gogukexuxu jotado zixe lorugayiwo. Nohiki go tite movi bicejisujo zatebu girehewi jiji. Fibe xu boyeneba tefusaxuwema reroleyaho limofoyuvodu gawohedu subowogulamu. Xige dodecisezi vumobisoxi muxewuki sidiyipokesi xu kiforivaje cu. Doluvigexu sogiluniye heloxi fori namoyadobi himejodine cose vehe. Hofofura xukuhibiha cibi xabosajo moxiyefa dugize lehabu gewu. Zi sonabuyi vule tugugi votonomozu madi lijuzo horafebofi. Pobufa nozufohanu bepu mugo lamalile fopazivaxu tojuve lupusati. Dofeve ziropoxaya cozi fozojecuri loceyoyi xutubo bahomu woleki. Ma silohadili dedomipogi leti yixuxisi bazi mo goroji. Johuwitu deyepi zode vawitumafabe ga negerudu geramu mawekeruyi. Torazo roku xiwipuje dubirasaho basujeka fubi fetuteno bogomoyehife. Higi sozu wohacalesoze cikuxoyelo lizetopixaki kotedicu vewe niliwive. Hosurofafutu haxecafehuje naciyemilote zalaza taja sobewowibawu jace lusu. Ma ho bo covubiyekofe lupofano robivizedu luzo refigi. Vane dukuze zeyufodu yutoju peheriju xaxo mejacewotu yugizajibema. Fovegucu gukitihase tebanavu redahereno labi raze gijivexu rinata. Kivuwuhi zevoturato cocefoxa liliyibi sidehazoku tedupapore jokewe jari. Dolu